



Federal Communication Commission

Equipment Authorization Division, Application Processing Branch
7435 Oakland Mills Road
Columbia, MD 21048

January 27, 2009

REF: **Answer to questions from FCC in relation to C2PC** for FCC ID: **VV7-MBMF3507G-D**

FCC question:

"Please provide more detail regarding the anomaly you have indicated. Our experiences are that if HSPA power is higher than WCDMA, either MPR is not being utilized or implementation issues and/or measurement problems have occurred."

Response:

MPR issue was detected by FW development team from Ericsson and after a deep analysis of the implication of this anomaly, Ericsson concluded that:

- From a regulatory point of view, FCC and other regulatory domains requirements, it was not relevant as far as testing has been carried out for HSPA in each band in the expected worst case configuration for HSDPA and HSUPA mode, however, the maximum SAR level is obtained in E/GPRS 850 configuration, which is consistent with the expected worst case outcome for this module.
- From 3GPP TS34.12 compliance point of view, it is not relevant because although power reduction in HSUPA mode is a possibility included in the specifications it is not a mandatory feature and the specifications allow the same output power in HSUPA and WCDMA modes.
- Ericsson quality system and production controls warranty the continuous compliance of the device with regulatory and 3GPP requirements by individual calibration of the modules in the production line to ensure the compliance with output power requirements in all the transmission modes of the device (GSM/GPRS/WCDMA/HSDPA/HSUPA).

Although this anomaly was not relevant for compliance, FW development team from Ericsson has continued to optimise the MPR implementation in the F3507g module.

The MPR implementation in this device is a result of the ongoing development of the Ericsson F3507G module. During this development the crest compensation and power turn down mechanisms were optimised throughout a number of iterations.

The patch to correct the unexpectedly high power in HSUPA mode is available and will be implemented this year in firmware release R2A. Test results confirm that the power level is then reduced as expected in MPR implementation.

Sincerely,

P.A.

Bernie Fuller, CEng, BEng, MIET
Certification ProjectTeam, Integration & Verification
Mobile Broadband Modules

Ericsson AB

Business Unit Network
Lindholmospiren 11
SE-417 56 Gothenburg
www.ericsson.com

Office: +46 31 747 4371
Fax: +46 31 747 6033
Mobile: +46 761 497182
Email: bernie.fuller@ericsson.com