



## **ANSI/IEEE Std. C95.1-1992 / RSS-102**

in accordance with the requirements of  
FCC Report and Order: ET Docket 93-62, and OET Bulletin 65 Supplement C

IC Report and Order: SSI/DRB-TP-D01-030



## **FCC/IC TEST REPORT**

**For**

**Lenovo Notebook Computer**

**Trade Name: lenovo**

**Model: TP00019A**

*Issued to*

**Wistron Corporation  
21F, 88, Sec. 1, Hsin Tai Wu Rd., Hsichih,  
Taipei Hsien 221, Taiwan, R.O.C.**

*Issued by*

**Compliance Certification Services Inc.  
No. 11, Wugong 6th Rd., Wugu Industrial Park,  
Taipei Hsien 248, Taiwan.  
<http://www.ccsrf.com.tw>  
service@ccsrf.com.**



***Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.***



## TABLE OF CONTENTS

|  |           |
|--|-----------|
| <b>1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION) .....</b>               | <b>3</b>  |
| <b>2. EUT DESCRIPTION .....</b>  | <b>4</b>  |
| <b>3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC .....</b>   | <b>5</b>  |
| <b>4. DOSIMETRIC ASSESSMENT SYSTEM .....</b>                             | <b>5</b>  |
| 4.1    MEASUREMENT SYSTEM DIAGRAM .....                                  | 6         |
| 4.2    SYSTEM COMPONENTS.....  | 7         |
| <b>5. EVALUATION PROCEDURES .....</b>                                    | <b>10</b> |
| <b>6. MEASUREMENT UNCERTAINTY .....</b>                                  | <b>14</b> |
| <b>7. EXPOSURE LIMIT .....</b>   | <b>16</b> |
| <b>8. TYPICAL COMPOSITION OF INGREDIENTS FOR LIQUID TISSUE PHANTOMS.</b> | <b>17</b> |
| <b>9. MEASUREMENT RESULTS.....</b>                                       | <b>18</b> |
| 9.1    TEST LIQUID CONFIRMATION .....                                    | 18        |
| 9.2    SYSTEM PERFORMANCE CHECK.....                                     | 20        |
| 9.3    EUT TUNE-UP PROCEDURES AND TEST MODE.....                         | 22        |
| 9.4    RF POWER OUTPUT FOR UMTS REL99 .....                              | 23        |
| 9.5    RF POWER OUTPUT FOR UMTS REL 6 HSDPA .....                        | 24        |
| 9.6    RF POWER OUTPUT UMTS REL 6 HSPA (HSDPA & HSUPA) .....             | 25        |
| 9.7    SAR MEASUREMENTS RESULTS.....                                     | 27        |
| <b>10. EUT PHOTOS .....</b>  | <b>38</b> |
| <b>11. EQUIPMENT LIST &amp; CALIBRATION STATUS .....</b>                 | <b>39</b> |
| <b>12. FACILITIES.....</b>   | <b>40</b> |
| <b>13. REFERENCES .....</b>  | <b>40</b> |
| <b>14. ATTACHMENTS.....</b>  | <b>41</b> |



## 1. CERTIFICATE OF COMPLIANCE (SAR EVALUATION)

**Applicant:** Wistron Corporation  
21F, 88, Sec. 1, Hsin Tai Wu Rd., Hsichih,  
Taipei Hsien 221, Taiwan, R.O.C.

**Equipment Under Test:** Lenovo Notebook Computer

**Trade Name:** lenovo

**Model Number:** TP00019A

**Date of Test:** December 22, 2010 ~ January 18, 2011

**Device Category:** PORTABLE DEVICES

**Exposure Category:** GENERAL POPULATION/UNCONTROLLED EXPOSURE

| APPLICABLE STANDARDS   |                         |
|--|-------------------------|
| STANDARD   |                         |
| FCC  | FCC OET 65 Supplement C |
| IC   | IC RSS-102              |
| Deviation from Applicable Standard   |                         |
| None   |                         |
| TEST RESULT  |                         |
| No non-compliance noted  |                         |
| The device was tested by Compliance Certification Services Inc. in accordance with the measurement methods and procedures specified in OET Bulletin 65 Supplement C (Edition 01-01). The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties. |                         |
| The device was tested by Compliance Certification Services Inc. in accordance with the measurement methods and procedures specified in IC RSS-102. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.                                   |                         |

Approved by:

Rex Lai  
Section Manager  
Compliance Certification Services Inc.

Tested by:

Anson Lu  
Test Engineer  
Compliance Certification Services Inc.



## 2. EUT DESCRIPTION

|                                      |   |
|--------------------------------------|---|
| <b>Product</b>                       | Lenovo Notebook Computer  |
| <b>Trade Name</b>                    | lenovo  |
| <b>Model Number</b>                  | TP00019A  |
| <b>WWAN Model</b>                    | Ericsson F5521GW  |
| <b>Model Discrepancy</b>             | N/A   |
| <b>Frequency Range</b>               | GPRS/EDGE850: 824.2 ~ 848.8 MHz<br>GPRS/EDGE1900: 1850.2 ~ 1909.8 MHz<br>WCDMA / HSDPA band V: 826.4 ~ 846.6 MHz<br>WCDMA/HSDPA/HSUPA band II: 1852.4 ~ 1907.6 MHz  |
| <b>Max. O/P Power:<br/>(Average)</b> | GPRS850: 27.12 dBm / EDGE850: 24.90 dBm<br>GPRS1900: 23.69 dBm / EDGE1900: 23.30 dBm<br>WCDMA band V: 27.48 dBm<br>HSDPA band V: 26.95 dBm / HSUPA band V: 26.68 dBm<br>WCDMA band II: 26.45 dBm<br>HSDPA band II: 25.83 dBm / HSUPA band II: 25.61 dBm           |
| <b>Max. SAR (1g):</b>                | GPRS850: 0.943 W/kg / EDGE850: 0.262 W/kg<br>GPRS1900: 1.070 W/kg / EDGE1900: 0.571 W/kg<br>WCDMA band V: 0.697 W/kg<br>HSDPA band V: 0.465 W/kg / HSUPA band V: 0.508 W/kg<br>WCDMA band II: 1.180 W/kg<br>HSDPA band II: 0.787 W/kg / HSUPA band II: 0.887 W/kg |
| <b>Modulation Technique</b>          | GPRS: GMSK / WCDMA: QPSK  |
| <b>Antenna Specification</b>         | Antenna type:<br>WWAN main antenna: PIFA antenna<br>WWAN aux antenna: PIFA antenna  |
| <b>Battery</b>                       | 1) model no: 42T4878<br>2) model no: 42T4882<br>3) model no: 42T4880<br>4) model no: 42T4904  |

**Remark:** The sample selected for test was prototype that approximated to production product and was provided by manufacturer.



### **3. REQUIREMENTS FOR COMPLIANCE TESTING DEFINED**

#### **3.1 REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE FCC**

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6]. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.


#### **3.2 REQUIREMENTS FOR COMPLIANCE TESTING DEFINED BY THE IC**

The US Federal Communications Commission has released the report and order "Guidelines for Evaluating the Environmental Effects of RF Radiation", ET Docket No. 93-62 in August 1996 [1]. The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g for an uncontrolled environment and 8.0 mW/g for an occupational/controlled environment as recommended by the ANSI/IEEE standard C95.1-1992 [6]. According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

### **4. DOSIMETRIC ASSESSMENT SYSTEM**

These measurements were performed with the automated near-field scanning system DASY4/DAST5 from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision robot (working range greater than 0.9 m) which positions the probes with a positional repeatability of better than  $\pm 0.02$  mm. Special E- and H-field probes have been developed for measurements close to material discontinuity, the sensors of which are directly loaded with a Schottky diode and connected via highly resistive lines to the data acquisition unit. The SAR measurements were conducted with the dosimetric probe EX3DV4-SN: 3554 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe has been calibrated according to the procedure with accuracy of better than  $\pm 10\%$ . The spherical isotropy was evaluated with the procedure and found to be better than  $\pm 0.25$  dB. The phantom used was the SAM Twin Phantom as described in FCC supplement C, IEEE P1528 and EN50361.

#### 4.1 MEASUREMENT SYSTEM DIAGRAM



The DASY4/DASY5 system for performing compliance tests consists of the following items:

- A standard high precision 6-axis robot (Staubli RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion between optical and electrical of the signals for the digital communication to the DAE and for the analog signal from the optical surface detection. The EOC is connected to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- A computer operating Windows 2000 or Windows XP.
- DASY4/DAST5 software.
- Remote control with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- The SAM twin phantom enabling testing left-hand and right-hand usage.
- The device holder for handheld mobile phones.
- Tissue simulating liquid mixed according to the given recipes.
- Validation dipole kits allowing validating the proper functioning of the system.



## 4.2 SYSTEM COMPONENTS

### DASY4/DASY5 Measurement Server



The DASY4/DASY5 measurement server is based on a PC/104 CPU board with a 166MHz low-power Pentium, 32MB chip disk and 64MB RAM. The necessary circuits for communication with either the DAE3 electronic box as well as the 16-bit AD-converter system for optical detection and digital I/O interface are contained on the DASY4/DASY5 I/O-board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation.



The PC-operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with two expansion slots which are reserved for future applications. Please note that the expansion slots do not have a standardized pinout and therefore only the expansion cards provided by SPEAG can be inserted. Expansion cards from any other supplier could seriously damage the measurement server. Calibration: No calibration required.

### Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE3) consists of a highly sensitive electrometer grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock. The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



### EX3DV4 Isotropic E-Field Probe for Dosimetric Measurements

|                       |   |
|-----------------------|---|
| <b>Construction:</b>  | Symmetrical design with triangular core<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE)             |
| <b>Calibration:</b>   | Basic Broad Band Calibration in air: 10-3000 MHz.<br>Conversion Factors (CF) for HSL 900 and HSL 1800<br>CF-Calibration for other liquids and frequencies upon request. |
| <b>Frequency:</b>     | 10 MHz to > 6 GHz; Linearity: $\pm 0.2$ dB (30 MHz to 3 GHz)  |
| <b>Directivity:</b>   | $\pm 0.3$ dB in HSL (rotation around probe axis)<br>$\pm 0.5$ dB in HSL (rotation normal to probe axis)   |
| <b>Dynamic Range:</b> | 10 $\mu$ W/g to > 100 mW/g; Linearity: $\pm 0.2$ dB<br>(noise: typically < 1 $\mu$ W/g)   |





**Dimensions:** Overall length: 330 mm (Tip: 20 mm)  
Tip diameter: 2.5 mm (Body: 12 mm)  
Distance from probe tip to dipole centers: 1 mm

**Application:** High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields). Only probe which enables compliance testing for frequencies up to 6 GHz with precision of better 30%.



Interior of probe


### SAM Phantom (V4.0)

**Construction:** The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528-200X, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

**Shell Thickness:**  $2 \pm 0.2$  mm

**Filling Volume:** Approx. 25 liters

**Dimensions:** Height: 810mm; Length: 1000mm; Width: 500mm



### SAM Phantom (ELI4)

#### Description

**Construction:** Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with the latest draft of the standard IEC 62209 Part II and all known tissue simulating liquids. ELI4 has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is supported by software version DASY4/DASY5.5 and higher and is compatible with all SPEAG dosimetric probes and dipoles

**Shell Thickness:**  $2.0 \pm 0.2$  mm (sagging: <1%)

**Filling Volume:** Approx. 25 liters

**Dimensions:** Major ellipse axis: 600 mm  
Minor axis: 400 mm 500mm





## Device Holder for SAM Twin Phantom

**Construction:** In combination with the Twin SAM Phantom V4.0 or Twin SAM, the Mounting Device (made from POM) enables the rotation of the mounted transmitter in spherical coordinates, whereby the rotation point is the ear opening. The devices can be easily and accurately positioned according to IEC, IEEE, CENELEC, FCC or other specifications. The device holder can be locked at different phantom locations (left head, right head, and flat phantom).



## System Validation Kits for SAM Phantom (V4.0)

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 450, 900, 1800, 2450, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:** D450V2: dipole length: 270 mm; overall height: 330 mm  
D835V2: dipole length: 161 mm; overall height: 340 mm  
D900V2: dipole length: 148.5 mm; overall height: 340 mm  
D1800V2: dipole length: 72.5 mm; overall height: 300 mm  
D1900V2: dipole length: 67.7 mm; overall height: 300 mm  
D1900V3: dipole length: 67.0 mm; overall height: 300 mm  
D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm



## System Validation Kits for ELI4 phantom

**Construction:** Symmetrical dipole with 1/4 balun Enables measurement of feedpoint impedance with NWA Matched for use near flat phantoms filled with brain simulating solutions Includes distance holder and tripod adaptor.

**Frequency:** 450, 900, 1800, 2450, 5800 MHz

**Return loss:** > 20 dB at specified validation position

**Power capability:** > 100 W (f < 1GHz); > 40 W (f > 1GHz)

**Dimensions:** D450V2: dipole length: 270 mm; overall height: 330 mm  
D835V2: dipole length: 161 mm; overall height: 340 mm  
D900V2: dipole length: 148.5 mm; overall height: 340 mm  
D1800V2: dipole length: 72.5 mm; overall height: 300 mm  
D1900V2: dipole length: 67.7 mm; overall height: 300 mm  
D1900V3: dipole length: 67.0 mm; overall height: 300 mm  
D2450V2: dipole length: 51.5 mm; overall height: 290 mm  
D5GHzV2: dipole length: 20.6 mm; overall height: 300 mm





## 5. EVALUATION PROCEDURES

### DATA EVALUATION

The DASY4/DAST5 post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

|                    |                           |                                  |
|--------------------|---------------------------|----------------------------------|
| Probe parameters:  | - Sensitivity             | $Norm_i, a_{i0}, a_{i1}, a_{i2}$ |
|                    | - Conversion factor       | $ConvF_i$                        |
|                    | - Diode compression point | $dcp_i$                          |
| Device parameters: | - Frequency               | $f$                              |
|                    | - Crest factor            | $cf$                             |
| Media parameters:  | - Conductivity            | $\sigma$                         |
|                    | - Density                 | $\rho$                           |

These parameters must be set correctly in the software. They can be found in the component documents or be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

|      |         |                                   |                  |
|------|---------|-----------------------------------|------------------|
| with | $V_i$   | = Compensated signal of channel i | (i = x, y, z)    |
|      | $U_i$   | = Input signal of channel i       | (i = x, y, z)    |
|      | $cf$    | = Crest factor of exciting field  | (DASY parameter) |
|      | $dcp_i$ | = Diode compression point         | (DASY parameter) |

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with  $V_i$  = Compensated signal of channel i (i = x, y, z)

$Norm_i$  = Sensor sensitivity of channel i (i = x, y, z)

$\mu\text{V}/(\text{V}/\text{m})^2$  for E0field Probes

$ConvF$  = Sensitivity enhancement in solution

$a_{ij}$  = Sensor sensitivity factors for H-field probes

$f$  = Carrier frequency (GHz)

$E_i$  = Electric field strength of channel i in V/m

$H_i$  = Magnetic field strength of channel i in A/m



The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with  $SAR$  = local specific absorption rate in mW/g

$E_{tot}$  = total field strength in V/m

$\sigma$  = conductivity in [mho/m] or [Siemens/m]

$\rho$  = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770} \quad \text{or} \quad P_{pwe} = H_{tot}^2 \cdot 37.7$$

with  $P_{pwe}$  = Equivalent power density of a plane wave in mW/cm<sup>2</sup>

$E_{tot}$  = total electric field strength in V/m

$H_{tot}$  = total magnetic field strength in A/m



## **SAR MEASUREMENT PROCEDURES**

The procedure for assessing the peak spatial-average SAR value consists of the following steps:

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY4/DAST5 software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to **15 mm by 15 mm** and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 7x7x9 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have DASY4/DAST5 software stop the measurements if this limit is exceeded.

- **Z-Scan**

The Z Scan job measures points along a vertical straight line. The line runs along the Z-axis of a one-dimensional grid. A user can anchor the grid to the current probe location. As with any other grids, the local Z-axis of the anchor location establishes the Z-axis of the grid.



## SPATIAL PEAK SAR EVALUATION

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1 g and 10 g.

The DASY4/DAST5 system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

### Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation.

Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 7x7x9 measurement points with 5mm resolution amounting to 441 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

### Boundary effect

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosimetric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_o + S_b \exp\left(-\frac{z}{a}\right) \cos\left(\pi \frac{z}{\lambda}\right)$$

Since the decay of the boundary effect dominates for small probes ( $a \ll \lambda$ ), the cos-term can be omitted. Factors  $S_b$  (parameter Alpha in the DASY4/DAST5 software) and  $a$  (parameter Delta in the DASY4/DAST5 software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- the boundary curvature is small
- the probe axis is angled less than 30° to the boundary normal
- the distance between probe and boundary is larger than 25% of the probe diameter
- the probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY4/DAST5 system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during postprocessing.



## 6. MEASUREMENT UNCERTAINTY

DASY4:

| UNCERTAINTY BUDGE ACCORDING TO IEEE P1528 |                           |                          |            |                 |                               |                    |
|---|---------------------------|--------------------------|------------|-----------------|-------------------------------|--------------------|
| Error Description                         | Uncertainty Value $\pm\%$ | Probability distribution | Divisor    | $C_1 1g$        | Standard unc.(1g/10g) $\pm\%$ | $V_1$ or $V_{eff}$ |
| <b>Measurement System</b>                 |                           |                          |            |                 |                               |                    |
| Probe calibration                         | $\pm 4.8$                 | normal                   | 1          | 1               | $\pm 4.8$                     | $\infty$           |
| Axial isotropy of probe                   | $\pm 4.6$                 | rectangular              | $\sqrt{3}$ | $(1-C_p)^{1/2}$ | $\pm 1.9$                     | $\infty$           |
| Sph. Isotropy of probe                    | $\pm 9.7$                 | rectangular              | $\sqrt{3}$ | $(C_p)^{1/2}$   | $\pm 3.9$                     | $\infty$           |
| Probe linearity                           | $\pm 4.5$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 2.7$                     | $\infty$           |
| Detection Limit                           | $\pm 0.9$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 0.6$                     | $\infty$           |
| Boundary effects                          | $\pm 8.5$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 4.8$                     | $\infty$           |
| Readoutelectronics                        | $\pm 1.0$                 | normal                   | 1          | 1               | $\pm 1.0$                     | $\infty$           |
| Response time                             | $\pm 0.9$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 0.5$                     | $\infty$           |
| Integration time                          | $\pm 1.2$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 0.8$                     | $\infty$           |
| Mech Constrains of robot                  | $\pm 0.5$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 0.2$                     | $\infty$           |
| Probe positioning                         | $\pm 2.7$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 1.7$                     | $\infty$           |
| Extrap. And integration                   | $\pm 4.0$                 | rectangular              | $\sqrt{3}$ | 1               | $\pm 2.3$                     | $\infty$           |
| RF ambient conditiona                     | $\pm 0.54$                | rectangular              | $\sqrt{3}$ | 1               | $\pm 0.43$                    | $\infty$           |
| <b>Test Sample Related</b>                |                           |                          |            |                 |                               |                    |
| Device positioning                        | $\pm 2.2$                 | normal                   | 1          | 1               | $\pm 2.23$                    | 11                 |
| Device holder uncertainty                 | $\pm 5$                   | normal                   | 1          | 1               | $\pm 5.0$                     | 7                  |
| Power drift                               | $\pm 5$                   | rectangular              | $\sqrt{3}$ | 1               | $\pm 2.9$                     | $\infty$           |
| <b>Phantom and Set up</b>                 |                           |                          |            |                 |                               |                    |
| Phantom uncertainty                       | $\pm 4$                   | rectangular              | $\sqrt{3}$ | 1               | $\pm 2.3$                     | $\infty$           |
| Liquid conductivity                       | $\pm 5$                   | rectangular              | $\sqrt{3}$ | 0.6             | $\pm 1.7$                     | $\infty$           |
| Liquid conductivity                       | $\pm 5$                   | rectangular              | $\sqrt{3}$ | 0.6             | $\pm 3.5/1.7$                 | $\infty$           |
| Liquid permittivity                       | $\pm 5$                   | rectangular              | $\sqrt{3}$ | 0.6             | $\pm 1.7$                     | $\infty$           |
| Liquid permittivity                       | $\pm 5$                   | rectangular              | $\sqrt{3}$ | 0.6             | $\pm 1.7$                     | $\infty$           |
|   |                           |                          |            |                 |                               |                    |
| <b>Combined Standard Uncertainty</b>      |                           |                          |            |                 | $\pm 12.14/11.76$             |                    |
| <b>Coverage Factor for 95%</b>            |                           | kp=2                     |            |                 |                               |                    |
| <b>Expanded Standard Uncertainty</b>      |                           |                          |            |                 | $\pm 24.29/23.51$             |                    |

Table: Worst-case uncertainty for DASY4 assessed according to IEEE P1528.

The budge is valid for the frequency range 300 MHz to 6G Hz and represents a worst-case analysis.



Dasy5:

| UNCERTAINTY BUDGE ACCORDING TO IEEE P1528 |                      |                          |         |                                    |                          |                                    |
|---|----------------------|--------------------------|---------|------------------------------------|--------------------------|------------------------------------|
| Error Description                         | Uncertainty Value ±% | Probability distribution | Divisor | C <sub>1</sub> 1g                  | Standard unc.(1g/10g) ±% | V <sub>1</sub> or V <sub>eff</sub> |
| <b>Measurement System</b>                 |                      |                          |         |                                    |                          |                                    |
| Probe calibration                         | ±5.9                 | normal                   | 1       | 1                                  | ±5.9                     | ∞                                  |
| Axial isotropy of probe                   | ±4.7                 | rectangular              | √3      | (1-C <sub>p</sub> ) <sup>1/2</sup> | ±1.9                     | ∞                                  |
| Sph. Isotropy of probe                    | ±9.6                 | rectangular              | √3      | (C <sub>p</sub> ) <sup>1/2</sup>   | ±3.9                     | ∞                                  |
| Probe linearity                           | ±4.7                 | rectangular              | √3      | 1                                  | ±2.7                     | ∞                                  |
| Detection Limit                           | ±1.0                 | rectangular              | √3      | 1                                  | ±0.6                     | ∞                                  |
| Boundary effects                          | ±1.0                 | rectangular              | √3      | 1                                  | ±0.6                     | ∞                                  |
| Readoutelectronics                        | ±0.3                 | normal                   | 1       | 1                                  | ±0.3                     | ∞                                  |
| Response time                             | ±0.8                 | rectangular              | √3      | 1                                  | ±0.5                     | ∞                                  |
| Integration time                          | ±2.6                 | rectangular              | √3      | 1                                  | ±1.5                     | ∞                                  |
| Probe positioning                         | ±0.4                 | rectangular              | √3      | 1                                  | ±0.2                     | ∞                                  |
| Extrap. And integration                   | ±4.0                 | rectangular              | √3      | 1                                  | ±2.3                     | ∞                                  |
| RF ambient conditiona                     | ±3.0                 | rectangular              | √3      | 1                                  | ±1.7                     | ∞                                  |
| RF ambient conditiona                     | ±3.0                 | rectangular              | √3      | 1                                  | ±1.7                     | ∞                                  |
| <b>Test Sample Related</b>                |                      |                          |         |                                    |                          |                                    |
| Device positioning                        | ±2.9                 | normal                   | 1       | 1                                  | ±2.9                     | 145                                |
| Device holder uncertainty                 | ±3.6                 | normal                   | 1       | 1                                  | ±3.6                     | 5                                  |
| Power drift                               | ±5.0                 | rectangular              | √3      | 1                                  | ±2.9                     | ∞                                  |
| <b>Phantom and Set up</b>                 |                      |                          |         |                                    |                          |                                    |
| Phantom uncertainty                       | ±4.0                 | rectangular              | √3      | 1                                  | ±2.3                     | ∞                                  |
| Liquid conductivity                       | ±5.0                 | rectangular              | √3      | 0.6                                | ±1.8/1.2                 | ∞                                  |
| Liquid conductivity                       | ±1.5                 | rectangular              | √3      | 0.6                                | ±0.6                     | ∞                                  |
| Liquid permittivity                       | ±5.0                 | rectangular              | √3      | 0.6                                | ±1.7/1.4                 | ∞                                  |
| Liquid permittivity                       | ±1.0                 | rectangular              | √3      | 0.6                                | ±0.4                     | ∞                                  |
| <b>Combined Standard Uncertainty</b>      |                      |                          |         |                                    |                          |                                    |
| <b>Coverage Factor for 95%</b>            |                      | kp=2                     |         |                                    |                          |                                    |
| <b>Expanded Standard Uncertainty</b>      |                      |                          |         |                                    | ±20.75/±19.23            |                                    |

Table: Worst-case uncertainty for DASY5 assessed according to IEEE P1528.

The budge is valid for the frequency range 300 MHz to 6G Hz and represents a worst-case analysis.



## **7. EXPOSURE LIMIT**

### **(A). Limits for Occupational/Controlled Exposure (W/kg)**

| <u>Whole-Body</u> | <u>Partial-Body</u> | <u>Hands, Wrists, Feet and Ankles</u> |
|-------------------|---------------------|---------------------------------------|
| 0.4               | 8.0                 | 2.0                                   |

### **(B). Limits for General Population/Uncontrolled Exposure (W/kg)**

| <u>Whole-Body</u> | <u>Partial-Body</u> | <u>Hands, Wrists, Feet and Ankles</u> |
|-------------------|---------------------|---------------------------------------|
| 0.08              | 1.6                 | 4.0                                   |

**NOTE:** *Whole-Body SAR* is averaged over the entire body, *partial-body SAR* is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. *SAR for hands, wrists, feet and ankles* is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

#### **Population/Uncontrolled Environments:**

are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

#### **Occupational/Controlled Environments:**

are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

**NOTE**  
**GENERAL POPULATION/UNCONTROLLED EXPOSURE**  
**PARTIAL BODY LIMIT**  
**1.6 W/kg**



## 8. TYPICAL COMPOSITION OF INGREDIENTS FOR LIQUID TISSUE PHANTOMS

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

| Ingredients<br>(% by weight) | Frequency (MHz) |       |       |      |       |       |       |      |      |      |
|------------------------------|-----------------|-------|-------|------|-------|-------|-------|------|------|------|
|                              | 450             |       | 835   |      | 915   |       | 1900  |      | 2450 |      |
| Tissue Type                  | Head            | Body  | Head  | Body | Head  | Body  | Head  | Body | Head | Body |
| Water                        | 38.56           | 51.16 | 41.45 | 52.4 | 41.05 | 56.0  | 54.9  | 40.4 | 62.7 | 73.2 |
| Salt (NaCl)                  | 3.95            | 1.49  | 1.45  | 1.4  | 1.35  | 0.76  | 0.18  | 0.5  | 0.5  | 0.04 |
| Sugar                        | 56.32           | 46.78 | 56.0  | 45.0 | 56.5  | 41.76 | 0.0   | 58.0 | 0.0  | 0.0  |
| HEC                          | 0.98            | 0.52  | 1.0   | 1.0  | 1.0   | 1.21  | 0.0   | 1.0  | 0.0  | 0.0  |
| Bactericide                  | 0.19            | 0.05  | 0.1   | 0.1  | 0.1   | 0.27  | 0.0   | 0.1  | 0.0  | 0.0  |
| Triton X-100                 | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 0.0   | 0.0  | 36.8 | 0.0  |
| DGBE                         | 0.0             | 0.0   | 0.0   | 0.0  | 0.0   | 0.0   | 44.92 | 0.0  | 0.0  | 26.7 |
| Dielectric Constant          | 43.42           | 58.0  | 42.54 | 56.1 | 42.0  | 56.8  | 39.9  | 54.0 | 39.8 | 52.5 |
| Conductivity (S/m)           | 0.85            | 0.83  | 0.91  | 0.95 | 1.0   | 1.07  | 1.42  | 1.45 | 1.88 | 1.78 |

Salt: 99<sup>+</sup>% Pure Sodium ChlorideSugar: 98<sup>+</sup>% Pure SucroseWater: De-ionized, 16 MΩ<sup>+</sup> resistivity

HEC: Hydroxyethyl Cellulose

DGBE: 99<sup>+</sup>% Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1, 1, 3, 3-tetramethylbutyl)phenyl]ether



## 9. MEASUREMENT RESULTS

### 9.1 TEST LIQUID CONFIRMATION

#### SIMULATING LIQUIDS PARAMETER CHECK

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the dielectric parameters are within the tolerances of the specified target values

The relative permittivity and conductivity of the tissue material should be within  $\pm 5\%$  of the values given in the table below. 5% may not be easily achieved at certain frequencies. Under such circumstances, 10% tolerance may be used until more precise tissue recipes are available

#### IEEE SCC-34/SC-2 P1528 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations and extrapolated according to the head parameters specified in P1528

| Target Frequency<br>(MHz) | Head         |                | Body         |                |
|---------------------------|--------------|----------------|--------------|----------------|
|                           | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 150                       | 52.3         | 0.76           | 61.9         | 0.80           |
| 300                       | 45.3         | 0.87           | 58.2         | 0.92           |
| 450                       | 43.5         | 0.87           | 56.7         | 0.94           |
| 835                       | 41.5         | 0.90           | 55.2         | 0.97           |
| 900                       | 41.5         | 0.97           | 55.0         | 1.05           |
| 915                       | 41.5         | 0.98           | 55.0         | 1.06           |
| 1450                      | 40.5         | 1.20           | 54.0         | 1.30           |
| 1610                      | 40.3         | 1.29           | 53.8         | 1.40           |
| 1800-2000                 | 40.0         | 1.40           | 53.3         | 1.52           |
| 2450                      | 39.2         | 1.80           | 52.7         | 1.95           |
| 3000                      | 38.5         | 2.40           | 52.0         | 2.73           |
| 5800                      | 45.3         | 5.27           | 48.2         | 6.00           |

#### SIMULATING LIQUIDS PARAMETER CHECK RESULTS

**Date:** January 01, 2011      **Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulatinf Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 835 MHz                | 23.60      | 15.00      | Permitivity:  | 55.20  | 55.00    | -0.36         | ±5          |
|                        |            |            | Conductivity: | 0.97   | 0.960    | -1.03         | ± 5         |

**Date:** January 09, 2011      **Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulatinf Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 835 MHz                | 23.60      | 15.00      | Permitivity:  | 55.20  | 55.00    | -0.36         | ±5          |
|                        |            |            | Conductivity: | 0.97   | 0.960    | -1.03         | ± 5         |

**Date:** January 18, 2011    **Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulating Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 835 MHz                | 23.60      | 15.00      | Permitivity:  | 55.20  | 55.00    | -0.36         | ±5          |
|                        |            |            | Conductivity: | 0.97   | 0.950    | -2.06         | ± 5         |

**Date:** January 05, 2011    **Ambient condition:** Temperature 24.6°C; Relative humidity: 53%


| Body Simulating Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth (cm) |               |        |          |               |             |
| 1900 MHz               | 23.60      | 15.00      | Permitivity:  | 53.30  | 51.80    | -2.81         | ± 5         |
|                        |            |            | Conductivity: | 1.52   | 1.50     | -1.32         | ± 5         |

**Date:** January 11, 2011    **Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulating Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth (cm) |               |        |          |               |             |
| 1900 MHz               | 23.60      | 15.00      | Permitivity:  | 53.30  | 52.50    | -1.50         | ± 5         |
|                        |            |            | Conductivity: | 1.52   | 1.53     | 0.66          | ± 5         |

**Date:** January 18, 2011    **Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulating Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth (cm) |               |        |          |               |             |
| 1900 MHz               | 23.60      | 15.00      | Permitivity:  | 53.30  | 51.70    | -3.00         | ± 5         |
|                        |            |            | Conductivity: | 1.52   | 1.52     | 0.00          | ± 5         |





## 9.2 SYSTEM PERFORMANCE CHECK

The system performance check is performed prior to any usage of the system in order to guarantee reproducible results. The system performance check verifies that the system operates within its specifications. The system performance check results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

### SYSTEM PERFORMANCE CHECK MEASUREMENT CONDITIONS

- The measurements were performed in the flat section of the SAM twin phantom filled with Body simulating liquid of the following parameters.
- The DASY4/DAST5 system with an E-field probe EX3DV4 SN:3578 was used for the measurements.
- The dipole was mounted on the small tripod so that the dipole feed point was positioned below the center marking of the flat phantom section and the dipole was oriented parallel to the body axis (the long side of the phantom). The standard measuring distance was 15 mm (below 1 GHz) and 10 mm (above 1 GHz) from dipole center to the simulating liquid surface.
- The coarse grid with a grid spacing of 10mm was aligned with the dipole.
- Special 7x7x7 fine cube was chosen for cube integration ( $dx = 5$  mm,  $dy = 5$  mm,  $dz = 5$  mm).
- Distance between probe sensors and phantom surface was set to 2.5 mm.
- The dipole input power (forward power) was  $250 \text{ mW} \pm 3\%$ .
- The results are normalized to 1 W input power.

#### Reference SAR values

The reference SAR values were using measurement results indicated in the dipole calibration document (see table below)

| Frequency (MHz) | 1g SAR | 10g SAR | Local SAR at Surface (Above Feed Point) | Local SAR at Surface (y = 2cm offset from feed point) |
|-----------------|--------|---------|---|---|
| 900             | 10.3   | 6.57    | 16.4                                    | 5.4   |
| 1800            | 38.2   | 20.3    | 69.5                                    | 6.8   |
| 2450(Body)      | 51.4   | 24.2    | 128.8                                   | N/A   |

## SYSTEM PERFORMANCE CHECK RESULTS

**Dipole: D835V2-SN: 4d015**

**Date:** January 01, 2011      **Ambient condition:** Temperature  $24.6^\circ\text{C}$ ; Relative humidity: 53%

| Body Simulation Liquid |            |            | Parameters    | Target | Measured | Deviation[%] | Limited[%] |
|------------------------|------------|------------|---------------|--------|----------|--------------|------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |              |            |
| 835.00                 | 23.60      | 15.00      | Permitivity:  | 55.20  | 55.00    | -0.36        | ±5         |
|                        |            |            | Conductivity: | 0.97   | 0.96     | -1.03        | ± 5        |
|                        |            |            | 1g SAR:       | 9.85   | 9.88     | 0.30         | ± 5        |

ps. 1g SAR is equal  $4 \times 2.472(250\text{mW}$  forward power SAR value)

**Dipole: D835V2-SN: 4d015****Date:** January 09, 2011**Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulation Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 835.00                 | 23.60      | 15.00      | Permitivity:  | 55.20  | 55.10    | -0.18         | ±5          |
|                        |            |            | Conductivity: | 0.97   | 0.97     | 0.00          | ± 5         |
|                        |            |            | 1g SAR:       | 9.85   | 9.80     | -0.51         | ± 5         |

ps. 1g SAR is equal 4x2.45(250mW forward power SAR value)

**Dipole: D835V2-SN: 4d015****Date:** January 18, 2011**Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulation Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 835.00                 | 23.60      | 15.00      | Permitivity:  | 55.20  | 55.00    | -0.36         | ±5          |
|                        |            |            | Conductivity: | 0.97   | 0.95     | -2.06         | ± 5         |
|                        |            |            | 1g SAR:       | 9.85   | 9.72     | -1.32         | ± 5         |

ps. 1g SAR is equal 4x2.43(250mW forward power SAR value)

**Dipole: D1900V2 SN: 5d056****Date:** January 05, 2011**Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulation Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 1900.00                | 23.60      | 15.00      | Permitivity:  | 53.30  | 51.80    | -2.81         | ±5          |
|                        |            |            | Conductivity: | 1.52   | 1.50     | -1.32         | ± 5         |
|                        |            |            | 1g SAR:       | 39.80  | 40.40    | 1.51          | ± 5         |

ps. 1g SAR is equal 4x10.1(250mW forward power SAR value)

**Dipole: D1900V2 SN: 5d056****Date:** January 11, 2011**Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulation Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 1900.00                | 23.60      | 15.00      | Permitivity:  | 53.30  | 52.50    | -1.50         | ±5          |
|                        |            |            | Conductivity: | 1.52   | 1.53     | 0.66          | ± 5         |
|                        |            |            | 1g SAR:       | 39.80  | 39.60    | -0.50         | ± 5         |

ps. 1g SAR is equal 4x9.9(250mW forward power SAR value)

**Dipole: D1900V2 SN: 5d056****Date:** January 18, 2011**Ambient condition:** Temperature 24.6°C; Relative humidity: 53%

| Body Simulation Liquid |            |            | Parameters    | Target | Measured | Deviation[% ] | Limited[% ] |
|------------------------|------------|------------|---------------|--------|----------|---------------|-------------|
| Frequency              | Temp. [°C] | Depth [cm] |               |        |          |               |             |
| 1900.00                | 23.60      | 15.00      | Permitivity:  | 53.30  | 51.70    | -3.00         | ±5          |
|                        |            |            | Conductivity: | 1.52   | 1.52     | 0.00          | ± 5         |
|                        |            |            | 1g SAR:       | 39.80  | 40.40    | 1.51          | ± 5         |

ps. 1g SAR is equal 4x10.1(250mW forward power SAR value)



### **9.3 EUT TUNE-UP PROCEDURES AND TEST MODE**

- Software used to control the EUT for staying in continuous transmitting mode was programmed.
- The output power (dBm) of the measured channel was measured before and after SAR test.
- During SAR test, the highest output channel per band measured first.
- The EUT is a Tablet computer and there are six configuration modes during SAR testing: 1)Notebook mode 、 2)Lap Head 、 3)Primary Landscape 、 4)Primary Portrait 、 5)Secondary Landscape(disable via software) 、 6)Secondary Portrait.
- There are four batteries for SAR testing(model no: 42T4878, 42T4882, 42T4880, 42T4904), and model no 42T4904 is the worst.
- This EUT screen can't rotation 180°(Secondary Landscape, disable via software), can rotation 90° and 270°(Left).

#### **GSM 850 / GPRS 850 / EDGE 850**

Network Support: *GSM only / GPRS/EDGE*

Main Service: *Circuit Switched / Packet data / Packet data*

Power Setting: *33dBm / 33dBm / 27dBm*

Class: 10 (2 Up / 3 Down)

#### **GSM 1900 / GPRS 1900 / EDGE 1900**

Network Support: *GSM only / GPRS/EDGE*

Main Service: *Circuit Switched / Packet data / Packet data*

Power Setting: *30dBm / 30dBm / 26dBm*

Class: 10 (2 Up / 3 Down)

*Output powers are measured as below:*

The respectively maximum output powers of each RF modes are as below:

#### **GPRS/EDGE output power (Average)(dBm)**

| channel   |        | Power  |       |
|-----------|--------|--------|-------|
|           |        | GPRS   | EDGE  |
| 850 band  | Ch 128 | 27.12  | 24.58 |
|           | Ch 190 | 27.08  | 24.90 |
|           | Ch 251 | 27.08  | 24.78 |
| 1900 band | Ch 512 | 23.38. | 23.08 |
|           | Ch 661 | 23.48  | 23.18 |
|           | Ch 810 | 23.69  | 23.30 |



## 9.4 RF POWER OUTPUT FOR UMTS REL99

The following tests were completed according to the test requirements outlined in section 5.2 of the 3GPP TS34.121-1 V8.7.0 specification. The EUT supports power Class 3, which has a nominal maximum output power of 24 dBm (+1.7/-3.7) 12.2kps RMC is used for this testing. Power control set to All bits up. A summary of these settings are illustrated below:

|                        |                         |                |
|------------------------|-------------------------|----------------|
|                        | Mode                    | Rel99          |
|                        | Subtest                 | -              |
| WCDMA General Settings | Loopback Mode           | Test Mode 1    |
|                        | Rel99 RMC               | 12.2kbps RMC   |
|                        | HSDPA FRC               | Not Applicable |
|                        | HSUPA Test              | Not Applicable |
|                        | Power Control Algorithm | Algorithm2     |
|                        | $\beta_c$               | Not Applicable |
|                        | $\beta_d$               | Not Applicable |
|                        | $\beta_{ec}$            | Not Applicable |
|                        | $\beta_c/\beta_d$       | 8/15           |
|                        | $\beta_{hs}$            | Not Applicable |
|                        | $\beta_{ed}$            | Not Applicable |

| Band                  | UL Ch | DL Ch | Frequency | Conducted output power (dBm) |
|-----------------------|-------|-------|-----------|------------------------------|
|                       |       |       |           | Average                      |
| UMTS1900<br>(Band II) | 9262  | 9662  | 1852.4    | 25.91                        |
|                       | 9400  | 9800  | 1880      | 26.45                        |
|                       | 9538  | 9938  | 1907.6    | 26.04                        |
| UMTS850<br>(Band V)   | 4132  | 4357  | 826.4     | 27.46                        |
|                       | 4182  | 4407  | 836.4     | 27.48                        |
|                       | 4233  | 4458  | 846.6     | 27.45                        |



## 9.5 RF POWER OUTPUT FOR UMTS REL 6 HSDPA

The following Sub-Tests were completed according to the test requirements outlined in section 5.2A of the 3GPP TS34.121-1 V8.7.0 specification. All TX RMS and Peak power requirements for Power Class 3 were met according to table 5.2AA.5 and achieved through the outlined test procedure in section 5.2AA.4.2. A summary of these settings are illustrated below:

|                         | Mode                                 | Rel6 HSDPA     | Rel6 HSDPA | Rel6 HSDPA | Rel6 HSDPA |
|-------------------------|--------------------------------------|----------------|------------|------------|------------|
|                         | Subtest                              | 1              | 2          | 3          | 4          |
| WCDMA General Settings  | Loopback Mode                        | Test Mode 1    |            |            |            |
|                         | Rel99 RMC                            | 12.2kbps RMC   |            |            |            |
|                         | HSDPA FRC                            | H-Set1         |            |            |            |
|                         | HSUPA Test                           | Not Applicable |            |            |            |
|                         | Power Control Algorithm              | Algorithm 2    |            |            |            |
|                         | $\beta_c$                            | 2/15           | 12/15      | 15/15      | 15/15      |
|                         | $\beta_d$                            | 15/15          | 15/15      | 8/15       | 4/15       |
|                         | $\beta_{ec}$                         | -              | -          | -          | -          |
|                         | $\beta_c/\beta_d$                    | 2/15           | 12/15      | 15/8       | 15/4       |
|                         | $\beta_{hs}$                         | 4/15           | 24/15      | 30/15      | 30/15      |
|                         | $\beta_{ed}$                         | Not Applicable |            |            |            |
| HSDPA Specific Settings | DACK                                 | 8              |            |            |            |
|                         | DNAK                                 | 8              |            |            |            |
|                         | DCQI                                 | 8              |            |            |            |
|                         | Ack-Nack repetition factor           | 3              |            |            |            |
|                         | CQI Feedback (Table 5.2B.4)          | 4ms            |            |            |            |
|                         | CQI Repetition Factor (Table 5.2B.4) | 2              |            |            |            |
|                         | Ahs = $\beta_{hs}/\beta_c$           | 30/15          |            |            |            |

### Result

| Band                  | Subtest | UL Ch | DL Ch | Frequency | Conducted output power (dBm) |  |
|-----------------------|---------|-------|-------|-----------|------------------------------|--|
|                       |         |       |       |           | Average                      |  |
| UMTS1900<br>(Band II) | 1       | 9262  | 9662  | 1852.4    | 25.46                        |  |
|                       |         | 9400  | 9800  | 1880.0    | 25.83                        |  |
|                       |         | 9538  | 9938  | 1907.6    | 25.61                        |  |
|                       | 2       | 9262  | 9662  | 1852.4    | 25.36                        |  |
|                       |         | 9400  | 9800  | 1880.0    | 25.79                        |  |
|                       |         | 9538  | 9938  | 1907.6    | 25.55                        |  |
|                       | 3       | 9262  | 9662  | 1852.4    | 25.01                        |  |
|                       |         | 9400  | 9800  | 1880.0    | 25.23                        |  |
|                       |         | 9538  | 9938  | 1907.6    | 24.99                        |  |
|                       | 4       | 9262  | 9662  | 1852.4    | 24.98                        |  |
|                       |         | 9400  | 9800  | 1880.0    | 25.22                        |  |
|                       |         | 9538  | 9938  | 1907.6    | 24.95                        |  |
| UMTS850<br>(Band V)   | 1       | 4132  | 4357  | 826.4     | 26.88                        |  |
|                       |         | 4182  | 4407  | 836.4     | 26.95                        |  |
|                       |         | 4233  | 4458  | 846.6     | 26.82                        |  |
|                       | 2       | 4132  | 4357  | 826.4     | 26.78                        |  |
|                       |         | 4182  | 4407  | 836.4     | 26.88                        |  |
|                       |         | 4233  | 4458  | 846.6     | 26.75                        |  |
|                       | 3       | 4132  | 4357  | 826.4     | 26.38                        |  |
|                       |         | 4182  | 4407  | 836.4     | 26.55                        |  |
|                       |         | 4233  | 4458  | 846.6     | 26.22                        |  |
|                       | 4       | 4132  | 4357  | 826.4     | 26.28                        |  |
|                       |         | 4182  | 4407  | 836.4     | 26.31                        |  |
|                       |         | 4233  | 4458  | 846.6     | 26.15                        |  |



## 9.6 RF POWER OUTPUT UMTS REL 6 HSPA (HSDPA & HSUPA)

The following 5 Sub-Tests were completed according to the test requirements outlined in section 5.2B of the 3GPP TS34.121-1 V8.7.0 specification. All TX RMS and Peak power requirements were met according to table 5.2B.5 and achieved through the outlined test procedure in section 5.2B.4.2. A summary of these settings are illustrated below:

|                         | Mode                                 | Rel6 HSUPA   | Rel6 HSUPA | Rel6 HSUPA | Rel6 HSUPA   | Rel6 HSUPA |  |
|-------------------------|--------------------------------------|--|------------|------------|--|------------|--|
|                         | Subtest                              | 1  | 2          | 3          | 4  | 5          |  |
| WCDMA General Settings  | Loopback Mode                        | Test Mode 1  |            |            |  |            |  |
|                         | Rel99 RMC                            | 12.2kbps RMC   |            |            |  |            |  |
|                         | HSDPA FRC                            | H-Set1   |            |            |  |            |  |
|                         | HSUPA Test                           | HSUPA Loopback   |            |            |  |            |  |
|                         | Power Control Algorithm              | Algorithm2   |            |            |  |            |  |
|                         | $\beta_c$                            | 11/15  | 6/15       | 15/15      | 2/15   | 15/15      |  |
|                         | $\beta_d$                            | 15/15  | 15/15      | 9/15       | 15/15  | 15/15      |  |
|                         | $\beta_{ec}$                         | 209/225  | 12/15      | 30/15      | 2/15   | 24/15      |  |
|                         | $\beta_c/\beta_d$                    | 11/15  | 6/15       | 15/9       | 2/15   | 15/15      |  |
|                         | $\beta_{hs}$                         | 22/15  | 12/15      | 30/15      | 4/15   | 30/15      |  |
| HSDPA Specific Settings | $\beta_{ed}$                         | 1309/225   | 94/75      | 47/15      | 56/75  | 134/15     |  |
|                         | DACK                                 | 8  |            |            |  |            |  |
|                         | DNAK                                 | 8  |            |            |  |            |  |
|                         | DCQI                                 | 8  |            |            |  |            |  |
|                         | Ack-Nack repetition factor           | 3  |            |            |  |            |  |
|                         | CQI Feedback (Table 5.2B.4)          | 4ms  |            |            |  |            |  |
|                         | CQI Repetition Factor (Table 5.2B.4) | 2  |            |            |  |            |  |
| HSUPA Specific Settings | $A_{hs} = \beta_{hs}/\beta_c$        | 30/15  |            |            |  |            |  |
|                         | D E-DPCCH                            | 6  | 8          | 8          | 5  | 7          |  |
|                         | DHARQ                                | 0  | 0          | 0          | 0  | 0          |  |
|                         | AG Index                             | 20   | 12         | 15         | 17   | 21         |  |
|                         | E-TFCI (from 34.121 Table C.11.1.3)  | 75   | 67         | 92         | 71   | 81         |  |
|                         | Associated Max UL Data Rate kbps     | 242.1  | 174.9      | 482.8      | 205.8  | 308.9      |  |
|                         | Reference E_TFCIs                    | E-TFCI 11<br>E-TFCI PO 4<br>E-TFCI 67<br>E-TFCI PO 18<br>E-TFCI 71<br>E-TFCI PO 23<br>E-TFCI 75<br>E-TFCI PO 26<br>E-TFCI 81<br>E-TFCI PO 27 |            |            | E-TFCI 11<br>E-TFCI PO 4<br>E-TFCI 67<br>E-TFCI PO 18<br>E-TFCI 71<br>E-TFCI PO 23<br>E-TFCI 75<br>E-TFCI PO 26<br>E-TFCI 81<br>E-TFCI PO 27 |            |  |

**REL 6 HSPA (HSDPA & HSUPA)**

| Band                  | Subtest | UL Ch | DL Ch | Frequency | Conducted output power (dBm) |
|-----------------------|---------|-------|-------|-----------|------------------------------|
|                       |         |       |       |           | Average                      |
| UMTS1900<br>(Band II) | 1       | 9262  | 9662  | 1852.4    | 25.20                        |
|                       |         | 9400  | 9800  | 1880.0    | 25.61                        |
|                       |         | 9538  | 9938  | 1907.6    | 25.48                        |
|                       | 2       | 9262  | 9662  | 1852.4    | 23.15                        |
|                       |         | 9400  | 9800  | 1880.0    | 23.51                        |
|                       |         | 9538  | 9938  | 1907.6    | 23.42                        |
|                       | 3       | 9262  | 9662  | 1852.4    | 24.33                        |
|                       |         | 9400  | 9800  | 1880.0    | 24.58                        |
|                       |         | 9538  | 9938  | 1907.6    | 24.38                        |
|                       | 4       | 9262  | 9662  | 1852.4    | 23.09                        |
|                       |         | 9400  | 9800  | 1880.0    | 23.47                        |
|                       |         | 9538  | 9938  | 1907.6    | 23.38                        |
|                       | 5       | 9262  | 9662  | 1852.4    | 25.11                        |
|                       |         | 9400  | 9800  | 1880.0    | 25.55                        |
|                       |         | 9538  | 9938  | 1907.6    | 25.42                        |
| UMTS850<br>(Band V)   | 1       | 4132  | 4357  | 826.4     | 26.62                        |
|                       |         | 4182  | 4407  | 836.4     | 26.68                        |
|                       |         | 4233  | 4458  | 846.6     | 26.61                        |
|                       | 2       | 4132  | 4357  | 826.4     | 24.53                        |
|                       |         | 4182  | 4407  | 836.4     | 24.62                        |
|                       |         | 4233  | 4458  | 846.6     | 24.55                        |
|                       | 3       | 4132  | 4357  | 826.4     | 25.55                        |
|                       |         | 4182  | 4407  | 836.4     | 25.47                        |
|                       |         | 4233  | 4458  | 846.6     | 25.49                        |
|                       | 4       | 4132  | 4357  | 826.4     | 24.47                        |
|                       |         | 4182  | 4407  | 836.4     | 24.55                        |
|                       |         | 4233  | 4458  | 846.6     | 24.49                        |
|                       | 5       | 4132  | 4357  | 826.4     | 26.58                        |
|                       |         | 4182  | 4407  | 836.4     | 26.53                        |
|                       |         | 4233  | 4458  | 846.6     | 26.51                        |



## 9.7 SAR MEASUREMENTS RESULTS

Body position:

|  |                          |   |  |   |  |
|--|--------------------------|---|--|---|--|
|  |                          | <p>Please see separate<br/>Test setup photos.</p> |  | <p>Please see separate<br/>Test setup photos.</p> |  |
|  | <p>Notebook mode</p>     |   |  | <p>Primary Portrait</p>                           |  |
|  |                          | <p>Please see separate<br/>Test setup photos.</p> |  | <p>Please see separate<br/>Test setup photos.</p> |  |
|  | <p>Lap Held</p>          |   |  | <p>Secondary Portrait</p>                         |  |
|  |                          | <p>Please see separate<br/>Test setup photos.</p> |  |   |  |
|  | <p>Primary Landscape</p> |   |  |   |  |

Test mode: GPRS 850, 2Up3Dn

Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |       | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|-------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz   |                   |                           |                 |
| Notebook mode      | Fixed   | 128       | 824.2 | 23.6              | 0.059                     | 1.6             |
| Lap Held           | Fixed   | 128       | 824.2 | 23.6              | 0.038                     |                 |
| Primary Landscape  | Fixed   | 128       | 824.2 | 23.6              | 0.032                     |                 |
| Primary Portrait   | Fixed   | 128       | 824.2 | 23.6              | 0.070                     |                 |
| Secondary Portrait | Fixed   | 128       | 824.2 | 23.6              | 0.943                     |                 |
| Secondary Portrait | Fixed   | 190       | 836.6 | 23.6              | 0.589                     |                 |
| Secondary Portrait | Fixed   | 251       | 848.8 | 23.6              | 0.587                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Bottom Flat position:**

|  |  |  |  |
|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |

Test mode: **EGPRS 850, 2Up3Dn**      Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |       | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|-------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz   |                   |                           |                 |
| Notebook mode      | Fixed   | 190       | 836.6 | 23.6              | 0.032                     | 1.6             |
| Lap Held           | Fixed   | 190       | 836.6 | 23.6              | 0.047                     |                 |
| Primary Landscape  | Fixed   | 190       | 836.6 | 23.6              | 0.017                     |                 |
| Primary Portrait   | Fixed   | 190       | 836.6 | 23.6              | 0.025                     |                 |
| Secondary Portrait | Fixed   | 190       | 836.6 | 23.6              | 0.262                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

| Test mode: <b>GPRS 1900, 2Up3Dn</b> |         |           |        | Depth of liquid: 15.0 cm |                           |                 |
|-------------------------------------|---------|-----------|--------|--------------------------|---------------------------|-----------------|
| EUT Position                        | Antenna | Frequency |        | Liquid<br>Temp_°C        | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|                                     |         | Channel   | MHz    |                          |                           |                 |
| Notebook mode                       | Fixed   | 810       | 1909.8 | 23.6                     | 0.075                     | 1.6             |
| Lap Held                            | Fixed   | 810       | 1909.8 | 23.6                     | 0.069                     |                 |
| Primary Landscape                   | Fixed   | 810       | 1909.8 | 23.6                     | 0.087                     |                 |
| Primary Portrait                    | Fixed   | 810       | 1909.8 | 23.6                     | 0.066                     |                 |
| Secondary Portrait                  | Fixed   | 512       | 1850.2 | 23.6                     | 0.999                     |                 |
| Secondary Portrait                  | Fixed   | 661       | 1880.0 | 23.6                     | 0.880                     |                 |
| Secondary Portrait                  | Fixed   | 810       | 1909.8 | 23.6                     | 1.070                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

Test mode: **EGPRS 1900, 2Up3Dn**      Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |        | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|--------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz    |                   |                           |                 |
| Notebook mode      | Fixed   | 810       | 1909.8 | 23.6              | 0.103                     | 1.6             |
| Lap Held           | Fixed   | 810       | 1909.8 | 23.6              | 0.083                     |                 |
| Primary Landscape  | Fixed   | 810       | 1909.8 | 23.6              | 0.065                     |                 |
| Primary Portrait   | Fixed   | 810       | 1909.8 | 23.6              | 0.057                     |                 |
| Secondary Portrait | Fixed   | 810       | 1909.8 | 23.6              | 0.571                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

Test mode: **WCDMA band V**, Crest Factor=1

Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |       | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|-------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz   |                   |                           |                 |
| Notebook mode      | Fixed   | 4182      | 836.4 | 23.6              | 0.039                     | 1.6             |
| Lap Held           | Fixed   | 4182      | 836.4 | 23.6              | 0.195                     |                 |
| Primary Landscape  | Fixed   | 4182      | 836.4 | 23.6              | 0.026                     |                 |
| Primary Portrait   | Fixed   | 4182      | 836.4 | 23.6              | 0.093                     |                 |
| Secondary Portrait | Fixed   | 4182      | 836.4 | 23.6              | 0.697                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

Test mode: **HSDPA band V, Crest Factor=1**

Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |       | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|-------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz   |                   |                           |                 |
| Notebook mode      | Fixed   | 4182      | 836.4 | 23.6              | 0.024                     | 1.6             |
| Lap Held           | Fixed   | 4182      | 836.4 | 23.6              | 0.155                     |                 |
| Primary Landscape  | Fixed   | 4182      | 836.4 | 23.6              | 0.018                     |                 |
| Primary Portrait   | Fixed   | 4182      | 836.4 | 23.6              | 0.056                     |                 |
| Secondary Portrait | Fixed   | 4182      | 836.4 | 23.6              | 0.465                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

Test mode: **HSUPA band V**, Crest Factor=1

Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |       | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|-------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz   |                   |                           |                 |
| Notebook mode      | Fixed   | 4182      | 836.4 | 23.6              | 0.026                     | 1.6             |
| Lap Held           | Fixed   | 4182      | 836.4 | 23.6              | 0.154                     |                 |
| Primary Landscape  | Fixed   | 4182      | 836.4 | 23.6              | 0.065                     |                 |
| Primary Portrait   | Fixed   | 4182      | 836.4 | 23.6              | 0.061                     |                 |
| Secondary Portrait | Fixed   | 4182      | 836.4 | 23.6              | 0.508                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

Test mode: **WCDMA band II**, Crest Factor=1

Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |        | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|--------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz    |                   |                           |                 |
| Notebook mode      | Fixed   | 9400      | 1880.0 | 23.6              | 0.042                     | 1.6             |
| Lap Held           | Fixed   | 9400      | 1880.0 | 23.6              | 0.098                     |                 |
| Primary Landscape  | Fixed   | 9400      | 1880.0 | 23.6              | 0.078                     |                 |
| Primary Portrait   | Fixed   | 9400      | 1880.0 | 23.6              | 0.120                     |                 |
| Secondary Portrait | Fixed   | 9262      | 1852.4 | 23.6              | 1.180                     |                 |
| Secondary Portrait | Fixed   | 9400      | 1880.0 | 23.6              | 1.050                     |                 |
| Secondary Portrait | Fixed   | 9538      | 1907.6 | 23.6              | 1.060                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

Test mode: **HSDPA band II**, Crest Factor=1

Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |        | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|--------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz    |                   |                           |                 |
| Notebook mode      | Fixed   | 9400      | 1880.0 | 23.6              | 0.040                     | 1.6             |
| Lap Held           | Fixed   | 9400      | 1880.0 | 23.6              | 0.097                     |                 |
| Primary Landscape  | Fixed   | 9400      | 1880.0 | 23.6              | 0.065                     |                 |
| Primary Portrait   | Fixed   | 9400      | 1880.0 | 23.6              | 0.125                     |                 |
| Secondary Portrait | Fixed   | 9400      | 1880.0 | 23.6              | 0.787                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

|  |  |  |  |  |
|--|--|--|--|--|
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Notebook mode</b></p>                              |  | <p><b>Primary Portrait</b></p>                           |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |
|  | <p><b>Lap Held</b></p>                                   |  | <p><b>Secondary Portrait</b></p>                         |  |
|  | <p><b>Please see separate<br/>Test setup photos.</b></p> |  |  |  |
|  | <p><b>Primary Landscape</b></p>                          |  |  |  |

Test mode: **HSUPA band II**, Crest Factor=1

Depth of liquid: 15.0 cm

| EUT Position       | Antenna | Frequency |        | Liquid<br>Temp_°C | <b>SAR (1g)</b><br>(W/kg) | Limit<br>(W/kg) |
|--------------------|---------|-----------|--------|-------------------|---------------------------|-----------------|
|                    |         | Channel   | MHz    |                   |                           |                 |
| Notebook mode      | Fixed   | 9400      | 1880.0 | 23.6              | 0.040                     | 1.6             |
| Lap Held           | Fixed   | 9400      | 1880.0 | 23.6              | 0.096                     |                 |
| Primary Landscape  | Fixed   | 9400      | 1880.0 | 23.6              | 0.054                     |                 |
| Primary Portrait   | Fixed   | 9400      | 1880.0 | 23.6              | 0.128                     |                 |
| Secondary Portrait | Fixed   | 9262      | 1852.4 | 23.6              | 0.849                     |                 |
| Secondary Portrait | Fixed   | 9400      | 1880.0 | 23.6              | 0.887                     |                 |
| Secondary Portrait | Fixed   | 9538      | 1907.6 | 23.6              | 0.746                     |                 |

Notes: 1) Please refer to attachment for the result presentation in plot format.



**Body position:**

Please see separate Test setup photo report.

**Notebook mode Tip edge 25mm**

Test mode: **GPRS 850, 2Up3Dn** Depth of liquid: 15.0 cm

| EUT Position | Antenna | Frequency |       | Liquid Temp_°C | <b>SAR (1g) (W/kg)</b> | Limit (W/kg) |
|--------------|---------|-----------|-------|----------------|------------------------|--------------|
|              |         | Channel   | MHz   |                |                        |              |
| 25mm         | Fixed   | 128       | 824.2 | 23.6           | 0.368                  | 1.6          |

Test mode: **EGPRS 1900, 2Up3Dn** Depth of liquid: 15.0 cm

| EUT Position | Antenna | Frequency |        | Liquid Temp_°C | <b>SAR (1g) (W/kg)</b> | Limit (W/kg) |
|--------------|---------|-----------|--------|----------------|------------------------|--------------|
|              |         | Channel   | MHz    |                |                        |              |
| 25mm         | Fixed   | 810       | 1909.8 | 23.6           | 0.229                  | 1.6          |

Test mode: **WCDMA band V, Crest Factor=1** Depth of liquid: 15.0 cm

| EUT Position | Antenna | Frequency |       | Liquid Temp_°C | <b>SAR (1g) (W/kg)</b> | Limit (W/kg) |
|--------------|---------|-----------|-------|----------------|------------------------|--------------|
|              |         | Channel   | MHz   |                |                        |              |
| 25mm         | Fixed   | 4182      | 836.4 | 23.6           | 0.185                  | 1.6          |

Test mode: **HSDPA band II, Crest Factor=1** Depth of liquid: 15.0 cm

| EUT Position | Antenna | Frequency |        | Liquid Temp_°C | <b>SAR (1g) (W/kg)</b> | Limit (W/kg) |
|--------------|---------|-----------|--------|----------------|------------------------|--------------|
|              |         | Channel   | MHz    |                |                        |              |
| 25mm         | Fixed   | 9400      | 1880.0 | 23.6           | 0.407                  | 1.6          |

Notes: 1) Please refer to attachment for the result presentation in plot format.



## **10. EUT PHOTOS**

**Please see separate Test setup photo report.**



## 11. EQUIPMENT LIST & CALIBRATION STATUS

| Name of Equipment                  | Manufacturer    | Type/Model  | Serial Number   | Calibration Cycle(days) | Calibration Due |
|------------------------------------|-----------------|-------------|-----------------|-------------------------|-----------------|
| S-Parameter Network Analyzer       | Agilent         | E8358A      | US40260243      | 365                     | 07/05/2011      |
| Electronic Probe kit               | Hewlett Packard | 85070D      | N/A             | N/A                     | N/A             |
| Power Meter                        | Anritsu         | ML2495A     | 1012009         | 365                     | 03/28/2011      |
| Power Sensor                       | Anritsu         | MA2411B     | 0917072         | 365                     | 03/09/2011      |
| Spectrum Analyzer                  | Agilent         | E4446A      | MY43360131      | 365                     | 03/03/2011      |
| Wireless Communication Test Set    | Agilent         | E5515C 8960 | MY48363204      | 365                     | 10/06/2011      |
| Data Acquisition Electronics (DAE) | SPEAG           | DAE4        | 877             | 365                     | 02/16/2011      |
| Dosimetric E-Field Probe           | SPEAG           | EX3DV4      | 3578            | 365                     | 06/21/2011      |
| 835 MHz System Validation Dipole   | SPEAG           | D835V2      | 4d015           | 730                     | 11/18/2012      |
| 1900 MHz System Validation Dipole  | SPEAG           | D1900V2     | 5d018           | 730                     | 06/14/2012      |
| 2450 MHz System Validation Dipole  | SPEAG           | D2450V2     | 728             | 730                     | 05/26/2012      |
| Probe Alignment Unit               | SPEAG           | LB (V2)     | 348             | N/A                     | N/A             |
| Robot                              | Staubli         | RX90B L     | F02/5T69A1/A/01 | N/A                     | N/A             |
| SAM Twin Phantom V4.0              | SPEAG           | N/A         | N/A             | N/A                     | N/A             |
| Devices Holder                     | SPEAG           | N/A         | N/A             | N/A                     | N/A             |
| Head/ Muscle 835 MHz               | CCS             | H/M 835A    | N/A             | N/A                     | N/A             |
| Head/ Muscle 1900 MHz              | CCS             | H/M 1900A   | N/A             | N/A                     | N/A             |



## 12. FACILITIES

All measurement facilities used to collect the measurement data are located at

- No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- No. 11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan.
- No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

## 13. REFERENCES

- [1] Federal Communications Commission, \Report and order: Guidelines for evaluating the environmental effects of radiofrequency radiation", Tech. Rep. FCC 96-326, FCC, Washington, D.C. 20554, 1996.
- [2] David L. Means Kwok Chan, Robert F. Cleveland, \Evaluating compliance with FCC guidelines for human exposure to radiofrequency electromagnetic fields", Tech. Rep., Federal Communication Commision, O\_ce of Engineering & Technology, Washington, DC, 1997.
- [3] Thomas Schmid, Oliver Egger, and Niels Kuster, \Automated E-eld scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp. 105{113, Jan. 1996.
- [4] Niels Kuster, Ralph Kastle, and Thomas Schmid, \Dosimetric evaluation of mobile communications equipment with known precision", IEICE Transactions on Communications, vol. E80-B, no. 5, pp. 645{652, May 1997.
- [5] CENELEC, \Considerations for evaluating of human exposure to electromagnetic fields (EMFs) from mobile telecommunication equipment (MTE) in the frequency range 30MHz - 6GHz", Tech. Rep., CENELEC, European Committee for Electrotechnical Standardization, Brussels, 1997.
- [6] ANSI, ANSI/IEEE C95.1-1992: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, The Institute of Electrical and Electronics Engineers, Inc., New York, NY 10017, 1992.
- [7] Katja Pokovic, Thomas Schmid, and Niels Kuster, \Robust setup for precise calibration of E-eld probes in tissue simulating liquids at mobile communications frequencies", in ICECOM \_ 97, Dubrovnik, October 15{17, 1997, pp. 120{124.
- [8] Katja Pokovic, Thomas Schmid, and Niels Kuster, \E-eld probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23{25 June, 1996, pp. 172{175.
- [9] Volker Hombach, Klaus Meier, Michael Burkhardt, Eberhard K. uhn, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 900 MHz", IEEE Transactions onMicrowave Theory and Techniques, vol. 44, no. 10, pp. 1865{1873, Oct. 1996.
- [10] Klaus Meier, Ralf Kastle, Volker Hombach, Roger Tay, and Niels Kuster, \The dependence of EM energy absorption upon human head modeling at 1800 MHz", IEEE Transactions on Microwave Theory and Techniques, Oct. 1997, in press.
- [11] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [12] W. H. Press, S. A. Teukolsky, W. T. Vetterling, and B. P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second Edition, Cambridge University Press, 1992..Dosimetric Evaluation of Sample device, month 1998 9
- [13] NIS81 NAMAS, \The treatment of uncertainty in EMC measurement", Tech. Rep., NAMAS Executive, National Physical Laboratory, Teddington, Middlesex, England, 1994.
- [14] Barry N. Taylor and Christ E. Kuyatt, \Guidelines for evaluating and expressing the uncertainty of NIST measurement results", Tech. Rep., National Institute of Standards and Technology, 1994. Dosimetric Evaluation of Sample device, month 1998 10



## 14. ATTACHMENTS

| Exhibit | Content                        |
|---------|--------------------------------|
| 1       | System Performance Check Plots |
| 2       | SAR Test Plots                 |
| 3       | Probe EX3DV4 sn3554            |
| 4       | Dipole D835V2_sn4d015          |
| 5       | Dipole D1900V2_sn5d018         |

**END OF REPORT**