

No.198 Kezhu Road, Science Town Economic& Technology Development District Guangzhou, China 510663 Telephone: +86 (0) 20 8215 5555 Fax: +86 (0) 20 8207 5059

Email: sgs_internet_operations@sgs.com

FEDERAL COMMUNICATIONS COMMISSION

Report No.: SZEMO080501823ETF Registration number: 556682

1 of 9 Page:

VVAAD296700 FCC ID:

TEST REPORT

SZEMO080501823ETF(SGS SZ NO.: SZTYR080501681/ EL) Application No.:

GUANGDONG ALPHA ANIMATION AND CULTURE CO., LTD. Applicant:

(Former Name: GUANG DONG AULDEY TOY INDUSTRY CO., LTD.)

AULDEY Manufacturer:

VVAAD296700 FCC ID:

Fundamental Frequency: 27.145MHz

Equipment Under Test (EUT):

EUT Name: CITROEN C4 Audi A4 DTM

Item No.: LC296700 LC296710.

Please refer to section 2 of this report which indicates which item was

actually tested and which were electrically identical.

Labelled Age Grading: AGE 6+ Country of Origin: **CHINA**

Standards: FCC PART 15, SUBPART C: 2007

Section 15.227

09 May 2008 Date of Receipt:

09 to 20 May 2008 **Date of Test:**

21 May 2008 Date of Issue:

Test Result: PASS *

Authorized Signature:

Robinson Lo Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This Test Report is issued by the Company subject to its General Conditions of Service printed overleaf. Attention is drawn to the limitations of liability, indemnification and jurisdictional issues defined therein. The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full, without prior written permission of the Company.

In the configuration tested, the EUT complied with the standards specified above.



Report No.: SZEMO080501823ETF

Page: 2 of 9

2 Test Summary

Test	Test Requirement	Stanadard Paragraph	Result
Radiated Emission (30MHz to 1000MHz)	FCC PART 15 :2007	Section 15.227	PASS*
Occupied Bandwidth	FCC PART 15 :2007	Section 15.215	PASS

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

Remark:

This report was an additional report copied from the report SZEMO071002832RFF, just changing the Item No., Photos and EUT Name. Since the electrical circuit design, layout, components used and internal wiring for the Items "LC296680, LC296690, LC296720, LC296740, LC2296660, LC296670" in the report SZEMO071002832RFF were exactly the same as the Items "LC296700 LC296710" in this report.

^{*} The EUT passed the RE test after retest.



Report No.: SZEMO080501823ETF

Page: 3 of 9

3 Contents

		F	⊃age
1	cov	'ER PAGE	1
2	TES	T SUMMARY	2
3	CON	ITENTS	3
4	GEN	IERAL INFORMATION	4
-			
	4.1 4.2	CLIENT INFORMATION DETAILS OF E.U.T.	
	4.2	DESCRIPTION OF SUPPORT UNITS	4 1⁄
	4.4	TEST LOCATION	д Д
	4.5	TEST LOCATION	4
5	TES	T RESULTS	5
	5.1	TEST INSTRUMENTS	5
	5.2	E.U.T. OPERATION	5
	5.3	TEST PROCEDURE & MEASUREMENT DATA	
	5.3.1		
	5.3.2	2 Occupied Bandwidth	



Report No.: SZEMO080501823ETF

Page: 4 of 9

4 General Information

4.1 Client Information

Applicant Name: GUANGDONG ALPHA ANIMATION AND CULTURE CO., LTD.

(Former Name: GUANG DONG AULDEY TOY INDUSTRY CO., LTD.)

Applicant Address: Auldey Ind Area, Wenguan Rd., (Central), Chenghai, Shantou,

Guangdong, China

4.2 Details of E.U.T.

EUT Name: CITROEN C4 Audi A4 DTM

Item No.: LC296700 LC296710

Power Supply: 3.0V DC (2 * 1.5V 'AA' Size Batteries) for Tx.

3.0V DC (2 * 1.5V 'AA' Size Batteries) for Rx.

Power Cord: N/A-

4.3 Description of Support Units

The EUT was tested as an independent unit: 27MHz radio transmitter.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic & Technology Development District Guangzhou, China 510663

Tel: +86 20 8215 5555 Fax: +86 20 8207 5059

4.5 Other Information Requested by the Customer

None.



Report No.: SZEMO080501823ETF

Page: 5 of 9

5 Test Results

5.1 Test Instruments

	R&TTE RE in Chamber											
Item	Test Equipment	Manufacturer	Model No.	Model No. Inventory No.		Cal.Due date (dd-mm-yy)						
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	16-06-2007	15-06-2009						
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	14-12-2006	13-12-2007						
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A						
4	Coaxial cable	SGS	N/A	SEL0028	01-06-2007	31-05-2008						
5	Coaxial cable	SGS	N/A	SEL0027	20-10-2007	19-10-2008						
6	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	03-04-2007	02-04-2008						
7	EMI Test Receiver Rohde & Schwarz		ESCI	SEL0022	27-06-2007	26-06-2008						
8	Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	15-06-2007	14-06-2008						

5.2 E.U.T. Operation

Input voltage: 3.0V DC (2 * 1.5V 'AA' Size Batteries)

Operating Environment:

Temperature: 26.0 °C
Humidity: 51% RH
Atmospheric Pressure: 1004mbar

EUT Operation: Test the EUT in transmitting mode.

5.3 Test Procedure & Measurement Data

5.3.1 Radiated Emissions

Test Requirement: FCC Part15 C Section 15.227

Test Method: ANSI C63.4-2003

Test Date: 16 October 2007(Initial Test)

08 November 2007(Retest)

Measurement Distance: 3m (Semi-Anechoic Chamber)

Requirements: Carrier frequency will not exceed 80dBuV/m AT 3m.

Out of band emissions shall not exceed: $40.0~dB\mu V/m$ between 30MHz~&~88MHz $43.5~dB\mu V/m$ between 88MHz~&~216MHz $46.0~dB\mu V/m$ between 216MHz~&~960MHz

54.0 dBuV/m above 960MHz

Detector: 9kHz to 30MHz RBW=9KHz VBW=30KHz

30MHz to 1000MHz RBW=120KHz VBW=300KHz



Report No.: SZEMO080501823ETF

Page: 6 of 9

Procedure:

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.

7 27.145MHz Mode. For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.4-2003 section 8.2.1. The The center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specied distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

Horizontal.

Test Frequency	Peak (dBμV/m)		Limits	N	largin (dB	3)	
(MHz)	Х	Υ	Z	(dBµV/m)	Х	Υ	Z
27.145	60.85	50.78	53.64	100.0	39.15	49.22	46.36

Test Frequency	Average (dBμV/m)		Limits	N	largin (dB	3)	
(MHz)	Х	Υ	Z	(dBµV/m)	X	Υ	Z
27.145	55.55	46.28	50.16	80.0	24.45	33.72	29.84

Vertical.

Test Frequency	Peak (dBμV/m)			Limits	N	largin (dB)
(MHz)	Х	Υ	Z	(dBµV/m)	X	Υ	Z
27.145	74.35	68.27	70.03	100.0	25.65	31.73	29.97

Test Frequency	Average (dBμV/m)			Limits	N	largin (dB	3)
(MHz)	X	Υ	Z	(dBµV/m)	X	Υ	Z
27.145	69.35	59.94	63.67	80.0	10.65	20.06	16.33

Y: EUT as per photograph in application document(setup).

X: As Y, but rotate EUT by 90° clockwise.

Z: As X, but rotate EUT by 90° vertically.



Report No.: SZEMO080501823ETF

Page: 7 of 9

Horizontal.

i ionzontai.							
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Peak Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
78.625	1.06	7.61	28.00	38.72	19.39	40.00	-20.61
105.925	1.22	8.81	27.82	38.32	20.53	43.50	-22.97
133.225	1.29	7.84	27.58	38.46	20.01	43.50	-23.49
160.525	1.34	9.59	27.38	37.03	20.58	43.50	-22.92
215.125	1.49	10.97	27.07	35.19	20.58	43.50	-22.92
242.425	1.64	12.07	26.95	37.13	23.89	46.00	-22.11
650.950	2.81	20.68	27.44	31.36	27.41	46.00	-18.59
678.250	2.86	21.44	27.35	30.85	27.80	46.00	-18.20

Vertical.

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Peak Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)
54.250	0.80	7.92	28.08	50.50	31.14	40.00	-8.86
78.625	1.06	7.61	28.00	43.23	23.90	40.00	-16.10
105.925	1.22	8.81	27.82	44.54	26.75	43.50	-16.75
160.525	1.34	9.59	27.38	46.20	29.75	43.50	-13.75
187.825	1.38	10.06	27.22	42.34	26.56	43.50	-16.94
215.125	1.49	10.97	27.07	50.91	36.30	43.50	-7.20
242.425	1.64	12.07	26.95	53.66	40.42	46.00	-5.58

Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

Test Results: The unit does meet the FCC Part 15 C Section 15.227 requirements.



Report No.: SZEMO080501823ETF

Page: 8 of 9

5.3.2 Occupied Bandwidth

Test Requirement: FCC Part 15 C Section 15.215 (C) and Section 15.227.

Test Method: ANSI C63.4

Operation within the band 26.960 - 27.280 MHz.

Test Date: 16 October 2007

Detector: Peak

26.960-27.280MHz Mode.

Requirements: Intentional radiators operating under the alternative provisions

to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the 20 dB bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of

out-of-band operation.

Method of measurement: The useful radiated emission from the EUT was detected by


the spectrum analyser with peak detector. The vertical Scale is set to 10dB per division. The horizontal scale is set

to42KHz per division.



Report No.: SZEMO080501823ETF

Page: 9 of 9



Ν

Date: 16.OCT.2007 10:07:11

The results: The unit does meet the FCC Part 15 C Section 15.215 requirements