

Conducted test results

No.1-7077/23-01-05_TR1-A209-R1

January 22, 2024

Test Standard(s) FCC 15.407

This document is electronically signed and valid without handwritten signature.
Public keys for verification of the electronic signatures can be requested at the testing laboratory.

Authorized

Andreas Kurzkurt
Testing Manager
Radio Labs

Table of Content

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-1	3
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-1	7
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-1	11
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-1	15
FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-1	19
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2A	21
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2A	25
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2A	30
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2A	34
FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2A	39
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	41
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C	45
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	50
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C	54
FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	59
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	61
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C	65
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	70
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C	74
FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	79
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	81
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C	85
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	90
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C	94
FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C	99
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-3	101
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-3	106
FCC 15.407, ISED RSS247 # Minimum emission bandwidth ~ WLAN5Gx ax-HE80 U-NII-3	110
FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-3	112
FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-3	117
FCC 15.407, ISED RSS247 # Minimum emission bandwidth ~ WLAN5Gx ax-HE80 U-NII-3	121
FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-3	123
FCC 15.407, ISED RSS247 # Emission mask (eirp) ~ WLAN5Gx ax-HE80 U-NII-3	125
FCC 15.407, ISED RSS247 # Emission mask (eirp) ~ WLAN5Gx ax-HE80 U-NII-3	128

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-1

References

TC start	19.01.2024 12:38:39
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5210
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5210 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	7.53	dBm	INFO
Ref. Frequency	---	---	5197.410	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:162					
Duty Cycle (Burst Ratio) max	---	---	0.969	---	INFO
Duty Cycle max	---	---	0.137	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.375	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.76	MHz	INFO
T1 26dB	---	---	5169.2000	MHz	INFO
T2 26dB	---	---	5250.9600	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.53 16.4 20
Start [MHz] Stop [MHz]	5130.000 5290.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	14.44	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	15.82	dBm	PASS
Limit: 11 dBm + 10 log 81.76					
Max Output Power DC corrected	---	30.13	15.82	dBm	na

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-3.28	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	-1.9	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-1

References

TC start	19.01.2024 12:41:10
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5210
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5210 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	6.84	dBm	INFO
Ref. Frequency	---	---	5181.830	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.84 16.4 15
Start [MHz] Stop [MHz]	5110.000 5310.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	76.923	MHz	INFO
T1 99%	5150.000000	---	5171.6384	MHz	PASS
T2 99%	---	5250.000000	5248.5614	MHz	PASS



BW 26dB



BW within Band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	82	MHz	INFO
T1 26dB	5150.000000	---	5169.0000	MHz	PASS
T2 26dB	---	5250.000000	5251.0000	MHz	DFS required

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-1

References

TC start	19.01.2024 12:41:54
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5210
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5210 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	6.25	dBm	INFO
Ref. Frequency	---	---	5224.790	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:158					
Duty Cycle (Burst Ratio) max	---	---	0.969	---	INFO
Duty Cycle max	---	---	0.137	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.375	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.44	MHz	INFO
T1 26dB	---	---	5169.5200	MHz	INFO
T2 26dB	---	---	5250.9600	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.25 16.4 20
Start [MHz] Stop [MHz]	5130.000 5290.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	14.68	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	16.06	dBm	PASS
Limit: 11 dBm + 10 log 81.44					
Max Output Power DC corrected	---	30.11	16.06	dBm	na

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-3.17	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	-1.79	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-1

References

TC start	19.01.2024 12:44:24
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5210
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5210 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	7.39	dBm	INFO
Ref. Frequency	---	---	5195.610	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.39 16.4 15
Start [MHz] Stop [MHz]	5110.000 5310.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.123	MHz	INFO
T1 99%	5150.000000	---	5171.6384	MHz	PASS
T2 99%	---	5250.000000	5248.7612	MHz	PASS



BW 26dB



BW within Band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.6	MHz	INFO
T1 26dB	5150.000000	---	5169.4000	MHz	PASS
T2 26dB	---	5250.000000	5251.0000	MHz	DFS required

Verdict

PASS

FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-1

References

TC start	19.01.2024 12:45:08
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	
Description	MIMO Σ FCC Power & psd - WLAN5Gx ax-HE80 U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5210
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	None

Equipment

Test at TX 5210 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Max Output Power DC corrected	---	---	15.82	dBm	INFO
Ant:1 BW 26dB	---	---	81.760	MHz	INFO
Ant:2 Max Output Power DC corrected	---	---	16.06	dBm	INFO
Ant:2 BW 26dB	---	---	81.440	MHz	INFO
Σ Limit absolute	---	24	18.95	dBm	PASS
Σ Limit: 11 dBm + 10 log 81.44	---	30.11	18.95	dBm	na

RESULT PSD

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 PSD	---	---	-1.9	dBm/1MHz	INFO
Ant:2 PSD	---	---	-1.79	dBm/1MHz	INFO
Σ	---	11	1.17	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2A

References

TC start	19.01.2024 12:46:47
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2A
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5290
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5290 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	6.19	dBm	INFO
Ref. Frequency	---	---	5275.010	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:156					
Duty Cycle (Burst Ratio) max	---	---	0.966	---	INFO
Duty Cycle max	---	---	0.15	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.1	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.6	MHz	INFO
T1 26dB	---	---	5249.3600	MHz	INFO
T2 26dB	---	---	5330.9600	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.19 16.2 20
Start [MHz] Stop [MHz]	5210.000 5370.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



Max OP and PSD

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	14.15	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	15.53	dBm	PASS
Limit: 11 dBm + 10 log 81.6					
Max Output Power DC corrected	---	30.12	15.53	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-3.43	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	-2.05	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2A

References

TC start	19.01.2024 12:49:18
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2A
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5290
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5290 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	6.24	dBm	INFO
Ref. Frequency	---	---	5316.370	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.24 16.2 15
Start [MHz] Stop [MHz]	5190.000 5390.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.123	MHz	INFO
T1 99%	5250.000000	---	5251.6384	MHz	PASS since U-NII-1 is supported
T2 99%	---	5350.000000	5328.7612	MHz	PASS



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	82	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5250.000000	---	5249.2000	MHz	PASS since U-NII-1 is supported
T2 26dB	---	5350.000000	5331.2000	MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2A

References

TC start	19.01.2024 12:49:58
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2A
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5290
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5290 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	7.61	dBm	INFO
Ref. Frequency	---	---	5302.990	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:155					
Duty Cycle (Burst Ratio) max	---	---	0.969	---	INFO
Duty Cycle max	---	---	0.137	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.375	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.44	MHz	INFO
T1 26dB	---	---	5249.3600	MHz	INFO
T2 26dB	---	---	5330.8000	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.61 16.2 20
Start [MHz] Stop [MHz]	5210.000 5370.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	14.64	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	16.02	dBm	PASS
Limit: 11 dBm + 10 log 81.44					
Max Output Power DC corrected	---	30.11	16.02	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-2.95	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	-1.57	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2A

References

TC start	19.01.2024 12:52:29
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2A
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5290
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5290 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	7.36	dBm	INFO
Ref. Frequency	---	---	5284.410	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.36 16.2 15
Start [MHz] Stop [MHz]	5190.000 5390.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.323	MHz	INFO
T1 99%	5250.000000	---	5251.4386	MHz	PASS since U-NII-1 is supported
T2 99%	---	5350.000000	5328.7612	MHz	PASS



BW 26dB



BW within Band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.4	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5250.000000	---	5249.6000	MHz	PASS since U-NII-1 is supported
T2 26dB	---	5350.000000	5331.0000	MHz	PASS

Verdict

PASS

FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2A

References

TC start	19.01.2024 12:53:09
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	
Description	MIMO Σ FCC Power & psd - WLAN5Gx ax-HE80 U-NII-2A
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5290
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	None

Equipment

Test at TX 5290 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Max Output Power DC corrected	---	---	15.53	dBm	INFO
Ant:1 BW 26dB	---	---	81.600	MHz	INFO
Ant:2 Max Output Power DC corrected	---	---	16.02	dBm	INFO
Ant:2 BW 26dB	---	---	81.440	MHz	INFO
Σ Limit absolute	---	24	18.79	dBm	PASS
Σ Limit: 11 dBm + 10 log 81.44	---	30.11	18.79	dBm	PASS

RESULT PSD

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 PSD	---	---	-2.05	dBm/1MHz	INFO
Ant:2 PSD	---	---	-1.57	dBm/1MHz	INFO
Σ	---	11	1.21	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 12:55:21
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5530 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	6.78	dBm	INFO
Ref. Frequency	---	---	5545.380	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:152					
Duty Cycle (Burst Ratio) max	---	---	0.966	---	INFO
Duty Cycle max	---	---	0.15	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.1	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	82.4	MHz	INFO
T1 26dB	---	---	5488.8800	MHz	INFO
T2 26dB	---	---	5571.2800	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.78 16.87 20
Start [MHz] Stop [MHz]	5450.000 5610.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	14.88	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	16.26	dBm	PASS
Limit: 11 dBm + 10 log 82.4					
Max Output Power DC corrected	---	30.16	16.26	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-3.1	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	-1.72	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 12:57:48
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5530 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	6.29	dBm	INFO
Ref. Frequency	---	---	5513.620	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.29 16.87 15
Start [MHz] Stop [MHz]	5430.000 5630.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.323	MHz	INFO
T1 99%	5470.000000	---	5491.4386	MHz	PASS since U-NII-3 is supported
T2 99%	---	5725.000000	5568.7612	MHz	



BW 26dB



BW within Band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.8	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5470.000000	---	5489.2000	MHz	PASS since U-NII-3 is supported
T2 26dB	---	5725.000000	5571.0000	MHz	

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 12:58:25
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5530 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	7.15	dBm	INFO
Ref. Frequency	---	---	5564.770	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:153					
Duty Cycle (Burst Ratio) max	---	---	0.966	---	INFO
Duty Cycle max	---	---	0.15	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.1	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.92	MHz	INFO
T1 26dB	---	---	5489.3600	MHz	INFO
T2 26dB	---	---	5571.2800	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.15 16.87 20
Start [MHz] Stop [MHz]	5450.000 5610.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	14.89	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	16.27	dBm	PASS
Limit: 11 dBm + 10 log 81.92					
Max Output Power DC corrected	---	30.13	16.27	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-3.09	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	-1.71	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 13:00:52
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5530 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	8.49	dBm	INFO
Ref. Frequency	---	---	5533.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.49 16.87 15
Start [MHz] Stop [MHz]	5430.000 5630.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE






BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.323	MHz	INFO
T1 99%	5470.000000	---	5491.4386	MHz	PASS since U-NII-3 is supported
T2 99%	---	5725.000000	5568.7612	MHz	



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	81.6	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5470.000000	---	5489.2000	MHz	PASS since U-NII-3 is supported
T2 26dB	---	5725.000000	5570.8000	MHz	

Verdict

PASS

FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 13:01:28
Ambit temp [°C] humidity [rel%]	22.3 29
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	
Description	MIMO Σ FCC Power & psd - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	None

Equipment

Test at TX 5530 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Max Output Power DC corrected	---	---	16.26	dBm	INFO
Ant:1 BW 26dB	---	---	82.400	MHz	INFO
Ant:2 Max Output Power DC corrected	---	---	16.27	dBm	INFO
Ant:2 BW 26dB	---	---	81.920	MHz	INFO
Σ Limit absolute	---	24	19.28	dBm	PASS
Σ Limit: 11 dBm + 10 log 81.92	---	30.13	19.28	dBm	PASS

RESULT PSD

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 PSD	---	---	-1.72	dBm/1MHz	INFO
Ant:2 PSD	---	---	-1.71	dBm/1MHz	INFO
Σ	---	11	1.3	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 13:13:42
Ambit temp [°C] humidity [rel%]	22.6 26
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	True Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5610 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	12.32	dBm	INFO
Ref. Frequency	---	---	5644.770	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:151					
Duty Cycle (Burst Ratio) max	---	---	0.966	---	INFO
Duty Cycle max	---	---	0.15	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.1	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	136	MHz	INFO
T1 26dB	---	---	5547.6000	MHz	INFO
T2 26dB	---	---	5683.6000	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	24.32 16.72 25
Start [MHz] Stop [MHz]	5530.000 5690.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



Max OP and PSD

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	19.24	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	20.62	dBm	PASS
Limit: 11 dBm + 10 log 136					
Max Output Power DC corrected	---	32.34	20.62	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	1.4	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	2.78	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 13:16:09
Ambit temp [°C] humidity [rel%]	22.6 27
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	True Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5610 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	11.28	dBm	INFO
Ref. Frequency	---	---	5632.380	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.28 16.72 20
Start [MHz] Stop [MHz]	5510.000 5710.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.722	MHz	INFO
T1 99%	5470.000000	---	5571.2388	MHz	PASS since U-NII-3 is supported
T2 99%	---	5725.000000	5648.9610	MHz	



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	135.4	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5470.000000	---	5544.6000	MHz	PASS since U-NII-3 is supported
T2 26dB	---	5725.000000	5680.0000	MHz	

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 13:16:45
Ambit temp [°C] humidity [rel%]	22.6 26
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	True Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5610 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	11.67	dBm	INFO
Ref. Frequency	---	---	5575.630	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:154					
Duty Cycle (Burst Ratio) max	---	---	0.966	---	INFO
Duty Cycle max	---	---	0.15	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	2.1	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	119.04	MHz	INFO
T1 26dB	---	---	5554.9600	MHz	INFO
T2 26dB	---	---	5674.0000	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	23.67 16.72 25
Start [MHz] Stop [MHz]	5530.000 5690.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



Max OP and PSD

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	19.56	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	20.94	dBm	PASS
Limit: 11 dBm + 10 log 119.04					
Max Output Power DC corrected	---	31.76	20.94	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	1.63	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	3.01	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 13:19:12
Ambit temp [°C] humidity [rel%]	22.6 25
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	True Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5610 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	10.91	dBm	INFO
Ref. Frequency	---	---	5581.430	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.91 16.72 20
Start [MHz] Stop [MHz]	5510.000 5710.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE






BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.722	MHz	INFO
T1 99%	5470.000000	---	5571.2388	MHz	PASS since U-NII-3 is supported
T2 99%	---	5725.000000	5648.9610	MHz	



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	116.2	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5470.000000	---	5555.0000	MHz	PASS since U-NII-3 is supported
T2 26dB	---	5725.000000	5671.2000	MHz	

Verdict

PASS

FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	19.01.2024 13:19:48
Ambit temp [°C] humidity [rel%]	22.6 26
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	
Description	MIMO Σ FCC Power & psd - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	True Freq [MHz] 5610
Frequency high to test	False Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	None

Equipment

Test at TX 5610 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Max Output Power DC corrected	---	---	20.62	dBm	INFO
Ant:1 BW 26dB	---	---	136.000	MHz	INFO
Ant:2 Max Output Power DC corrected	---	---	20.94	dBm	INFO
Ant:2 BW 26dB	---	---	119.040	MHz	INFO
Σ Limit absolute	---	24	23.79	dBm	PASS
Σ Limit: 11 dBm + 10 log 119.04	---	31.76	23.79	dBm	PASS

RESULT PSD

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 PSD	---	---	2.78	dBm/1MHz	INFO
Ant:2 PSD	---	---	3.01	dBm/1MHz	INFO
Σ	---	11	5.91	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	22.01.2024 09:54:38
Ambit temp [°C] humidity [rel%]	20.0 35
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	True Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5690 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	10.56	dBm	INFO
Ref. Frequency	---	---	5698.790	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:147					
Duty Cycle (Burst Ratio) max	---	---	0.961	---	INFO
Duty Cycle max	---	---	0.173	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	1.825	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	106.88	MHz	INFO
T1 26dB	---	---	5638.8000	MHz	INFO
T2 26dB	---	---	5745.6800	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.56 16.66 20
Start [MHz] Stop [MHz]	5610.000 5770.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	19.07	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	20.45	dBm	PASS
Limit: 11 dBm + 10 log 106.88					
Max Output Power DC corrected	---	31.29	20.45	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	1.16	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	2.54	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	22.01.2024 09:57:02
Ambit temp [°C] humidity [rel%]	19.9 36
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	True Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5690 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	12.21	dBm	INFO
Ref. Frequency	---	---	5693.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.21 16.66 20
Start [MHz] Stop [MHz]	5590.000 5790.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.722	MHz	INFO
T1 99%	5470.000000	---	5651.2388	MHz	PASS since U-NII-3 is supported
T2 99%	---	5725.000000	5728.9610	MHz	



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	119.2	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5470.000000	---	5627.6000	MHz	PASS since U-NII-3 is supported
T2 26dB	---	5725.000000	5746.8000	MHz	

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	22.01.2024 09:57:38
Ambit temp [°C] humidity [rel%]	19.8 36
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	True Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5690 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	11.59	dBm	INFO
Ref. Frequency	---	---	5705.180	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:146					
Duty Cycle (Burst Ratio) max	---	---	0.961	---	INFO
Duty Cycle max	---	---	0.173	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	1.825	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	120	MHz	INFO
T1 26dB	---	---	5630.3200	MHz	INFO
T2 26dB	---	---	5750.3200	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	23.59 16.66 25
Start [MHz] Stop [MHz]	5610.000 5770.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	19.38	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	24	20.76	dBm	PASS
Limit: 11 dBm + 10 log 120					
Max Output Power DC corrected	---	31.79	20.76	dBm	PASS

Power Spectral Density

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	1.52	dBm/1MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	11	2.9	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	22.01.2024 10:00:02
Ambit temp [°C] humidity [rel%]	19.8 36
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	True Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5690 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	11.18	dBm	INFO
Ref. Frequency	---	---	5700.990	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.18 16.66 20
Start [MHz] Stop [MHz]	5590.000 5790.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.522	MHz	INFO
T1 99%	5470.000000	---	5651.2388	MHz	PASS since U-NII-3 is supported
T2 99%	---	5725.000000	5728.7612	MHz	



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	117.4	MHz	INFO

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T1 26dB	5470.000000	---	5633.6000	MHz	PASS since U-NII-3 is supported
T2 26dB	---	5725.000000	5751.0000	MHz	

Verdict

PASS

FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-2C

References

TC start	22.01.2024 10:00:39
Ambit temp [°C] humidity [rel%]	19.8 36
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	
Description	MIMO Σ FCC Power & psd - WLAN5Gx ax-HE80 U-NII-2C
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5530
Frequency mid to test	False Freq [MHz] 5610
Frequency high to test	True Freq [MHz] 5690
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	None

Equipment

Test at TX 5690 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Max Output Power DC corrected	---	---	20.45	dBm	INFO
Ant:1 BW 26dB	---	---	106.880	MHz	INFO
Ant:2 Max Output Power DC corrected	---	---	20.76	dBm	INFO
Ant:2 BW 26dB	---	---	120.000	MHz	INFO
Σ Limit absolute	---	24	23.62	dBm	PASS
Σ Limit: 11 dBm + 10 log 106.88	---	31.29	23.62	dBm	PASS

RESULT PSD

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 PSD	---	---	2.54	dBm/1MHz	INFO
Ant:2 PSD	---	---	2.9	dBm/1MHz	INFO
Σ	---	11	5.73	dBm/1MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	22.01.2024 08:23:36
Ambit temp [°C] humidity [rel%]	20.3 31
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5775 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	10.60	dBm	INFO
Ref. Frequency	---	---	5769.410	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:151					
Duty Cycle (Burst Ratio) max	---	---	0.961	---	INFO
Duty Cycle max	---	---	0.173	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	1.825	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	87.84	MHz	INFO
T1 26dB	---	---	5730.2000	MHz	INFO
T2 26dB	---	---	5818.0400	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.60 16.82 20
Start [MHz] Stop [MHz]	5695.000 5855.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	18.73	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	30	20.11	dBm	PASS
Limit: 11 dBm + 10 log 87.84					
Max Output Power DC corrected	---	30.44	20.11	dBm	na

Power Spectral Density U-NII-3

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.60 16.82 25
Start [MHz] Stop [MHz]	5695.000 5855.000
RBW [MHz] VBW [MHz]	0.500000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-2.06	dBm/0.5MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	30	-0.68	dBm/0.5MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	22.01.2024 08:28:02
Ambit temp [°C] humidity [rel%]	20.4 31
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5775 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	11.06	dBm	INFO
Ref. Frequency	---	---	5795.980	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.06 16.82 20
Start [MHz] Stop [MHz]	5675.000 5875.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.323	MHz	INFO
T1 99%	5725.000000	---	5736.4386	MHz	PASS
T2 99%	---	5850.000000	5813.7612	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	---	---	80.2	MHz	INFO
T1 20dB	5725.000000	---	5735.0000	MHz	PASS
T2 20dB	---	5850.000000	5815.2000	MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Minimum emission bandwidth ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	22.01.2024 08:28:41
Ambit temp [°C] humidity [rel%]	20.4 31
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	KDB789033 D02, C.2.
Description	FCC 15.407 Min Emission Bandwidth - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5775 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	11.34	dBm	INFO
Ref. Frequency	---	---	5786.990	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	23.34 16.82 25
Start [MHz] Stop [MHz]	5675.000 5875.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	2 1500 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth (6dB)	0.500	---	77.4	MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	22.01.2024 08:29:11
Ambit temp [°C] humidity [rel%]	20.4 31
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5775 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	11.17	dBm	INFO
Ref. Frequency	---	---	5785.190	MHz	INFO


Evaluation max. Duty Cycle

Duty Cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Result Summary					
Number of detected Bursts:148					
Duty Cycle (Burst Ratio) max	---	---	0.961	---	INFO
Duty Cycle max	---	---	0.173	dB	INFO
Duty Cycle (Burst Ratio) min	---	---	0.727	---	INFO
Duty Cycle min	---	---	1.385	dB	INFO
Max TX Burst Length	---	---	1.825	ms	INFO
Min Gap Length	---	---	0.075	ms	INFO
Max Gap Length	---	---	0.075	ms	INFO



Evaluation Bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	113.28	MHz	INFO
T1 26dB	---	---	5724.4400	MHz	INFO
T2 26dB	---	---	5837.7200	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	23.17 16.82 25
Start [MHz] Stop [MHz]	5695.000 5855.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



Max OP and PSD


RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max Output Power	---	---	18.44	dBm	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Limit absolute					
Max Output Power DC corrected	---	30	19.82	dBm	PASS
Limit: 11 dBm + 10 log 113.28					
Max Output Power DC corrected	---	31.54	19.82	dBm	na

Power Spectral Density U-NII-3

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	23.17 16.82 25
Start [MHz] Stop [MHz]	5695.000 5855.000
RBW [MHz] VBW [MHz]	0.500000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	107000 1 320 SWE



PSD UNII-3

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power Spectral Density	---	---	-2.31	dBm/0.5MHz	INFO
Duty Cycle Correction	---	---	1.38	dB	INFO
Power Spectral Density DC corrected	---	30	-0.93	dBm/0.5MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	22.01.2024 08:33:36
Ambit temp [°C] humidity [rel%]	20.4 31
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5775 MHz


RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	10.34	dBm	INFO
Ref. Frequency	---	---	5789.590	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.34 16.82 20
Start [MHz] Stop [MHz]	5675.000 5875.000
RBW [MHz] VBW [MHz]	1.000000 5.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within Band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	77.522	MHz	INFO
T1 99%	5725.000000	---	5736.4386	MHz	PASS
T2 99%	---	5813.9610	5813.9610	MHz	PASS



BW 20dB



BW within Band 20dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	---	---	80.2	MHz	INFO
T1 20dB	5725.000000	---	5735.0000	MHz	PASS
T2 20dB	---	5850.000000	5815.2000	MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Minimum emission bandwidth ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	22.01.2024 08:34:14
Ambit temp [°C] humidity [rel%]	20.4 31
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	KDB789033 D02, C.2.
Description	FCC 15.407 Min Emission Bandwidth - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI


Test at TX 5775 MHz

RESULT: Reference Power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	10.66	dBm	INFO
Ref. Frequency	---	---	5764.010	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.66 16.82 25
Start [MHz] Stop [MHz]	5675.000 5875.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	2 1500 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth (6dB)	0.500	---	76.8	MHz	PASS

Verdict

PASS

FCC 15.407 # MIMO Σ Max output power and psd ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	22.01.2024 08:34:43
Ambit temp [°C] humidity [rel%]	20.4 31
System version	4.7.1.5
Standard Version	FCC 15.407 NI
Method	
Description	MIMO Σ FCC Power & psd - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	several
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	1.4
Full path name type	None

Equipment

Test at TX 5775 MHz

RESULT Power

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 Max Output Power DC corrected	---	---	20.11	dBm	INFO
Ant:1 BW 26dB	---	---	87.840	MHz	INFO
Ant:2 Max Output Power DC corrected	---	---	19.82	dBm	INFO
Ant:2 BW 26dB	---	---	113.280	MHz	INFO
Σ Limit absolute	---	30	22.98	dBm	PASS
Σ Limit: 11 dBm + 10 log 87.84	---	30.44	22.98	dBm	na

RESULT PSD

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ant:1 PSD	---	---	-0.68	dBm/0.5MHz	INFO
Ant:2 PSD	---	---	-0.93	dBm/0.5MHz	INFO
Σ	---	30	2.21	dBm/0.5MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Emission mask (eirp) ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	19.01.2024 14:28:07
Ambit temp [°C] humidity [rel%]	23.4 26
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	NI
Description	FCC 15.407 Emission mask - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	3.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5775 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	12.14	dBm	INFO
Ref. Frequency	---	---	5767.210	MHz	INFO

Antenna gain

Considered antenna gain [dBi]: 2 / max found in range 5625 to 5950 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.14 18.82 15
Start [MHz] Stop [MHz]	5625.000 5950.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
-------------	-------------	-------------	----------	------	---------

Verdict

PASS

FCC 15.407, ISED RSS247 # Emission mask (eirp) ~ WLAN5Gx ax-HE80 U-NII-3

References

TC start	19.01.2024 14:28:44
Ambit temp [°C] humidity [rel%]	23.4 27
System version	4.7.1.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	NI
Description	FCC 15.407 Emission mask - WLAN5Gx ax-HE80 U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of Antenna Ports	2
User Interaction	No
Device Class UNII_1	Client
Limit W52 Japan	Standard

Test Parameter

Technology to test	WLAN5Gx ax-HE80
Antenna port used	2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 0
Frequency mid to test	True Freq [MHz] 5775
Frequency high to test	False Freq [MHz] 0
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	3.4
Full path name type	EUT - SignalingUnit - SpectrumAnalyzer

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.70
Switch matrix,CTCadvanced,SPM-4 NI DAQ,28016133,NI

Test at TX 5775 MHz

RESULT: Reference Power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. Power 1MHz/1MHz cond.	---	---	12.71	dBm	INFO
Ref. Frequency	---	---	5737.640	MHz	INFO

Antenna gain

Considered antenna gain [dBi]: 2 / max found in range 5625 to 5950 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.71 18.82 15
Start [MHz] Stop [MHz]	5625.000 5950.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
-------------	-------------	-------------	----------	------	---------

Verdict

PASS

- END OF DOCUMENT -