



# RADIO TEST REPORT

**FCC ID** : VW3FAST5380V2  
**Equipment** : Copper Wireless Router  
**Brand Name** : SAGEMCOM  
**Model Name** : FAST 5380  
**Applicant** : SAGEMCOM BROADBAND SAS  
250 Route de l'Empereur - 92848 RUEIL MALMAISON  
CEDEX- FRANCE  
**Manufacturer** : SAGEMCOM BROADBAND SAS  
250 Route de l'Empereur - 92848 RUEIL MALMAISON  
CEDEX- FRANCE  
**Standard** : 47 CFR FCC Part 15.407

The product was received on Feb. 12, 2022, and testing was started from Feb. 18, 2022 and completed on Feb. 22, 2022. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

**Sporton International Inc. Hsinchu Laboratory**

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



## Table of Contents

|                                                           |           |
|-----------------------------------------------------------|-----------|
| <b>History of this test report.....</b>                   | <b>3</b>  |
| <b>Summary of Test Result.....</b>                        | <b>4</b>  |
| <b>1 General Description .....</b>                        | <b>5</b>  |
| 1.1 Information.....                                      | 5         |
| 1.2 Applicable Standards .....                            | 10        |
| 1.3 Testing Location Information .....                    | 10        |
| 1.4 Measurement Uncertainty .....                         | 10        |
| <b>2 Test Configuration of EUT .....</b>                  | <b>11</b> |
| 2.1 Test Channel Mode .....                               | 11        |
| 2.2 The Worst Case Measurement Configuration .....        | 13        |
| 2.3 EUT Operation during Test .....                       | 13        |
| 2.4 Accessories .....                                     | 14        |
| 2.5 Support Equipment.....                                | 14        |
| 2.6 Test Setup Diagram .....                              | 15        |
| <b>3 Transmitter Test Result .....</b>                    | <b>16</b> |
| 3.1 Emission Bandwidth .....                              | 16        |
| 3.2 Maximum Output Power .....                            | 18        |
| 3.3 Power Spectral Density .....                          | 21        |
| 3.4 Unwanted Emissions.....                               | 24        |
| <b>4 Test Equipment and Calibration Data .....</b>        | <b>27</b> |
| <b>Appendix A. Test Results of Emission Bandwidth</b>     |           |
| <b>Appendix B. Test Results of Maximum Output Power</b>   |           |
| <b>Appendix C. Test Results of Power Spectral Density</b> |           |
| <b>Appendix D. Test Results of Unwanted Emissions</b>     |           |
| <b>Appendix E. Test Photos</b>                            |           |
| <b>Photographs of EUT v01</b>                             |           |



TEL : 886-3-656-9065  
FAX : 886-3-656-9085  
Report Template No.: CB-A12\_1 Ver1.4



## Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items             | Result (PASS/FAIL) | Remark |
|---------------|-----------------|------------------------|--------------------|--------|
| 1.1.2         | 15.203          | Antenna Requirement    | PASS               | -      |
| 3.1           | 15.407(a)       | Emission Bandwidth     | PASS               | -      |
| 3.2           | 15.407(a)       | Maximum Output Power   | PASS               | -      |
| 3.3           | 15.407(a)       | Power Spectral Density | PASS               | -      |
| 3.4           | 15.407(b)       | Unwanted Emissions     | PASS               | -      |

**Declaration of Conformity:**

1. The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Measurement Uncertainty".

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by:** Sam Chen

**Report Producer:** Vicky Huang



# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

| Frequency Range (MHz) | IEEE Std. 802.11                       | Ch. Frequency (MHz) | Channel Number |
|-----------------------|----------------------------------------|---------------------|----------------|
| 5250-5350             | a, n (HT20), ac (VHT20),<br>ax (HEW20) | 5260-5320           | 52-64 [4]      |
| 5470-5725             |                                        | 5500-5720           | 100-144 [12]   |
| 5250-5350             | n (HT40), ac (VHT40),<br>ax (HEW40)    | 5270-5310           | 54-62 [2]      |
| 5470-5725             |                                        | 5510-5710           | 102-142 [6]    |
| 5250-5350             | ac (VHT80), ax (HEW80)                 | 5290                | 58 [1]         |
| 5470-5725             |                                        | 5530-5690           | 106-138 [3]    |
| 5150-5350             | ax (HEW160)                            | 5250                | 50 [1]         |
| 5470-5725             |                                        | 5570                | 114 [1]        |

| Band          | Mode               | BWch (MHz) | Nant |
|---------------|--------------------|------------|------|
| 5.25-5.35GHz  | 802.11a            | 20         | 4    |
| 5.25-5.35GHz  | 802.11n HT20       | 20         | 4    |
| 5.25-5.35GHz  | 802.11n HT20-BF    | 20         | 4    |
| 5.25-5.35GHz  | 802.11ac VHT20     | 20         | 4    |
| 5.25-5.35GHz  | 802.11ac VHT20-BF  | 20         | 4    |
| 5.25-5.35GHz  | 802.11ax HEW20     | 20         | 4    |
| 5.25-5.35GHz  | 802.11ax HEW20-BF  | 20         | 4    |
| 5.25-5.35GHz  | 802.11n HT40       | 40         | 4    |
| 5.25-5.35GHz  | 802.11n HT40-BF    | 40         | 4    |
| 5.25-5.35GHz  | 802.11ac VHT40     | 40         | 4    |
| 5.25-5.35GHz  | 802.11ac VHT40-BF  | 40         | 4    |
| 5.25-5.35GHz  | 802.11ax HEW40     | 40         | 4    |
| 5.25-5.35GHz  | 802.11ax HEW40-BF  | 40         | 4    |
| 5.25-5.35GHz  | 802.11ac VHT80     | 80         | 4    |
| 5.25-5.35GHz  | 802.11ac VHT80-BF  | 80         | 4    |
| 5.25-5.35GHz  | 802.11ax HEW80     | 80         | 4    |
| 5.25-5.35GHz  | 802.11ax HEW80-BF  | 80         | 4    |
| 5.15-5.35GHz  | 802.11ax HEW160    | 160        | 4    |
| 5.15-5.35GHz  | 802.11ax HEW160-BF | 160        | 4    |
| 5.47-5.725GHz | 802.11a            | 20         | 4    |

| Band          | Mode               | BWch (MHz) | Nant |
|---------------|--------------------|------------|------|
| 5.47-5.725GHz | 802.11n HT20       | 20         | 4    |
| 5.47-5.725GHz | 802.11n HT20-BF    | 20         | 4    |
| 5.47-5.725GHz | 802.11ac VHT20     | 20         | 4    |
| 5.47-5.725GHz | 802.11ac VHT20-BF  | 20         | 4    |
| 5.47-5.725GHz | 802.11ax HEW20     | 20         | 4    |
| 5.47-5.725GHz | 802.11ax HEW20-BF  | 20         | 4    |
| 5.47-5.725GHz | 802.11n HT40       | 40         | 4    |
| 5.47-5.725GHz | 802.11n HT40-BF    | 40         | 4    |
| 5.47-5.725GHz | 802.11ac VHT40     | 40         | 4    |
| 5.47-5.725GHz | 802.11ac VHT40-BF  | 40         | 4    |
| 5.47-5.725GHz | 802.11ax HEW40     | 40         | 4    |
| 5.47-5.725GHz | 802.11ax HEW40-BF  | 40         | 4    |
| 5.47-5.725GHz | 802.11ac VHT80     | 80         | 4    |
| 5.47-5.725GHz | 802.11ac VHT80-BF  | 80         | 4    |
| 5.47-5.725GHz | 802.11ax HEW80     | 80         | 4    |
| 5.47-5.725GHz | 802.11ax HEW80-BF  | 80         | 4    |
| 5.47-5.725GHz | 802.11ax HEW160    | 160        | 4    |
| 5.47-5.725GHz | 802.11ax HEW160-BF | 160        | 4    |

**Note:**

- ♦ 11a, HT20 and HT40 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
- ♦ VHT20, VHT40, VHT80 use a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM modulation.
- ♦ HEW20, HEW40, HEW80 and HEW160 use a combination of OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM modulation.
- ♦ BWch is the nominal channel bandwidth.

**1.1.2 Antenna Information**

| Ant. | 2.4GHz | 5GHz | 6GHz | Brand      | Model Name                                   | Antenna Type | Connector | Gain (dBi) |
|------|--------|------|------|------------|----------------------------------------------|--------------|-----------|------------|
| 1    | 1      | 2    | -    | Galtronics | 02102140-07252C1 DB1                         | PCB Antenna  | I-PEX     | Note 1     |
| 2    | 2      | 3    | -    | Galtronics | 02102140-07252C2 DB2                         | PCB Antenna  | I-PEX     |            |
| 3    | 3      | 4    | -    | Galtronics | 02102140-07252c3 DB3                         | PCB Antenna  | I-PEX     |            |
| 4    | -      | 1    | -    | Galtronics | 02102142-07252CX 5G                          | PCB Antenna  | I-PEX     |            |
| 5    | -      | -    | 1    | Galtronics | 02102475-07252-X_A<br>(02102475-07252-1 6G1) | PCB Antenna  | I-PEX     |            |
| 6    | -      | -    | 2    | Galtronics | 02102475-07252-X_A<br>(02102475-07252-2 6G2) | PCB Antenna  | I-PEX     |            |
| 7    | -      | -    | 3    | Galtronics | 02102475-07252-X_A<br>(02102475-07252-3 6G3) | PCB Antenna  | I-PEX     |            |
| 8    | -      | -    | 4    | Galtronics | 02102475-07252-X_A<br>(02102475-07252-4 6G4) | PCB Antenna  | I-PEX     |            |

Note 1:

| Ant. | Gain (dBi) |             |              |              |             |
|------|------------|-------------|--------------|--------------|-------------|
|      | 2.GHz      | 5GHz UNII 1 | 5GHz UNII 2A | 5GHz UNII 2C | 5GHz UNII 3 |
| 1    | 4.72       | 3.53        | 3.91         | 2.86         | 2.92        |
| 2    | 4.89       | 3.61        | 3.75         | 2.69         | 2.74        |
| 3    | 3.98       | 4.08        | 4.34         | 2.7          | 3.34        |
| 4    | -          | 4.84        | 4.88         | 4.09         | 4.68        |

| Ant. | Gain (dBi)  |             |             |             |
|------|-------------|-------------|-------------|-------------|
|      | 6GHz UNII 5 | 6GHz UNII 6 | 6GHz UNII 7 | 6GHz UNII 8 |
| 5    | 3.3         | 1.49        | 2.64        | 4.11        |
| 6    | 3.45        | 1.23        | 1.71        | 2.34        |
| 7    | 2.67        | 2.77        | 3.32        | 4.56        |
| 8    | 3.93        | 4.52        | 4.82        | 4.22        |

| Ant. | Directional Gain (dBi) |      |             |      |       |              |      |      |              |      |       |             |      |       |
|------|------------------------|------|-------------|------|-------|--------------|------|------|--------------|------|-------|-------------|------|-------|
|      | 2.GHz                  |      | 5GHz UNII 1 |      |       | 5GHz UNII 2A |      |      | 5GHz UNII 2C |      |       | 5GHz UNII 3 |      |       |
|      | 3T1S                   | 3T3S | 4T1S        | 4T2S | 4T4S  | 4T1S         | 4T2S | 4T4S | 4T1S         | 4T2S | 4T4S  | 4T1S        | 4T2S | 4T4S  |
| 1    | 5.05                   | 1.05 | 5.06        | 2.06 | -0.33 | 5.88         | 2.88 | 0.21 | 4.5          | 1.5  | -0.76 | 5.09        | 2.09 | -0.11 |
| 2    |                        |      |             |      |       |              |      |      |              |      |       |             |      |       |
| 3    |                        |      |             |      |       |              |      |      |              |      |       |             |      |       |
| 4    | -                      | -    |             |      |       |              |      |      |              |      |       |             |      |       |

| Ant. | Directional Gain (dBi) |      |       |             |      |       |             |      |       |             |      |      |
|------|------------------------|------|-------|-------------|------|-------|-------------|------|-------|-------------|------|------|
|      | 6GHz UNII 5            |      |       | 6GHz UNII 6 |      |       | 6GHz UNII 7 |      |       | 6GHz UNII 8 |      |      |
|      | 4T1S                   | 4T2S | 4T4S  | 4T1S        | 4T2S | 4T4S  | 4T1S        | 4T2S | 4T4S  | 4T1S        | 4T2S | 4T4S |
| 5    | 4.28                   | 1.28 | -1.11 | 4.78        | 1.78 | -0.77 | 5.14        | 2.14 | -0.57 | 5.34        | 2.34 | 0.24 |
| 6    |                        |      |       |             |      |       |             |      |       |             |      |      |
| 7    |                        |      |       |             |      |       |             |      |       |             |      |      |
| 8    |                        |      |       |             |      |       |             |      |       |             |      |      |

Note 2: The above information was declared by manufacturer.

Note 3: Maximum Directional Gain following KDB662911 D03.

The antenna report is provided in the operational description for this application.

**For 2.4GHz:**

**For IEEE 802.11b/g/n/VHT/ax mode (3TX/3RX):**

Port 1, Port 2 and Port 3 can be used as transmitting/receiving antenna.

Port 1, Port 2 and Port 3 could transmit/receive simultaneously.

**For 5GHz UNII 1~3:**

**For IEEE 802.11a/n/ac/ax mode (4TX/4RX):**

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

**For 6GHz UNII 5~8:**

**For IEEE 802.11ax mode (4TX/4RX):**

Port 1, Port 2, Port 3 and Port 4 can be used as transmitting/receiving antenna.

Port 1, Port 2, Port 3 and Port 4 could transmit/receive simultaneously.

**1.1.3 Mode Test Duty Cycle**

| Mode            | DC    | DCF(dB) | T(s)     | VBW(Hz) $\geq 1/T$ |
|-----------------|-------|---------|----------|--------------------|
| 802.11a         | 0.964 | 0.16    | 2.1m     | 1k                 |
| 802.11ax HEW20  | 0.976 | 0.11    | 1.488m   | 1k                 |
| 802.11ax HEW40  | 0.965 | 0.15    | 780.625u | 3k                 |
| 802.11ax HEW80  | 0.928 | 0.32    | 413.75u  | 3k                 |
| 802.11ax HEW160 | 0.894 | 0.49    | 236.625u | 10k                |

Note:

- ♦ DC is Duty Cycle.
- ♦ DCF is Duty Cycle Factor.

**1.1.4 EUT Operational Condition**

|                              |                                                                                                         |                     |                                     |                      |
|------------------------------|---------------------------------------------------------------------------------------------------------|---------------------|-------------------------------------|----------------------|
| <b>EUT Power Type</b>        | From Power Adapter                                                                                      |                     |                                     |                      |
| <b>Beamforming Function</b>  | <input checked="" type="checkbox"/>                                                                     | With beamforming    | <input type="checkbox"/>            | Without beamforming  |
|                              | The product has beamforming function for 11n/VHT/11ax in 2.4GHz, 11n/11ac/11ax in 5GHz and 11ax in 6GHz |                     |                                     |                      |
| <b>Weather Band</b>          | <input checked="" type="checkbox"/>                                                                     | With 5600~5650MHz   | <input type="checkbox"/>            | Without 5600~5650MHz |
| <b>Function</b>              | <input type="checkbox"/>                                                                                | Outdoor P2M         | <input checked="" type="checkbox"/> | Indoor P2M           |
|                              | <input type="checkbox"/>                                                                                | Fixed P2P           | <input type="checkbox"/>            | Client               |
|                              | <input checked="" type="checkbox"/>                                                                     | Point-to-multipoint | <input type="checkbox"/>            | Point-to-point       |
| <b>TPC Function</b>          | <input checked="" type="checkbox"/>                                                                     | With TPC            | <input type="checkbox"/>            | Without TPC          |
| <b>Test Software Version</b> | Mtool V3.2.1.3                                                                                          |                     |                                     |                      |

Note: The above information was declared by manufacturer.

**1.1.5 Table for Permissive Change**

This product is an extension of original one reported under Sporton project number: FR160328-03

Below is the table for the change of the product with respect to the original one.

| Modifications                                                                                                                        | Performance Checking                                                                                   |
|--------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|
| 1. Adding U-NII-2A and U-NII-2C bands (5250~5350 MHz, 5470~5725 MHz) for this device.<br>2. Enabling the 160MHz in ax mode for 5GHz. | 1. Emission Bandwidth<br>2. Maximum Output Power<br>3. Power Spectral Density<br>4. Unwanted Emissions |



## 1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ FCC KDB 789033 D02 v02r01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ FCC KDB 662911 D03 v01
- ♦ FCC KDB 412172 D01 v01r01

## 1.3 Testing Location Information

| Testing Location Information                              |                                                                                                                                                                                                                                                |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Lab. : Sporton International Inc. Hsinchu Laboratory |                                                                                                                                                                                                                                                |
| Hsinchu<br>(TAF: 3787)                                    | ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)<br>TEL: 886-3-656-9065 FAX: 886-3-656-9085<br>Test site Designation No. TW3787 with FCC.<br>Conformity Assessment Body Identifier (CABID) TW3787 with ISED. |

| Test Condition | Test Site No. | Test Engineer | Test Environment<br>(°C / %) | Test Date                       |
|----------------|---------------|---------------|------------------------------|---------------------------------|
| RF Conducted   | TH01-CB       | Serway Lee    | 19.4~19.9 / 63~70            | Feb. 18, 2022~<br>Feb. 23, 2022 |
| Radiated       | 03CH02-CB     | Ken Yeh       | 23.1-23.8 / 62-64            | Feb. 22, 2022                   |

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

| Test Items                        | Uncertainty | Remark                   |
|-----------------------------------|-------------|--------------------------|
| Radiated Emission (1GHz ~ 18GHz)  | 4.7 dB      | Confidence levels of 95% |
| Radiated Emission (18GHz ~ 40GHz) | 4.2 dB      | Confidence levels of 95% |
| Conducted Emission                | 2.5 dB      | Confidence levels of 95% |
| Output Power Measurement          | 1.3 dB      | Confidence levels of 95% |
| Power Density Measurement         | 2.5 dB      | Confidence levels of 95% |
| Bandwidth Measurement             | 0.9%        | Confidence levels of 95% |



## 2 Test Configuration of EUT

### 2.1 Test Channel Mode

For Non-beamforming

| Mode                           | Power Setting |
|--------------------------------|---------------|
| 802.11a_Nss1,(6Mbps)_4TX       | -             |
| 5260MHz                        | 70            |
| 5300MHz                        | 70            |
| 5320MHz                        | 70            |
| 5500MHz                        | 71            |
| 5580MHz                        | 72            |
| 5700MHz                        | 68            |
| 5720MHz Straddle 5.47-5.725GHz | 72            |
| 5720MHz Straddle 5.725-5.85GHz | 72            |
| 802.11ax HEW20_Nss1,(MCS0)_4TX | -             |
| 5260MHz                        | 69            |
| 5300MHz                        | 70            |
| 5320MHz                        | 70            |
| 5500MHz                        | 71            |
| 5580MHz                        | 72            |
| 5700MHz                        | 62            |
| 5720MHz Straddle 5.47-5.725GHz | 72            |
| 5720MHz Straddle 5.725-5.85GHz | 72            |
| 802.11ax HEW40_Nss1,(MCS0)_4TX | -             |
| 5270MHz                        | 70            |
| 5310MHz                        | 70            |
| 5510MHz                        | 71            |
| 5550MHz                        | 73            |
| 5670MHz                        | 71            |
| 5710MHz Straddle 5.47-5.725GHz | 73            |
| 5710MHz Straddle 5.725-5.85GHz | 73            |
| 802.11ax HEW80_Nss1,(MCS0)_4TX | -             |
| 5290MHz                        | 71            |
| 5530MHz                        | 69            |
| 5610MHz                        | 72            |
| 5690MHz Straddle 5.47-5.725GHz | 71            |
| 5690MHz Straddle 5.725-5.85GHz | 71            |



|                                 |    |
|---------------------------------|----|
| 802.11ax HEW160_Nss1,(MCS0)_4TX | -  |
| 5250MHz Straddle 5.15-5.25GHz   | 70 |
| 5250MHz Straddle 5.25-5.35GHz   | 70 |
| 5570MHz                         | 68 |

**For beamforming**

| <b>Mode</b>                        | <b>Power Setting</b> |
|------------------------------------|----------------------|
| 802.11ax HEW20-BF_Nss1,(MCS0)_4TX  | -                    |
| 5260MHz                            | 69                   |
| 5300MHz                            | 70                   |
| 5320MHz                            | 70                   |
| 5500MHz                            | 71                   |
| 5580MHz                            | 72                   |
| 5700MHz                            | 62                   |
| 5720MHz Straddle 5.47-5.725GHz     | 72                   |
| 5720MHz Straddle 5.725-5.85GHz     | 72                   |
| 802.11ax HEW40-BF_Nss1,(MCS0)_4TX  | -                    |
| 5270MHz                            | 70                   |
| 5310MHz                            | 70                   |
| 5510MHz                            | 71                   |
| 5550MHz                            | 73                   |
| 5670MHz                            | 71                   |
| 5710MHz Straddle 5.47-5.725GHz     | 73                   |
| 5710MHz Straddle 5.725-5.85GHz     | 73                   |
| 802.11ax HEW80-BF_Nss1,(MCS0)_4TX  | -                    |
| 5290MHz                            | 71                   |
| 5530MHz                            | 69                   |
| 5610MHz                            | 72                   |
| 5690MHz Straddle 5.47-5.725GHz     | 71                   |
| 5690MHz Straddle 5.725-5.85GHz     | 71                   |
| 802.11ax HEW160-BF_Nss1,(MCS0)_4TX | -                    |
| 5250MHz Straddle 5.15-5.25GHz      | 70                   |
| 5250MHz Straddle 5.25-5.35GHz      | 70                   |
| 5570MHz                            | 68                   |

**Note:**

- ♦ Evaluated HEW20/HEW40/HEW80 mode only due to the similar modulation. The power setting of HT20/HT40/VHT20/VHT40/VHT80 mode are the same or lower than HEW20/HEW40/HEW80
- ♦ The EUT supports beamforming and CDD modes, and the CDD mode is the worst case. Therefore, all test items are evaluated in the report. The beamforming mode only evaluates the output power.

## 2.2 The Worst Case Measurement Configuration

| The Worst Case Mode for Following Conformance Tests |                                                                      |
|-----------------------------------------------------|----------------------------------------------------------------------|
| <b>Tests Item</b>                                   | Emission Bandwidth<br>Maximum Output Power<br>Power Spectral Density |
| <b>Test Condition</b>                               | Conducted measurement at transmit chains                             |

| The Worst Case Mode for Following Conformance Tests |                                                                                                                                                                                                                                                     |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tests Item</b>                                   | Unwanted Emissions                                                                                                                                                                                                                                  |
| <b>Test Condition</b>                               | Radiated measurement<br>If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type. |
| <b>Operating Mode &gt; 1GHz</b>                     | CTX                                                                                                                                                                                                                                                 |
|                                                     | The EUT was performed at X axis, Y axis and Z axis position, and the worst case was found at X axis. So the measurement will follow this same test configuration                                                                                    |
| 1                                                   | EUT in X axis                                                                                                                                                                                                                                       |

| The Worst Case Mode for Following Conformance Tests                                   |                                                                         |
|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| <b>Tests Item</b>                                                                     | Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation |
| <b>Operating Mode</b>                                                                 |                                                                         |
| 1                                                                                     | WLAN 2.4GHz + WLAN 5GHz + WLAN 6GHz                                     |
| Refer to Sporton Test Report No.: FA160328-05 for Co-location RF Exposure Evaluation. |                                                                         |

## 2.3 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.




## 2.4 Accessories

| Accessories                                      |            |                          |                                                         |
|--------------------------------------------------|------------|--------------------------|---------------------------------------------------------|
| Equipment Name                                   | Brand Name | Model Name               | Rating                                                  |
| Adapter 1                                        | SAGEMCOM   | ADS-42FKJ-12 12042EPCU-L | INPUT: 100-120V~50/60Hz, Max.1.2A<br>OUTPUT: 12V, 3.5A  |
| Adapter 2                                        | SAGEMCOM   | MSG-V3500AR120-042A0-US  | Input: 100-120V~50/60Hz, 1.2A Max.<br>Output: 12V, 3.5A |
| Adapter 3                                        | SAGEMCOM   | NBS42E120350VU           | INPUT: 100-120V~50/60Hz, 1.0A<br>OUTPUT: 12.0V, 3.5A    |
| Others                                           |            |                          |                                                         |
| RJ-11 cable*1(two by one): Non-Shielded, 2m      |            |                          |                                                         |
| ADSL RJ-11 cable*1(two by one): Non-Shielded, 2m |            |                          |                                                         |
| RJ-45 cable*1: Shielded, 1.8m                    |            |                          |                                                         |

## 2.5 Support Equipment

| Support Equipment |           |            |            |        |
|-------------------|-----------|------------|------------|--------|
| No.               | Equipment | Brand Name | Model Name | FCC ID |
| A                 | NB        | DELL       | E4300      | N/A    |

## 2.6 Test Setup Diagram





### 3 Transmitter Test Result

#### 3.1 Emission Bandwidth

##### 3.1.1 Emission Bandwidth Limit

| Emission Bandwidth Limit            |                                                                                                                                                                                       |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>UNII Devices</b>                 |                                                                                                                                                                                       |
| <input type="checkbox"/>            | For the 5.15-5.25 GHz band, N/A                                                                                                                                                       |
| <input checked="" type="checkbox"/> | For the 5.25-5.35 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.            |
| <input checked="" type="checkbox"/> | For the 5.47-5.725 GHz band, the maximum conducted output power shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz.           |
| <input checked="" type="checkbox"/> | For the 5.725-5.85 GHz band, 26 dB emission bandwidth ,N/A.<br>6 dB emission bandwidth $\geq$ 500kHz.                                                                                 |
| <input type="checkbox"/>            | For the 5.85-5.895 GHz band, 26 dB emission bandwidth ,N/A.<br>6 dB emission bandwidth $\geq$ 500kHz.                                                                                 |
| <b>LE-LAN Devices</b>               |                                                                                                                                                                                       |
| <input type="checkbox"/>            | For the band 5.15-5.25 GHz, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.                      |
| <input type="checkbox"/>            | For the 5.25-5.35 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz                        |
| <input type="checkbox"/>            | For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz |
| <input type="checkbox"/>            | For the 5.725-5.85 GHz band, 6 dB emission bandwidth $\geq$ 500kHz.                                                                                                                   |


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

| Test Method                                                                    |                                                                                 |
|--------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| ▪ For the emission bandwidth shall be measured using one of the options below: |                                                                                 |
| <input checked="" type="checkbox"/>                                            | Refer as FCC KDB 789033 D02, clause C for EBW and clause D for OBW measurement. |
| <input type="checkbox"/>                                                       | Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.              |
| <input type="checkbox"/>                                                       | Refer as IC RSS-Gen, clause 4.6 for bandwidth testing.                          |

### 3.1.4 Test Setup



### 3.1.5 Test Result of Emission Bandwidth

Refer as Appendix A



## 3.2 Maximum Output Power

### 3.2.1 Limit

| Maximum Output Power Limit                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>UNII Devices</b>                                                                                                                                                                                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/> For the 5.15-5.25 GHz band:                                                                                                                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/>                                                                                                                                                                                       | <ul style="list-style-type: none"><li>Outdoor AP: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math>. e.i.r.p. at any elevation angle above 30 degrees <math>\leq 125</math>mW [21dBm]</li><li>Indoor AP: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math></li><li>Point-to-point AP: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 23</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 23)</math>.</li><li>Mobile or Portable Client: the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 250 mW. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 24 - (G_{TX} - 6)</math>.</li></ul> |
| <input checked="" type="checkbox"/>                                                                                                                                                                            | For the 5.25-5.35 GHz band, the maximum conducted output power ( $P_{Out}$ ) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <input checked="" type="checkbox"/>                                                                                                                                                                            | For the 5.47-5.725 GHz band, the maximum conducted output power ( $P_{Out}$ ) shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6$ dBi, then $P_{Out} = 24 - (G_{TX} - 6)$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> For the 5.725-5.85 GHz band:                                                                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/>                                                                                                                                                                                       | <ul style="list-style-type: none"><li>Point-to-multipoint systems (P2M): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math>.</li><li>Point-to-point systems (P2P): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>Maximum EIRP Limit</b>                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/> For the 5.85-5.895 GHz band:                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/>                                                                                                                                                                                       | <ul style="list-style-type: none"><li>Indoor AP &amp; subordinate device &lt; 36 dBm</li><li>Client device &lt; 30 dBm</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>LE-LAN Devices</b>                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/> For the 5.15-5.25 GHz band, the maximum e.i.r.p. shall not exceed 200 mW or 10 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/> For the 5.25-5.35 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/> For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or 17 + 10 log B, dBm, whichever power is less. B is the 99% emission bandwidth in MHz |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/> For the 5.725-5.85 GHz band:                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <input type="checkbox"/>                                                                                                                                                                                       | <ul style="list-style-type: none"><li>Point-to-multipoint systems (P2M): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the lesser of 1 W. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 30 - (G_{TX} - 6)</math>.</li><li>Point-to-point systems (P2P): the maximum conducted output power (<math>P_{Out}</math>) shall not exceed the</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |



lesser of 1 W.

$P_{Out}$  = maximum conducted output power in dBm,

$G_{TX}$  = the maximum transmitting antenna directional gain in dBi.

### 3.2.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures


| Test Method                         |                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                     | Average over on/off periods with duty factor                                                                                                                                                                                                                                                                                                                         |
| <input checked="" type="checkbox"/> | Refer as FCC KDB 789033 D02, clause E Method SA-2 (spectral trace averaging).                                                                                                                                                                                                                                                                                        |
| <input type="checkbox"/>            | Refer as FCC KDB 789033 D02, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)                                                                                                                                                                                                                                                                         |
|                                     | Wideband RF power meter and average over on/off periods with duty factor                                                                                                                                                                                                                                                                                             |
| <input checked="" type="checkbox"/> | Refer as FCC KDB 789033 D02, clause E Method PM-G (using an RF average power meter).                                                                                                                                                                                                                                                                                 |
| <input checked="" type="checkbox"/> | For conducted measurement.                                                                                                                                                                                                                                                                                                                                           |
|                                     | <ul style="list-style-type: none"><li>If the EUT supports multiple transmit chains using options given below:<br/>Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.</li></ul> |
|                                     | <ul style="list-style-type: none"><li>If multiple transmit chains, EIRP calculation could be following as methods:<br/><math>P_{total} = P_1 + P_2 + \dots + P_n</math><br/>(calculated in linear unit [mW] and transfer to log unit [dBm])<br/><math>EIRP_{total} = P_{total} + DG</math></li></ul>                                                                 |
| <input type="checkbox"/>            | For radiated measurement.                                                                                                                                                                                                                                                                                                                                            |
|                                     | <ul style="list-style-type: none"><li>Refer as FCC KDB 789033 D02 clause II A.1.F "Antenna-port Conducted versus Radiated Testing"</li></ul>                                                                                                                                                                                                                         |
|                                     | <ul style="list-style-type: none"><li>Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz.</li></ul>                                                                                                                                                                                                                                                  |
|                                     | <ul style="list-style-type: none"><li>Refer as FCC KDB 412172 D01 clause 2.2 for EIRP calculation.</li></ul>                                                                                                                                                                                                                                                         |

### 3.2.4 Test Setup

For Straddle channels



For other channels



### 3.2.5 Test Result of Maximum Output Power

Refer as Appendix B



### 3.3 Power Spectral Density

#### 3.3.1 Limit

| Peak Power Spectral Density Limit                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|---------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>UNII Devices</b>                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/> For the 5.15-5.25 GHz band:                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/>                                                                                                              | <ul style="list-style-type: none"><li>Outdoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 17 - (G_{TX} - 6)</math>.</li><li>Indoor AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>P_{Out} = 17 - (G_{TX} - 6)</math>.</li><li>Point-to-point AP: the peak power spectral density (PPSD) shall not exceed the lesser of 17dBm/MHz. If <math>G_{TX} &gt; 23</math> dBi, then <math>P_{Out} = 17 - (G_{TX} - 23)</math>.</li><li>Mobile or Portable Client: the peak power spectral density (PPSD) <math>\leq 11</math> dBm/MHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>PPSD = 11 - (G_{TX} - 6)</math>.</li></ul> |
| <input checked="" type="checkbox"/>                                                                                                   | For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| <input checked="" type="checkbox"/>                                                                                                   | For the 5.47-5.725 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz. If $G_{TX} > 6$ dBi, then $PPSD = 11 - (G_{TX} - 6)$ .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> For the 5.725-5.85 GHz band:                                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/>                                                                                                              | <ul style="list-style-type: none"><li>Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>PPSD = 30 - (G_{TX} - 6)</math>.</li><li>Point-to-point systems (P2P): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>EIRP Power Spectral Density Limit</b>                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/> For the 5.85-5.895 GHz band:                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/>                                                                                                              | <ul style="list-style-type: none"><li>Indoor AP &amp; subordinate device <math>&lt; 20</math>dBm/MHz</li><li>Client device <math>&lt; 14</math>dBm/MHz</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <b>LE-LAN Devices</b>                                                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/> For the 5.15-5.25 GHz band, the e.i.r.p. peak power spectral density (PPSD) $\leq 10$ dBm/MHz.               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/> For the 5.25-5.35 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz.                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/>                                                                                                              | <ul style="list-style-type: none"><li>e.i.r.p. greater than 200 mW shall comply with the following e.i.r.p. at different elevations, where <math>\theta</math> is the angle above the local horizontal plane (of the Earth) as shown below:<br/>-13 dBW/MHz for <math>0^\circ \leq \theta &lt; 8^\circ</math> ; -13 - 0.716 (<math>\theta</math>-8) dBW/MHz for <math>8^\circ \leq \theta &lt; 40^\circ</math><br/>-35.9 - 1.22 (<math>\theta</math>-40) dBW/MHz for <math>40^\circ \leq \theta \leq 45^\circ</math> ; -42 dBW/MHz for <math>\theta &gt; 45^\circ</math></li></ul>                                                                                                                                                                                                                          |
| <input type="checkbox"/> For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the peak power spectral density (PPSD) $\leq 11$ dBm/MHz. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/> For the 5.725-5.85 GHz band:                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <input type="checkbox"/>                                                                                                              | <ul style="list-style-type: none"><li>Point-to-multipoint systems (P2M): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz. If <math>G_{TX} &gt; 6</math> dBi, then <math>PPSD = 30 - (G_{TX} - 6)</math>.</li><li>Point-to-point systems (P2P): the peak power spectral density (PPSD) <math>\leq 30</math> dBm/500kHz.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <b>PPSD</b> = peak power spectral density that he same method as used to determine the conducted output                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |



power shall be used to determine the power spectral density. And power spectral density in dBm/MHz  
 $G_{TX}$  = the maximum transmitting antenna directional gain in dBi.

### 3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.3.3 Test Procedures

| Test Method                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>Peak power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the peak power spectral density and use the peak search function on the spectrum analyzer to find the peak of the spectrum. For the peak power spectral density shall be measured using below options:</li></ul> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                      | Refer as FCC KDB 789033 D02, F)5) power spectral density can be measured using resolution bandwidths < 1 MHz provided that the results are integrated over 1 MHz bandwidth                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| [duty cycle ≥ 98% or external video / power trigger]                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <input checked="" type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                           | Refer as FCC KDB 789033 D02, clause E Method SA-1 (spectral trace averaging).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                      | Refer as FCC KDB 789033 D02, clause E Method SA-1 Alt. (RMS detection with slow sweep speed)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| duty cycle < 98% and average over on/off periods with duty factor                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <input checked="" type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                           | Refer as FCC KDB 789033 D02, clause E Method SA-2 (spectral trace averaging).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                      | Refer as FCC KDB 789033 D02, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> For conducted measurement.                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <ul style="list-style-type: none"><li>If the EUT supports multiple transmit chains using options given below:</li></ul>                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| <input checked="" type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                           | Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace. |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                      | Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,                                                                                                                                                                                                         |
| <input type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                      | Option 3: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.                                                                                                                                                                                                                                                                                                                  |
| <ul style="list-style-type: none"><li>If multiple transmit chains, EIRP PPSD calculation could be following as methods:<br/><math>PPSD_{total} = PPSD_1 + PPSD_2 + \dots + PPSD_n</math><br/>(calculated in linear unit [mW] and transfer to log unit [dBm])</li></ul>                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |

| Test Method              |                                                                                                                                                |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
|                          | $EIRP_{total} = PPSD_{total} + DG$                                                                                                             |
| <input type="checkbox"/> | For radiated measurement.                                                                                                                      |
|                          | <ul style="list-style-type: none"> <li>Refer as FCC KDB 789033 D02 clause II A.1.F "Antenna-port Conducted versus Radiated Testing"</li> </ul> |
|                          | <ul style="list-style-type: none"> <li>Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz.</li> </ul>                          |
|                          | <ul style="list-style-type: none"> <li>Refer as FCC KDB 412172 D01 clause 2.2 for EIRP calculation.</li> </ul>                                 |

### 3.3.4 Test Setup



### 3.3.5 Test Result of Power Spectral Density

Refer as Appendix C



### 3.4 Unwanted Emissions

#### 3.4.1 Transmitter Unwanted Emissions Limit

| Unwanted emissions below 1 GHz and restricted band emissions above 1GHz limit |                       |                         |                      |
|-------------------------------------------------------------------------------|-----------------------|-------------------------|----------------------|
| Frequency Range (MHz)                                                         | Field Strength (uV/m) | Field Strength (dBuV/m) | Measure Distance (m) |
| 0.009~0.490                                                                   | 2400/F(kHz)           | 48.5 - 13.8             | 300                  |
| 0.490~1.705                                                                   | 24000/F(kHz)          | 33.8 - 23               | 30                   |
| 1.705~30.0                                                                    | 30                    | 29                      | 30                   |
| 30~88                                                                         | 100                   | 40                      | 3                    |
| 88~216                                                                        | 150                   | 43.5                    | 3                    |
| 216~960                                                                       | 200                   | 46                      | 3                    |
| Above 960                                                                     | 500                   | 54                      | 3                    |

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

| Un-restricted band emissions above 1GHz Limit        |                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Operating Band                                       | Limit                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <input type="checkbox"/> 5.15 - 5.25 GHz             | e.i.r.p. -27 dBm [68.2 dBuV/m@3m]                                                                                                                                                                                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> 5.25 - 5.35 GHz  | e.i.r.p. -27 dBm [68.2 dBuV/m@3m]                                                                                                                                                                                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> 5.47 - 5.725 GHz | e.i.r.p. -27 dBm [68.2 dBuV/m@3m]                                                                                                                                                                                                                                                                                                                                                                                               |
| <input checked="" type="checkbox"/> 5.725 - 5.85 GHz | all emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. |
| <input type="checkbox"/> 5.85 - 5.895 GHz            | (i) For an indoor access point or subordinate device, all emissions at or above 5.895 GHz shall not exceed an e.i.r.p. of 15 dBm/MHz and shall decrease linearly to an e.i.r.p. of - 7 dBm/MHz at or above 5.925 GHz.<br>(ii) For a client device, all emissions at or above 5.895 GHz shall not exceed an                                                                                                                      |



|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | e.i.r.p. of -5 dBm/MHz and shall decrease linearly to an e.i.r.p. of -27 dBm/MHz at or above 5.925 GHz.<br>(iii) For a client device or indoor access point or subordinate device, all emissions below 5.725 GHz shall not exceed an e.i.r.p. of -27 dBm/MHz at 5.65 GHz increasing linearly to 10 dBm/ MHz at 5.7 GHz, and from 5.7 GHz increasing linearly to a level of 15.6 dBm/MHz at 5.72 GHz, and from 5.72 GHz increasing linearly to a level of 27 dBm/MHz at 5.725 GHz. |
| Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements). |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### 3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

### 3.4.3 Test Procedures

| Test Method                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                            |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"><li>Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).</li></ul> |                                                                                                                                            |
| <ul style="list-style-type: none"><li>The average emission levels shall be measured in [duty cycle <math>\geq</math> 98 or duty factor].</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                            |
| <ul style="list-style-type: none"><li>For the transmitter unwanted emissions shall be measured using following options below:</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                            |
| <ul style="list-style-type: none"><li>For radiated measurement.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | <ul style="list-style-type: none"><li>Refer as FCC KDB 789033 D02, clause G)2) for unwanted emissions into non-restricted bands.</li></ul> |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <ul style="list-style-type: none"><li>Refer as FCC KDB 789033 D02, clause G)1) for unwanted emissions into restricted bands.</li></ul>     |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <input type="checkbox"/> Refer as FCC KDB 789033 D02, G)6) Method AD (Trace Averaging).                                                    |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <input checked="" type="checkbox"/> Refer as FCC KDB 789033 D02, G)6) Method VB (Reduced VBW).                                             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <input type="checkbox"/> Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW $\geq$ 1/T, where T is pulse time.                    |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <input type="checkbox"/> Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.                                               |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | <input checked="" type="checkbox"/> Refer as FCC KDB 789033 D02, clause G)5) measurement procedure peak limit.                             |
| <ul style="list-style-type: none"><li>The any unwanted emissions level shall not exceed the fundamental emission level.</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <input type="checkbox"/> Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.                                          |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                            |

**Test Method**

- All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

**3.4.4 Test Setup**

**3.4.5 Measurement Results Calculation**

The measured Level is calculated using:

Corrected Reading: Antenna factor (AF) + Cable loss (CL) + Read level (Raw) - Preamp factor (PA)(if applicable) = Level.

**3.4.6 Test Result of Transmitter Unwanted Emissions**

Refer as Appendix D



## 4 Test Equipment and Calibration Data

| Instrument                    | Brand       | Model No.         | Serial No.          | Characteristics     | Calibration Date | Calibration Due Date | Remark                   |
|-------------------------------|-------------|-------------------|---------------------|---------------------|------------------|----------------------|--------------------------|
| 3m Semi Anechoic Chamber VSWR | RIKEN       | SAC-3M            | 03CH02-CB           | 1GHz ~18GHz<br>3m   | Mar. 27, 2021    | Mar. 26, 2022        | Radiation<br>(03CH02-CB) |
| Horn Antenna                  | EMCO        | 3115              | 9610-4976           | 1GHz ~ 18GHz        | May 04, 2021     | May 03, 2022         | Radiation<br>(03CH02-CB) |
| Horn Antenna                  | Schwarzbeck | BBHA 9170         | BBHA9170252         | 15GHz ~ 40GHz       | Aug. 05, 2021    | Aug. 04, 2022        | Radiation<br>(03CH02-CB) |
| Pre-Amplifier                 | Agilent     | 83017A            | MY39501305          | 1GHz ~<br>26.5GHz   | Jul. 12, 2021    | Jul. 11, 2022        | Radiation<br>(03CH02-CB) |
| Pre-Amplifier                 | MITEQ       | TTA1840-35-H<br>G | 1864479             | 18GHz ~ 40GHz       | Jul. 13, 2021    | Jul. 12, 2022        | Radiation<br>(03CH02-CB) |
| Spectrum analyzer             | R&S         | FSU               | 100015              | 9kHz~26GHz          | Oct. 25, 2021    | Oct. 24, 2022        | Radiation<br>(03CH02-CB) |
| RF Cable-high                 | Woken       | RG402             | High Cable-18       | 1GHz ~ 18GHz        | Oct. 04, 2021    | Oct. 03, 2022        | Radiation<br>(03CH02-CB) |
| RF Cable-high                 | Woken       | RG402             | High<br>Cable-18+19 | 1GHz ~ 18GHz        | Oct. 04, 2021    | Oct. 03, 2022        | Radiation<br>(03CH02-CB) |
| High Cable                    | Woken       | WCA0929M          | 40G#5+7             | 1GHz ~ 40 GHz       | Dec. 14, 2021    | Dec. 13, 2022        | Radiation<br>(03CH02-CB) |
| High Cable                    | Woken       | WCA0929M          | 40G#5               | 1GHz ~ 40 GHz       | Dec. 08, 2021    | Dec. 07, 2022        | Radiation<br>(03CH02-CB) |
| High Cable                    | Woken       | WCA0929M          | 40G#7               | 1GHz ~ 40 GHz       | Dec. 14, 2021    | Dec. 13, 2022        | Radiation<br>(03CH02-CB) |
| Test Software                 | SPORTON     | SENSE             | V5.10               | -                   | N.C.R.           | N.C.R.               | Radiation<br>(03CH02-CB) |
| Spectrum analyzer             | R&S         | FSV40             | 100979              | 9kHz~40GHz          | May 21, 2021     | May 20, 2022         | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | High Cable-06       | 1 GHz –<br>26.5 GHz | Oct. 04, 2021    | Oct. 03, 2022        | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | High Cable-07       | 1 GHz –<br>26.5 GHz | Oct. 04, 2021    | Oct. 03, 2022        | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | High Cable-08       | 1 GHz –<br>26.5 GHz | Oct. 04, 2021    | Oct. 03, 2022        | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | High Cable-09       | 1 GHz –<br>26.5 GHz | Oct. 04, 2021    | Oct. 03, 2022        | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | High Cable-10       | 1 GHz –<br>26.5 GHz | Oct. 04, 2021    | Oct. 03, 2022        | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | High Cable-30       | 1 GHz –<br>26.5 GHz | Oct. 04, 2021    | Oct. 03, 2022        | Conducted<br>(TH01-CB)   |
| Switch                        | SPTCB       | SP-SWI            | SWI-01              | 1 GHz –<br>26.5 GHz | Dec. 13, 2021    | Dec. 12, 2022        | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | SWI-01-P1           | 1 GHz –<br>26.5 GHz | Dec. 13, 2021    | Dec. 12, 2022        | Conducted<br>(TH01-CB)   |
| RF Cable-high                 | Woken       | RG402             | SWI-01-P2           | 1 GHz –<br>26.5 GHz | Dec. 13, 2021    | Dec. 12, 2022        | Conducted<br>(TH01-CB)   |



| Instrument    | Brand   | Model No. | Serial No. | Characteristics  | Calibration Date | Calibration Due Date | Remark              |
|---------------|---------|-----------|------------|------------------|------------------|----------------------|---------------------|
| RF Cable-high | Woken   | RG402     | SWI-01-P3  | 1 GHz – 26.5 GHz | Dec. 13, 2021    | Dec. 12, 2022        | Conducted (TH01-CB) |
| RF Cable-high | Woken   | RG402     | SWI-01-P4  | 1 GHz – 26.5 GHz | Dec. 13, 2021    | Dec. 12, 2022        | Conducted (TH01-CB) |
| RF Cable-high | Woken   | RG402     | SWI-01-P5  | 1 GHz – 26.5 GHz | Dec. 13, 2021    | Dec. 12, 2022        | Conducted (TH01-CB) |
| Power Sensor  | Agilent | U2021XA   | MY53410001 | 50MHz~18GHz      | Nov. 05, 2021    | Nov. 04, 2022        | Conducted (TH01-CB) |
| Power Sensor  | Agilent | U2021XA   | MY53410002 | 50MHz~18GHz      | Nov. 05, 2021    | Nov. 04, 2022        | Conducted (TH01-CB) |
| Power Sensor  | Agilent | U2021XA   | MY54320014 | 50MHz~18GHz      | Apr. 15, 2021    | Apr. 14, 2022        | Conducted (TH01-CB) |
| Power Sensor  | Agilent | U2021XA   | MY54320015 | 50MHz~18GHz      | Apr. 15, 2021    | Apr. 14, 2022        | Conducted (TH01-CB) |
| Test Software | SPORTON | SENSE     | V5.10      | -                | N.C.R.           | N.C.R.               | Conducted (TH01-CB) |

Note: Calibration Interval of instruments listed above is one year.

NCR means Non-Calibration required.

**Summary**

| Mode                            | Max-N dB<br>(Hz) | Max-OBW<br>(Hz) | ITU-Code | Min-N dB<br>(Hz) | Min-OBW<br>(Hz) |
|---------------------------------|------------------|-----------------|----------|------------------|-----------------|
| 5.15-5.25GHz                    | -                | -               | -        | -                | -               |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 82.88M           | 78.281M         | 78M3D1D  | 82.48M           | 78.121M         |
| 5.25-5.35GHz                    | -                | -               | -        | -                | -               |
| 802.11a_Nss1,(6Mbps)_4TX        | 21.78M           | 17.181M         | 17M2D1D  | 21.42M           | 16.942M         |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 21.93M           | 19.16M          | 19M2D1D  | 21.51M           | 19.1M           |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 40.74M           | 38.021M         | 38M0D1D  | 40.44M           | 37.901M         |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 82.32M           | 77.721M         | 77M7D1D  | 81.84M           | 77.601M         |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 83.04M           | 78.601M         | 78M6D1D  | 82.16M           | 78.361M         |
| 5.47-5.725GHz                   | -                | -               | -        | -                | -               |
| 802.11a_Nss1,(6Mbps)_4TX        | 22.08M           | 17.151M         | 17M2D1D  | 15.63M           | 13.523M         |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 21.96M           | 19.16M          | 19M2D1D  | 15.75M           | 14.558M         |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 40.92M           | 38.021M         | 38M0D1D  | 35.21M           | 33.828M         |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 82.44M           | 77.841M         | 77M8D1D  | 75.9M            | 73.463M         |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 165.6M           | 156.882M        | 157MD1D  | 164.4M           | 156.642M        |
| 5.725-5.85GHz                   | -                | -               | -        | -                | -               |
| 802.11a_Nss1,(6Mbps)_4TX        | 3.16M            | 4.298M          | 4M30D1D  | 3.14M            | 4.218M          |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 4.5M             | 4.718M          | 4M72D1D  | 4.46M            | 4.678M          |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 3.94M            | 4.178M          | 4M18D1D  | 3.76M            | 4.138M          |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 4.02M            | 4.238M          | 4M24D1D  | 3.74M            | 4.178M          |

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;  
 Max-OBW = Maximum 99% occupied bandwidth;  
 Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;  
 Min-OBW = Minimum 99% occupied bandwidth


**Result**

| Mode                            | Result | Limit (Hz) | Port 1-N dB (Hz) | Port 1-OBW (Hz) | Port 2-N dB (Hz) | Port 2-OBW (Hz) | Port 3-N dB (Hz) | Port 3-OBW (Hz) | Port 4-N dB (Hz) | Port 4-OBW (Hz) |
|---------------------------------|--------|------------|------------------|-----------------|------------------|-----------------|------------------|-----------------|------------------|-----------------|
| 802.11a_Nss1,(6Mbps)_4TX        | -      | -          | -                | -               | -                | -               | -                | -               | -                | -               |
| 5260MHz                         | Pass   | Inf        | 21.63M           | 17.181M         | 21.6M            | 17.061M         | 21.57M           | 17.001M         | 21.45M           | 16.942M         |
| 5300MHz                         | Pass   | Inf        | 21.78M           | 17.091M         | 21.69M           | 17.061M         | 21.42M           | 17.001M         | 21.57M           | 16.972M         |
| 5320MHz                         | Pass   | Inf        | 21.6M            | 17.151M         | 21.72M           | 17.061M         | 21.57M           | 16.972M         | 21.42M           | 16.942M         |
| 5500MHz                         | Pass   | Inf        | 21.54M           | 17.151M         | 21.78M           | 17.121M         | 21.57M           | 17.001M         | 21.63M           | 16.972M         |
| 5580MHz                         | Pass   | Inf        | 21.66M           | 17.091M         | 21.93M           | 17.121M         | 22.08M           | 17.001M         | 21.78M           | 16.972M         |
| 5700MHz                         | Pass   | Inf        | 21.84M           | 17.151M         | 21.57M           | 17.061M         | 21.57M           | 17.031M         | 21.6M            | 16.942M         |
| 5720MHz Straddle 5.47-5.725GHz  | Pass   | Inf        | 15.825M          | 13.613M         | 15.915M          | 13.628M         | 15.63M           | 13.523M         | 15.81M           | 13.553M         |
| 5720MHz Straddle 5.725-5.85GHz  | Pass   | 500k       | 3.16M            | 4.298M          | 3.14M            | 4.258M          | 3.16M            | 4.238M          | 3.16M            | 4.218M          |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | -      | -          | -                | -               | -                | -               | -                | -               | -                | -               |
| 5260MHz                         | Pass   | Inf        | 21.93M           | 19.1M           | 21.66M           | 19.13M          | 21.69M           | 19.13M          | 21.84M           | 19.1M           |
| 5300MHz                         | Pass   | Inf        | 21.93M           | 19.1M           | 21.51M           | 19.16M          | 21.51M           | 19.13M          | 21.6M            | 19.1M           |
| 5320MHz                         | Pass   | Inf        | 21.78M           | 19.13M          | 21.72M           | 19.1M           | 21.93M           | 19.13M          | 21.72M           | 19.13M          |
| 5500MHz                         | Pass   | Inf        | 21.96M           | 19.1M           | 21.75M           | 19.1M           | 21.69M           | 19.16M          | 21.6M            | 19.1M           |
| 5580MHz                         | Pass   | Inf        | 21.78M           | 19.13M          | 21.72M           | 19.13M          | 21.78M           | 19.13M          | 21.57M           | 19.1M           |
| 5700MHz                         | Pass   | Inf        | 21.66M           | 19.16M          | 21.6M            | 19.1M           | 21.78M           | 19.13M          | 21.6M            | 19.07M          |
| 5720MHz Straddle 5.47-5.725GHz  | Pass   | Inf        | 15.885M          | 14.588M         | 15.75M           | 14.558M         | 15.78M           | 14.558M         | 15.795M          | 14.573M         |
| 5720MHz Straddle 5.725-5.85GHz  | Pass   | 500k       | 4.46M            | 4.718M          | 4.46M            | 4.698M          | 4.5M             | 4.718M          | 4.46M            | 4.678M          |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | -      | -          | -                | -               | -                | -               | -                | -               | -                | -               |
| 5270MHz                         | Pass   | Inf        | 40.68M           | 37.961M         | 40.62M           | 37.961M         | 40.44M           | 37.961M         | 40.62M           | 38.021M         |
| 5310MHz                         | Pass   | Inf        | 40.74M           | 37.961M         | 40.62M           | 37.901M         | 40.5M            | 37.961M         | 40.44M           | 37.901M         |
| 5510MHz                         | Pass   | Inf        | 40.62M           | 37.961M         | 40.74M           | 37.901M         | 40.44M           | 37.901M         | 40.44M           | 37.901M         |
| 5550MHz                         | Pass   | Inf        | 40.68M           | 37.961M         | 40.62M           | 37.961M         | 40.92M           | 37.901M         | 40.5M            | 37.961M         |
| 5670MHz                         | Pass   | Inf        | 40.62M           | 37.841M         | 40.56M           | 37.901M         | 40.68M           | 37.961M         | 40.62M           | 38.021M         |
| 5710MHz Straddle 5.47-5.725GHz  | Pass   | Inf        | 35.35M           | 33.828M         | 35.21M           | 33.898M         | 35.385M          | 33.898M         | 35.21M           | 33.828M         |
| 5710MHz Straddle 5.725-5.85GHz  | Pass   | 500k       | 3.94M            | 4.138M          | 3.94M            | 4.178M          | 3.86M            | 4.138M          | 3.76M            | 4.138M          |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | -      | -          | -                | -               | -                | -               | -                | -               | -                | -               |
| 5290MHz                         | Pass   | Inf        | 81.84M           | 77.601M         | 81.96M           | 77.721M         | 81.84M           | 77.721M         | 82.32M           | 77.721M         |
| 5530MHz                         | Pass   | Inf        | 81.96M           | 77.721M         | 81.48M           | 77.601M         | 82.44M           | 77.721M         | 81.72M           | 77.481M         |
| 5610MHz                         | Pass   | Inf        | 82.32M           | 77.841M         | 81.84M           | 77.841M         | 81.96M           | 77.841M         | 82.32M           | 77.841M         |
| 5690MHz Straddle 5.47-5.725GHz  | Pass   | Inf        | 75.975M          | 73.463M         | 76.125M          | 73.463M         | 75.9M            | 73.463M         | 75.975M          | 73.463M         |
| 5690MHz Straddle 5.725-5.85GHz  | Pass   | 500k       | 3.88M            | 4.198M          | 3.74M            | 4.178M          | 4.02M            | 4.238M          | 3.86M            | 4.178M          |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | -      | -          | -                | -               | -                | -               | -                | -               | -                | -               |
| 5250MHz Straddle 5.15-5.25GHz   | Pass   | Inf        | 82.88M           | 78.201M         | 82.56M           | 78.281M         | 82.48M           | 78.201M         | 82.56M           | 78.121M         |
| 5250MHz Straddle 5.25-5.35GHz   | Pass   | Inf        | 82.8M            | 78.521M         | 83.04M           | 78.601M         | 82.56M           | 78.521M         | 82.16M           | 78.361M         |
| 5570MHz                         | Pass   | Inf        | 164.64M          | 156.882M        | 165.6M           | 156.882M        | 164.4M           | 156.882M        | 165.12M          | 156.642M        |


Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band  
Port X-OBW = Port X 99% occupied bandwidth

**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5260MHz**

23/02/2022



**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5300MHz**

23/02/2022




**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5320MHz**

23/02/2022



**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5500MHz**

23/02/2022




**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5580MHz**

23/02/2022



**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5700MHz**

23/02/2022




**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5720MHz Straddle 5.47-5.725GHz**

23/02/2022



**802.11a\_Nss1,(6Mbps)\_4TX**
**EBW**
**5720MHz Straddle 5.725-5.85GHz**

23/02/2022




**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5260MHz**

23/02/2022



**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5300MHz**

23/02/2022




**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5320MHz**

23/02/2022



**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5500MHz**

23/02/2022




**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5580MHz**

23/02/2022



**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5700MHz**

23/02/2022




**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5720MHz Straddle 5.47-5.725GHz**

23/02/2022



**802.11ax HEW20\_Nss1,(MCS0)\_4TX**
**EBW**
**5720MHz Straddle 5.725-5.85GHz**

23/02/2022




**802.11ax HEW40\_Nss1,(MCS0)\_4TX**
**EBW**
**5270MHz**

23/02/2022



**802.11ax HEW40\_Nss1,(MCS0)\_4TX**
**EBW**
**5310MHz**

23/02/2022




**802.11ax HEW40\_Nss1,(MCS0)\_4TX**
**EBW**
**5510MHz**

23/02/2022



**802.11ax HEW40\_Nss1,(MCS0)\_4TX**
**EBW**
**5550MHz**

23/02/2022




**802.11ax HEW40\_Nss1,(MCS0)\_4TX**
**EBW**
**5670MHz**

23/02/2022



**802.11ax HEW40\_Nss1,(MCS0)\_4TX**
**EBW**
**5710MHz Straddle 5.47-5.725GHz**

23/02/2022




**802.11ax HEW40\_Nss1,(MCS0)\_4TX**
**EBW**
**5710MHz Straddle 5.725-5.85GHz**

23/02/2022



**802.11ax HEW80\_Nss1,(MCS0)\_4TX**
**EBW**
**5290MHz**

23/02/2022




**802.11ax HEW80\_Nss1,(MCS0)\_4TX**
**EBW**
**5530MHz**

23/02/2022



**802.11ax HEW80\_Nss1,(MCS0)\_4TX**
**EBW**
**5610MHz**

23/02/2022




**802.11ax HEW80\_Nss1,(MCS0)\_4TX**
**EBW**
**5690MHz Straddle 5.47-5.725GHz**

23/02/2022



**802.11ax HEW80\_Nss1,(MCS0)\_4TX**
**EBW**
**5690MHz Straddle 5.725-5.85GHz**

23/02/2022




**802.11ax HEW160\_Nss1,(MCS0)\_4TX**
**EBW**
**5250MHz Straddle 5.15-5.25GHz**

23/02/2022


**802.11ax HEW160\_Nss1,(MCS0)\_4TX**
**EBW**
**5250MHz Straddle 5.25-5.35GHz**

23/02/2022




## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

EBW

5570MHz

23/02/2022





**For Non-beamforming  
Summary**

| Mode                            | Total Power<br>(dBm) | Total Power<br>(W) |
|---------------------------------|----------------------|--------------------|
| 5.15-5.25GHz                    | -                    | -                  |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 21.07                | 0.12794            |
| 5.25-5.35GHz                    | -                    | -                  |
| 802.11a_Nss1,(6Mbps)_4TX        | 23.77                | 0.23823            |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 23.96                | 0.24889            |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 23.93                | 0.24717            |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 23.94                | 0.24774            |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 21.28                | 0.13428            |
| 5.47-5.725GHz                   | -                    | -                  |
| 802.11a_Nss1,(6Mbps)_4TX        | 23.71                | 0.23496            |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 23.96                | 0.24889            |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 23.96                | 0.24889            |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 23.97                | 0.24946            |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 22.63                | 0.18323            |
| 5.725-5.85GHz                   | -                    | -                  |
| 802.11a_Nss1,(6Mbps)_4TX        | 16.77                | 0.04753            |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 17.84                | 0.06081            |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 14.46                | 0.02793            |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 10.89                | 0.01227            |

## Result

| Mode                            | Result | DG<br>(dBi) | Port 1<br>(dBm) | Port 2<br>(dBm) | Port 3<br>(dBm) | Port 4<br>(dBm) | Total Power<br>(dBm) | Power Limit<br>(dBm) |
|---------------------------------|--------|-------------|-----------------|-----------------|-----------------|-----------------|----------------------|----------------------|
| 802.11a_Nss1,(6Mbps)_4TX        | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5260MHz                         | Pass   | 4.88        | 18.12           | 17.32           | 17.79           | 17.75           | 23.77                | 23.98                |
| 5300MHz                         | Pass   | 4.88        | 17.96           | 17.27           | 17.66           | 17.85           | 23.71                | 23.98                |
| 5320MHz                         | Pass   | 4.88        | 18.05           | 17.29           | 17.37           | 17.73           | 23.64                | 23.98                |
| 5500MHz                         | Pass   | 4.09        | 17.38           | 16.42           | 16.96           | 17.16           | 23.01                | 23.98                |
| 5580MHz                         | Pass   | 4.09        | 17.46           | 17.49           | 17.81           | 17.98           | 23.71                | 23.98                |
| 5700MHz                         | Pass   | 4.09        | 16.92           | 16.13           | 16.58           | 17.04           | 22.70                | 23.98                |
| 5720MHz Straddle 5.47-5.725GHz  | Pass   | 4.09        | 16.89           | 16.32           | 16.73           | 17.02           | 22.77                | 22.94                |
| 5720MHz Straddle 5.725-5.85GHz  | Pass   | 4.68        | 10.83           | 10.34           | 10.88           | 10.94           | 16.77                | 30.00                |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5260MHz                         | Pass   | 4.88        | 18.04           | 17.42           | 17.57           | 17.96           | 23.78                | 23.98                |
| 5300MHz                         | Pass   | 4.88        | 18.21           | 17.46           | 17.89           | 18.14           | 23.96                | 23.98                |
| 5320MHz                         | Pass   | 4.88        | 18.32           | 17.39           | 17.73           | 18.08           | 23.91                | 23.98                |
| 5500MHz                         | Pass   | 4.09        | 17.86           | 16.75           | 17.36           | 17.19           | 23.33                | 23.98                |
| 5580MHz                         | Pass   | 4.09        | 17.79           | 17.59           | 18.06           | 18.28           | 23.96                | 23.98                |
| 5700MHz                         | Pass   | 4.09        | 15.91           | 14.87           | 15.46           | 15.98           | 21.60                | 23.98                |
| 5720MHz Straddle 5.47-5.725GHz  | Pass   | 4.09        | 17.15           | 16.33           | 16.89           | 17.28           | 22.95                | 22.97                |
| 5720MHz Straddle 5.725-5.85GHz  | Pass   | 4.68        | 11.99           | 11.29           | 12.00           | 11.95           | 17.84                | 30.00                |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5270MHz                         | Pass   | 4.88        | 18.22           | 17.35           | 17.92           | 18.11           | 23.93                | 23.98                |
| 5310MHz                         | Pass   | 4.88        | 18.19           | 17.26           | 17.74           | 18.09           | 23.86                | 23.98                |
| 5510MHz                         | Pass   | 4.09        | 17.47           | 16.77           | 17.60           | 17.74           | 23.43                | 23.98                |
| 5550MHz                         | Pass   | 4.09        | 18.22           | 17.29           | 17.77           | 18.38           | 23.96                | 23.98                |
| 5670MHz                         | Pass   | 4.09        | 18.05           | 17.67           | 17.71           | 18.12           | 23.91                | 23.98                |
| 5710MHz Straddle 5.47-5.725GHz  | Pass   | 4.09        | 18.06           | 17.34           | 17.74           | 18.31           | 23.90                | 23.98                |
| 5710MHz Straddle 5.725-5.85GHz  | Pass   | 4.68        | 8.64            | 7.84            | 8.56            | 8.67            | 14.46                | 30.00                |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5290MHz                         | Pass   | 4.88        | 18.06           | 17.43           | 17.88           | 18.27           | 23.94                | 23.98                |
| 5530MHz                         | Pass   | 4.09        | 16.68           | 16.24           | 16.99           | 17.21           | 22.82                | 23.98                |
| 5610MHz                         | Pass   | 4.09        | 17.92           | 17.60           | 18.16           | 18.08           | 23.97                | 23.98                |
| 5690MHz Straddle 5.47-5.725GHz  | Pass   | 4.09        | 17.86           | 17.64           | 17.80           | 18.09           | 23.87                | 23.98                |
| 5690MHz Straddle 5.725-5.85GHz  | Pass   | 4.68        | 4.80            | 4.45            | 5.15            | 5.04            | 10.89                | 30.00                |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5250MHz Straddle 5.15-5.25GHz   | Pass   | 4.84        | 15.06           | 14.74           | 15.22           | 15.15           | 21.07                | 30.00                |
| 5250MHz Straddle 5.25-5.35GHz   | Pass   | 4.88        | 15.32           | 14.97           | 15.19           | 15.55           | 21.28                | 23.98                |
| 5570MHz                         | Pass   | 4.09        | 16.36           | 16.28           | 16.69           | 17.06           | 22.63                | 23.98                |


DG = Directional Gain; Port X = Port X output power

## 802.11a\_Nss1,(6Mbps)\_4TX

## AV Power

### 5720MHz Straddle 5.47-5.725GHz\_TnomVnom

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

## AV Power

### 5720MHz Straddle 5.725-5.85GHz\_TnomVnom

23/02/2022




## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## AV Power

### 5720MHz Straddle 5.47-5.725GHz\_TnomVnom

23/02/2022




## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## AV Power

### 5720MHz Straddle 5.725-5.85GHz\_TnomVnom

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## AV Power

### 5710MHz Straddle 5.47-5.725GHz\_TnomVnom

23/02/2022

CF  
5.69GHz  
Span  
140MHz  
RBW  
1MHz  
VBW  
3MHz  
Sweep Time  
20ms  
Detector Type  
RMS  
CP BW  
70MHz



Port 1  
Port 2  
Port 3  
Port 4

Sum= Total Power  
PX=Port X

| Sum(dBm) | P1(dBm) | P2(dBm) | P3(dBm) | P4(dBm) |
|----------|---------|---------|---------|---------|
| 23.90    | 18.06   | 17.34   | 17.74   | 18.31   |


## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## AV Power

### 5710MHz Straddle 5.725-5.85GHz\_TnomVnom

23/02/2022

CF  
5.735GHz  
Span  
40MHz  
RBW  
1MHz  
VBW  
3MHz  
Sweep Time  
20ms  
Detector Type  
RMS  
CP BW  
20MHz



Port 1  
Port 2  
Port 3  
Port 4

Sum= Total Power  
PX=Port X


| Sum(dBm) | P1(dBm) | P2(dBm) | P3(dBm) | P4(dBm) |
|----------|---------|---------|---------|---------|
| 14.46    | 8.64    | 7.84    | 8.56    | 8.67    |

## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## AV Power

### 5690MHz Straddle 5.47-5.725GHz\_TnomVnom

23/02/2022




## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## AV Power

### 5690MHz Straddle 5.725-5.85GHz\_TnomVnom

23/02/2022




## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## AV Power

### 5250MHz Straddle 5.15-5.25GHz\_TnomVnom

23/02/2022




## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## AV Power

### 5250MHz Straddle 5.25-5.35GHz\_TnomVnom

23/02/2022



## For beamforming Summary

| Mode                               | Total Power<br>(dBm) | Total Power<br>(W) |
|------------------------------------|----------------------|--------------------|
| 5.15-5.25GHz                       | -                    | -                  |
| 802.11ax HEW160-BF_Nss1,(MCS0)_4TX | 21.07                | 0.12794            |
| 5.25-5.35GHz                       | -                    | -                  |
| 802.11ax HEW20-BF_Nss1,(MCS0)_4TX  | 23.96                | 0.24889            |
| 802.11ax HEW40-BF_Nss1,(MCS0)_4TX  | 23.93                | 0.24717            |
| 802.11ax HEW80-BF_Nss1,(MCS0)_4TX  | 23.94                | 0.24774            |
| 802.11ax HEW160-BF_Nss1,(MCS0)_4TX | 21.28                | 0.13428            |
| 5.47-5.725GHz                      | -                    | -                  |
| 802.11ax HEW20-BF_Nss1,(MCS0)_4TX  | 23.96                | 0.24889            |
| 802.11ax HEW40-BF_Nss1,(MCS0)_4TX  | 23.96                | 0.24889            |
| 802.11ax HEW80-BF_Nss1,(MCS0)_4TX  | 23.97                | 0.24946            |
| 802.11ax HEW160-BF_Nss1,(MCS0)_4TX | 22.63                | 0.18323            |
| 5.725-5.85GHz                      | -                    | -                  |
| 802.11ax HEW20-BF_Nss1,(MCS0)_4TX  | 17.84                | 0.06081            |
| 802.11ax HEW40-BF_Nss1,(MCS0)_4TX  | 14.46                | 0.02793            |
| 802.11ax HEW80-BF_Nss1,(MCS0)_4TX  | 10.89                | 0.01227            |

**Result**

| Mode                               | Result | DG<br>(dBi) | Port 1<br>(dBm) | Port 2<br>(dBm) | Port 3<br>(dBm) | Port 4<br>(dBm) | Total Power<br>(dBm) | Power Limit<br>(dBm) |
|------------------------------------|--------|-------------|-----------------|-----------------|-----------------|-----------------|----------------------|----------------------|
| 802.11ax HEW20-BF_Nss1,(MCS0)_4TX  | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5260MHz                            | Pass   | 5.88        | 18.04           | 17.42           | 17.57           | 17.96           | 23.78                | 23.98                |
| 5300MHz                            | Pass   | 5.88        | 18.21           | 17.46           | 17.89           | 18.14           | 23.96                | 23.98                |
| 5320MHz                            | Pass   | 5.88        | 18.32           | 17.39           | 17.73           | 18.08           | 23.91                | 23.98                |
| 5500MHz                            | Pass   | 4.50        | 17.86           | 16.75           | 17.36           | 17.19           | 23.33                | 23.98                |
| 5580MHz                            | Pass   | 4.50        | 17.79           | 17.59           | 18.06           | 18.28           | 23.96                | 23.98                |
| 5700MHz                            | Pass   | 4.50        | 15.91           | 14.87           | 15.46           | 15.98           | 21.60                | 23.98                |
| 5720MHz Straddle 5.47-5.725GHz     | Pass   | 4.50        | 17.15           | 16.33           | 16.89           | 17.28           | 22.95                | 22.97                |
| 5720MHz Straddle 5.725-5.85GHz     | Pass   | 5.09        | 11.99           | 11.29           | 12.00           | 11.95           | 17.84                | 30.00                |
| 802.11ax HEW40-BF_Nss1,(MCS0)_4TX  | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5270MHz                            | Pass   | 5.88        | 18.22           | 17.35           | 17.92           | 18.11           | 23.93                | 23.98                |
| 5310MHz                            | Pass   | 5.88        | 18.19           | 17.26           | 17.74           | 18.09           | 23.86                | 23.98                |
| 5510MHz                            | Pass   | 4.50        | 17.47           | 16.77           | 17.6            | 17.74           | 23.43                | 23.98                |
| 5550MHz                            | Pass   | 4.50        | 18.22           | 17.29           | 17.77           | 18.38           | 23.96                | 23.98                |
| 5670MHz                            | Pass   | 4.50        | 18.05           | 17.67           | 17.71           | 18.12           | 23.91                | 23.98                |
| 5710MHz Straddle 5.47-5.725GHz     | Pass   | 4.50        | 18.06           | 17.34           | 17.74           | 18.31           | 23.90                | 23.98                |
| 5710MHz Straddle 5.725-5.85GHz     | Pass   | 5.09        | 8.64            | 7.84            | 8.56            | 8.67            | 14.46                | 30.00                |
| 802.11ax HEW80-BF_Nss1,(MCS0)_4TX  | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5290MHz                            | Pass   | 5.88        | 18.06           | 17.43           | 17.88           | 18.27           | 23.94                | 23.98                |
| 5530MHz                            | Pass   | 4.50        | 16.68           | 16.24           | 16.99           | 17.21           | 22.82                | 23.98                |
| 5610MHz                            | Pass   | 4.50        | 17.92           | 17.6            | 18.16           | 18.08           | 23.97                | 23.98                |
| 5690MHz Straddle 5.47-5.725GHz     | Pass   | 4.50        | 17.86           | 17.64           | 17.8            | 18.09           | 23.87                | 23.98                |
| 5690MHz Straddle 5.725-5.85GHz     | Pass   | 5.09        | 4.8             | 4.45            | 5.15            | 5.04            | 10.89                | 30.00                |
| 802.11ax HEW160-BF_Nss1,(MCS0)_4TX | -      | -           | -               | -               | -               | -               | -                    | -                    |
| 5250MHz Straddle 5.15-5.25GHz      | Pass   | 5.06        | 15.06           | 14.74           | 15.22           | 15.15           | 21.07                | 30.00                |
| 5250MHz Straddle 5.25-5.35GHz      | Pass   | 5.88        | 15.32           | 14.97           | 15.19           | 15.55           | 21.28                | 23.98                |
| 5570MHz                            | Pass   | 4.50        | 16.36           | 16.28           | 16.69           | 17.06           | 22.63                | 23.98                |


DG = Directional Gain; Port X = Port X output power

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## AV Power

### 5720MHz Straddle 5.47-5.725GHz\_TnomVnom

23/02/2022




## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## AV Power

### 5720MHz Straddle 5.725-5.85GHz\_TnomVnom

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## AV Power

### 5710MHz Straddle 5.47-5.725GHz\_TnomVnom

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## AV Power

### 5710MHz Straddle 5.725-5.85GHz\_TnomVnom

23/02/2022




## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## AV Power

### 5690MHz Straddle 5.47-5.725GHz\_TnomVnom

23/02/2022




## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## AV Power

### 5690MHz Straddle 5.725-5.85GHz\_TnomVnom

23/02/2022




## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## AV Power

### 5250MHz Straddle 5.15-5.25GHz\_TnomVnom

23/02/2022




## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## AV Power

### 5250MHz Straddle 5.25-5.35GHz\_TnomVnom

23/02/2022



**Summary**

| Mode                            | PD<br>(dBm/RBW) |
|---------------------------------|-----------------|
| 5.15-5.25GHz                    | -               |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 2.24            |
| 5.25-5.35GHz                    | -               |
| 802.11a_Nss1,(6Mbps)_4TX        | 10.93           |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 10.47           |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 7.59            |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 4.83            |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 2.26            |
| 5.47-5.725GHz                   | -               |
| 802.11a_Nss1,(6Mbps)_4TX        | 10.80           |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 10.52           |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 7.76            |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 4.95            |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | 1.27            |
| 5.725-5.85GHz                   | -               |
| 802.11a_Nss1,(6Mbps)_4TX        | 9.05            |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | 8.80            |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | 6.05            |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | 2.66            |

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

**Result**

| Mode                            | Result | DG<br>(dBi) | Port 1<br>(dBm/RBW) | Port 2<br>(dBm/RBW) | Port 3<br>(dBm/RBW) | Port 4<br>(dBm/RBW) | PD<br>(dBm/RBW) | PD Limit<br>(dBm/RBW) |
|---------------------------------|--------|-------------|---------------------|---------------------|---------------------|---------------------|-----------------|-----------------------|
| 802.11a_Nss1,(6Mbps)_4TX        | -      | -           | -                   | -                   | -                   | -                   | -               | -                     |
| 5260MHz                         | Pass   | 5.88        | 5.43                | 4.70                | 4.89                | 4.98                | 10.93           | 11.00                 |
| 5300MHz                         | Pass   | 5.88        | 5.23                | 4.56                | 4.81                | 5.00                | 10.77           | 11.00                 |
| 5320MHz                         | Pass   | 5.88        | 5.36                | 4.46                | 4.60                | 4.96                | 10.80           | 11.00                 |
| 5500MHz                         | Pass   | 4.50        | 4.48                | 3.35                | 3.95                | 4.25                | 9.93            | 11.00                 |
| 5580MHz                         | Pass   | 4.50        | 4.68                | 4.66                | 5.02                | 5.16                | 10.80           | 11.00                 |
| 5700MHz                         | Pass   | 4.50        | 3.94                | 3.31                | 3.76                | 4.16                | 9.73            | 11.00                 |
| 5720MHz Straddle 5.47-5.725GHz  | Pass   | 4.50        | 4.91                | 4.09                | 4.71                | 5.12                | 10.63           | 11.00                 |
| 5720MHz Straddle 5.725-5.85GHz  | Pass   | 5.09        | 3.33                | 2.68                | 3.16                | 3.32                | 9.05            | 30.00                 |
| 802.11ax HEW20_Nss1,(MCS0)_4TX  | -      | -           | -                   | -                   | -                   | -                   | -               | -                     |
| 5260MHz                         | Pass   | 5.88        | 4.80                | 3.81                | 4.30                | 4.36                | 10.27           | 11.00                 |
| 5300MHz                         | Pass   | 5.88        | 4.82                | 3.97                | 4.46                | 4.72                | 10.47           | 11.00                 |
| 5320MHz                         | Pass   | 5.88        | 4.98                | 3.83                | 4.30                | 4.70                | 10.43           | 11.00                 |
| 5500MHz                         | Pass   | 4.50        | 4.34                | 3.12                | 3.75                | 3.97                | 9.75            | 11.00                 |
| 5580MHz                         | Pass   | 4.50        | 4.40                | 4.20                | 4.70                | 4.92                | 10.52           | 11.00                 |
| 5700MHz                         | Pass   | 4.50        | 2.42                | 1.36                | 1.97                | 2.51                | 8.03            | 11.00                 |
| 5720MHz Straddle 5.47-5.725GHz  | Pass   | 4.50        | 4.66                | 3.81                | 4.46                | 4.77                | 10.38           | 11.00                 |
| 5720MHz Straddle 5.725-5.85GHz  | Pass   | 5.09        | 3.04                | 2.23                | 2.93                | 3.02                | 8.80            | 30.00                 |
| 802.11ax HEW40_Nss1,(MCS0)_4TX  | -      | -           | -                   | -                   | -                   | -                   | -               | -                     |
| 5270MHz                         | Pass   | 5.88        | 1.93                | 1.06                | 1.68                | 1.89                | 7.59            | 11.00                 |
| 5310MHz                         | Pass   | 5.88        | 1.93                | 1.06                | 1.59                | 1.87                | 7.57            | 11.00                 |
| 5510MHz                         | Pass   | 4.50        | 1.10                | 0.45                | 1.37                | 1.53                | 7.02            | 11.00                 |
| 5550MHz                         | Pass   | 4.50        | 1.96                | 1.03                | 1.56                | 2.28                | 7.67            | 11.00                 |
| 5670MHz                         | Pass   | 4.50        | 1.83                | 1.47                | 1.68                | 1.79                | 7.61            | 11.00                 |
| 5710MHz Straddle 5.47-5.725GHz  | Pass   | 4.50        | 1.97                | 1.21                | 1.81                | 2.27                | 7.76            | 11.00                 |
| 5710MHz Straddle 5.725-5.85GHz  | Pass   | 5.09        | 0.28                | -0.53               | 0.21                | 0.35                | 6.05            | 30.00                 |
| 802.11ax HEW80_Nss1,(MCS0)_4TX  | -      | -           | -                   | -                   | -                   | -                   | -               | -                     |
| 5290MHz                         | Pass   | 5.88        | -0.93               | -1.54               | -1.10               | -0.73               | 4.83            | 11.00                 |
| 5530MHz                         | Pass   | 4.50        | -2.11               | -2.73               | -1.92               | -1.56               | 3.87            | 11.00                 |
| 5610MHz                         | Pass   | 4.50        | -1.15               | -1.41               | -0.68               | -0.85               | 4.95            | 11.00                 |
| 5690MHz Straddle 5.47-5.725GHz  | Pass   | 4.50        | -1.46               | -1.35               | -1.52               | -1.08               | 4.58            | 11.00                 |
| 5690MHz Straddle 5.725-5.85GHz  | Pass   | 5.09        | -3.35               | -3.73               | -2.93               | -3.18               | 2.66            | 30.00                 |
| 802.11ax HEW160_Nss1,(MCS0)_4TX | -      | -           | -                   | -                   | -                   | -                   | -               | -                     |
| 5250MHz Straddle 5.15-5.25GHz   | Pass   | 5.06        | -3.63               | -3.91               | -3.49               | -3.66               | 2.24            | 17.00                 |
| 5250MHz Straddle 5.25-5.35GHz   | Pass   | 5.88        | -3.60               | -3.97               | -3.48               | -3.30               | 2.26            | 11.00                 |
| 5570MHz                         | Pass   | 4.50        | -4.84               | -4.88               | -4.48               | -4.25               | 1.27            | 11.00                 |

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

## 802.11a\_Nss1,(6Mbps)\_4TX

## PSD

5260MHz

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

## PSD

5300MHz

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

## PSD

5320MHz

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

## PSD

5500MHz

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

## PSD

5580MHz

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

## PSD

5700MHz

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

### 5720MHz Straddle 5.47-5.725GHz

## PSD

23/02/2022




## 802.11a\_Nss1,(6Mbps)\_4TX

### 5720MHz Straddle 5.725-5.85GHz

## PSD

23/02/2022




## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## PSD

5260MHz

23/02/2022




## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## PSD

5300MHz

23/02/2022




# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## PSD

5320MHz

23/02/2022




# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## PSD

5500MHz

23/02/2022




# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## PSD

5580MHz

23/02/2022




# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## PSD

5700MHz

23/02/2022




# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5720MHz Straddle 5.47-5.725GHz

### PSD

23/02/2022




# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5720MHz Straddle 5.725-5.85GHz

### PSD

23/02/2022




# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## PSD

5270MHz

23/02/2022




# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## PSD

5310MHz

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## PSD

5510MHz

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## PSD

5550MHz

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## PSD

5670MHz

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## PSD

5710MHz Straddle 5.47-5.725GHz

23/02/2022




## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

### 5710MHz Straddle 5.725-5.85GHz

## PSD

23/02/2022




## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5290MHz

## PSD

23/02/2022




# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## PSD

5530MHz

23/02/2022




# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## PSD

5610MHz

23/02/2022




## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5690MHz Straddle 5.47-5.725GHz

## PSD

23/02/2022




## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5690MHz Straddle 5.725-5.85GHz

## PSD

23/02/2022




## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## PSD

### 5250MHz Straddle 5.15-5.25GHz

23/02/2022




## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## PSD

### 5250MHz Straddle 5.25-5.35GHz

23/02/2022




# 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## PSD

5570MHz

23/02/2022




**Summary**

| Mode                     | Result | Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comments |
|--------------------------|--------|------|--------------|-------------------|-------------------|----------------|-------------|------------|----------------|---------------|----------|
| 5.47-5.725GHz            | -      | -    | -            | -                 | -                 | -              | -           | -          | -              | -             | -        |
| 802.11a_Nss1.(6Mbps)_4TX | Pass   | PK   | 16.73424G    | 68.19             | 68.20             | -0.01          | 3           | Horizontal | 121            | 1.60          | -        |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5260MHz\_TnomVnom




EUT\_X\_4TX  
Setting 91  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1472G      | 57.94             | 74.00             | -16.06         | 51.34         | 3           | Vertical  | 60             | 2.28          | -       | 33.50      | 5.25       | 32.15      |
| AV   | 5.149G       | 45.73             | 54.00             | -8.27          | 39.13         | 3           | Vertical  | 60             | 2.28          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.2576G      | 118.72            | Inf               | -Inf           | 111.91        | 3           | Vertical  | 60             | 2.28          | -       | 33.62      | 5.33       | 32.14      |
| AV   | 5.2582G      | 109.22            | Inf               | -Inf           | 102.41        | 3           | Vertical  | 60             | 2.28          | -       | 33.62      | 5.33       | 32.14      |
| PK   | 5.4088G      | 58.35             | 74.00             | -15.65         | 51.26         | 3           | Vertical  | 60             | 2.28          | -       | 33.82      | 5.41       | 32.14      |
| AV   | 5.362G       | 46.02             | 54.00             | -7.98          | 39.06         | 3           | Vertical  | 60             | 2.28          | -       | 33.72      | 5.38       | 32.14      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5260MHz\_TnomVnom




EUT\_X\_4TX  
Setting 91  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1376G      | 58.53             | 74.00             | -15.47         | 51.94         | 3           | Horizontal | 355            | 1.00          | -       | 33.50      | 5.24       | 32.15      |
| AV   | 5.1496G      | 45.93             | 54.00             | -8.07          | 39.33         | 3           | Horizontal | 355            | 1.00          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.2564G      | 118.79            | Inf               | -Inf           | 111.99        | 3           | Horizontal | 355            | 1.00          | -       | 33.61      | 5.33       | 32.14      |
| AV   | 5.2564G      | 108.76            | Inf               | -Inf           | 101.96        | 3           | Horizontal | 355            | 1.00          | -       | 33.61      | 5.33       | 32.14      |
| PK   | 5.368G       | 59.39             | 74.00             | -14.61         | 52.41         | 3           | Horizontal | 355            | 1.00          | -       | 33.74      | 5.38       | 32.14      |
| AV   | 5.356G       | 47.03             | 54.00             | -6.97          | 40.08         | 3           | Horizontal | 355            | 1.00          | -       | 33.71      | 5.38       | 32.14      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5260MHz\_TnomVnom




EUT X\_4TX  
Setting 91  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.78448G    | 60.46             | 74.00             | -13.54         | 46.65         | 3           | Vertical  | 189            | 2.08          | -       | 37.40      | 9.90       | 33.49      |
| AV   | 15.78384G    | 45.37             | 54.00             | -8.63          | 31.55         | 3           | Vertical  | 189            | 2.08          | -       | 37.40      | 9.90       | 33.48      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5260MHz\_TnomVnom




EUT X\_4TX  
Setting 91  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.79072G    | 70.94             | 74.00             | -3.06          | 57.12         | 3           | Horizontal | 124            | 2.24          | -       | 37.40      | 9.91       | 33.49      |
| AV   | 15.7728G     | 53.76             | 54.00             | -0.24          | 39.93         | 3           | Horizontal | 124            | 2.24          | -       | 37.40      | 9.90       | 33.47      |

# 802.11a\_Nss1,(6Mbps)\_4TX

## 5300MHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.302G       | 120.21            | Inf               | -Inf           | 113.30        | 3           | Vertical  | 32             | 2.18          | -       | 33.70      | 5.35       | 32.14      |
| AV   | 5.3012G      | 110.48            | Inf               | -Inf           | 103.57        | 3           | Vertical  | 32             | 2.18          | -       | 33.70      | 5.35       | 32.14      |
| PK   | 5.35G        | 70.52             | 74.00             | -3.48          | 63.58         | 3           | Vertical  | 32             | 2.18          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.35G        | 52.14             | 54.00             | -1.86          | 45.20         | 3           | Vertical  | 32             | 2.18          | -       | 33.70      | 5.38       | 32.14      |

# 802.11a\_Nss1,(6Mbps)\_4TX

## 5300MHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.294G       | 119.85            | Inf               | -Inf           | 112.95        | 3           | Horizontal | 172            | 2.79          | -       | 33.69      | 5.35       | 32.14      |
| AV   | 5.294G       | 109.82            | Inf               | -Inf           | 102.92        | 3           | Horizontal | 172            | 2.79          | -       | 33.69      | 5.35       | 32.14      |
| PK   | 5.354G       | 69.41             | 74.00             | -4.59          | 62.46         | 3           | Horizontal | 172            | 2.79          | -       | 33.71      | 5.38       | 32.14      |
| AV   | 5.35G        | 50.67             | 54.00             | -3.33          | 43.73         | 3           | Horizontal | 172            | 2.79          | -       | 33.70      | 5.38       | 32.14      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5300MHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 15.906G      | 65.57             | 74.00             | -8.43          | 51.75         | 3           | Vertical  | 165            | 2.40          | -       | 37.49      | 9.96       | 33.63      |  |
| AV   | 15.90416G    | 50.78             | 54.00             | -3.22          | 36.95         | 3           | Vertical  | 165            | 2.40          | -       | 37.50      | 9.96       | 33.63      |  |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5300MHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 15.89136G    | 70.70             | 74.00             | -3.30          | 56.87         | 3           | Horizontal | 126            | 2.12          | -       | 37.49      | 9.95       | 33.61      |  |
| AV   | 15.89248G    | 53.91             | 54.00             | -0.09          | 40.08         | 3           | Horizontal | 126            | 2.12          | -       | 37.49      | 9.95       | 33.61      |  |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5320MHz\_TnomVnom




EUT\_X\_4TX  
Setting 81  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3224G      | 115.50            | Inf               | -Inf           | 108.58        | 3           | Vertical  | 39             | 2.25          | -       | 33.70      | 5.36       | 32.14      |
| AV   | 5.3216G      | 105.65            | Inf               | -Inf           | 98.73         | 3           | Vertical  | 39             | 2.25          | -       | 33.70      | 5.36       | 32.14      |
| PK   | 5.3576G      | 68.53             | 74.00             | -5.47          | 61.57         | 3           | Vertical  | 39             | 2.25          | -       | 33.72      | 5.38       | 32.14      |
| AV   | 5.35G        | 48.87             | 54.00             | -5.13          | 41.93         | 3           | Vertical  | 39             | 2.25          | -       | 33.70      | 5.38       | 32.14      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5320MHz\_TnomVnom




EUT\_X\_4TX  
Setting 81  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3138G      | 115.84            | Inf               | -Inf           | 108.92        | 3           | Horizontal | 0              | 1.17          | -       | 33.70      | 5.36       | 32.14      |
| AV   | 5.3142G      | 105.70            | Inf               | -Inf           | 98.78         | 3           | Horizontal | 0              | 1.17          | -       | 33.70      | 5.36       | 32.14      |
| PK   | 5.3516G      | 73.79             | 74.00             | -0.21          | 66.85         | 3           | Horizontal | 0              | 1.17          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.3504G      | 50.41             | 54.00             | -3.59          | 43.47         | 3           | Horizontal | 0              | 1.17          | -       | 33.70      | 5.38       | 32.14      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5320MHz\_TnomVnom




EUT X\_4TX  
Setting 81  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.95672G    | 52.25             | 74.00             | -21.75         | 38.52         | 3           | Vertical  | 42             | 1.67          | -       | 37.44      | 9.98       | 33.69      |
| AV   | 15.95936G    | 39.10             | 54.00             | -14.90         | 25.37         | 3           | Vertical  | 42             | 1.67          | -       | 37.44      | 9.98       | 33.69      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5320MHz\_TnomVnom




EUT\_X\_4TX  
Setting 81  
02-B-K-5

| Type | Freq      | Level    | Limit    | Margin | Raw    | Dist | Condition  | Azimuth | Height | Comment | AF    | CL   | PA    |
|------|-----------|----------|----------|--------|--------|------|------------|---------|--------|---------|-------|------|-------|
|      | (Hz)      | (dBuV/m) | (dBuV/m) | (dB)   | (dBuV) | (m)  |            | (°)     | (m)    |         | (dB)  | (dB) | (dB)  |
| PK   | 15.9563G  | 52.13    | 74.00    | -21.87 | 38.40  | 3    | Horizontal | 289     | 2.73   | -       | 37.44 | 9.98 | 33.69 |
| AV   | 15.95534G | 39.36    | 54.00    | -14.64 | 25.63  | 3    | Horizontal | 289     | 2.73   | -       | 37.44 | 9.98 | 33.69 |

# 802.11a\_Nss1,(6Mbps)\_4TX

## 5500MHz\_TnomVnom




EUT X\_4TX  
Setting 71  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.451G       | 58.86             | 74.00             | -15.14         | 51.64         | 3           | Vertical  | 57             | 2.14          | -       | 33.90      | 5.45       | 32.13      |  |
| AV   | 5.46G        | 45.99             | 54.00             | -8.01          | 38.76         | 3           | Vertical  | 57             | 2.14          | -       | 33.90      | 5.46       | 32.13      |  |
| PK   | 5.4696G      | 66.78             | 68.20             | -1.42          | 59.54         | 3           | Vertical  | 57             | 2.14          | -       | 33.90      | 5.47       | 32.13      |  |
| PK   | 5.495G       | 112.01            | Inf               | -Inf           | 104.74        | 3           | Vertical  | 57             | 2.14          | -       | 33.90      | 5.50       | 32.13      |  |
| AV   | 5.4934G      | 101.82            | Inf               | -Inf           | 94.56         | 3           | Vertical  | 57             | 2.14          | -       | 33.90      | 5.49       | 32.13      |  |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5500MHz\_TnomVnom




EUT X\_4TX  
Setting 71  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.4568G      | 59.83             | 74.00             | -14.17         | 52.60         | 3           | Horizontal | 360            | 1.11          | -       | 33.90      | 5.46       | 32.13      |  |
| AV   | 5.459G       | 46.75             | 54.00             | -7.25          | 39.52         | 3           | Horizontal | 360            | 1.11          | -       | 33.90      | 5.46       | 32.13      |  |
| PK   | 5.4682G      | 67.98             | 68.20             | -0.22          | 60.74         | 3           | Horizontal | 360            | 1.11          | -       | 33.90      | 5.47       | 32.13      |  |
| PK   | 5.4964G      | 113.01            | Inf               | -Inf           | 105.74        | 3           | Horizontal | 360            | 1.11          | -       | 33.90      | 5.50       | 32.13      |  |
| AV   | 5.4962G      | 102.79            | Inf               | -Inf           | 95.52         | 3           | Horizontal | 360            | 1.11          | -       | 33.90      | 5.50       | 32.13      |  |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5500MHz\_TnomVnom




EUT\_X\_4TX  
Setting 71  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.0013G     | 52.05             | 74.00             | -21.95         | 39.12         | 3           | Vertical  | 140            | 1.27          | -       | 38.50      | 7.70       | 33.27      |
| AV   | 10.99922G    | 38.06             | 54.00             | -15.94         | 25.13         | 3           | Vertical  | 140            | 1.27          | -       | 38.50      | 7.70       | 33.27      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5500MHz\_TnomVnom




EUT\_X\_4TX  
Setting 71  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 11.0015G     | 52.14             | 74.00             | -21.86         | 39.21         | 3           | Horizontal | 86             | 2.57          | -       | 38.50      | 7.70       | 33.27      |  |
| AV   | 11.0013G     | 38.07             | 54.00             | -15.93         | 25.14         | 3           | Horizontal | 86             | 2.57          | -       | 38.50      | 7.70       | 33.27      |  |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5580MHz\_TnomVnom




EUT X\_4TX  
Setting 91  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.4472G      | 58.57             | 74.00             | -15.43         | 51.36         | 3           | Vertical  | 78             | 1.62          | -       | 33.89      | 5.45       | 32.13      |
| AV   | 5.4336G      | 45.86             | 54.00             | -8.14          | 38.69         | 3           | Vertical  | 78             | 1.62          | -       | 33.87      | 5.43       | 32.13      |
| PK   | 5.468G       | 57.76             | 68.20             | -10.44         | 50.52         | 3           | Vertical  | 78             | 1.62          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.5752G      | 116.68            | Inf               | -Inf           | 109.33        | 3           | Vertical  | 78             | 1.62          | -       | 33.90      | 5.58       | 32.13      |
| AV   | 5.5752G      | 106.76            | Inf               | -Inf           | 99.41         | 3           | Vertical  | 78             | 1.62          | -       | 33.90      | 5.58       | 32.13      |
| PK   | 5.76G        | 59.63             | 68.20             | -8.57          | 52.40         | 3           | Vertical  | 78             | 1.62          | -       | 33.78      | 5.60       | 32.15      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5580MHz\_TnomVnom




EUT\_X\_4TX  
Setting 91  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.392G       | 58.58             | 74.00             | -15.42         | 51.54         | 3           | Horizontal | 261            | 2.12          | -       | 33.78      | 5.40       | 32.14      |
| AV   | 5.4088G      | 45.88             | 54.00             | -8.12          | 38.79         | 3           | Horizontal | 261            | 2.12          | -       | 33.82      | 5.41       | 32.14      |
| PK   | 5.4616G      | 58.41             | 68.20             | -9.79          | 51.18         | 3           | Horizontal | 261            | 2.12          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.5728G      | 116.23            | Inf               | -Inf           | 108.89        | 3           | Horizontal | 261            | 2.12          | -       | 33.90      | 5.57       | 32.13      |
| AV   | 5.5728G      | 106.99            | Inf               | -Inf           | 99.65         | 3           | Horizontal | 261            | 2.12          | -       | 33.90      | 5.57       | 32.13      |
| PK   | 5.7552G      | 58.76             | 68.20             | -9.44          | 51.52         | 3           | Horizontal | 261            | 2.12          | -       | 33.79      | 5.60       | 32.15      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5580MHz\_TnomVnom




EUT\_X\_4TX  
Setting 91  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.1603G     | 52.64             | 74.00             | -21.36         | 39.47         | 3           | Vertical  | 53             | 1.65          | -       | 38.66      | 7.76       | 33.25      |
| AV   | 11.16076G    | 38.64             | 54.00             | -15.36         | 25.47         | 3           | Vertical  | 53             | 1.65          | -       | 38.66      | 7.76       | 33.25      |
| PK   | 16.74624G    | 62.18             | 68.20             | -6.02          | 45.13         | 3           | Vertical  | 166            | 2.74          | -       | 39.98      | 10.37      | 33.30      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5580MHz\_TnomVnom




EUT X\_4TX  
Setting 91  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.1628G     | 52.43             | 74.00             | -21.57         | 39.25         | 3           | Horizontal | 344            | 2.73          | -       | 38.66      | 7.77       | 33.25      |
| AV   | 11.16086G    | 38.74             | 54.00             | -15.26         | 25.57         | 3           | Horizontal | 344            | 2.73          | -       | 38.66      | 7.76       | 33.25      |
| PK   | 16.73424G    | 68.19             | 68.20             | -0.01          | 51.20         | 3           | Horizontal | 121            | 1.60          | -       | 39.91      | 10.37      | 33.29      |

# 802.11a\_Nss1,(6Mbps)\_4TX

## 5700MHz\_TnomVnom




EUT\_X\_4TX  
Setting 68  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.6938G      | 111.51            | Inf               | -Inf           | 104.34        | 3           | Vertical  | 79             | 1.96          | -       | 33.71      | 5.60       | 32.14      |  |
| AV   | 5.6934G      | 101.56            | Inf               | -Inf           | 94.39         | 3           | Vertical  | 79             | 1.96          | -       | 33.71      | 5.60       | 32.14      |  |
| PK   | 5.725G       | 67.05             | 68.20             | -1.15          | 59.84         | 3           | Vertical  | 79             | 1.96          | -       | 33.75      | 5.60       | 32.14      |  |

# 802.11a\_Nss1,(6Mbps)\_4TX

## 5700MHz\_TnomVnom




EUT\_X\_4TX  
Setting 68  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.7048G      | 109.18            | Inf               | -Inf           | 102.01        | 3           | Horizontal | 349            | 1.96          | -       | 33.71      | 5.60       | 32.14      |
| AV   | 5.7046G      | 99.04             | Inf               | -Inf           | 91.87         | 3           | Horizontal | 349            | 1.96          | -       | 33.71      | 5.60       | 32.14      |
| PK   | 5.725G       | 66.60             | 68.20             | -1.60          | 59.39         | 3           | Horizontal | 349            | 1.96          | -       | 33.75      | 5.60       | 32.14      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5700MHz\_TnomVnom




EUT X\_4TX  
Setting 68  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.3984G     | 52.43             | 74.00             | -21.57         | 39.00         | 3           | Vertical  | 188            | 2.26          | -       | 38.80      | 7.86       | 33.23      |
| AV   | 11.39918G    | 38.70             | 54.00             | -15.30         | 25.27         | 3           | Vertical  | 188            | 2.26          | -       | 38.80      | 7.86       | 33.23      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5700MHz\_TnomVnom




EUT\_X\_4TX  
Setting 68  
02-B-K-5

| Type | Freq      | Level    | Limit    | Margin | Raw    | Dist | Condition  | Azimuth | Height | Comment | AF    | CL   | PA    |
|------|-----------|----------|----------|--------|--------|------|------------|---------|--------|---------|-------|------|-------|
|      | (Hz)      | (dBuV/m) | (dBuV/m) | (dB)   | (dBuV) | (m)  |            | (°)     | (m)    |         | (dB)  | (dB) | (dB)  |
| PK   | 11.39918G | 51.99    | 74.00    | -22.01 | 38.56  | 3    | Horizontal | 264     | 2.80   | -       | 38.80 | 7.86 | 33.23 |
| AV   | 11.4041G  | 38.71    | 54.00    | -15.29 | 25.27  | 3    | Horizontal | 264     | 2.80   | -       | 38.81 | 7.86 | 33.23 |

# 802.11a\_Nss1,(6Mbps)\_4TX

## 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 88  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.7136G      | 116.00            | Inf               | -Inf           | 108.81        | 3           | Vertical  | 79             | 1.94          | -       | 33.73      | 5.60       | 32.14      |  |
| AV   | 5.7136G      | 106.50            | Inf               | -Inf           | 99.31         | 3           | Vertical  | 79             | 1.94          | -       | 33.73      | 5.60       | 32.14      |  |
| PK   | 5.8512G      | 57.91             | 68.20             | -10.29         | 50.61         | 3           | Vertical  | 79             | 1.94          | -       | 33.80      | 5.65       | 32.15      |  |

# 802.11a\_Nss1,(6Mbps)\_4TX

## 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 88  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.7256G      | 116.47            | Inf               | -Inf           | 109.26        | 3           | Horizontal | 8              | 1.04          | -       | 33.75      | 5.60       | 32.14      |
| AV   | 5.7272G      | 106.56            | Inf               | -Inf           | 99.35         | 3           | Horizontal | 8              | 1.04          | -       | 33.75      | 5.60       | 32.14      |
| PK   | 5.9016G      | 57.30             | 68.20             | -10.90         | 49.75         | 3           | Horizontal | 8              | 1.04          | -       | 34.00      | 5.70       | 32.15      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 88  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.43984G    | 54.31             | 74.00             | -19.69         | 40.78         | 3           | Vertical  | 351            | 1.80          | -       | 38.88      | 7.88       | 33.23      |
| AV   | 11.43976G    | 41.42             | 54.00             | -12.58         | 27.89         | 3           | Vertical  | 351            | 1.80          | -       | 38.88      | 7.88       | 33.23      |
| PK   | 17.16344G    | 61.19             | 68.20             | -7.01          | 42.22         | 3           | Vertical  | 146            | 2.36          | -       | 41.74      | 10.58      | 33.35      |

## 802.11a\_Nss1,(6Mbps)\_4TX

### 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 88  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.45848G    | 51.94             | 74.00             | -22.06         | 38.36         | 3           | Horizontal | 89             | 1.94          | -       | 38.92      | 7.88       | 33.22      |
| AV   | 11.44448G    | 39.11             | 54.00             | -14.89         | 25.57         | 3           | Horizontal | 89             | 1.94          | -       | 38.89      | 7.88       | 33.23      |
| PK   | 17.1564G     | 67.97             | 68.20             | -0.23          | 49.06         | 3           | Horizontal | 122            | 2.92          | -       | 41.69      | 10.58      | 33.36      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5260MHz\_TnomVnom




EUT X\_4TX  
Setting 93  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1454G      | 57.71             | 74.00             | -16.29         | 51.11         | 3           | Vertical  | 43             | 2.30          | -       | 33.50      | 5.25       | 32.15      |
| AV   | 5.1478G      | 45.76             | 54.00             | -8.24          | 39.16         | 3           | Vertical  | 43             | 2.30          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.2546G      | 118.76            | Inf               | -Inf           | 111.96        | 3           | Vertical  | 43             | 2.30          | -       | 33.61      | 5.33       | 32.14      |
| AV   | 5.2552G      | 107.24            | Inf               | -Inf           | 100.44        | 3           | Vertical  | 43             | 2.30          | -       | 33.61      | 5.33       | 32.14      |
| PK   | 5.3698G      | 58.85             | 74.00             | -15.15         | 51.87         | 3           | Vertical  | 43             | 2.30          | -       | 33.74      | 5.38       | 32.14      |
| AV   | 5.353G       | 45.91             | 54.00             | -8.09          | 38.96         | 3           | Vertical  | 43             | 2.30          | -       | 33.71      | 5.38       | 32.14      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5260MHz\_TnomVnom




EUT X\_4TX  
Setting 93  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1478G      | 57.85             | 74.00             | -16.15         | 51.25         | 3           | Horizontal | 351            | 1.00          | -       | 33.50      | 5.25       | 32.15      |
| AV   | 5.1484G      | 45.70             | 54.00             | -8.30          | 39.10         | 3           | Horizontal | 351            | 1.00          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.2522G      | 119.95            | Inf               | -Inf           | 113.16        | 3           | Horizontal | 351            | 1.00          | -       | 33.60      | 5.33       | 32.14      |
| AV   | 5.2534G      | 107.78            | Inf               | -Inf           | 100.98        | 3           | Horizontal | 351            | 1.00          | -       | 33.61      | 5.33       | 32.14      |
| PK   | 5.3608G      | 59.15             | 74.00             | -14.85         | 52.19         | 3           | Horizontal | 351            | 1.00          | -       | 33.72      | 5.38       | 32.14      |
| AV   | 5.3536G      | 46.80             | 54.00             | -7.20          | 39.85         | 3           | Horizontal | 351            | 1.00          | -       | 33.71      | 5.38       | 32.14      |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5260MHz\_TnomVnom




EUT X\_4TX  
Setting 93  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.7912G     | 59.84             | 74.00             | -14.16         | 46.02         | 3           | Vertical  | 182            | 1.68          | -       | 37.40      | 9.91       | 33.49      |
| AV   | 15.7859G     | 44.58             | 54.00             | -9.42          | 30.77         | 3           | Vertical  | 182            | 1.68          | -       | 37.40      | 9.90       | 33.49      |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5260MHz\_TnomVnom




EUT X\_4TX  
Setting 93  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.7718G     | 70.43             | 74.00             | -3.57          | 56.60         | 3           | Horizontal | 124            | 2.22          | -       | 37.40      | 9.90       | 33.47      |
| AV   | 15.782G      | 53.76             | 54.00             | -0.24          | 39.94         | 3           | Horizontal | 124            | 2.22          | -       | 37.40      | 9.90       | 33.48      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5300MHz\_TnomVnom




EUT\_X\_4TX  
Setting 97  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3056G      | 120.74            | Inf               | -Inf           | 113.83        | 3           | Vertical  | 39             | 2.16          | -       | 33.70      | 5.35       | 32.14      |
| AV   | 5.3052G      | 108.37            | Inf               | -Inf           | 101.46        | 3           | Vertical  | 39             | 2.16          | -       | 33.70      | 5.35       | 32.14      |
| PK   | 5.35G        | 72.84             | 74.00             | -1.16          | 65.90         | 3           | Vertical  | 39             | 2.16          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.3504G      | 53.77             | 54.00             | -0.23          | 46.83         | 3           | Vertical  | 39             | 2.16          | -       | 33.70      | 5.38       | 32.14      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5300MHz\_TnomVnom




EUT\_X\_4TX  
Setting 97  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.296G       | 120.91            | Inf               | -Inf           | 114.01        | 3           | Horizontal | 188            | 1.06          | -       | 33.69      | 5.35       | 32.14      |
| AV   | 5.3012G      | 108.59            | Inf               | -Inf           | 101.68        | 3           | Horizontal | 188            | 1.06          | -       | 33.70      | 5.35       | 32.14      |
| PK   | 5.3504G      | 73.77             | 74.00             | -0.23          | 66.83         | 3           | Horizontal | 188            | 1.06          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.3512G      | 53.86             | 54.00             | -0.14          | 46.92         | 3           | Horizontal | 188            | 1.06          | -       | 33.70      | 5.38       | 32.14      |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5300MHz\_TnomVnom




EUT X\_4TX  
Setting 97  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 15.911G      | 61.65             | 74.00             | -12.35         | 47.83         | 3           | Vertical  | 182            | 1.70          | -       | 37.49      | 9.96       | 33.63      |  |
| AV   | 15.896G      | 45.77             | 54.00             | -8.23          | 31.94         | 3           | Vertical  | 182            | 1.70          | -       | 37.50      | 9.95       | 33.62      |  |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5300MHz\_TnomVnom




EUT X\_4TX  
Setting 97  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.8922G     | 67.70             | 74.00             | -6.30          | 53.87         | 3           | Horizontal | 131            | 1.96          | -       | 37.49      | 9.95       | 33.61      |
| AV   | 15.8972G     | 52.25             | 54.00             | -1.75          | 38.42         | 3           | Horizontal | 131            | 1.96          | -       | 37.50      | 9.95       | 33.62      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5320MHz\_TnomVnom




EUT\_X\_4TX  
Setting 78  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3252G      | 116.53            | Inf               | -Inf           | 109.61        | 3           | Vertical  | 36             | 2.15          | -       | 33.70      | 5.36       | 32.14      |
| AV   | 5.3152G      | 103.87            | Inf               | -Inf           | 96.95         | 3           | Vertical  | 36             | 2.15          | -       | 33.70      | 5.36       | 32.14      |
| PK   | 5.3548G      | 73.83             | 74.00             | -0.17          | 66.88         | 3           | Vertical  | 36             | 2.15          | -       | 33.71      | 5.38       | 32.14      |
| AV   | 5.3502G      | 51.65             | 54.00             | -2.35          | 44.71         | 3           | Vertical  | 36             | 2.15          | -       | 33.70      | 5.38       | 32.14      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5320MHz\_TnomVnom




EUT\_X\_4TX  
Setting 78  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.3168G      | 117.13            | Inf               | -Inf           | 110.21        | 3           | Horizontal | 355            | 1.17          | -       | 33.70      | 5.36       | 32.14      |  |
| AV   | 5.3222G      | 104.12            | Inf               | -Inf           | 97.20         | 3           | Horizontal | 355            | 1.17          | -       | 33.70      | 5.36       | 32.14      |  |
| PK   | 5.3544G      | 71.85             | 74.00             | -2.15          | 64.90         | 3           | Horizontal | 355            | 1.17          | -       | 33.71      | 5.38       | 32.14      |  |
| AV   | 5.3524G      | 51.57             | 54.00             | -2.43          | 44.63         | 3           | Horizontal | 355            | 1.17          | -       | 33.70      | 5.38       | 32.14      |  |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5320MHz\_TnomVnom




EUT X\_4TX  
Setting 78  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.95892G    | 52.37             | 74.00             | -21.63         | 38.64         | 3           | Vertical  | 38             | 2.51          | -       | 37.44      | 9.98       | 33.69      |
| AV   | 15.95776G    | 39.32             | 54.00             | -14.68         | 25.59         | 3           | Vertical  | 38             | 2.51          | -       | 37.44      | 9.98       | 33.69      |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5320MHz\_TnomVnom




EUT X\_4TX  
Setting 78  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.96392G    | 52.47             | 74.00             | -21.53         | 38.75         | 3           | Horizontal | 199            | 1.36          | -       | 37.44      | 9.98       | 33.70      |
| AV   | 15.95786G    | 39.26             | 54.00             | -14.74         | 25.53         | 3           | Horizontal | 199            | 1.36          | -       | 37.44      | 9.98       | 33.69      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5500MHz\_TnomVnom




EUT X\_4TX  
Setting 71  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.4598G      | 62.22             | 74.00             | -11.78         | 54.99         | 3           | Vertical  | 56             | 1.95          | -       | 33.90      | 5.46       | 32.13      |  |
| AV   | 5.46G        | 46.06             | 54.00             | -7.94          | 38.83         | 3           | Vertical  | 56             | 1.95          | -       | 33.90      | 5.46       | 32.13      |  |
| PK   | 5.4662G      | 67.79             | 68.20             | -0.41          | 60.55         | 3           | Vertical  | 56             | 1.95          | -       | 33.90      | 5.47       | 32.13      |  |
| PK   | 5.5012G      | 113.79            | Inf               | -Inf           | 106.52        | 3           | Vertical  | 56             | 1.95          | -       | 33.90      | 5.50       | 32.13      |  |
| AV   | 5.5012G      | 101.01            | Inf               | -Inf           | 93.74         | 3           | Vertical  | 56             | 1.95          | -       | 33.90      | 5.50       | 32.13      |  |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5500MHz\_TnomVnom




EUT X\_4TX  
Setting 71  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.4592G      | 59.86             | 74.00             | -14.14         | 52.63         | 3           | Horizontal | 186            | 1.12          | -       | 33.90      | 5.46       | 32.13      |  |
| AV   | 5.46G        | 45.96             | 54.00             | -8.04          | 38.73         | 3           | Horizontal | 186            | 1.12          | -       | 33.90      | 5.46       | 32.13      |  |
| PK   | 5.4654G      | 68.09             | 68.20             | -0.11          | 60.85         | 3           | Horizontal | 186            | 1.12          | -       | 33.90      | 5.47       | 32.13      |  |
| PK   | 5.5056G      | 115.39            | Inf               | -Inf           | 108.11        | 3           | Horizontal | 186            | 1.12          | -       | 33.90      | 5.51       | 32.13      |  |
| AV   | 5.5008G      | 102.89            | Inf               | -Inf           | 95.62         | 3           | Horizontal | 186            | 1.12          | -       | 33.90      | 5.50       | 32.13      |  |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5500MHz\_TnomVnom




EUT X\_4TX  
Setting 71  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.00388G    | 52.27             | 74.00             | -21.73         | 39.34         | 3           | Vertical  | 327            | 2.53          | -       | 38.50      | 7.70       | 33.27      |
| AV   | 11.00306G    | 38.43             | 54.00             | -15.57         | 25.50         | 3           | Vertical  | 327            | 2.53          | -       | 38.50      | 7.70       | 33.27      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5500MHz\_TnomVnom




EUT\_X\_4TX  
Setting 71  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 10.99994G    | 52.57             | 74.00             | -21.43         | 39.64         | 3           | Horizontal | 130            | 2.01          | -       | 38.50      | 7.70       | 33.27      |
| AV   | 10.99962G    | 38.21             | 54.00             | -15.79         | 25.28         | 3           | Horizontal | 130            | 2.01          | -       | 38.50      | 7.70       | 33.27      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5580MHz\_TnomVnom




EUT X\_4TX  
Setting 95  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.4488G      | 57.23             | 74.00             | -16.77         | 50.01         | 3           | Vertical  | 268            | 2.34          | -       | 33.90      | 5.45       | 32.13      |
| AV   | 5.3864G      | 44.82             | 54.00             | -9.18          | 37.80         | 3           | Vertical  | 268            | 2.34          | -       | 33.77      | 5.39       | 32.14      |
| PK   | 5.4688G      | 56.14             | 68.20             | -12.06         | 48.90         | 3           | Vertical  | 268            | 2.34          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.5816G      | 113.01            | Inf               | -Inf           | 105.66        | 3           | Vertical  | 268            | 2.34          | -       | 33.90      | 5.58       | 32.13      |
| AV   | 5.5872G      | 101.22            | Inf               | -Inf           | 93.87         | 3           | Vertical  | 268            | 2.34          | -       | 33.90      | 5.59       | 32.14      |
| PK   | 5.7528G      | 57.14             | 68.20             | -11.06         | 49.90         | 3           | Vertical  | 268            | 2.34          | -       | 33.79      | 5.60       | 32.15      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5580MHz\_TnomVnom




EUT X\_4TX  
Setting 95  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.4184G      | 57.88             | 74.00             | -16.12         | 50.75         | 3           | Horizontal | 270            | 2.11          | -       | 33.84      | 5.42       | 32.13      |
| AV   | 5.4176G      | 45.81             | 54.00             | -8.19          | 38.68         | 3           | Horizontal | 270            | 2.11          | -       | 33.84      | 5.42       | 32.13      |
| PK   | 5.4608G      | 57.19             | 68.20             | -11.01         | 49.96         | 3           | Horizontal | 270            | 2.11          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.5816G      | 118.67            | Inf               | -Inf           | 111.32        | 3           | Horizontal | 270            | 2.11          | -       | 33.90      | 5.58       | 32.13      |
| AV   | 5.5768G      | 106.40            | Inf               | -Inf           | 99.05         | 3           | Horizontal | 270            | 2.11          | -       | 33.90      | 5.58       | 32.13      |
| PK   | 5.7752G      | 58.69             | 68.20             | -9.51          | 51.49         | 3           | Horizontal | 270            | 2.11          | -       | 33.75      | 5.60       | 32.15      |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5580MHz\_TnomVnom




EUT X\_4TX  
Setting 95  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.1513G     | 51.60             | 74.00             | -22.40         | 38.44         | 3           | Vertical  | 229            | 2.06          | -       | 38.65      | 7.76       | 33.25      |
| AV   | 11.1601G     | 39.19             | 54.00             | -14.81         | 26.02         | 3           | Vertical  | 229            | 2.06          | -       | 38.66      | 7.76       | 33.25      |
| PK   | 16.7373G     | 61.72             | 68.20             | -6.48          | 44.72         | 3           | Vertical  | 142            | 2.12          | -       | 39.92      | 10.37      | 33.29      |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5580MHz\_TnomVnom




EUT X\_4TX  
Setting 95  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.154G      | 55.48             | 74.00             | -18.52         | 42.32         | 3           | Horizontal | 133            | 1.84          | -       | 38.65      | 7.76       | 33.25      |
| AV   | 11.1588G     | 42.46             | 54.00             | -11.54         | 29.29         | 3           | Horizontal | 133            | 1.84          | -       | 38.66      | 7.76       | 33.25      |
| PK   | 16.7515G     | 68.15             | 68.20             | -0.05          | 51.07         | 3           | Horizontal | 121            | 1.70          | -       | 40.01      | 10.38      | 33.31      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5700MHz\_TnomVnom




EUT\_X\_4TX  
Setting 62  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.7012G      | 112.45            | Inf               | -Inf           | 105.29        | 3           | Vertical  | 79             | 2.10          | -       | 33.70      | 5.60       | 32.14      |
| AV   | 5.7014G      | 99.75             | Inf               | -Inf           | 92.59         | 3           | Vertical  | 79             | 2.10          | -       | 33.70      | 5.60       | 32.14      |
| PK   | 5.726G       | 64.75             | 68.20             | -3.45          | 57.54         | 3           | Vertical  | 79             | 2.10          | -       | 33.75      | 5.60       | 32.14      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5700MHz\_TnomVnom




EUT\_X\_4TX  
Setting 62  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.6956G      | 113.32            | Inf               | -Inf           | 106.15        | 3           | Horizontal | 20             | 1.00          | -       | 33.71      | 5.60       | 32.14      |
| AV   | 5.6982G      | 100.06            | Inf               | -Inf           | 92.90         | 3           | Horizontal | 20             | 1.00          | -       | 33.70      | 5.60       | 32.14      |
| PK   | 5.7254G      | 67.97             | 68.20             | -0.23          | 60.76         | 3           | Horizontal | 20             | 1.00          | -       | 33.75      | 5.60       | 32.14      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5700MHz\_TnomVnom




EUT X\_4TX  
Setting 62  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.39822G    | 52.10             | 74.00             | -21.90         | 38.67         | 3           | Vertical  | 131            | 1.49          | -       | 38.80      | 7.86       | 33.23      |
| AV   | 11.40396G    | 38.73             | 54.00             | -15.27         | 25.29         | 3           | Vertical  | 131            | 1.49          | -       | 38.81      | 7.86       | 33.23      |

## 802.11ax HEW20\_Nss1,(MCS0)\_4TX

### 5700MHz\_TnomVnom




EUT X\_4TX  
Setting 62  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.39668G    | 51.92             | 74.00             | -22.08         | 38.49         | 3           | Horizontal | 242            | 2.16          | -       | 38.80      | 7.86       | 33.23      |
| AV   | 11.39622G    | 38.75             | 54.00             | -15.25         | 25.32         | 3           | Horizontal | 242            | 2.16          | -       | 38.80      | 7.86       | 33.23      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT X\_4TX  
Setting 88  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.7264G      | 118.80            | Inf               | -Inf           | 111.59        | 3           | Vertical  | 77             | 1.94          | -       | 33.75      | 5.60       | 32.14      |
| AV   | 5.7216G      | 105.87            | Inf               | -Inf           | 98.67         | 3           | Vertical  | 77             | 1.94          | -       | 33.74      | 5.60       | 32.14      |
| PK   | 5.864G       | 57.76             | 68.20             | -10.44         | 50.39         | 3           | Vertical  | 77             | 1.94          | -       | 33.86      | 5.66       | 32.15      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 88  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.7208G      | 118.09            | Inf               | -Inf           | 110.89        | 3           | Horizontal | 8              | 1.28          | -       | 33.74      | 5.60       | 32.14      |
| AV   | 5.716G       | 105.82            | Inf               | -Inf           | 98.63         | 3           | Horizontal | 8              | 1.28          | -       | 33.73      | 5.60       | 32.14      |
| PK   | 5.9184G      | 57.55             | 68.20             | -10.65         | 49.95         | 3           | Horizontal | 8              | 1.28          | -       | 34.04      | 5.72       | 32.16      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 88  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.4388G     | 54.91             | 74.00             | -19.09         | 41.38         | 3           | Vertical  | 338            | 2.42          | -       | 38.88      | 7.88       | 33.23      |
| AV   | 11.4402G     | 41.82             | 54.00             | -12.18         | 28.29         | 3           | Vertical  | 338            | 2.42          | -       | 38.88      | 7.88       | 33.23      |
| PK   | 17.163G      | 61.95             | 68.20             | -6.25          | 42.98         | 3           | Vertical  | 24             | 2.20          | -       | 41.74      | 10.58      | 33.35      |

# 802.11ax HEW20\_Nss1,(MCS0)\_4TX

## 5720MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT X\_4TX  
Setting 88  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.4366G     | 52.54             | 74.00             | -21.46         | 39.03         | 3           | Horizontal | 286            | 2.33          | -       | 38.87      | 7.87       | 33.23      |
| AV   | 11.4462G     | 39.22             | 54.00             | -14.78         | 25.68         | 3           | Horizontal | 286            | 2.33          | -       | 38.89      | 7.88       | 33.23      |
| PK   | 17.1526G     | 67.98             | 68.20             | -0.22          | 49.10         | 3           | Horizontal | 124            | 2.92          | -       | 41.67      | 10.58      | 33.37      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5270MHz\_TnomVnom




EUT\_X\_4TX  
Setting 92  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1494G      | 61.42             | 74.00             | -12.58         | 54.82         | 3           | Vertical  | 49             | 2.28          | -       | 33.50      | 5.25       | 32.15      |
| AV   | 5.1494G      | 48.00             | 54.00             | -6.00          | 41.40         | 3           | Vertical  | 49             | 2.28          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.285G       | 116.84            | Inf               | -Inf           | 109.97        | 3           | Vertical  | 49             | 2.28          | -       | 33.67      | 5.34       | 32.14      |
| AV   | 5.2748G      | 104.81            | Inf               | -Inf           | 97.96         | 3           | Vertical  | 49             | 2.28          | -       | 33.65      | 5.34       | 32.14      |
| PK   | 5.3522G      | 69.54             | 74.00             | -4.46          | 62.60         | 3           | Vertical  | 49             | 2.28          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.3528G      | 53.85             | 54.00             | -0.15          | 46.90         | 3           | Vertical  | 49             | 2.28          | -       | 33.71      | 5.38       | 32.14      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5270MHz\_TnomVnom




EUT\_X\_4TX  
Setting 92  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1476G      | 59.42             | 74.00             | -14.58         | 52.82         | 3           | Horizontal | 2              | 2.95          | -       | 33.50      | 5.25       | 32.15      |
| AV   | 5.1494G      | 47.21             | 54.00             | -6.79          | 40.61         | 3           | Horizontal | 2              | 2.95          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.2586G      | 116.73            | Inf               | -Inf           | 109.92        | 3           | Horizontal | 2              | 2.95          | -       | 33.62      | 5.33       | 32.14      |
| AV   | 5.2592G      | 104.95            | Inf               | -Inf           | 98.14         | 3           | Horizontal | 2              | 2.95          | -       | 33.62      | 5.33       | 32.14      |
| PK   | 5.3528G      | 67.97             | 74.00             | -6.03          | 61.02         | 3           | Horizontal | 2              | 2.95          | -       | 33.71      | 5.38       | 32.14      |
| AV   | 5.35G        | 53.04             | 54.00             | -0.96          | 46.10         | 3           | Horizontal | 2              | 2.95          | -       | 33.70      | 5.38       | 32.14      |

## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

### 5270MHz\_TnomVnom




EUT X\_4TX  
Setting 92  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 15.81588G    | 55.45             | 74.00             | -18.55         | 41.63         | 3           | Vertical  | 183            | 1.62          | -       | 37.42      | 9.92       | 33.52      |  |
| AV   | 15.81574G    | 43.11             | 54.00             | -10.89         | 29.29         | 3           | Vertical  | 183            | 1.62          | -       | 37.42      | 9.92       | 33.52      |  |

## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

### 5270MHz\_TnomVnom




EUT X\_4TX  
Setting 92  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.83226G    | 63.95             | 74.00             | -10.05         | 50.14         | 3           | Horizontal | 123            | 1.98          | -       | 37.43      | 9.92       | 33.54      |
| AV   | 15.81224G    | 49.87             | 54.00             | -4.13          | 36.06         | 3           | Horizontal | 123            | 1.98          | -       | 37.41      | 9.92       | 33.52      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5310MHz\_TnomVnom




EUT\_X\_4TX  
Setting 74  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3204G      | 112.23            | Inf               | -Inf           | 105.31        | 3           | Vertical  | 40             | 2.17          | -       | 33.70      | 5.36       | 32.14      |
| AV   | 5.3052G      | 100.79            | Inf               | -Inf           | 93.88         | 3           | Vertical  | 40             | 2.17          | -       | 33.70      | 5.35       | 32.14      |
| PK   | 5.3512G      | 69.66             | 74.00             | -4.34          | 62.72         | 3           | Vertical  | 40             | 2.17          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.3532G      | 52.63             | 54.00             | -1.37          | 45.68         | 3           | Vertical  | 40             | 2.17          | -       | 33.71      | 5.38       | 32.14      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5310MHz\_TnomVnom




EUT\_X\_4TX  
Setting 74  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3116G      | 113.15            | Inf               | -Inf           | 106.23        | 3           | Horizontal | 360            | 1.14          | -       | 33.70      | 5.36       | 32.14      |
| AV   | 5.312G       | 100.29            | Inf               | -Inf           | 93.37         | 3           | Horizontal | 360            | 1.14          | -       | 33.70      | 5.36       | 32.14      |
| PK   | 5.3524G      | 73.76             | 74.00             | -0.24          | 66.82         | 3           | Horizontal | 360            | 1.14          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.3516G      | 53.36             | 54.00             | -0.64          | 46.42         | 3           | Horizontal | 360            | 1.14          | -       | 33.70      | 5.38       | 32.14      |

## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

### 5310MHz\_TnomVnom




EUT X\_4TX  
Setting 74  
02-B-K-5

| Type | Freq      | Level    | Limit    | Margin | Raw    | Dist | Condition | Azimuth | Height | Comment | AF    | CL   | PA    |  |
|------|-----------|----------|----------|--------|--------|------|-----------|---------|--------|---------|-------|------|-------|--|
|      | (Hz)      | (dBuV/m) | (dBuV/m) | (dB)   | (dBuV) | (m)  |           | (°)     | (m)    |         | (dB)  | (dB) | (dB)  |  |
| PK   | 15.9293G  | 52.91    | 74.00    | -21.09 | 39.13  | 3    | Vertical  | 94      | 2.94   | -       | 37.47 | 9.97 | 33.66 |  |
| AV   | 15.92508G | 40.57    | 54.00    | -13.43 | 26.78  | 3    | Vertical  | 94      | 2.94   | -       | 37.47 | 9.97 | 33.65 |  |

## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

### 5310MHz\_TnomVnom




EUT X\_4TX  
Setting 74  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 15.92858G    | 52.63             | 74.00             | -21.37         | 38.85         | 3           | Horizontal | 322            | 2.66          | -       | 37.47      | 9.97       | 33.66      |  |
| AV   | 15.92506G    | 40.42             | 54.00             | -13.58         | 26.63         | 3           | Horizontal | 322            | 2.66          | -       | 37.47      | 9.97       | 33.65      |  |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5510MHz\_TnomVnom




EUT\_X\_4TX  
Setting 71  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 5.4592G      | 65.40             | 74.00             | -8.60          | 58.17         | 3           | Vertical  | 56             | 2.12          | -       | 33.90      | 5.46       | 32.13      |  |
| AV   | 5.46G        | 48.43             | 54.00             | -5.57          | 41.20         | 3           | Vertical  | 56             | 2.12          | -       | 33.90      | 5.46       | 32.13      |  |
| PK   | 5.4668G      | 67.96             | 68.20             | -0.24          | 60.72         | 3           | Vertical  | 56             | 2.12          | -       | 33.90      | 5.47       | 32.13      |  |
| PK   | 5.5168G      | 112.18            | Inf               | -Inf           | 104.89        | 3           | Vertical  | 56             | 2.12          | -       | 33.90      | 5.52       | 32.13      |  |
| AV   | 5.5216G      | 99.06             | Inf               | -Inf           | 91.77         | 3           | Vertical  | 56             | 2.12          | -       | 33.90      | 5.52       | 32.13      |  |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5510MHz\_TnomVnom




EUT X\_4TX  
Setting 71  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.4572G      | 63.73             | 74.00             | -10.27         | 56.50         | 3           | Horizontal | 167            | 2.84          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.46G        | 48.48             | 54.00             | -5.52          | 41.25         | 3           | Horizontal | 167            | 2.84          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.466G       | 67.10             | 68.20             | -1.10          | 59.86         | 3           | Horizontal | 167            | 2.84          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.5164G      | 110.62            | Inf               | -Inf           | 103.33        | 3           | Horizontal | 167            | 2.84          | -       | 33.90      | 5.52       | 32.13      |
| AV   | 5.5264G      | 99.09             | Inf               | -Inf           | 91.79         | 3           | Horizontal | 167            | 2.84          | -       | 33.90      | 5.53       | 32.13      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5510MHz\_TnomVnom




EUT\_X\_4TX  
Setting 71  
02-B-K-5

| Type | Freq      | Level    | Limit    | Margin | Raw    | Dist | Condition | Azimuth | Height | Comment | AF    | CL   | PA    |
|------|-----------|----------|----------|--------|--------|------|-----------|---------|--------|---------|-------|------|-------|
|      | (Hz)      | (dBuV/m) | (dBuV/m) | (dB)   | (dBuV) | (m)  |           | (°)     | (m)    |         | (dB)  | (dB) | (dB)  |
| PK   | 11.02434G | 52.23    | 74.00    | -21.77 | 39.27  | 3    | Vertical  | 51      | 1.69   | -       | 38.52 | 7.71 | 33.27 |
| AV   | 11.015G   | 39.44    | 54.00    | -14.56 | 26.48  | 3    | Vertical  | 51      | 1.69   | -       | 38.52 | 7.71 | 33.27 |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5510MHz\_TnomVnom




EUT\_X\_4TX  
Setting 71  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.018G      | 52.33             | 74.00             | -21.67         | 39.37         | 3           | Horizontal | 253            | 1.37          | -       | 38.52      | 7.71       | 33.27      |
| AV   | 11.01652G    | 39.49             | 54.00             | -14.51         | 26.53         | 3           | Horizontal | 253            | 1.37          | -       | 38.52      | 7.71       | 33.27      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5550MHz\_TnomVnom




EUT X\_4TX  
Setting 90  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.341G       | 59.44             | 68.20             | -8.76          | 52.51         | 3           | Vertical  | 60             | 2.72          | -       | 33.70      | 5.37       | 32.14      |
| PK   | 5.457G       | 66.38             | 74.00             | -7.62          | 59.15         | 3           | Vertical  | 60             | 2.72          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.456G       | 48.76             | 54.00             | -5.24          | 41.53         | 3           | Vertical  | 60             | 2.72          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.467G       | 67.15             | 68.20             | -1.05          | 59.91         | 3           | Vertical  | 60             | 2.72          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.535G       | 114.74            | Inf               | -Inf           | 107.43        | 3           | Vertical  | 60             | 2.72          | -       | 33.90      | 5.54       | 32.13      |
| AV   | 5.545G       | 103.58            | Inf               | -Inf           | 96.27         | 3           | Vertical  | 60             | 2.72          | -       | 33.90      | 5.54       | 32.13      |
| PK   | 5.742G       | 58.16             | 68.20             | -10.04         | 50.92         | 3           | Vertical  | 60             | 2.72          | -       | 33.78      | 5.60       | 32.14      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5550MHz\_TnomVnom




EUT X\_4TX  
Setting 90  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.334G       | 58.35             | 68.20             | -9.85          | 51.42         | 3           | Horizontal | 174            | 2.38          | -       | 33.70      | 5.37       | 32.14      |
| PK   | 5.455G       | 64.47             | 74.00             | -9.53          | 57.24         | 3           | Horizontal | 174            | 2.38          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.459G       | 50.40             | 54.00             | -3.60          | 43.17         | 3           | Horizontal | 174            | 2.38          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.465G       | 68.00             | 68.20             | -0.20          | 60.77         | 3           | Horizontal | 174            | 2.38          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.54G        | 115.00            | Inf               | -Inf           | 107.69        | 3           | Horizontal | 174            | 2.38          | -       | 33.90      | 5.54       | 32.13      |
| AV   | 5.545G       | 103.31            | Inf               | -Inf           | 96.00         | 3           | Horizontal | 174            | 2.38          | -       | 33.90      | 5.54       | 32.13      |
| PK   | 5.75G        | 58.44             | 68.20             | -9.76          | 51.18         | 3           | Horizontal | 174            | 2.38          | -       | 33.80      | 5.60       | 32.14      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5550MHz\_TnomVnom




EUT X\_4TX  
Setting 90  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.10024G    | 52.05             | 74.00             | -21.95         | 38.97         | 3           | Vertical  | 80             | 2.16          | -       | 38.60      | 7.74       | 33.26      |
| AV   | 11.10446G    | 39.49             | 54.00             | -14.51         | 26.41         | 3           | Vertical  | 80             | 2.16          | -       | 38.60      | 7.74       | 33.26      |
| PK   | 16.64776G    | 57.47             | 68.20             | -10.73         | 40.71         | 3           | Vertical  | 170            | 2.42          | -       | 39.65      | 10.32      | 33.21      |

## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

### 5550MHz\_TnomVnom




EUT X\_4TX  
Setting 90  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.097G      | 52.58             | 74.00             | -21.42         | 39.50         | 3           | Horizontal | 110            | 1.54          | -       | 38.60      | 7.74       | 33.26      |
| AV   | 11.1013G     | 39.50             | 54.00             | -14.50         | 26.42         | 3           | Horizontal | 110            | 1.54          | -       | 38.60      | 7.74       | 33.26      |
| PK   | 16.65658G    | 63.41             | 68.20             | -4.79          | 46.64         | 3           | Horizontal | 120            | 1.92          | -       | 39.66      | 10.33      | 33.22      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5670MHz\_TnomVnom




EUT\_X\_4TX  
Setting 75  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.6756G      | 113.22            | Inf               | -Inf           | 106.01        | 3           | Vertical  | 79             | 2.13          | -       | 33.75      | 5.60       | 32.14      |
| AV   | 5.676G       | 100.44            | Inf               | -Inf           | 93.23         | 3           | Vertical  | 79             | 2.13          | -       | 33.75      | 5.60       | 32.14      |
| PK   | 5.7264G      | 67.59             | 68.20             | -0.61          | 60.38         | 3           | Vertical  | 79             | 2.13          | -       | 33.75      | 5.60       | 32.14      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5670MHz\_TnomVnom




EUT X\_4TX  
Setting 75  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.6564G      | 112.72            | Inf               | -Inf           | 105.47        | 3           | Horizontal | 264            | 1.00          | -       | 33.79      | 5.60       | 32.14      |
| AV   | 5.6664G      | 100.38            | Inf               | -Inf           | 93.15         | 3           | Horizontal | 264            | 1.00          | -       | 33.77      | 5.60       | 32.14      |
| PK   | 5.7256G      | 68.11             | 68.20             | -0.09          | 60.90         | 3           | Horizontal | 264            | 1.00          | -       | 33.75      | 5.60       | 32.14      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5670MHz\_TnomVnom




EUT\_X\_4TX  
Setting 75  
02-B-K-5

| Type | Freq      | Level    | Limit    | Margin | Raw    | Dist | Condition | Azimuth | Height | Comment | AF    | CL   | PA    |
|------|-----------|----------|----------|--------|--------|------|-----------|---------|--------|---------|-------|------|-------|
|      | (Hz)      | (dBuV/m) | (dBuV/m) | (dB)   | (dBuV) | (m)  |           | (°)     | (m)    |         | (dB)  | (dB) | (dB)  |
| PK   | 11.34178G | 52.30    | 74.00    | -21.70 | 38.96  | 3    | Vertical  | 184     | 2.80   | -       | 38.74 | 7.84 | 33.24 |
| AV   | 11.33742G | 38.93    | 54.00    | -15.07 | 25.60  | 3    | Vertical  | 184     | 2.80   | -       | 38.74 | 7.83 | 33.24 |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5670MHz\_TnomVnom




EUT X\_4TX  
Setting 75  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.34478G    | 51.49             | 74.00             | -22.51         | 38.15         | 3           | Horizontal | 10             | 2.37          | -       | 38.74      | 7.84       | 33.24      |
| AV   | 11.34458G    | 39.21             | 54.00             | -14.79         | 25.87         | 3           | Horizontal | 10             | 2.37          | -       | 38.74      | 7.84       | 33.24      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5710MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.7012G      | 117.24            | Inf               | -Inf           | 110.08        | 3           | Vertical  | 82             | 1.93          | -       | 33.70      | 5.60       | 32.14      |
| AV   | 5.7012G      | 105.64            | Inf               | -Inf           | 98.48         | 3           | Vertical  | 82             | 1.93          | -       | 33.70      | 5.60       | 32.14      |
| PK   | 5.8516G      | 60.15             | 68.20             | -8.05          | 52.84         | 3           | Vertical  | 82             | 1.93          | -       | 33.81      | 5.65       | 32.15      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5710MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.7012G      | 117.13            | Inf               | -Inf           | 109.97        | 3           | Horizontal | 12             | 1.31          | -       | 33.70      | 5.60       | 32.14      |
| AV   | 5.7012G      | 106.28            | Inf               | -Inf           | 99.12         | 3           | Horizontal | 12             | 1.31          | -       | 33.70      | 5.60       | 32.14      |
| PK   | 5.8516G      | 62.10             | 68.20             | -6.10          | 54.79         | 3           | Horizontal | 12             | 1.31          | -       | 33.81      | 5.65       | 32.15      |

# 802.11ax HEW40\_Nss1,(MCS0)\_4TX

## 5710MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 11.42462G    | 53.20             | 74.00             | -20.80         | 39.71         | 3           | Vertical  | 345            | 2.78          | -       | 38.85      | 7.87       | 33.23      |  |
| AV   | 11.42378G    | 40.92             | 54.00             | -13.08         | 27.43         | 3           | Vertical  | 345            | 2.78          | -       | 38.85      | 7.87       | 33.23      |  |
| PK   | 17.1349G     | 62.92             | 68.20             | -5.28          | 44.20         | 3           | Vertical  | 145            | 2.36          | -       | 41.54      | 10.57      | 33.39      |  |

## 802.11ax HEW40\_Nss1,(MCS0)\_4TX

### 5710MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 101  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.42266G    | 51.50             | 74.00             | -22.50         | 38.01         | 3           | Horizontal | 294            | 1.41          | -       | 38.85      | 7.87       | 33.23      |
| AV   | 11.41636G    | 39.80             | 54.00             | -14.20         | 26.33         | 3           | Horizontal | 294            | 1.41          | -       | 38.83      | 7.87       | 33.23      |
| PK   | 17.14288G    | 67.97             | 68.20             | -0.23          | 49.18         | 3           | Horizontal | 118            | 2.90          | -       | 41.60      | 10.57      | 33.38      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5290MHz\_TnomVnom




EUT X\_4TX  
Setting 75  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1492G      | 59.27             | 74.00             | -14.73         | 52.67         | 3           | Vertical  | 47             | 2.29          | -       | 33.50      | 5.25       | 32.15      |
| AV   | 5.1492G      | 46.33             | 54.00             | -7.67          | 39.73         | 3           | Vertical  | 47             | 2.29          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.2596G      | 108.24            | Inf               | -Inf           | 101.43        | 3           | Vertical  | 47             | 2.29          | -       | 33.62      | 5.33       | 32.14      |
| AV   | 5.2596G      | 97.43             | Inf               | -Inf           | 90.62         | 3           | Vertical  | 47             | 2.29          | -       | 33.62      | 5.33       | 32.14      |
| PK   | 5.3628G      | 68.30             | 74.00             | -5.70          | 61.33         | 3           | Vertical  | 47             | 2.29          | -       | 33.73      | 5.38       | 32.14      |
| AV   | 5.3532G      | 51.87             | 54.00             | -2.13          | 44.92         | 3           | Vertical  | 47             | 2.29          | -       | 33.71      | 5.38       | 32.14      |
| PK   | 5.4644G      | 57.80             | 68.20             | -10.40         | 50.57         | 3           | Vertical  | 47             | 2.29          | -       | 33.90      | 5.46       | 32.13      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5290MHz\_TnomVnom




EUT X\_4TX  
Setting 75  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1396G      | 57.95             | 74.00             | -16.05         | 51.36         | 3           | Horizontal | 7              | 1.11          | -       | 33.50      | 5.24       | 32.15      |
| AV   | 5.15G        | 46.15             | 54.00             | -7.85          | 39.55         | 3           | Horizontal | 7              | 1.11          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.2764G      | 108.63            | Inf               | -Inf           | 101.78        | 3           | Horizontal | 7              | 1.11          | -       | 33.65      | 5.34       | 32.14      |
| AV   | 5.2812G      | 97.64             | Inf               | -Inf           | 90.78         | 3           | Horizontal | 7              | 1.11          | -       | 33.66      | 5.34       | 32.14      |
| PK   | 5.3524G      | 72.90             | 74.00             | -1.10          | 65.96         | 3           | Horizontal | 7              | 1.11          | -       | 33.70      | 5.38       | 32.14      |
| AV   | 5.3516G      | 53.76             | 54.00             | -0.24          | 46.82         | 3           | Horizontal | 7              | 1.11          | -       | 33.70      | 5.38       | 32.14      |
| PK   | 5.474G       | 58.51             | 68.20             | -9.69          | 51.27         | 3           | Horizontal | 7              | 1.11          | -       | 33.90      | 5.47       | 32.13      |

## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5290MHz\_TnomVnom




EUT X\_4TX  
Setting 75  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.86738G    | 52.58             | 74.00             | -21.42         | 38.75         | 3           | Vertical  | 261            | 2.61          | -       | 37.47      | 9.94       | 33.58      |
| AV   | 15.87046G    | 40.45             | 54.00             | -13.55         | 26.63         | 3           | Vertical  | 261            | 2.61          | -       | 37.47      | 9.94       | 33.59      |

## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5290MHz\_TnomVnom




EUT X\_4TX  
Setting 75  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.86642G    | 52.59             | 74.00             | -21.41         | 38.76         | 3           | Horizontal | 100            | 2.43          | -       | 37.47      | 9.94       | 33.58      |
| AV   | 15.86766G    | 40.20             | 54.00             | -13.80         | 26.37         | 3           | Horizontal | 100            | 2.43          | -       | 37.47      | 9.94       | 33.58      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5530MHz\_TnomVnom




EUT X\_4TX  
Setting 69  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.315G       | 57.81             | 68.20             | -10.39         | 50.89         | 3           | Vertical  | 58             | 2.13          | -       | 33.70      | 5.36       | 32.14      |
| AV   | 5.35G        | 45.45             | 54.00             | -8.55          | 38.52         | 3           | Vertical  | 58             | 2.13          | -       | 33.70      | 5.37       | 32.14      |
| PK   | 5.46G        | 65.12             | 74.00             | -8.88          | 57.89         | 3           | Vertical  | 58             | 2.13          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.46G        | 52.21             | 54.00             | -1.79          | 44.98         | 3           | Vertical  | 58             | 2.13          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.468G       | 67.64             | 68.20             | -0.56          | 60.40         | 3           | Vertical  | 58             | 2.13          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.566G       | 107.39            | Inf               | -Inf           | 100.05        | 3           | Vertical  | 58             | 2.13          | -       | 33.90      | 5.57       | 32.13      |
| AV   | 5.521G       | 95.97             | Inf               | -Inf           | 88.68         | 3           | Vertical  | 58             | 2.13          | -       | 33.90      | 5.52       | 32.13      |
| PK   | 5.725G       | 58.41             | 68.20             | -9.79          | 51.20         | 3           | Vertical  | 58             | 2.13          | -       | 33.75      | 5.60       | 32.14      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5530MHz\_TnomVnom




EUT\_X\_4TX  
Setting 69  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.341G       | 57.12             | 68.20             | -11.08         | 50.19         | 3           | Horizontal | -0             | 1.00          | -       | 33.70      | 5.37       | 32.14      |
| AV   | 5.35G        | 45.53             | 54.00             | -8.47          | 38.60         | 3           | Horizontal | -0             | 1.00          | -       | 33.70      | 5.37       | 32.14      |
| PK   | 5.46G        | 66.66             | 74.00             | -7.34          | 59.43         | 3           | Horizontal | -0             | 1.00          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.459G       | 53.94             | 54.00             | -0.06          | 46.71         | 3           | Horizontal | -0             | 1.00          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.47G        | 66.54             | 68.20             | -1.66          | 59.30         | 3           | Horizontal | -0             | 1.00          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.519G       | 109.20            | Inf               | -Inf           | 101.91        | 3           | Horizontal | -0             | 1.00          | -       | 33.90      | 5.52       | 32.13      |
| AV   | 5.545G       | 96.18             | Inf               | -Inf           | 88.87         | 3           | Horizontal | -0             | 1.00          | -       | 33.90      | 5.54       | 32.13      |
| PK   | 5.77G        | 57.52             | 68.20             | -10.68         | 50.31         | 3           | Horizontal | -0             | 1.00          | -       | 33.76      | 5.60       | 32.15      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5530MHz\_TnomVnom




EUT X\_4TX  
Setting 69  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.0569G     | 52.04             | 74.00             | -21.96         | 39.02         | 3           | Vertical  | 70             | 1.34          | -       | 38.56      | 7.72       | 33.26      |
| AV   | 11.0605G     | 39.40             | 54.00             | -14.60         | 26.38         | 3           | Vertical  | 70             | 1.34          | -       | 38.56      | 7.72       | 33.26      |

## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5530MHz\_TnomVnom




EUT X\_4TX  
Setting 69  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.06364G    | 52.25             | 74.00             | -21.75         | 39.22         | 3           | Horizontal | 315            | 1.54          | -       | 38.56      | 7.73       | 33.26      |
| AV   | 11.05922G    | 38.93             | 54.00             | -15.07         | 25.91         | 3           | Horizontal | 315            | 1.54          | -       | 38.56      | 7.72       | 33.26      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5610MHz\_TnomVnom




EUT X\_4TX  
Setting 82  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.4572G      | 62.04             | 74.00             | -11.96         | 54.81         | 3           | Vertical  | 78             | 2.14          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.458G       | 48.37             | 54.00             | -5.63          | 41.14         | 3           | Vertical  | 78             | 2.14          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.4668G      | 63.78             | 68.20             | -4.42          | 56.54         | 3           | Vertical  | 78             | 2.14          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.6364G      | 110.26            | Inf               | -Inf           | 102.97        | 3           | Vertical  | 78             | 2.14          | -       | 33.83      | 5.60       | 32.14      |
| AV   | 5.6364G      | 98.78             | Inf               | -Inf           | 91.49         | 3           | Vertical  | 78             | 2.14          | -       | 33.83      | 5.60       | 32.14      |
| PK   | 5.7372G      | 67.98             | 68.20             | -0.22          | 60.75         | 3           | Vertical  | 78             | 2.14          | -       | 33.77      | 5.60       | 32.14      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5610MHz\_TnomVnom




EUT X\_4TX  
Setting 82  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.4588G      | 59.95             | 74.00             | -14.05         | 52.72         | 3           | Horizontal | 264            | 2.14          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.4596G      | 47.17             | 54.00             | -6.83          | 39.94         | 3           | Horizontal | 264            | 2.14          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.466G       | 62.24             | 68.20             | -5.96          | 55.00         | 3           | Horizontal | 264            | 2.14          | -       | 33.90      | 5.47       | 32.13      |
| PK   | 5.5812G      | 109.16            | Inf               | -Inf           | 101.81        | 3           | Horizontal | 264            | 2.14          | -       | 33.90      | 5.58       | 32.13      |
| AV   | 5.642G       | 96.53             | Inf               | -Inf           | 89.25         | 3           | Horizontal | 264            | 2.14          | -       | 33.82      | 5.60       | 32.14      |
| PK   | 5.7252G      | 65.73             | 68.20             | -2.47          | 58.52         | 3           | Horizontal | 264            | 2.14          | -       | 33.75      | 5.60       | 32.14      |

## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5610MHz\_TnomVnom




EUT X\_4TX  
Setting 82  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.2189G     | 52.46             | 74.00             | -21.54         | 39.22         | 3           | Vertical  | 251            | 2.99          | -       | 38.70      | 7.79       | 33.25      |
| AV   | 11.21822G    | 39.47             | 54.00             | -14.53         | 26.23         | 3           | Vertical  | 251            | 2.99          | -       | 38.70      | 7.79       | 33.25      |

## 802.11ax HEW80\_Nss1,(MCS0)\_4TX

### 5610MHz\_TnomVnom




EUT X\_4TX  
Setting 82  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.225G      | 51.88             | 74.00             | -22.12         | 38.64         | 3           | Horizontal | 210            | 2.42          | -       | 38.70      | 7.79       | 33.25      |
| AV   | 11.22276G    | 39.24             | 54.00             | -14.76         | 26.00         | 3           | Horizontal | 210            | 2.42          | -       | 38.70      | 7.79       | 33.25      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5690MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 105  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.6844G      | 114.40            | Inf               | -Inf           | 107.21        | 3           | Vertical  | 264            | 1.80          | -       | 33.73      | 5.60       | 32.14      |
| AV   | 5.674G       | 102.81            | Inf               | -Inf           | 95.60         | 3           | Vertical  | 264            | 1.80          | -       | 33.75      | 5.60       | 32.14      |
| PK   | 5.85G        | 68.06             | 68.20             | -0.14          | 60.76         | 3           | Vertical  | 264            | 1.80          | -       | 33.80      | 5.65       | 32.15      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5690MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 105  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.6836G      | 116.64            | Inf               | -Inf           | 109.45        | 3           | Horizontal | 267            | 1.95          | -       | 33.73      | 5.60       | 32.14      |
| AV   | 5.674G       | 102.78            | Inf               | -Inf           | 95.57         | 3           | Horizontal | 267            | 1.95          | -       | 33.75      | 5.60       | 32.14      |
| PK   | 5.8524G      | 67.97             | 68.20             | -0.23          | 60.66         | 3           | Horizontal | 267            | 1.95          | -       | 33.81      | 5.65       | 32.15      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5690MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 105  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.4042G     | 52.43             | 74.00             | -21.57         | 38.99         | 3           | Vertical  | 6.4            | 1.80          | -       | 38.81      | 7.86       | 33.23      |
| AV   | 11.3777G     | 40.13             | 54.00             | -13.87         | 26.73         | 3           | Vertical  | 6.4            | 1.80          | -       | 38.78      | 7.85       | 33.23      |
| PK   | 17.0574G     | 60.88             | 68.20             | -7.32          | 42.56         | 3           | Vertical  | 144            | 1.78          | -       | 41.26      | 10.53      | 33.47      |

# 802.11ax HEW80\_Nss1,(MCS0)\_4TX

## 5690MHz Straddle 5.47-5.725GHz\_TnomVnom




EUT\_X\_4TX  
Setting 105  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.38262G    | 51.19             | 74.00             | -22.81         | 37.79         | 3           | Horizontal | 68             | 1.32          | -       | 38.78      | 7.85       | 33.23      |
| AV   | 11.37992G    | 39.15             | 54.00             | -14.85         | 25.75         | 3           | Horizontal | 68             | 1.32          | -       | 38.78      | 7.85       | 33.23      |
| PK   | 17.08128G    | 67.00             | 68.20             | -1.20          | 48.63         | 3           | Horizontal | 118            | 1.73          | -       | 41.28      | 10.54      | 33.45      |

# 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## 5250MHz Straddle 5.25-5.35GHz\_TnomVnom




EUT\_X\_4TX  
Setting 70  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1412G      | 62.31             | 74.00             | -11.69         | 55.72         | 3           | Vertical  | 54             | 2.32          | -       | 33.50      | 5.24       | 32.15      |
| AV   | 5.1492G      | 52.51             | 54.00             | -1.49          | 45.91         | 3           | Vertical  | 54             | 2.32          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.226G       | 105.20            | Inf               | -Inf           | 98.49         | 3           | Vertical  | 54             | 2.32          | -       | 33.55      | 5.31       | 32.15      |
| AV   | 5.226G       | 94.07             | Inf               | -Inf           | 87.36         | 3           | Vertical  | 54             | 2.32          | -       | 33.55      | 5.31       | 32.15      |
| PK   | 5.3556G      | 66.16             | 74.00             | -7.84          | 59.21         | 3           | Vertical  | 54             | 2.32          | -       | 33.71      | 5.38       | 32.14      |
| AV   | 5.386G       | 52.14             | 54.00             | -1.86          | 45.12         | 3           | Vertical  | 54             | 2.32          | -       | 33.77      | 5.39       | 32.14      |
| PK   | 5.4756G      | 60.54             | 68.20             | -7.66          | 53.29         | 3           | Vertical  | 54             | 2.32          | -       | 33.90      | 5.48       | 32.13      |

# 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## 5250MHz Straddle 5.25-5.35GHz\_TnomVnom




EUT\_X\_4TX  
Setting 70  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.1492G      | 65.34             | 74.00             | -8.66          | 58.74         | 3           | Horizontal | 354            | 1.00          | -       | 33.50      | 5.25       | 32.15      |
| AV   | 5.146G       | 53.33             | 54.00             | -0.67          | 46.73         | 3           | Horizontal | 354            | 1.00          | -       | 33.50      | 5.25       | 32.15      |
| PK   | 5.258G       | 105.96            | Inf               | -Inf           | 99.15         | 3           | Horizontal | 354            | 1.00          | -       | 33.62      | 5.33       | 32.14      |
| AV   | 5.2388G      | 95.18             | Inf               | -Inf           | 88.43         | 3           | Horizontal | 354            | 1.00          | -       | 33.58      | 5.32       | 32.15      |
| PK   | 5.3764G      | 68.27             | 74.00             | -5.73          | 61.27         | 3           | Horizontal | 354            | 1.00          | -       | 33.75      | 5.39       | 32.14      |
| AV   | 5.3764G      | 53.76             | 54.00             | -0.24          | 46.76         | 3           | Horizontal | 354            | 1.00          | -       | 33.75      | 5.39       | 32.14      |
| PK   | 5.4612G      | 65.45             | 68.20             | -2.75          | 58.22         | 3           | Horizontal | 354            | 1.00          | -       | 33.90      | 5.46       | 32.13      |

## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

### 5250MHz Straddle 5.25-5.35GHz\_TnomVnom




EUT\_X\_4TX  
Setting 70  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.7544G     | 53.29             | 74.00             | -20.71         | 39.45         | 3           | Vertical  | 14             | 2.21          | -       | 37.40      | 9.89       | 33.45      |
| AV   | 15.74826G    | 42.34             | 54.00             | -11.66         | 28.49         | 3           | Vertical  | 14             | 2.21          | -       | 37.40      | 9.89       | 33.44      |

## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

### 5250MHz Straddle 5.25-5.35GHz\_TnomVnom




EUT\_X\_4TX  
Setting 70  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 15.75128G    | 52.69             | 74.00             | -21.31         | 38.85         | 3           | Horizontal | 170            | 2.49          | -       | 37.40      | 9.89       | 33.45      |
| AV   | 15.75098G    | 41.89             | 54.00             | -12.11         | 28.05         | 3           | Horizontal | 170            | 2.49          | -       | 37.40      | 9.89       | 33.45      |

# 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## 5570MHz\_TnomVnom




EUT\_X\_4TX  
Setting 68  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3204G      | 57.75             | 68.20             | -10.45         | 50.83         | 3           | Vertical  | 78             | 1.80          | -       | 33.70      | 5.36       | 32.14      |
| PK   | 5.4276G      | 62.23             | 74.00             | -11.77         | 55.07         | 3           | Vertical  | 78             | 1.80          | -       | 33.86      | 5.43       | 32.13      |
| PK   | 5.466G       | 62.77             | 68.20             | -5.43          | 55.53         | 3           | Vertical  | 78             | 1.80          | -       | 33.90      | 5.47       | 32.13      |
| AV   | 5.4484G      | 52.12             | 54.00             | -1.88          | 44.90         | 3           | Vertical  | 78             | 1.80          | -       | 33.90      | 5.45       | 32.13      |
| PK   | 5.6324G      | 103.77            | Inf               | -Inf           | 96.47         | 3           | Vertical  | 78             | 1.80          | -       | 33.84      | 5.60       | 32.14      |
| AV   | 5.6324G      | 92.13             | Inf               | -Inf           | 84.83         | 3           | Vertical  | 78             | 1.80          | -       | 33.84      | 5.60       | 32.14      |
| PK   | 5.7284G      | 59.66             | 68.20             | -8.54          | 52.44         | 3           | Vertical  | 78             | 1.80          | -       | 33.76      | 5.60       | 32.14      |

# 802.11ax HEW160\_Nss1,(MCS0)\_4TX

## 5570MHz\_TnomVnom




EUT X\_4TX  
Setting 68  
02-B-K-5-10

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 5.3316G      | 58.04             | 68.20             | -10.16         | 51.11         | 3           | Horizontal | 174            | 1.32          | -       | 33.70      | 5.37       | 32.14      |
| PK   | 5.4516G      | 63.56             | 74.00             | -10.44         | 56.34         | 3           | Horizontal | 174            | 1.32          | -       | 33.90      | 5.45       | 32.13      |
| PK   | 5.4628G      | 63.33             | 68.20             | -4.87          | 56.10         | 3           | Horizontal | 174            | 1.32          | -       | 33.90      | 5.46       | 32.13      |
| AV   | 5.458G       | 53.81             | 54.00             | -0.19          | 46.58         | 3           | Horizontal | 174            | 1.32          | -       | 33.90      | 5.46       | 32.13      |
| PK   | 5.5828G      | 103.84            | Inf               | -Inf           | 96.49         | 3           | Horizontal | 174            | 1.32          | -       | 33.90      | 5.58       | 32.13      |
| AV   | 5.5876G      | 93.49             | Inf               | -Inf           | 86.14         | 3           | Horizontal | 174            | 1.32          | -       | 33.90      | 5.59       | 32.14      |
| PK   | 5.7284G      | 61.29             | 68.20             | -6.91          | 54.07         | 3           | Horizontal | 174            | 1.32          | -       | 33.76      | 5.60       | 32.14      |

## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

### 5570MHz\_TnomVnom




EUT\_X\_4TX  
Setting 68  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |  |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|-----------|----------------|---------------|---------|------------|------------|------------|--|
| PK   | 11.13832G    | 52.69             | 74.00             | -21.31         | 39.55         | 3           | Vertical  | 25             | 1.08          | -       | 38.64      | 7.76       | 33.26      |  |
| AV   | 11.14094G    | 41.47             | 54.00             | -12.53         | 28.33         | 3           | Vertical  | 25             | 1.08          | -       | 38.64      | 7.76       | 33.26      |  |

## 802.11ax HEW160\_Nss1,(MCS0)\_4TX

### 5570MHz\_TnomVnom



EUT\_X\_4TX  
Setting 68  
02-B-K-5

| Type | Freq<br>(Hz) | Level<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Raw<br>(dBuV) | Dist<br>(m) | Condition  | Azimuth<br>(°) | Height<br>(m) | Comment | AF<br>(dB) | CL<br>(dB) | PA<br>(dB) |
|------|--------------|-------------------|-------------------|----------------|---------------|-------------|------------|----------------|---------------|---------|------------|------------|------------|
| PK   | 11.1378G     | 51.98             | 74.00             | -22.02         | 38.84         | 3           | Horizontal | 220            | 1.00          | -       | 38.64      | 7.76       | 33.26      |
| AV   | 11.13504G    | 41.07             | 54.00             | -12.93         | 27.94         | 3           | Horizontal | 220            | 1.00          | -       | 38.64      | 7.75       | 33.26      |