

H	G	F	E	D	C	B	A
REV.LTR	DATE	UPDATE DESCRIPTION			REMARK	SIGN	APPROVER
*	20211225	1510-379600 FIRST RELEASE FOR REVIEW				Jeacol	Sujing
A	20220210	Remove Sagemcom logo, change Printing Content for factory and Background color, release 1510-38F6000				Jeacol	Sujing
B						Jeacol	Sujing
						Jeacol	Sujing
						Jeacol	Sujing
						Jeacol	Sujing

### 2.8.3 Labels (with all printed contents including barcodes)

#### Label without safety marking

The test should be performed in accordance with Guide SCT U31 001 F, under the following conditions:

- Chemical resistance: 25s each for water, alcohol, isopropanol;

#### Label with safety marking

Test should be performed in accordance with IEC60950-1 1.7.11, under the following conditions:

- Chemical resistance: 15s for water, 15s for petroleum spirit;

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.



### 2.11 Temperature cycling test

Temperature cycling test should be applied on the components with glue or adhesive tape (sticker / foam / rubber etc). The test should be performed in accordance with standard IEC 60068-2-14, under the following conditions:

- Sample size: 2 pcs;
- Sample status: Non-operating;
- Temperature range: -40 ~ 70°C
- 40°C during 1h
- 40°C to +0°C during 1h
- +70°C at 90% humidity during 1h
- +70°C to -40°C during 1h
- Duration: 168h (42 cycles)

After test, below phenomenon should not appear on the part:

- Significant discoloration on the surface.
- Cracks, blistering and deformation (material degradation)
- Turn up or peel off
- Haze of transparent plastics



Printing Content for supplier  
供應商印刷內容  
Scale 1:1



Arial MT Bold 8.5pt  
Arial MT Bold 5.5pt, Arial Regular 5.5pt



Printing position for factory  
工廠印刷位置

: L=7.2 x H=9.6 mm

: L=5.6 x H=4.7 mm

SPEC		Roll type	Material Structure	DESCRIPTION			PEGATRON Corporation
Material (Brand/Model No.): (ex.PET / PP / ART PAPER(Brand/Model No.))	50μ White Polyester(Matt)/FASSON_MZ0336A	Roll form packaging 包裝方式: 卷狀外翻					
Adhesive (Brand/Model No): (ex.Acrylic(Brand/Model No.))	Acrylic(Embossed )	Outer diameter of the paper roll core: 3'(76.2mm) 紙張芯外直徑: 3'(76.2mm)		All Dimension	±0.20mm	SCAL E	MODEL NO.
Coating (Brand/Model No.): (ex.PET / OPP(Brand/Model No.))	Matt OPP Film	Outer diameter of the paper roll: <8(203mm) 紙張卷外直徑: <8(203mm)		Edge distance	±0.50mm	1:1	PARTS NO.
Printable:	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No			GAP distance	±0.50mm		1510-38F6000
Printing color: (ex.Black 100% / Other)	<input checked="" type="checkbox"/> Black 100%			DESIGNED	Jeacol	CHECKED	APPROVED
Background color: (ex.White / Other)	White			REMARK	Jeacol	Sujing	Sujing
Packing method:	<input type="checkbox"/> Single page <input checked="" type="checkbox"/> Roll			DATE	20220210	1510-379600 FIRST RELEASE FOR REVIEW	
Safety certification:	<input type="checkbox"/> PGJ12 <input type="checkbox"/> PGDQ2 <input type="checkbox"/> NA			UPDATE			
Printing ribbon:	<input checked="" type="checkbox"/> high temperature ribbon <input type="checkbox"/> Low temperature ribbon <input type="checkbox"/> No			DESCRIPTION			
Artwork version (File name / Released date)	<input checked="" type="checkbox"/> 20220210			REMARK			