

Appendix 10

Prüfbericht - Nr.:
Test Report No.

19660079 001

Seite 1 von 2
Page 1 of 2

RF Exposure Report

RF Exposure Measurement

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

Appendix 10

Prüfbericht - Nr.:

19660079 001

Test Report No.

Seite 2 von 2
Page 2 of 2

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.

EUT Operation condition

EUT was enabled to transmit and receive at lowest, middle and highest channels.

Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.

Test Results

1. External Antenna

Gain (G) = 3dBi= 1.995262315(Linear)

Highest measured power at 914MHz i.e. 8.50dBm

Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm^2)	Limit (mW/cm^2)
914	7.0794578	0.002810	1.000

2. UFL-cable integrated with Antenna

Gain (G) = 1.3dBi= 1.348962883(Linear)

Highest measured power at 240MHz i.e. 8.50dBm

Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm^2)	Limit (mW/cm^2)
914	7.0794578	0.001900	1.000