# APPENDIX I RADIO FREQUENCY EXPOSURE

## **LIMIT**

### **EUT Specification**

EUT	GSM/GPRS Terminal
Frequency band (Operating)	<ul> <li>WLAN: 2.412GHz ~ 2.462GHz</li> <li>WLAN: 5.725GHz ~ 5.850GHz</li> <li>WLAN: 5.15GHz ~ 5.35GHz</li> <li>Others: _824 ~ 849 MHz</li> </ul>
Device category	Portable (<20cm separation) Mobile (>20cm separation) Others
Exposure classification	Occupational/Controlled exposure (S = 5mW/cm2) General Population/Uncontrolled exposure (S=0.55mW/cm2)
Antenna diversity	<ul> <li>Single antenna</li> <li>Multiple antennas</li> <li>☐ Tx diversity</li> <li>☐ Rx diversity</li> <li>☐ Tx/Rx diversity</li> </ul>
Max. output power	GSM 850: 26.37 dBm (433.51mW) GPRS 850: 26.22 dBm (418.79mW)
Antenna gain (Max)	4 dBi (Numeric gain: 2.51)
Evaluation applied	<ul><li>MPE Evaluation</li><li>SAR Evaluation</li><li>N/A</li></ul>
<ul> <li>antenna gain.)</li> <li>DTS device is not subject to recompliance.</li> <li>For mobile or fixed location to</li> </ul>	s 26.37 dBm (433.51mW) at 836.60MHz (with 2.51 numeric outine RF evaluation; MPE estimate is used to justify the ransmitters, no SAR consideration applied. The maximum even if the calculation indicates that the power density

## **TEST RESULTS**

No non-compliance noted.

**Calculation** 

$$E = \frac{\sqrt{30 \times P \times G}}{d} \& S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

 $S = Power\ density\ in\ milliwatts\ /\ square\ centimeter$ 

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000 \text{ and}$$

$$d(cm) = d(m) / 100$$

**Yields** 

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$
 Equation 1

Where

d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power\ density\ in\ mW/cm^2$ 

#### **Maximum Permissible Exposure**

EUT output power = 433.51 mW

Numeric Antenna gain = 2.51

Substituting the MPE safe distance using d = 20 cm into Equation 1:

**Yields** 

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

 $S = Power\ density\ in\ mW/cm^2$ 

#### $\rightarrow$ Power density = 0.2165 mW/cm2

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)

> Page 77 Rev. 00

#### **EUT Specification**

EUT	GSM/GPRS Terminal
Frequency band (Operating)	<ul> <li>WLAN: 2.412GHz ~ 2.462GHz</li> <li>WLAN: 5.725GHz ~ 5.850GHz</li> <li>WLAN: 5.15GHz ~ 5.35GHz</li> <li>Others: _1850 ~ 1910 MHz</li> </ul>
Device category	☐ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others
Exposure classification	Occupational/Controlled exposure (S = 5mW/cm2) General Population/Uncontrolled exposure (S=1mW/cm2)
Antenna diversity	<ul> <li>Single antenna</li> <li>Multiple antennas</li> <li>☐ Tx diversity</li> <li>☐ Rx diversity</li> <li>☐ Tx/Rx diversity</li> </ul>
Max. output power	GSM 1900: 26.44 dBm (440.55mW) GPRS 1900: 26.59 dBm (456.03mW)
Antenna gain (Max)	4 dBi (Numeric gain: 2.51)
Evaluation applied	<ul><li></li></ul>
Remark:	
<ul> <li>4. The maximum output power is 26.59 dBm (456.03mW) at 1850.20MHz (with 2.51 numeric antenna gain.)</li> <li>5. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.</li> </ul>	
6. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.	

### **TEST RESULTS**

No non-compliance noted.

**Calculation** 

$$E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

 $S = Power\ density\ in\ milliwatts\ /\ square\ centimeter$ 

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000 \text{ and}$$

$$d(cm) = d(m) / 100$$

**Yields** 

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$
 Equation 1

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power\ density\ in\ mW/cm^2$ 

#### Maximum Permissible Exposure

EUT output power = 456.03mW

Numeric Antenna gain = 2.51

Substituting the MPE safe distance using d = 20 cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW/cm^2$ 

#### $\rightarrow$ Power density = 0.227 mW/cm2

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm<sup>2</sup> even if the calculation indicates that the power density would be larger.)

> Page 79 Rev. 00