

Appendix B: Test Results of FCC 15B


APPENDIX B: TEST RESULTS OF FCC 15B	1
APPENDIX B.1: TEST PLOTS OF CONDUCTED EMISSION ON AC MAINS	2
SD Data transfer with PC.....	2
Front camera on (with adapter)	4
Rear camera on with LED on (with adapter)	6
Video play with 1KHz (with adapter).....	8
Bluetooth link (with adapter)	10
Wi-Fi link (with adapter)	12
2G/3G/4G link (with adapter)	14
Print (with adapter).....	16
APPENDIX B.2: TEST PLOTS OF RADIATED EMISSION, BELOW 1GHz	18
SD Data transfer with PC.....	18
Front camera on (with adapter)	20
Rear camera on with LED on (with adapter)	22
Video play with 1KHz (with adapter).....	24
Bluetooth link (with adapter)	26
Wi-Fi link (with adapter)	28
2G/3G/4G link (with adapter)	30
Print (with adapter).....	32
APPENDIX B.3: TEST PLOTS OF RADIATED EMISSION, ABOVE 1GHz.....	34
SD Data transfer with PC.....	34
Front camera on (with adapter)	36
Rear camera on with LED on (with adapter)	38
Video play with 1KHz (with adapter).....	40
Bluetooth link (with adapter)	42
Wi-Fi link (with adapter)	44
2G/3G/4G link (with adapter)	46
Print (with adapter).....	48

Appendix B.1: Test Plots of Conducted Emission on AC Mains

SD Data transfer with PC

EUT Information

EUT Name:	Android POS
Order No.:	168279564
Model:	APOLLO
Test Mode:	SD Data transfer with PC
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	SR1




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.154000	56.02	---	65.78	9.76	L1	9.6
0.158000	---	34.70	55.57	20.87	L1	9.6
0.258000	42.08	---	61.50	19.42	L1	9.6
0.528000	---	22.24	46.00	23.76	L1	9.7
3.088000	---	23.45	46.00	22.55	L1	9.8
3.548000	33.98	---	56.00	22.02	L1	9.8
4.844000	---	29.99	46.00	16.01	L1	9.9
4.932000	42.03	---	56.00	13.97	L1	9.9
6.244000	36.03	---	60.00	23.97	L1	10.0
9.100000	---	23.13	50.00	26.87	L1	10.0
11.188000	38.19	---	60.00	21.81	L1	10.2
11.512000	---	25.32	50.00	24.68	L1	10.2

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: SD Data transfer with PC
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.166000	54.14	---	65.16	11.02	N	9.6
0.178000	---	33.77	54.58	20.81	N	9.6
0.258000	45.11	---	61.50	16.38	N	9.6
0.258000	---	23.38	51.50	28.12	N	9.6
3.352000	---	23.48	46.00	22.52	N	9.8
3.444000	33.85	---	56.00	22.15	N	9.8
4.836000	---	30.36	46.00	15.64	N	9.9
4.952000	41.32	---	56.00	14.68	N	9.9
7.160000	---	23.59	50.00	26.41	N	10.0
7.680000	33.89	---	60.00	26.11	N	10.0
11.532000	38.11	---	60.00	21.89	N	10.2
11.984000	---	25.06	50.00	24.94	N	10.2

Front camera on (with adapter)

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Front camera on
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.452500	49.87	---	56.73	6.86	L1	9.7
0.534500	53.89	---	56.00	2.11	L1	9.7
0.542500	---	40.35	46.00	5.65	L1	9.7
0.598500	51.98	---	56.00	4.02	L1	9.7
0.606500	---	39.46	46.00	6.54	L1	9.7
1.026500	50.58	---	56.00	5.42	L1	9.7
1.382500	49.64	---	56.00	6.36	L1	9.7
2.182500	50.66	---	56.00	5.34	L1	9.7

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.452500	46.93	---	56.83	9.90	200.0	9.000	L1	9.7
0.534500	50.01	---	56.00	5.99	200.0	9.000	L1	9.7
0.542500	---	39.76	46.00	6.24	200.0	9.000	L1	9.7
0.598500	47.47	---	56.00	8.53	200.0	9.000	L1	9.7
0.606500	---	38.98	46.00	7.02	200.0	9.000	L1	9.7
1.026500	47.11	---	56.00	8.89	200.0	9.000	L1	9.7
1.382500	44.16	---	56.00	11.84	200.0	9.000	L1	9.7
2.182500	45.26	---	56.00	10.74	200.0	9.000	L1	9.7

EUT Information

EUT Name: Android POS
Order No.: 168279564
Model: APOLLO
Test Mode: Front camera on
Test Voltage: AC 120V/60Hz
Test By: Tom Guo
Review By: Gary Chen
Remark: SR1



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.448500	49.42	---	56.88	7.45	N	9.7
0.534500	51.87	---	56.00	4.13	N	9.7
0.538500	---	39.37	46.00	6.63	N	9.7
0.606500	50.41	---	56.00	5.59	N	9.7
0.970500	49.50	---	56.00	6.50	N	9.7
1.022500	49.49	---	56.00	6.51	N	9.7
1.026500	---	38.74	46.00	7.26	N	9.7
1.873500	48.13	---	56.00	7.87	N	9.7


Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.448500	44.01	---	56.90	12.90	200.0	9.000	N	9.7
0.534500	47.30	---	56.00	8.70	200.0	9.000	N	9.7
0.538500	---	39.13	46.00	6.87	200.0	9.000	N	9.7
0.606500	46.21	---	56.00	9.79	200.0	9.000	N	9.7
0.970500	44.15	---	56.00	11.85	200.0	9.000	N	9.7
1.022500	44.92	---	56.00	11.08	200.0	9.000	N	9.7
1.026500	---	38.22	46.00	7.78	200.0	9.000	N	9.7
1.873500	43.41	---	56.00	12.59	200.0	9.000	N	9.7

Rear camera on with LED on (with adapter)

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Rear camera on with LED on
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.452500	51.45	---	56.80	5.35	L1	9.7
0.534500	55.02	---	56.00	0.98	L1	9.7
0.542500	---	40.01	46.00	5.99	L1	9.7
0.606500	52.83	---	56.00	3.17	L1	9.7
0.610500	---	38.89	46.00	7.11	L1	9.7
1.010500	51.11	---	56.00	4.89	L1	9.7
1.022500	---	37.14	46.00	8.86	L1	9.7
2.178500	51.10	---	56.00	4.90	L1	9.7

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.452500	47.52	---	56.83	9.31	200.0	9.000	L1	9.7
0.534500	49.58	---	56.00	6.42	200.0	9.000	L1	9.7
0.542500	---	39.48	46.00	6.52	200.0	9.000	L1	9.7
0.606500	48.80	---	56.00	7.20	200.0	9.000	L1	9.7
0.610500	---	39.14	46.00	6.86	200.0	9.000	L1	9.7
1.010500	45.80	---	56.00	10.20	200.0	9.000	L1	9.7
1.022500	---	37.83	46.00	8.17	200.0	9.000	L1	9.7
2.178500	45.19	---	56.00	10.81	200.0	9.000	L1	9.7

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Rear camera on with LED on
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.534500	52.13	---	56.00	3.87	N	9.7
0.542500	---	39.42	46.00	6.58	N	9.7
0.598500	49.79	---	56.00	6.21	N	9.7
0.610500	---	39.45	46.00	6.55	N	9.7
1.026500	49.37	---	56.00	6.63	N	9.7
1.026500	---	38.11	46.00	7.89	N	9.7
1.866500	---	36.31	46.00	9.69	N	9.7
1.870500	48.99	---	56.00	7.01	N	9.7


Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.534500	46.97	---	56.00	9.03	200.0	9.000	N	9.7
0.542500	---	38.98	46.00	7.02	200.0	9.000	N	9.7
0.598500	45.16	---	56.00	10.84	200.0	9.000	N	9.7
0.610500	---	38.97	46.00	7.03	200.0	9.000	N	9.7
1.026500	44.68	---	56.00	11.32	200.0	9.000	N	9.7
1.026500	---	37.97	46.00	8.03	200.0	9.000	N	9.7
1.866500	---	36.07	46.00	9.93	200.0	9.000	N	9.7
1.870500	43.44	---	56.00	12.56	200.0	9.000	N	9.7

Video play with 1KHz (with adapter)

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Video play with 1KHz
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.314000	---	38.02	49.86	11.84	L1	9.6
0.314000	44.11	---	59.86	15.75	L1	9.6
0.468500	45.34	---	56.66	11.32	L1	9.7
0.476500	---	39.06	46.59	7.52	L1	9.7
0.526500	---	41.59	46.00	4.41	L1	9.7
0.538500	49.75	---	56.00	6.25	L1	9.7
1.008000	---	36.19	46.00	9.81	L1	9.7
1.012000	46.81	---	56.00	9.19	L1	9.7
1.880000	---	32.65	46.00	13.35	L1	9.7
1.908000	45.81	---	56.00	10.19	L1	9.7
3.088000	---	31.39	46.00	14.61	L1	9.8
3.160000	44.34	---	56.00	11.66	L1	9.8

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.468500	40.95	---	56.54	15.59	200.0	9.000	L1	9.7
0.476500	---	32.63	46.40	13.77	200.0	9.000	L1	9.7
0.526500	---	39.83	46.00	6.17	200.0	9.000	L1	9.7
0.538500	43.52	---	56.00	12.48	200.0	9.000	L1	9.7

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Video play with 1KHz
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.430000	---	25.82	47.25	21.44	N	9.7
0.434000	42.77	---	57.18	14.41	N	9.7
0.522500	---	32.97	46.00	13.03	N	9.7
0.526500	50.52	---	56.00	5.48	N	9.7
0.984000	39.87	---	56.00	16.13	N	9.7
1.000000	---	24.06	46.00	21.94	N	9.7
1.504000	---	22.66	46.00	23.34	N	9.7
1.508000	39.76	---	56.00	16.24	N	9.7
2.240000	---	21.63	46.00	24.37	N	9.7
2.288000	37.41	---	56.00	18.59	N	9.7
2.940000	---	21.45	46.00	24.55	N	9.8
2.940000	38.11	---	56.00	17.89	N	9.8


Final Result

Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.522500	---	32.59	46.00	13.41	200.0	9.000	N	9.7
0.526500	40.69	---	56.00	15.31	200.0	9.000	N	9.7

Bluetooth link (with adapter)

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Bluetooth link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.194000	---	32.30	53.86	21.56	L1	9.6
0.194000	41.16	---	63.86	22.71	L1	9.6
0.302000	40.35	---	60.19	19.84	L1	9.6
0.306000	---	29.64	50.08	20.43	L1	9.6
0.506500	50.06	---	56.00	5.94	L1	9.7
0.526500	---	38.56	46.00	7.44	L1	9.7
0.606500	44.62	---	56.00	11.38	L1	9.7
0.629500	---	33.11	46.00	12.89	L1	9.7
1.006500	43.38	---	56.00	12.62	L1	9.7
1.022500	---	32.36	46.00	13.64	L1	9.7
1.844000	43.14	---	56.00	12.86	L1	9.7
1.856000	---	31.36	46.00	14.64	L1	9.7

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.506500	37.43	---	56.00	18.57	200.0	9.000	L1	9.7
0.526500	---	37.21	46.00	8.79	200.0	9.000	L1	9.7

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Bluetooth link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.326000	---	26.01	49.55	23.55	N	9.7
0.326000	43.98	---	59.55	15.57	N	9.7
0.508000	48.90	---	56.00	7.10	N	9.7
0.512000	---	32.55	46.00	13.45	N	9.7
0.688000	---	27.42	46.00	18.58	N	9.7
0.700000	44.36	---	56.00	11.64	N	9.7
1.172000	43.06	---	56.00	12.94	N	9.7
1.188000	---	24.15	46.00	21.85	N	9.7
1.736000	---	24.28	46.00	21.72	N	9.7
1.816000	42.74	---	56.00	13.26	N	9.7
2.720000	43.49	---	56.00	12.51	N	9.8
2.836000	---	24.19	46.00	21.81	N	9.8


Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.508000	40.84	---	56.00	15.16	200.0	9.000	N	9.7
0.512000	---	33.09	46.00	12.91	200.0	9.000	N	9.7

Wi-Fi link (with adapter)

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: WiFi Link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.226000	---	29.09	52.60	23.50	L1	9.6
0.230000	37.96	---	62.45	24.49	L1	9.6
0.362000	40.71	---	58.68	17.97	L1	9.7
0.374000	---	29.24	48.41	19.17	L1	9.7
0.510500	---	38.07	46.00	7.93	L1	9.7
0.524000	48.07	---	56.00	7.93	L1	9.7
0.768000	41.15	---	56.00	14.85	L1	9.7
0.800000	---	29.72	46.00	16.28	L1	9.7
1.356000	39.34	---	56.00	16.66	L1	9.7
1.360000	---	27.66	46.00	18.34	L1	9.7
1.868000	---	27.78	46.00	18.22	L1	9.7
1.892000	38.81	---	56.00	17.19	L1	9.7

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.510500	---	30.43	46.00	15.57	200.0	9.000	L1	9.7
0.524000	31.71	---	56.00	24.29	200.0	9.000	L1	9.7

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: WiFi Link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.342000	---	26.19	49.16	22.97	N	9.7
0.366000	42.54	---	58.59	16.05	N	9.7
0.512000	---	32.29	46.00	13.71	N	9.7
0.512000	49.75	---	56.00	6.25	N	9.7
0.708000	44.65	---	56.00	11.35	N	9.7
0.716000	---	26.60	46.00	19.40	N	9.7
1.056000	---	24.94	46.00	21.06	N	9.7
1.204000	43.80	---	56.00	12.20	N	9.7
1.660000	43.32	---	56.00	12.68	N	9.7
1.712000	---	24.46	46.00	21.54	N	9.7
2.168000	42.51	---	56.00	13.49	N	9.7
2.176000	---	23.26	46.00	22.74	N	9.7


Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.512000	---	32.10	46.00	13.90	200.0	9.000	N	9.7
0.512000	39.82	---	56.00	16.18	200.0	9.000	N	9.7

2G/3G/4G link (with adapter)

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: 2G/3G/4G link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.418000	39.57	---	57.49	17.92	L1	9.7
0.426000	---	32.23	47.33	15.10	L1	9.7
0.446000	42.15	---	56.95	14.80	L1	9.7
0.500000	---	31.31	46.00	14.69	L1	9.7
0.512000	46.27	---	56.00	9.73	L1	9.7
0.516000	---	37.59	46.00	8.41	L1	9.7
0.984000	---	29.52	46.00	16.48	L1	9.7
0.984000	38.80	---	56.00	17.20	L1	9.7
1.684000	---	25.95	46.00	20.05	L1	9.7
1.776000	35.18	---	56.00	20.82	L1	9.7
2.380000	34.98	---	56.00	21.02	L1	9.7
2.480000	---	25.38	46.00	20.62	L1	9.8

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: 2G/3G/4G link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.366000	---	25.53	48.59	23.07	N	9.7
0.494000	46.51	---	56.10	9.59	N	9.7
0.500000	---	29.74	46.00	16.26	N	9.7
0.516000	48.87	---	56.00	7.13	N	9.7
0.516000	---	32.86	46.00	13.14	N	9.7
0.760000	43.14	---	56.00	12.86	N	9.7
0.788000	---	25.99	46.00	20.01	N	9.7
1.368000	---	23.86	46.00	22.14	N	9.7
1.376000	42.69	---	56.00	13.31	N	9.7
1.780000	41.85	---	56.00	14.15	N	9.7
2.416000	41.07	---	56.00	14.93	N	9.8
2.436000	---	23.16	46.00	22.84	N	9.8

Print (with adapter)

EUT Information

EUT Name: Android POS
 Order No.: 168279564
 Model: APOLLO
 Test Mode: Print
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: SR1




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.500000	40.95	---	56.00	15.05	L1	9.7
0.500000	---	31.77	46.00	14.23	L1	9.7
0.524000	49.65	---	56.00	6.35	L1	9.7
0.524000	---	38.49	46.00	7.51	L1	9.7
1.044000	---	31.31	46.00	14.69	L1	9.7
1.048000	42.68	---	56.00	13.32	L1	9.7
1.920000	42.38	---	56.00	13.62	L1	9.7
1.940000	---	29.85	46.00	16.15	L1	9.7
2.864000	---	29.04	46.00	16.96	L1	9.8
2.948000	41.33	---	56.00	14.67	L1	9.8
3.788000	40.28	---	56.00	15.72	L1	9.8
3.816000	---	28.31	46.00	17.69	L1	9.8

EUT Information

EUT Name: Android POS
Order No.: 168279564
Model: APOLLO
Test Mode: Print
Test Voltage: AC 120V/60Hz
Test By: Tom Guo
Review By: Gary Chen
Remark: SR1



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Line	Corr. (dB)
0.430000	40.22	---	57.25	17.03	N	9.7
0.430000	---	17.14	47.25	30.12	N	9.7
0.490000	36.69	---	56.17	19.48	N	9.7
0.500000	---	17.52	46.00	28.48	N	9.7
0.504000	36.79	---	56.00	19.21	N	9.7
0.512000	---	18.06	46.00	27.94	N	9.7
0.636000	39.81	---	56.00	16.19	N	9.7
0.772000	---	15.33	46.00	30.67	N	9.7
1.412000	35.31	---	56.00	20.69	N	9.7
1.688000	35.83	---	56.00	20.17	N	9.7
2.916000	---	15.64	46.00	30.36	N	9.8
4.868000	---	16.17	46.00	29.83	N	9.9

Appendix B.2: Test Plots of Radiated Emission, Below 1GHz

SD Data transfer with PC

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	SD Data transfer with PC
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
63.465000	28.87	40.00	11.13	200.0	H	192.0	20
120.792000	27.22	43.50	16.28	200.0	H	0.0	19
221.963000	30.13	46.00	15.87	100.0	H	350.0	19
240.005000	36.25	46.00	9.75	100.0	H	7.0	19
403.159000	31.73	46.00	14.27	100.0	H	260.0	23
979.048000	34.16	54.00	19.84	100.0	H	0.0	32

EUT Information

EUT Name: Android POS
Model: APOLLO
Order No: 168279564
Test Mode: SD Data transfer with PC
Test Voltage: AC 120V/60Hz
Test By: Tom Guo
Review By: Gary Chen
Remark: 3m Chamber



Critical Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
63.659000	27.91	40.00	12.09	100.0	V	24.0	20
155.421000	32.07	43.50	11.43	100.0	V	176.0	21
240.025000	47.94	46.00	-1.94	264.0	V	71.0	19
258.920000	28.87	46.00	17.13	100.0	V	288.0	20
409.561000	31.16	46.00	14.84	200.0	V	15.0	24
720.058000	42.64	46.00	3.36	100.0	V	184.0	29

Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
240.025000	43.67	46.00	2.33	1000.0	120.000	264.0	V	71.0	19

EUT Information

EUT Name: Android POS
Model: APOLLO
Order No: 168279564
Test Mode: Front camera on
Test Voltage: AC 120V/60Hz
Test By: Tom Guo
Review By: Gary Chen
Remark: 3m Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.716000	38.17	40.00	1.83	136.0	V	312.0	18
47.266000	31.82	40.00	8.18	100.0	V	273.0	21
78.791000	24.97	40.00	15.03	100.0	V	310.0	16
167.934000	27.16	43.50	16.34	100.0	V	254.0	22
311.979000	29.95	46.00	16.05	200.0	V	261.0	22
359.994000	29.67	46.00	16.33	200.0	V	28.0	23


Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.716000	30.72	40.00	9.28	1000.0	120.000	136.0	V	312.0	18

Rear camera on with LED on (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Rear camera on with LED on
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.094000	30.56	40.00	9.44	137.0	V	331.0	18
38.536000	35.02	40.00	4.98	100.0	V	108.0	19
46.878000	30.09	40.00	9.91	100.0	V	20.0	21
170.262000	26.51	43.50	16.99	100.0	V	226.0	22
408.009000	36.29	46.00	9.71	200.0	V	177.0	24
621.991000	35.13	46.00	10.87	100.0	V	156.0	27

Final_Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.094000	22.46	40.00	17.54	1000.0	120.000	137.0	V	331.0	18

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Rear camera on with LED on
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
33.027000	31.22	40.00	8.78	100.0	V	165.0	18
47.363000	31.18	40.00	8.82	100.0	V	294.0	21
75.008000	24.81	40.00	15.19	100.0	V	215.0	17
164.636000	23.79	43.50	19.71	100.0	V	230.0	21
408.009000	34.27	46.00	11.73	200.0	V	180.0	24
621.991000	35.80	46.00	10.20	100.0	V	144.0	27


Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
33.027000	19.36	40.00	20.64	1000.0	120.000	100.0	V	165.0	18

Video play with 1KHz (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Video play with 1KHz
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
203.727000	29.56	43.50	13.94	100.0	H	228.0	17
621.991000	33.42	46.00	12.58	100.0	H	257.0	27
164.636000	27.35	43.50	16.15	100.0	H	274.0	21
409.561000	31.33	46.00	14.67	100.0	H	278.0	24
60.652000	20.07	40.00	19.93	200.0	H	173.0	21
45.811000	19.33	40.00	20.67	200.0	H	272.0	21

EUT Information

EUT Name: Android POS
Model: APOLLO
Order No: 168279564
Test Mode: Video play with 1KHz
Test Voltage: AC 120V/60Hz
Test By: Tom Guo
Review By: Gary Chen
Remark: 3m Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
36.947000	35.05	40.00	6.72	106.0	V	163.0	19
85.193000	24.77	40.00	15.23	100.0	V	317.0	15
138.931000	24.95	43.50	18.55	100.0	V	294.0	20
153.966000	25.42	43.50	18.08	100.0	V	0.0	21
570.193000	32.25	46.00	13.75	100.0	V	189.0	26
621.991000	36.82	46.00	9.18	100.0	V	167.0	27


Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
36.947000	29.73	40.00	10.27	1000.0	120.000	106.0	V	163.0	19

Bluetooth link (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Bluetooth link
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
931.130000	32.53	46.00	13.47	100.0	H	78.0	32
57.451000	19.21	40.00	20.79	100.0	H	133.0	21
187.237000	24.56	43.50	18.94	100.0	H	245.0	18
409.561000	31.69	46.00	14.31	100.0	H	272.0	24
154.257000	22.34	43.50	21.16	200.0	H	76.0	21
51.146000	19.75	40.00	20.25	200.0	H	242.0	21

EUT Information

EUT Name: Android POS
Model: APOLLO
Order No: 168279564
Test Mode: Bluetooth link
Test Voltage: AC 120V/60Hz
Test By: Tom Guo
Review By: Gary Chen
Remark: 3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
153.675000	24.91	43.50	18.59	100.0	V	20.0	21
466.500000	29.23	46.00	16.77	100.0	V	135.0	25
621.991000	34.78	46.00	11.22	100.0	V	186.0	27
177.828000	23.53	43.50	19.97	100.0	V	242.0	20
57.451000	23.92	40.00	16.08	100.0	V	286.0	21
38.245000	31.76	40.00	8.24	200.0	V	275.0	19

Wi-Fi link (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	WIFI link
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
621.991000	33.12	46.00	12.88	100.0	H	254.0	27
403.159000	34.23	46.00	11.77	100.0	H	292.0	23
58.130000	20.70	40.00	19.30	200.0	H	0.0	21
178.798000	24.66	43.50	18.84	200.0	H	92.0	20
47.945000	19.24	40.00	20.76	200.0	H	140.0	21
168.710000	24.14	43.50	19.36	200.0	H	292.0	22

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	WIFI link
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
178.119000	21.47	43.50	22.03	100.0	V	273.0	20
34.171000	28.63	40.00	11.37	100.0	V	295.0	18
170.844000	23.48	43.50	20.02	100.0	V	355.0	22
941.703000	32.58	46.00	13.42	200.0	V	25.0	32
399.958000	27.20	46.00	18.80	200.0	V	214.0	23
73.553000	22.48	40.00	17.52	200.0	V	316.0	17

2G/3G/4G link (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564 60
Test Mode:	4G Link
Test Voltage:	AC 120V/60Hz
Test By:	Shower Dai
Review By:	Gary Chen
Remark:	3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
45.326000	20.49	40.00	19.51	100.0	H	240.0	21
86.745000	20.39	40.00	19.61	200.0	H	15.0	15
198.489000	28.14	43.50	15.36	200.0	H	4.0	17
229.044000	26.23	46.00	19.77	100.0	H	36.0	19
399.958000	32.76	46.00	13.24	100.0	H	130.0	23
570.193000	30.80	46.00	15.20	200.0	H	139.0	26

EUT Information

EUT Name: Android POS
Model: APOLLO
Order No: 168279564 60
Test Mode: 4G Link
Test Voltage: AC 120V/60Hz
Test By: Shower Dai
Review By: Gary Chen
Remark: 3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
32.328000	22.91	40.00	17.09	100.0	V	317.0	18
38.827000	24.82	40.00	15.18	100.0	V	0.0	19
47.848000	22.90	40.00	17.10	200.0	V	142.0	21
158.525000	23.00	43.50	20.50	100.0	V	203.0	22
390.355000	28.14	46.00	17.86	100.0	V	62.0	23
635.765000	29.79	46.00	16.21	300.0	V	84.0	28

Print (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Print
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.490000	20.15	40.00	19.85	100.0	H	70.0	21
390.355000	31.70	46.00	14.30	100.0	H	112.0	23
57.160000	19.80	40.00	20.20	100.0	H	209.0	21
308.390000	29.06	46.00	16.94	100.0	H	358.0	22
160.465000	24.18	43.50	19.32	200.0	H	66.0	22
958.484000	32.53	46.00	13.47	200.0	H	160.0	32

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Print
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
136.118000	26.78	43.50	16.72	100.0	V	60.0	20
55.317000	23.70	40.00	16.30	100.0	V	76.0	21
33.977000	32.18	40.00	7.82	100.0	V	84.0	18
182.096000	22.00	43.50	21.50	100.0	V	84.0	19
466.500000	27.19	46.00	18.81	100.0	V	99.0	25
621.991000	36.72	46.00	9.28	100.0	V	161.0	27


Appendix B.3: Test Plots of Radiated Emission, Above 1GHz

Refer to radio report for test data above 6GHz.

SD Data transfer with PC

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	SD Data transfer with PC
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1200.000000	---	34.27	54.00	19.73	100.0	H	53.0	-14
1200.000000	35.61	---	74.00	38.39	100.0	H	53.0	-14
1666.000000	---	34.08	54.00	19.92	100.0	H	230.0	-10
1666.000000	35.01	---	74.00	38.99	100.0	H	230.0	-10
2073.500000	---	34.19	54.00	19.81	100.0	H	352.0	-7
2073.500000	35.15	---	74.00	38.85	100.0	H	352.0	-7
2655.500000	---	37.86	54.00	16.14	200.0	H	351.0	-3
2656.500000	39.43	---	74.00	34.57	100.0	H	252.0	-3
3390.500000	---	38.96	54.00	15.04	100.0	H	65.0	-2
3390.500000	40.69	---	74.00	33.31	100.0	H	65.0	-2
4382.000000	---	40.64	54.00	13.36	200.0	H	289.0	2
4382.000000	41.90	---	74.00	32.10	200.0	H	289.0	2

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: SD Data transfer with PC
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1665.000000	---	32.79	54.00	21.21	100.0	V	356.0	-10
1665.000000	35.16	---	74.00	38.84	100.0	V	356.0	-10
1777.500000	---	33.50	54.00	20.50	100.0	V	163.0	-10
1777.500000	35.75	---	74.00	38.25	100.0	V	163.0	-10
2322.000000	---	39.23	54.00	14.77	100.0	V	55.0	-6
2322.000000	40.33	---	74.00	33.67	100.0	V	55.0	-6
2664.000000	---	40.80	54.00	13.20	100.0	V	91.0	-3
2664.000000	41.71	---	74.00	32.29	100.0	V	91.0	-3
3626.000000	---	39.19	54.00	14.81	100.0	V	215.0	0
3626.000000	41.26	---	74.00	32.74	100.0	V	215.0	0
4210.500000	---	40.91	54.00	13.09	200.0	V	183.0	1
4210.500000	42.70	---	74.00	31.30	200.0	V	183.0	1

Front camera on (with adapter)

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: Front camera on
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1101.500000	---	31.03	54.00	22.97	200.0	H	341.0	-12
1101.500000	32.19	---	74.00	41.81	200.0	H	341.0	-12
2036.000000	---	32.71	54.00	21.29	200.0	H	71.0	-7
2036.000000	35.88	---	74.00	38.12	200.0	H	71.0	-7
2719.000000	---	38.78	54.00	15.22	100.0	H	44.0	-3
2719.000000	39.82	---	74.00	34.18	100.0	H	44.0	-3
3257.000000	---	38.60	54.00	15.40	200.0	H	8.0	-2
3257.000000	40.17	---	74.00	33.83	200.0	H	8.0	-2
3726.000000	---	39.48	54.00	14.52	200.0	H	269.0	0
3726.000000	40.99	---	74.00	33.01	200.0	H	269.0	0
4342.000000	---	41.16	54.00	12.84	200.0	H	19.0	2
4342.000000	41.91	---	74.00	32.09	200.0	H	19.0	2

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: Front camera on
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1128.000000	---	33.70	54.00	20.30	100.0	V	15.0	-13
1128.000000	34.21	---	74.00	39.79	100.0	V	15.0	-13
1176.000000	---	34.90	54.00	19.10	100.0	V	124.0	-14
1176.000000	35.15	---	74.00	38.85	200.0	V	112.0	-14
1224.000000	---	35.65	54.00	18.35	200.0	V	127.0	-14
1224.000000	36.09	---	74.00	37.91	200.0	V	127.0	-14
2607.000000	---	37.37	54.00	16.63	200.0	V	224.0	-4
2607.000000	39.15	---	74.00	34.85	200.0	V	224.0	-4
3676.000000	41.47	---	74.00	32.53	100.0	V	1.0	0
3678.000000	---	37.95	54.00	16.05	100.0	V	175.0	0
4356.500000	---	40.75	54.00	13.25	200.0	V	183.0	2
4356.500000	42.25	---	74.00	31.75	200.0	V	183.0	2

Rear camera on with LED on (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Rear camera on with LED on
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1080.000000	---	32.79	54.00	21.21	200.0	H	211.0	-13
1080.000000	33.64	---	74.00	40.36	200.0	H	211.0	-13
1128.000000	---	32.88	54.00	21.12	100.0	H	224.0	-13
1128.000000	33.12	---	74.00	40.88	100.0	H	224.0	-13
1909.500000	---	33.45	54.00	20.55	100.0	H	248.0	-8
1909.500000	34.10	---	74.00	39.90	100.0	H	248.0	-8
2579.000000	---	37.49	54.00	16.51	200.0	H	92.0	-4
2579.000000	38.83	---	74.00	35.17	200.0	H	92.0	-4
3503.000000	---	38.89	54.00	15.11	200.0	H	326.0	-1
3503.000000	40.44	---	74.00	33.56	200.0	H	326.0	-1
4332.000000	---	41.69	54.00	12.31	200.0	H	101.0	2
4332.000000	42.92	---	74.00	31.08	200.0	H	101.0	2

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: Rear camera on with LED on
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1080.000000	---	33.21	54.00	20.79	100.0	V	180.0	-13
1080.000000	34.28	---	74.00	39.72	100.0	V	180.0	-13
1128.000000	---	33.28	54.00	20.72	100.0	V	194.0	-13
1128.000000	34.07	---	74.00	39.93	100.0	V	194.0	-13
1451.500000	---	31.77	54.00	22.23	100.0	V	309.0	-13
1451.500000	32.68	---	74.00	41.32	100.0	V	309.0	-13
1997.000000	---	33.76	54.00	20.24	200.0	V	0.0	-7
1997.000000	35.39	---	74.00	38.61	200.0	V	0.0	-7
2710.000000	---	38.40	54.00	15.60	100.0	V	143.0	-3
2710.000000	39.88	---	74.00	34.12	100.0	V	143.0	-3
4469.000000	---	42.12	54.00	11.88	100.0	V	0.0	2
4469.000000	43.62	---	74.00	30.38	100.0	V	0.0	2

Video play with 1KHz (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	Video play with 1KHz
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1091.000000	---	30.31	54.00	23.69	200.0	H	329.0	-13
1091.000000	30.98	---	74.00	43.02	200.0	H	329.0	-13
1451.500000	---	32.31	54.00	21.69	100.0	H	45.0	-13
1451.500000	33.81	---	74.00	40.19	100.0	H	45.0	-13
1816.000000	---	33.41	54.00	20.59	200.0	H	244.0	-9
1816.000000	34.77	---	74.00	39.23	200.0	H	244.0	-9
2707.500000	---	37.74	54.00	16.26	100.0	H	293.0	-3
2707.500000	38.86	---	74.00	35.14	100.0	H	293.0	-3
3668.000000	---	39.99	54.00	14.01	200.0	H	106.0	0
3668.000000	41.33	---	74.00	32.67	200.0	H	106.0	0
4330.500000	---	40.45	54.00	13.55	200.0	H	244.0	2
4330.500000	42.47	---	74.00	31.53	200.0	H	244.0	2

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: Video play with 1KHz
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1087.500000	---	26.75	54.00	27.25	100.0	V	257.0	-13
1087.500000	30.34	---	74.00	43.66	100.0	V	257.0	-13
1451.500000	---	32.91	54.00	21.09	100.0	V	154.0	-13
1451.500000	33.58	---	74.00	40.42	100.0	V	154.0	-13
2068.000000	35.54	---	74.00	38.46	200.0	V	295.0	-7
2069.000000	---	32.67	54.00	21.33	200.0	V	68.0	-7
3049.500000	---	38.21	54.00	15.79	100.0	V	346.0	-3
3049.500000	39.19	---	74.00	34.81	100.0	V	346.0	-3
3662.500000	---	39.93	54.00	14.07	100.0	V	223.0	0
3662.500000	41.01	---	74.00	32.99	100.0	V	223.0	0
4321.500000	41.77	---	74.00	32.23	200.0	V	223.0	2
4322.000000	---	40.41	54.00	13.59	200.0	V	87.0	2

Bluetooth link (with adapter)

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: Bluetooth link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1105.000000	---	28.66	54.00	25.34	100.0	H	48.0	-12
1105.000000	31.11	---	74.00	42.89	100.0	H	48.0	-12
1451.500000	---	32.41	54.00	21.59	100.0	H	194.0	-13
1451.500000	33.74	---	74.00	40.26	100.0	H	194.0	-13
1984.500000	---	33.95	54.00	20.05	100.0	H	309.0	-8
1984.500000	34.87	---	74.00	39.13	100.0	H	309.0	-8
2707.000000	---	37.87	54.00	16.13	100.0	H	88.0	-3
2707.000000	39.30	---	74.00	34.70	100.0	H	88.0	-3
3663.000000	---	39.13	54.00	14.87	100.0	H	231.0	0
3663.000000	40.41	---	74.00	33.59	100.0	H	231.0	0
4308.500000	42.33	---	74.00	31.67	200.0	H	327.0	2
4308.500000	---	41.21	54.00	12.79	200.0	H	327.0	2

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: Bluetooth link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1125.500000	---	29.81	54.00	24.19	200.0	V	118.0	-13
1125.500000	30.80	---	74.00	43.20	200.0	V	118.0	-13
1971.000000	---	35.62	54.00	18.38	100.0	V	336.0	-8
1971.000000	36.97	---	74.00	37.03	100.0	V	336.0	-8
2724.500000	---	38.37	54.00	15.63	200.0	V	323.0	-3
2724.500000	39.83	---	74.00	34.17	200.0	V	323.0	-3
3711.500000	---	39.69	54.00	14.31	200.0	V	177.0	0
3711.500000	40.21	---	74.00	33.79	200.0	V	177.0	0
4215.000000	---	40.30	54.00	13.70	200.0	V	228.0	1
4215.000000	41.40	---	74.00	32.60	200.0	V	228.0	1
4751.000000	---	41.76	54.00	12.24	200.0	V	346.0	3
4751.000000	42.80	---	74.00	31.20	200.0	V	346.0	3

Wi-Fi link (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564
Test Mode:	WIFI link
Test Voltage:	AC 120V/60Hz
Test By:	Tom Guo
Review By:	Gary Chen
Remark:	3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1080.500000	---	30.38	54.00	23.62	200.0	H	271.0	-13
1080.500000	30.88	---	74.00	43.12	200.0	H	271.0	-13
1294.500000	---	28.38	54.00	25.62	200.0	H	238.0	-14
1295.000000	30.79	---	74.00	43.21	200.0	H	238.0	-14
1844.000000	---	34.62	54.00	19.38	200.0	H	87.0	-9
1844.000000	35.42	---	74.00	38.58	200.0	H	87.0	-9
2727.500000	---	38.07	54.00	15.93	100.0	H	101.0	-3
2727.500000	39.12	---	74.00	34.88	100.0	H	101.0	-3
3756.500000	40.89	---	74.00	33.11	200.0	H	14.0	0
3757.000000	---	39.47	54.00	14.53	200.0	H	14.0	0
4311.500000	---	41.64	54.00	12.36	200.0	H	4.0	2
4311.500000	42.54	---	74.00	31.46	200.0	H	4.0	2

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564
 Test Mode: WIFI link
 Test Voltage: AC 120V/60Hz
 Test By: Tom Guo
 Review By: Gary Chen
 Remark: 3m Chamber




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1451.500000	---	33.41	54.00	20.59	100.0	V	178.0	-13
1451.500000	33.76	---	74.00	40.24	100.0	V	178.0	-13
1921.000000	---	33.89	54.00	20.11	200.0	V	170.0	-8
1921.000000	37.34	---	74.00	36.66	200.0	V	170.0	-8
2706.500000	---	37.16	54.00	16.84	200.0	V	320.0	-3
2706.500000	39.45	---	74.00	34.55	200.0	V	320.0	-3
3499.500000	---	38.92	54.00	15.08	200.0	V	316.0	-1
3499.500000	40.25	---	74.00	33.75	200.0	V	316.0	-1
4640.500000	---	41.51	54.00	12.49	200.0	V	25.0	2
4640.500000	42.00	---	74.00	32.00	200.0	V	25.0	2
5533.000000	---	45.08	54.00	8.92	100.0	V	335.0	1
5533.000000	46.44	---	74.00	27.56	100.0	V	335.0	1

2G/3G/4G link (with adapter)

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564 60
 Test Mode: 4G Link
 Test Voltage: AC 120V/60Hz
 Test By: Shower Dai
 Review By: Gary Chen
 Remark: 3m Chamber
 Note: Over the limit is fundamental and spurious emissions of license radio




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1645.500000	---	43.13	54.00	10.87	100.0	H	217.0	-10
1645.500000	45.00	---	74.00	29.00	100.0	H	217.0	-10
1946.500000	78.50	---	---	---	200.0	H	295.0	-8
1946.500000	---	75.80	---	---	200.0	H	295.0	-8
2143.500000	50.39	---	74.00	23.61	100.0	H	29.0	-8
2143.500000	---	48.27	54.00	5.73	100.0	H	29.0	-8
2681.000000	47.20	---	74.00	26.80	100.0	H	199.0	-3
2682.000000	---	45.20	54.00	8.80	100.0	H	194.0	-3
3897.000000	77.98	---	---	---	100.0	H	185.0	0
3897.000000	---	75.73	---	---	100.0	H	185.0	0
5848.500000	---	61.26	---	---	100.0	H	208.0	1
5848.500000	63.27	---	---	---	100.0	H	208.0	1

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564 60
 Test Mode: 4G Link
 Test Voltage: AC 120V/60Hz
 Test By: Shower Dai
 Review By: Gary Chen
 Remark: 3m Chamber
 Note: Over the limit is fundamental and spurious emissions of license radio




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1250.000000	---	40.50	54.00	13.50	100.0	V	270.0	-14
1250.000000	41.28	---	74.00	32.72	100.0	V	270.0	-14
1945.000000	---	72.56	---	---	200.0	V	3.0	-8
1945.000000	75.61	---	---	---	200.0	V	3.0	-8
2138.000000	---	37.50	54.00	16.50	200.0	V	228.0	-8
2138.500000	45.60	---	74.00	28.40	200.0	V	57.0	-8
2620.500000	---	41.75	54.00	12.25	200.0	V	0.0	-4
2620.500000	44.39	---	74.00	29.61	200.0	V	0.0	-4
3898.500000	---	68.21	---	---	100.0	V	354.0	0
3898.500000	74.10	---	---	---	200.0	V	18.0	0
5851.500000	---	74.97	---	---	200.0	V	18.0	1
5851.500000	80.80	---	---	---	200.0	V	18.0	1

Print (with adapter)

EUT Information

EUT Name:	Android POS
Model	APOLLO
Order No:	168279564 60
Test Mode:	Print
Test Voltage:	AC 120V/60Hz
Test By:	Shower Dai
Review By:	Gary Chen
Remark:	3m Chamber




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1111.000000	---	29.16	54.00	24.84	100.0	H	80.0	-12
1111.000000	31.24	---	74.00	42.76	100.0	H	80.0	-12
1451.500000	---	31.06	54.00	22.94	100.0	H	244.0	-13
1451.500000	32.12	---	74.00	41.88	100.0	H	244.0	-13
2588.000000	---	38.04	54.00	15.96	100.0	H	18.0	-4
2588.000000	39.30	---	74.00	34.70	100.0	H	18.0	-4
3241.000000	---	37.14	54.00	16.86	200.0	H	136.0	-2
3241.000000	40.23	---	74.00	33.77	200.0	H	136.0	-2
4282.000000	43.65	---	74.00	30.35	100.0	H	0.0	2
4282.500000	---	40.85	54.00	13.15	100.0	H	0.0	2
4689.500000	43.00	---	74.00	31.00	200.0	H	190.0	3
4691.500000	---	40.83	54.00	13.17	200.0	H	141.0	3

EUT Information

EUT Name: Android POS
 Model: APOLLO
 Order No: 168279564 60
 Test Mode: Print
 Test Voltage: AC 120V/60Hz
 Test By: Shower Dai
 Review By: Gary Chen
 Remark: 3m Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1451.500000	---	33.57	54.00	20.43	100.0	V	224.0	-13
1451.500000	34.08	---	74.00	39.92	100.0	V	224.0	-13
2239.500000	---	35.43	54.00	18.57	100.0	V	61.0	-7
2239.500000	36.97	---	74.00	37.03	100.0	V	61.0	-7
2475.500000	---	37.35	54.00	16.65	200.0	V	161.0	-5
2475.500000	39.05	---	74.00	34.95	200.0	V	161.0	-5
4133.500000	---	40.22	54.00	13.78	100.0	V	251.0	1
4133.500000	41.23	---	74.00	32.77	100.0	V	251.0	1
4799.000000	---	41.07	54.00	12.93	200.0	V	190.0	2
4799.000000	41.99	---	74.00	32.01	200.0	V	190.0	2
5797.000000	---	39.87	54.00	14.13	100.0	V	129.0	1
5797.000000	42.30	---	74.00	31.70	100.0	V	129.0	1