

Table of Contents

1.	RADIATED SPURIOUS EMISSIONS	2
1.1	WiFi, 5GHz, BLEOW 1GHz.....	2
1.2	WiFi, 5GHz, 802.11A, ABOVE 1GHz	6
1.3	WiFi, 5GHz, 802.11A, BANDEDGE.....	58
1.4	WiFi, 5GHz, 802.11N-HT20, ABOVE 1GHz	70
1.5	WiFi, 5GHz, 802.11N-HT20, BANDEDGE	122
1.6	WiFi, 5GHz, 802.11N-HT40, ABOVE 1GHz	134
1.7	WiFi, 5GHz, 802.11N-HT40, BANDEDGE	174


1. Radiated Spurious Emissions

1.1 WiFi, 5GHz, bleow 1GHz

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_High Channel
Test Voltage:: 120V/60Hz
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.517500	18.99	---	40.00	21.01	100.0	H	316.0	-21.2
243.739500	24.42	---	46.00	21.58	100.0	H	203.0	-17.9
409.609500	30.18	---	46.00	15.82	100.0	H	126.0	-13.9
844.800000	35.96	---	46.00	10.04	100.0	H	297.0	-6.0

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_High Channel
Test Voltage:: 120V/60Hz
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.469000	20.28	---	40.00	19.72	100.0	V	291.0	-21.3
55.462500	28.68	---	40.00	11.32	100.0	V	236.0	-18.8
710.697500	36.00	---	46.00	10.00	100.0	V	0.0	-8.2
844.848500	37.99	---	46.00	8.01	100.0	V	115.0	-6.0

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Low Channel
Test Voltage:: 120V/60Hz
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
166.673000	21.14	---	43.50	22.36	100.0	H	293.0	-21.7
244.224500	24.03	---	46.00	21.97	100.0	H	22.0	-17.9
403.207500	27.43	---	46.00	18.57	100.0	H	92.0	-14.0
844.897000	36.95	---	46.00	9.05	100.0	H	76.0	-6.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Low Channel
Test Voltage::	120V/60Hz
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
49.060500	26.61	---	40.00	13.39	100.0	V	211.0	-18.6
71.710000	25.47	---	40.00	14.53	100.0	V	279.0	-22.7
845.673000	36.87	---	46.00	9.13	100.0	V	18.0	-6.0

1.2 WiFi, 5GHz, 802.11a, above 1GHz

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch36
Test Voltage:: Battery
Remark: Temp 23 Humi:42%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	---	49.53	54.00	4.47	100.0	H	39.0	10.1
4000.500000	55.01	---	74.00	18.99	100.0	H	90.0	10.1
4499.500000	54.38	---	74.00	19.62	100.0	H	321.0	13.7
4499.500000	---	47.93	54.00	6.07	100.0	H	321.0	13.7
5000.000000	53.42	---	74.00	20.58	100.0	H	4.0	13.1
5000.000000	---	45.18	54.00	8.82	100.0	H	4.0	13.1
5500.000000	53.56	---	74.00	20.44	100.0	H	36.0	14.3
5500.000000	---	47.55	54.00	6.45	100.0	H	36.0	14.3
6000.000000	---	50.24	54.00	3.76	100.0	H	187.0	15.7
6000.500000	55.33	---	74.00	18.67	100.0	H	142.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch36
Test Voltage:: Battery
Remark: Temp 23 Humi:42%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2499.825000	51.72	---	74.00	22.28	100.0	V	357.0	7.4
2500.037500	---	45.19	54.00	8.81	100.0	V	0.0	7.4
3999.862500	55.43	---	74.00	18.57	100.0	V	329.0	10.1
4000.075000	---	49.80	54.00	4.20	100.0	V	329.0	10.1
6000.000000	56.74	---	74.00	17.26	100.0	V	28.0	15.7
6000.500000	---	49.70	54.00	4.30	100.0	V	28.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch40
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	53.74	---	74.00	20.26	100.0	H	358.0	10.1
4000.075000	---	46.21	54.00	7.79	100.0	H	358.0	10.1
5000.000000	52.53	---	74.00	21.47	100.0	H	4.0	13.1
5000.000000	---	43.77	54.00	10.23	100.0	H	4.0	13.1
6000.000000	---	48.64	54.00	5.36	100.0	H	205.0	15.7
6000.500000	57.54	---	74.00	16.46	100.0	H	205.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch40
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	49.27	---	74.00	24.73	100.0	V	0.0	6.0
2000.237500	---	41.60	54.00	12.40	100.0	V	0.0	6.0
2500.037500	50.22	---	74.00	23.78	100.0	V	0.0	7.4
2500.037500	---	43.13	54.00	10.87	100.0	V	0.0	7.4
4000.075000	---	47.01	54.00	6.99	100.0	V	304.0	10.1
4000.287500	54.06	---	74.00	19.94	100.0	V	325.0	10.1
6000.000000	56.57	---	74.00	17.43	100.0	V	345.0	15.7
6000.000000	---	50.22	54.00	3.78	100.0	V	345.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch48
Test Voltage:: Battery
Remark: Temp 23 Humi:42%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4499.500000	55.63	---	74.00	18.37	100.0	H	328.0	13.7
4499.500000	---	50.45	54.00	3.55	100.0	H	328.0	13.7
5500.000000	55.94	---	74.00	18.06	100.0	H	30.0	14.3
5500.000000	---	49.13	54.00	4.87	100.0	H	30.0	14.3
6000.000000	---	50.84	54.00	3.16	100.0	H	216.0	15.7
6000.500000	56.28	---	74.00	17.72	100.0	H	216.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch48
Test Voltage::	Battery
Remark:	Temp 23 Humi:42%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2500.037500	---	45.57	54.00	8.43	100.0	V	0.0	7.4
2500.250000	52.28	---	74.00	21.72	100.0	V	0.0	7.4
4000.075000	---	49.03	54.00	4.97	100.0	V	327.0	10.1
4000.712500	54.60	---	74.00	19.40	100.0	V	327.0	10.1
6000.000000	56.10	---	74.00	17.90	100.0	V	147.0	15.7
6000.000000	---	49.67	54.00	4.33	100.0	V	147.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch52
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4499.500000	---	50.86	54.00	3.14	100.0	H	328.0	13.7
4500.000000	56.52	---	74.00	17.48	100.0	H	328.0	13.7
4999.500000	53.66	---	74.00	20.34	100.0	H	0.0	13.1
5000.000000	---	45.40	54.00	8.60	100.0	H	0.0	13.1
6000.000000	57.79	---	74.00	16.21	100.0	H	30.0	15.7
6000.500000	---	50.64	54.00	3.36	100.0	H	30.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch52
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	49.64	---	74.00	24.36	100.0	V	352.0	6.0
2000.025000	---	44.36	54.00	9.64	100.0	V	358.0	6.0
4000.075000	55.48	---	74.00	18.52	100.0	V	352.0	10.1
4000.287500	---	50.19	54.00	3.81	100.0	V	352.0	10.1
4499.500000	54.26	---	74.00	19.75	100.0	V	36.0	13.7
4500.000000	---	47.90	54.00	6.10	100.0	V	0.0	13.7
5000.000000	53.61	---	74.00	20.39	100.0	V	23.0	13.1
5000.000000	---	45.02	54.00	8.98	100.0	V	23.0	13.1
5500.000000	55.72	---	74.00	18.28	100.0	V	65.0	14.3
5500.000000	---	48.38	54.00	5.62	100.0	V	65.0	14.3
6000.500000	57.05	---	74.00	16.95	100.0	V	327.0	15.7
6000.500000	---	50.99	54.00	3.01	100.0	V	327.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch56
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	53.19	---	74.00	20.81	100.0	H	92.0	10.1
3999.862500	---	46.05	54.00	7.95	100.0	H	92.0	10.1
5000.000000	53.23	---	74.00	20.77	100.0	H	12.0	13.1
5000.000000	---	44.87	54.00	9.13	100.0	H	12.0	13.1
5500.000000	54.36	---	74.00	19.64	100.0	H	27.0	14.3
5500.000000	---	45.50	54.00	8.50	100.0	H	27.0	14.3
6000.000000	56.11	---	74.00	17.89	100.0	H	331.0	15.7
6000.000000	---	50.09	54.00	3.91	100.0	H	331.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch56
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2499.825000	---	43.56	54.00	10.44	100.0	V	358.0	7.4
2500.250000	50.58	---	74.00	23.42	100.0	V	0.0	7.4
4000.075000	---	50.73	54.00	3.27	100.0	V	329.0	10.1
4000.287500	56.07	---	74.00	17.93	100.0	V	329.0	10.1
5000.000000	52.40	---	74.00	21.60	100.0	V	66.0	13.1
5000.000000	---	44.59	54.00	9.41	100.0	V	66.0	13.1
6000.000000	---	49.99	54.00	4.01	100.0	V	66.0	15.7
6000.500000	56.70	---	74.00	17.30	100.0	V	66.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch64
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4499.500000	---	50.84	54.00	3.16	100.0	H	325.0	13.7
4500.000000	55.17	---	74.00	18.83	100.0	H	325.0	13.7
5000.000000	52.99	---	74.00	21.01	100.0	H	162.0	13.1
5000.000000	---	44.63	54.00	9.37	100.0	H	162.0	13.1
6000.000000	57.83	---	74.00	16.17	100.0	H	162.0	15.7
6000.500000	---	50.90	54.00	3.10	100.0	H	0.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch64
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	49.66	---	74.00	24.34	100.0	V	320.0	6.0
2000.025000	---	43.59	54.00	10.41	100.0	V	320.0	6.0
4000.075000	---	48.40	54.00	5.60	100.0	V	45.0	10.1
4000.287500	54.05	---	74.00	19.95	100.0	V	332.0	10.1
4499.500000	---	47.26	54.00	6.74	100.0	V	0.0	13.7
4500.000000	54.16	---	74.00	19.84	100.0	V	358.0	13.7
5500.000000	54.51	---	74.00	19.49	100.0	V	55.0	14.3
5500.000000	---	47.47	54.00	6.53	100.0	V	55.0	14.3
6000.000000	56.97	---	74.00	17.03	100.0	V	55.0	15.7
6000.000000	---	50.26	54.00	3.74	100.0	V	55.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch100
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4499.500000	54.85	---	74.00	19.15	100.0	H	25.0	13.7
4499.500000	---	50.15	54.00	3.85	100.0	H	25.0	13.7
5000.000000	---	44.32	54.00	9.68	100.0	H	5.0	13.1
5000.000000	53.35	---	74.00	20.65	100.0	H	5.0	13.1
6000.000000	---	50.00	54.00	4.00	100.0	H	39.0	15.7
6000.500000	57.02	---	74.00	16.98	100.0	H	0.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch100
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.237500	49.17	---	74.00	24.83	100.0	V	345.0	6.0
2000.237500	---	43.55	54.00	10.45	100.0	V	345.0	6.0
3999.650000	53.43	---	74.00	20.57	100.0	V	282.0	10.1
4000.075000	---	49.19	54.00	4.81	100.0	V	203.0	10.1
6000.000000	55.79	---	74.00	18.21	100.0	V	19.0	15.7
6000.000000	---	50.20	54.00	3.80	100.0	V	19.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch120
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	53.90	---	74.00	20.10	100.0	H	50.0	10.1
4000.075000	---	48.77	54.00	5.23	100.0	H	50.0	10.1
4499.500000	---	49.48	54.00	4.52	100.0	H	24.0	13.7
4500.000000	54.36	---	74.00	19.64	100.0	H	24.0	13.7
6000.000000	56.89	---	74.00	17.11	100.0	H	243.0	15.7
6000.000000	---	50.26	54.00	3.74	100.0	H	243.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch120
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	49.41	---	74.00	24.59	100.0	V	343.0	6.0
2000.025000	---	43.79	54.00	10.21	100.0	V	354.0	6.0
4000.287500	55.18	---	74.00	18.82	100.0	V	333.0	10.1
4000.287500	---	49.52	54.00	4.48	100.0	V	333.0	10.1
5000.000000	53.06	---	74.00	20.94	100.0	V	341.0	13.1
5000.000000	---	43.91	54.00	10.09	100.0	V	341.0	13.1
5500.000000	---	49.72	54.00	4.28	100.0	V	56.0	14.3
5500.500000	56.69	---	74.00	17.31	100.0	V	56.0	14.3
6000.000000	58.46	---	74.00	15.54	100.0	V	56.0	15.7
6000.500000	---	50.91	54.00	3.09	100.0	V	56.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch140
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	---	46.36	54.00	7.64	100.0	H	53.0	10.1
4002.412500	53.26	---	74.00	20.74	100.0	H	262.0	10.1
4499.500000	55.16	---	74.00	18.84	100.0	H	25.0	13.7
4499.500000	---	49.26	54.00	4.74	100.0	H	25.0	13.7
5000.000000	52.88	---	74.00	21.12	100.0	H	6.0	13.1
5000.000000	---	45.40	54.00	8.60	100.0	H	6.0	13.1
6000.500000	---	50.02	54.00	3.98	100.0	H	6.0	15.7
6000.500000	56.48	---	74.00	17.52	100.0	H	6.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	55.37	---	74.00	18.63	100.0	V	333.0	10.1
4000.287500	---	50.80	54.00	3.20	100.0	V	333.0	10.1
4499.500000	54.29	---	74.00	19.71	100.0	V	47.0	13.7
4500.000000	---	46.74	54.00	7.26	100.0	V	47.0	13.7
5500.000000	55.13	---	74.00	18.87	100.0	V	57.0	14.3
5500.000000	---	48.49	54.00	5.51	100.0	V	57.0	14.3
6000.000000	---	49.52	54.00	4.48	100.0	V	57.0	15.7
6000.500000	57.25	---	74.00	16.75	100.0	V	20.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch144
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	---	47.92	54.00	6.08	100.0	H	39.0	10.1
4000.075000	53.87	---	74.00	20.13	100.0	H	39.0	10.1
4999.500000	52.95	---	74.00	21.05	100.0	H	1.0	13.1
5000.000000	---	45.41	54.00	8.59	100.0	H	5.0	13.1
5499.500000	53.79	---	74.00	20.21	100.0	H	332.0	14.3
5500.000000	---	46.21	54.00	7.79	100.0	H	25.0	14.3
6000.000000	---	52.54	54.00	1.46	100.0	H	332.0	15.7
6000.500000	57.88	---	74.00	16.12	100.0	H	332.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch144
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2500.037500	50.02	---	74.00	23.98	100.0	V	357.0	7.4
2500.250000	---	43.24	54.00	10.76	100.0	V	0.0	7.4
3999.437500	54.27	---	74.00	19.73	100.0	V	349.0	10.1
4000.287500	---	47.55	54.00	6.45	100.0	V	297.0	10.1
5000.000000	53.23	---	74.00	20.77	100.0	V	282.0	13.1
5000.000000	---	45.22	54.00	8.78	100.0	V	282.0	13.1
6000.000000	56.70	---	74.00	17.30	100.0	V	67.0	15.7
6000.000000	---	48.31	54.00	5.69	100.0	V	67.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch149
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.287500	---	47.79	54.00	6.21	100.0	H	48.0	10.1
4000.500000	53.38	---	74.00	20.62	100.0	H	48.0	10.1
4999.500000	52.60	---	74.00	21.40	100.0	H	6.0	13.1
5000.000000	---	44.32	54.00	9.68	100.0	H	6.0	13.1
6000.000000	55.54	---	74.00	18.46	100.0	H	321.0	15.7
6000.000000	---	49.70	54.00	4.30	100.0	H	321.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch149
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	---	42.28	54.00	11.72	100.0	V	320.0	6.0
2000.237500	48.20	---	74.00	25.80	100.0	V	1.0	6.0
2499.825000	50.67	---	74.00	23.33	100.0	V	1.0	7.4
2499.825000	---	42.87	54.00	11.13	100.0	V	1.0	7.4
3999.862500	---	47.26	54.00	6.74	100.0	V	1.0	10.1
4000.287500	53.65	---	74.00	20.35	100.0	V	59.0	10.1
6000.000000	---	49.23	54.00	4.77	100.0	V	341.0	15.7
6000.500000	56.26	---	74.00	17.74	100.0	V	314.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch157
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	---	47.16	54.00	6.84	100.0	H	306.0	10.1
4000.500000	53.27	---	74.00	20.73	100.0	H	39.0	10.1
5000.000000	52.09	---	74.00	21.91	100.0	H	4.0	13.1
5000.000000	---	44.69	54.00	9.31	100.0	H	4.0	13.1
5500.000000	53.14	---	74.00	20.86	100.0	H	44.0	14.3
5500.000000	---	46.83	54.00	7.17	100.0	H	44.0	14.3
6000.000000	---	49.57	54.00	4.43	100.0	H	73.0	15.7
6000.000000	56.63	---	74.00	17.37	100.0	H	73.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch157
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.600000	48.17	---	74.00	25.83	100.0	V	358.0	6.0
2000.025000	---	43.15	54.00	10.85	100.0	V	350.0	6.0
3999.862500	---	50.69	54.00	3.31	100.0	V	329.0	10.1
4000.500000	55.05	---	74.00	18.95	100.0	V	329.0	10.1
6000.000000	---	49.82	54.00	4.18	100.0	V	66.0	15.7
6000.500000	57.62	---	74.00	16.38	100.0	V	66.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch165
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	---	47.41	54.00	6.59	100.0	H	75.0	10.1
4000.075000	53.93	---	74.00	20.07	100.0	H	0.0	10.1
5500.000000	---	44.94	54.00	9.06	100.0	H	329.0	14.3
5500.000000	53.97	---	74.00	20.03	100.0	H	329.0	14.3
6000.500000	56.22	---	74.00	17.78	100.0	H	335.0	15.7
6000.500000	---	50.89	54.00	3.11	100.0	H	335.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch165
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	48.50	---	74.00	25.50	100.0	V	320.0	6.0
2000.025000	---	42.53	54.00	11.47	100.0	V	22.0	6.0
4000.075000	53.11	---	74.00	20.89	100.0	V	0.0	10.1
4000.075000	---	47.72	54.00	6.28	100.0	V	0.0	10.1
5000.000000	52.66	---	74.00	21.34	100.0	V	342.0	13.1
5000.000000	---	43.58	54.00	10.42	100.0	V	342.0	13.1
5500.000000	---	45.50	54.00	8.50	100.0	V	269.0	14.3
5500.000000	53.68	---	74.00	20.32	100.0	V	269.0	14.3
6000.000000	---	48.52	54.00	5.48	100.0	V	349.0	15.7
6000.500000	55.81	---	74.00	18.19	100.0	V	335.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch36
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10363.433333	---	35.67	54.00	18.33	100.0	H	0.0	11.8
10364.416667	45.95	---	74.00	28.05	100.0	H	194.0	11.8

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch36
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10000.091667	---	38.25	54.00	15.75	100.0	V	78.0	11.1
10000.091667	46.75	---	74.00	27.25	100.0	V	78.0	11.1
10364.908333	45.23	---	74.00	28.77	100.0	V	119.0	11.8
10364.908333	---	35.86	54.00	18.14	100.0	V	119.0	11.8

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch40
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10402.275000	44.88	---	74.00	29.12	100.0	H	308.0	11.9
10403.258333	---	35.68	54.00	18.32	100.0	H	0.0	11.9

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch40
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9999.600000	---	38.23	54.00	15.77	100.0	V	54.0	11.1
10000.091667	47.32	---	74.00	26.68	100.0	V	341.0	11.1
10398.341667	---	35.98	54.00	18.02	100.0	V	156.0	11.9
10406.208333	46.49	---	74.00	27.51	100.0	V	156.0	11.9

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch48
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6499.916667	46.86	---	74.00	27.14	100.0	H	44.0	8.8
6499.916667	---	39.09	54.00	14.91	100.0	H	44.0	8.8
10476.025000	45.61	---	74.00	28.39	100.0	H	133.0	12.0
10480.450000	---	36.35	54.00	17.65	100.0	H	328.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch48
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9999.600000	45.83	---	74.00	28.17	100.0	V	302.0	11.1
10000.091667	---	37.57	54.00	16.43	100.0	V	359.0	11.1
10475.041667	---	36.36	54.00	17.64	100.0	V	47.0	12.0
10482.416667	46.44	---	74.00	27.56	100.0	V	359.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch52
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6499.425000	45.93	---	74.00	28.07	100.0	H	330.0	8.8
6499.916667	---	39.78	54.00	14.22	100.0	H	243.0	8.8
6749.683333	---	39.02	54.00	14.98	100.0	H	318.0	8.6
6749.683333	46.09	---	74.00	27.91	100.0	H	318.0	8.6
6999.941667	---	37.29	54.00	16.71	100.0	H	46.0	8.6
6999.941667	45.13	---	74.00	28.87	100.0	H	46.0	8.6
10528.141667	45.92	---	74.00	28.08	100.0	H	268.0	12.0
10529.616667	---	36.54	54.00	17.46	100.0	H	305.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch52
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9980.425000	45.96	---	74.00	28.04	100.0	V	0.0	11.1
10000.091667	---	37.54	54.00	16.46	100.0	V	42.0	11.1
10515.358333	45.08	---	74.00	28.92	100.0	V	82.0	12.0
10515.850000	---	36.27	54.00	17.73	100.0	V	107.0	12.0

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch56
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10558.625000	45.84	---	74.00	28.16	100.0	H	22.0	12.0
10564.525000	---	35.98	54.00	18.02	100.0	H	161.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch56
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10544.858333	---	36.38	54.00	17.62	100.0	V	295.0	12.0
10547.316667	45.98	---	74.00	28.02	100.0	V	270.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10640.241667	46.15	---	74.00	27.85	100.0	H	226.0	12.0
10642.700000	---	36.53	54.00	17.47	100.0	H	315.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10638.766667	46.12	---	74.00	27.88	100.0	V	131.0	12.0
10643.191667	---	36.55	54.00	17.45	100.0	V	194.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch100
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11012.925000	---	36.57	54.00	17.43	100.0	H	113.0	12.2
11014.400000	46.15	---	74.00	27.85	100.0	H	8.0	12.2

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch100
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11000.141667	45.76	---	74.00	28.24	100.0	V	235.0	12.2
11005.058333	---	35.81	54.00	18.19	100.0	V	260.0	12.2

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch120
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11200.250000	45.56	---	74.00	28.44	100.0	H	205.0	12.6
11202.216667	---	36.07	54.00	17.93	100.0	H	357.0	12.6

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch120
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11189.433333	---	36.29	54.00	17.71	100.0	V	208.0	12.6
11202.708333	45.74	---	74.00	28.26	100.0	V	53.0	12.6

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11396.916667	---	37.20	54.00	16.80	100.0	H	107.0	12.7
11405.766667	47.10	---	74.00	26.90	100.0	H	287.0	12.8

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch140
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9999.600000	46.95	---	74.00	27.05	100.0	V	357.0	11.1
10000.091667	---	37.62	54.00	16.38	100.0	V	77.0	11.1
11394.458333	---	36.82	54.00	17.18	100.0	V	320.0	12.7
11415.108333	46.81	---	74.00	27.19	100.0	V	180.0	12.9

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch144
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11436.741667	---	37.15	54.00	16.85	100.0	H	200.0	13.2
11447.066667	46.43	---	74.00	27.57	100.0	H	73.0	13.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch144
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11430.841667	47.06	---	74.00	26.94	100.0	V	313.0	13.1
11435.758333	---	37.13	54.00	16.87	100.0	V	194.0	13.2

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch149
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6499.916667	---	38.77	54.00	15.23	100.0	H	15.0	8.8
6508.766667	46.90	---	74.00	27.10	100.0	H	219.0	8.8
11482.958333	46.82	---	74.00	27.18	100.0	H	1.0	13.7
11489.841667	---	36.76	54.00	17.24	100.0	H	130.0	13.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch149
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10000.091667	46.77	---	74.00	27.23	100.0	V	74.0	11.1
10000.091667	---	38.56	54.00	15.44	100.0	V	74.0	11.1
11492.300000	46.19	---	74.00	27.81	100.0	V	348.0	13.7
11492.791667	---	36.72	54.00	17.28	100.0	V	244.0	13.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch157
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6499.916667	---	39.67	54.00	14.33	100.0	H	103.0	8.8
6500.408333	46.27	---	74.00	27.73	100.0	H	306.0	8.8
11569.000000	46.75	---	74.00	27.25	100.0	H	255.0	13.4
11575.391667	---	36.73	54.00	17.27	100.0	H	129.0	13.4

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch157
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11566.541667	46.45	---	74.00	27.55	100.0	V	114.0	13.4
11567.525000	---	37.13	54.00	16.87	100.0	V	155.0	13.4

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch165
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11651.600000	46.91	---	74.00	27.09	100.0	H	27.0	13.3
11656.516667	---	37.35	54.00	16.65	100.0	H	39.0	13.3

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch165
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11648.158333	47.05	---	74.00	26.95	100.0	V	154.0	13.3
11657.991667	---	37.11	54.00	16.89	100.0	V	319.0	13.3

1.3 WiFi, 5GHz, 802.11a, Bandedge

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch36
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5121.666667	53.43	---	74.00	20.57	100.0	H	293.0	13.5
5122.055556	---	40.66	54.00	13.34	100.0	H	64.0	13.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch36
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5102.388889	---	40.03	54.00	13.97	100.0	V	237.0	13.4
5102.500000	52.65	---	74.00	21.35	100.0	V	343.0	13.4

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5396.600000	---	40.93	54.00	13.07	100.0	H	252.0	14.3
5398.000000	53.15	---	74.00	20.85	100.0	H	2.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5402.150000	---	40.90	54.00	13.10	100.0	V	326.0	14.3
5402.800000	53.74	---	74.00	20.26	100.0	V	293.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch100
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5404.784722	---	40.82	54.00	13.18	100.0	H	321.0	14.3
5404.881945	53.20	---	74.00	20.80	100.0	H	357.0	14.3
5467.347222	54.68	---	68.20	13.52	100.0	H	288.0	14.3
5468.611111	---	42.29	68.20	25.91	100.0	H	288.0	14.3

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch100
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5447.416667	54.03	---	74.00	19.97	100.0	V	295.0	14.3
5447.659722	---	43.29	54.00	10.71	100.0	V	295.0	14.3
5465.597222	61.88	---	68.20	6.32	100.0	V	271.0	14.3
5469.631945	---	45.30	68.20	22.90	100.0	V	287.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5727.565278	66.29	---	74.00	7.71	100.0	H	298.0	14.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11a_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	DET 2 (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5727.220833	64.46	---	74.00	9.54	100.0	V	267.0	14.5

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch149
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5607.083333	54.17	---	68.20	14.03	100.0	H	115.0	14.3

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch149
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5625.468750	52.48	---	68.20	15.72	100.0	V	280.0	14.3

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch165
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	DET 2 (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5934.420139	55.27	---	68.20	12.93	100.0	H	12.0	15.4

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11a_Ch165
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5949.649306	54.75	---	68.20	13.45	100.0	V	324.0	15.5

1.4 WiFi, 5GHz, 802.11n-HT20, above 1GHz

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch36
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	---	46.81	54.00	7.19	100.0	H	41.0	10.1
4012.825000	53.73	---	74.00	20.27	100.0	H	326.0	10.1
4999.500000	53.08	---	74.00	20.92	100.0	H	1.0	13.1
5000.000000	---	44.08	54.00	9.92	100.0	H	1.0	13.1
6000.000000	57.10	---	74.00	16.90	100.0	H	47.0	15.7
6000.000000	---	47.85	54.00	6.15	100.0	H	47.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch36
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.237500	48.71	---	74.00	25.29	100.0	V	359.0	6.0
2000.237500	---	41.92	54.00	12.08	100.0	V	359.0	6.0
3999.650000	54.86	---	74.00	19.14	100.0	V	333.0	10.1
4000.287500	---	49.97	54.00	4.03	100.0	V	333.0	10.1
5500.000000	---	46.07	54.00	7.93	100.0	V	327.0	14.3
6000.000000	---	49.44	54.00	4.56	100.0	V	290.0	15.7
6000.500000	55.84	---	74.00	18.16	100.0	V	290.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch40
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5000.000000	---	45.58	54.00	8.42	100.0	H	5.0	13.1
5000.500000	53.05	---	74.00	20.95	100.0	H	5.0	13.1
5500.000000	53.92	---	74.00	20.08	100.0	H	46.0	14.3
5500.000000	---	46.92	54.00	7.08	100.0	H	46.0	14.3
6000.000000	55.78	---	74.00	18.22	100.0	H	329.0	15.7
6000.000000	---	48.71	54.00	5.29	100.0	H	329.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch40
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	48.39	---	74.00	25.61	100.0	V	351.0	6.0
2000.025000	---	41.86	54.00	12.14	100.0	V	351.0	6.0
2499.825000	50.54	---	74.00	23.46	100.0	V	321.0	7.4
2499.825000	---	43.25	54.00	10.75	100.0	V	321.0	7.4
4000.075000	---	49.95	54.00	4.05	100.0	V	331.0	10.1
4000.500000	53.70	---	74.00	20.30	100.0	V	331.0	10.1
6000.000000	---	48.49	54.00	5.51	100.0	V	342.0	15.7
6000.500000	56.23	---	74.00	17.77	100.0	V	342.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch48
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3963.312500	53.77	---	74.00	20.23	100.0	H	50.0	10.1
4000.075000	---	46.00	54.00	8.00	100.0	H	40.0	10.1
4999.500000	52.59	---	74.00	21.41	100.0	H	1.0	13.1
5000.000000	---	43.64	54.00	10.36	100.0	H	1.0	13.1
5500.000000	---	45.56	54.00	8.44	100.0	H	27.0	14.3
5500.000000	53.95	---	74.00	20.05	100.0	H	27.0	14.3
6000.000000	57.13	---	74.00	16.87	100.0	H	89.0	15.7
6000.000000	---	48.11	54.00	5.89	100.0	H	89.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch48
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2500.037500	---	43.12	54.00	10.88	100.0	V	0.0	7.4
2500.037500	50.82	---	74.00	23.18	100.0	V	0.0	7.4
3999.650000	54.39	---	74.00	19.61	100.0	V	325.0	10.1
4000.075000	---	47.88	54.00	6.12	100.0	V	60.0	10.1
5000.000000	54.89	---	74.00	19.11	100.0	V	349.0	13.1
5000.000000	---	45.33	54.00	8.67	100.0	V	349.0	13.1
6000.000000	---	48.41	54.00	5.59	100.0	V	28.0	15.7
6000.500000	55.87	---	74.00	18.13	100.0	V	22.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch52
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.287500	53.39	---	74.00	20.61	100.0	H	44.0	10.1
4000.287500	---	46.98	54.00	7.02	100.0	H	44.0	10.1
4999.500000	53.18	---	74.00	20.82	100.0	H	21.0	13.1
5000.000000	---	44.09	54.00	9.91	100.0	H	21.0	13.1
6000.000000	56.39	---	74.00	17.61	100.0	H	61.0	15.7
6000.500000	---	48.14	54.00	5.86	100.0	H	61.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch52
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	---	42.32	54.00	11.68	100.0	V	352.0	6.0
2499.825000	---	42.87	54.00	11.13	100.0	V	321.0	7.4
2500.037500	50.16	---	74.00	23.84	100.0	V	352.0	7.4
3999.862500	55.11	---	74.00	18.89	100.0	V	331.0	10.1
4000.075000	---	50.23	54.00	3.77	100.0	V	331.0	10.1
5000.000000	---	44.66	54.00	9.34	100.0	V	352.0	13.1
5000.500000	52.45	---	74.00	21.55	100.0	V	282.0	13.1
5500.000000	53.60	---	74.00	20.40	100.0	V	324.0	14.3
5500.000000	---	45.71	54.00	8.29	100.0	V	324.0	14.3
6000.000000	55.50	---	74.00	18.50	100.0	V	55.0	15.7
6000.000000	---	49.35	54.00	4.65	100.0	V	55.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch56
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.012500	52.38	---	74.00	21.62	100.0	H	242.0	10.1
4000.075000	---	46.34	54.00	7.66	100.0	H	81.0	10.1
5000.000000	52.09	---	74.00	21.91	100.0	H	4.0	13.1
5000.000000	---	44.43	54.00	9.57	100.0	H	4.0	13.1
5500.000000	54.76	---	74.00	19.24	100.0	H	44.0	14.3
5500.000000	---	48.24	54.00	5.76	100.0	H	44.0	14.3
6000.000000	---	50.62	54.00	3.38	100.0	H	318.0	15.7
6000.500000	56.76	---	74.00	17.24	100.0	H	289.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch56
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2500.037500	50.37	---	74.00	23.63	100.0	V	0.0	7.4
2500.037500	---	42.37	54.00	11.63	100.0	V	0.0	7.4
3999.862500	54.12	---	74.00	19.88	100.0	V	328.0	10.1
4000.075000	---	48.80	54.00	5.20	100.0	V	328.0	10.1
6000.000000	---	50.22	54.00	3.78	100.0	V	64.0	15.7
6000.000000	56.68	---	74.00	17.32	100.0	V	64.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch64
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	---	47.62	54.00	6.38	100.0	H	42.0	10.1
4080.825000	53.64	---	74.00	20.36	100.0	H	0.0	10.1
5500.000000	---	45.33	54.00	8.67	100.0	H	46.0	14.3
5578.000000	53.38	---	74.00	20.62	100.0	H	59.0	14.3
6000.500000	55.90	---	74.00	18.10	100.0	H	81.0	15.7
6000.500000	---	47.94	54.00	6.06	100.0	H	81.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch64
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	---	41.57	54.00	12.43	100.0	V	349.0	6.0
2000.450000	48.15	---	74.00	25.85	100.0	V	357.0	6.0
4000.287500	55.91	---	74.00	18.09	100.0	V	330.0	10.1
4000.287500	---	50.74	54.00	3.26	100.0	V	330.0	10.1
5499.500000	53.63	---	74.00	20.37	100.0	V	34.0	14.3
5500.000000	---	45.70	54.00	8.30	100.0	V	34.0	14.3
6000.000000	55.68	---	74.00	18.32	100.0	V	320.0	15.7
6000.000000	---	49.41	54.00	4.59	100.0	V	320.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch100
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4499.500000	53.10	---	74.00	20.90	100.0	H	326.0	13.7
4500.000000	---	44.62	54.00	9.38	100.0	H	326.0	13.7
5000.000000	52.37	---	74.00	21.63	100.0	H	62.0	13.1
5000.000000	---	44.43	54.00	9.57	100.0	H	62.0	13.1
6000.000000	56.47	---	74.00	17.53	100.0	H	62.0	15.7
6000.000000	---	49.38	54.00	4.62	100.0	H	62.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch100
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	48.23	---	74.00	25.77	100.0	V	0.0	6.0
2000.025000	---	42.85	54.00	11.15	100.0	V	0.0	6.0
2500.037500	51.83	---	74.00	22.17	100.0	V	0.0	7.4
2500.037500	---	43.14	54.00	10.86	100.0	V	0.0	7.4
4000.287500	53.59	---	74.00	20.41	100.0	V	326.0	10.1
4000.287500	---	48.77	54.00	5.23	100.0	V	326.0	10.1
5000.000000	---	44.36	54.00	9.64	100.0	V	312.0	13.1
5000.000000	52.53	---	74.00	21.47	100.0	V	312.0	13.1
6000.500000	56.31	---	74.00	17.69	100.0	V	62.0	15.7
6000.500000	---	48.28	54.00	5.72	100.0	V	62.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch120
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3994.550000	53.56	---	74.00	20.44	100.0	H	199.0	10.1
4000.075000	---	47.18	54.00	6.82	100.0	H	42.0	10.1
5000.000000	52.41	---	74.00	21.59	100.0	H	71.0	13.1
5000.000000	---	44.48	54.00	9.52	100.0	H	71.0	13.1
5500.000000	54.19	---	74.00	19.81	100.0	H	44.0	14.3
5500.000000	---	47.08	54.00	6.92	100.0	H	44.0	14.3
6000.000000	56.99	---	74.00	17.01	100.0	H	342.0	15.7
6000.500000	---	50.08	54.00	3.92	100.0	H	170.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch120
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	---	42.83	54.00	11.17	100.0	V	347.0	6.0
2000.025000	49.05	---	74.00	24.95	100.0	V	347.0	6.0
3999.862500	---	50.71	54.00	3.29	100.0	V	327.0	10.1
4000.075000	55.65	---	74.00	18.35	100.0	V	327.0	10.1
4999.500000	52.84	---	74.00	21.16	100.0	V	346.0	13.1
5000.000000	---	43.95	54.00	10.05	100.0	V	4.0	13.1
6000.000000	55.98	---	74.00	18.02	100.0	V	66.0	15.7
6000.000000	---	49.04	54.00	4.96	100.0	V	66.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	---	45.73	54.00	8.27	100.0	H	38.0	10.1
4000.075000	53.93	---	74.00	20.07	100.0	H	38.0	10.1
5000.000000	53.60	---	74.00	20.40	100.0	H	14.0	13.1
5000.000000	---	45.11	54.00	8.89	100.0	H	14.0	13.1
6000.000000	---	51.39	54.00	2.61	100.0	H	327.0	15.7
6000.500000	57.41	---	74.00	16.59	100.0	H	327.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch140
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	---	42.54	54.00	11.46	100.0	V	316.0	6.0
2000.237500	49.09	---	74.00	24.91	100.0	V	0.0	6.0
2500.037500	51.41	---	74.00	22.59	100.0	V	350.0	7.4
2500.037500	---	43.68	54.00	10.32	100.0	V	350.0	7.4
4000.287500	---	49.03	54.00	4.97	100.0	V	326.0	10.1
4000.287500	54.07	---	74.00	19.93	100.0	V	326.0	10.1
6000.000000	56.18	---	74.00	17.82	100.0	V	67.0	15.7
6000.500000	---	48.48	54.00	5.52	100.0	V	67.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch144
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5000.000000	---	45.25	54.00	8.75	100.0	H	11.0	13.1
5000.000000	53.18	---	74.00	20.82	100.0	H	11.0	13.1
5500.000000	---	46.18	54.00	7.82	100.0	H	45.0	14.3
5500.000000	53.64	---	74.00	20.36	100.0	H	45.0	14.3
6000.000000	---	52.50	54.00	1.50	100.0	H	333.0	15.7
6000.500000	58.21	---	74.00	15.79	100.0	H	333.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch144
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	48.45	---	74.00	25.55	100.0	V	317.0	6.0
2000.025000	---	42.80	54.00	11.20	100.0	V	317.0	6.0
3999.862500	53.89	---	74.00	20.11	100.0	V	328.0	10.1
4000.075000	---	49.59	54.00	4.41	100.0	V	328.0	10.1
5000.000000	---	43.73	54.00	10.27	100.0	V	21.0	13.1
5000.500000	52.14	---	74.00	21.86	100.0	V	336.0	13.1
6000.000000	---	48.03	54.00	5.97	100.0	V	328.0	15.7
6000.000000	55.73	---	74.00	18.27	100.0	V	328.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch149
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.287500	---	46.86	54.00	7.14	100.0	H	113.0	10.1
4000.287500	54.11	---	74.00	19.89	100.0	H	113.0	10.1
4999.500000	52.42	---	74.00	21.58	100.0	H	2.0	13.1
5000.000000	---	45.04	54.00	8.96	100.0	H	2.0	13.1
5500.000000	---	46.69	54.00	7.31	100.0	H	42.0	14.3
5500.000000	53.96	---	74.00	20.04	100.0	H	42.0	14.3
6000.000000	56.15	---	74.00	17.85	100.0	H	71.0	15.7
6000.000000	---	49.17	54.00	4.83	100.0	H	71.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch149
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	---	42.43	54.00	11.57	100.0	V	6.0	6.0
2000.237500	48.57	---	74.00	25.43	100.0	V	358.0	6.0
2499.825000	51.23	---	74.00	22.77	100.0	V	351.0	7.4
2500.037500	---	43.36	54.00	10.64	100.0	V	0.0	7.4
3999.862500	---	50.31	54.00	3.69	100.0	V	332.0	10.1
4000.075000	54.68	---	74.00	19.32	100.0	V	332.0	10.1
6000.000000	56.49	---	74.00	17.51	100.0	V	142.0	15.7
6000.000000	---	50.07	54.00	3.93	100.0	V	142.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch157
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4499.500000	53.67	---	74.00	20.33	100.0	H	327.0	13.7
4499.500000	---	45.72	54.00	8.28	100.0	H	327.0	13.7
5000.000000	53.21	---	74.00	20.79	100.0	H	2.0	13.1
5000.000000	---	45.52	54.00	8.48	100.0	H	2.0	13.1
6000.000000	55.94	---	74.00	18.06	100.0	H	49.0	15.7
6000.000000	---	47.73	54.00	6.27	100.0	H	49.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch157
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2500.037500	---	43.02	54.00	10.98	100.0	V	0.0	7.4
2520.225000	50.75	---	74.00	23.25	100.0	V	0.0	7.5
4000.075000	---	50.05	54.00	3.95	100.0	V	333.0	10.1
4000.287500	55.13	---	74.00	18.87	100.0	V	333.0	10.1
5000.000000	---	44.17	54.00	9.83	100.0	V	269.0	13.1
5000.000000	53.39	---	74.00	20.61	100.0	V	269.0	13.1
5500.000000	54.46	---	74.00	19.54	100.0	V	277.0	14.3
5500.000000	---	45.87	54.00	8.13	100.0	V	277.0	14.3
6000.000000	56.48	---	74.00	17.52	100.0	V	96.0	15.7
6000.000000	---	49.02	54.00	4.98	100.0	V	96.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch165
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5000.000000	53.83	---	74.00	20.17	100.0	H	2.0	13.1
5000.000000	---	44.82	54.00	9.18	100.0	H	2.0	13.1
5500.000000	53.58	---	74.00	20.42	100.0	H	0.0	14.3
5500.000000	---	45.46	54.00	8.54	100.0	H	0.0	14.3
6000.000000	55.57	---	74.00	18.43	100.0	H	18.0	15.7
6000.000000	---	48.25	54.00	5.75	100.0	H	18.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch165
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	48.42	---	74.00	25.58	100.0	V	0.0	6.0
1999.812500	---	42.08	54.00	11.92	100.0	V	0.0	6.0
2499.825000	50.45	---	74.00	23.55	100.0	V	348.0	7.4
2499.825000	---	43.26	54.00	10.74	100.0	V	348.0	7.4
3999.862500	55.72	---	74.00	18.28	100.0	V	328.0	10.1
3999.862500	---	50.71	54.00	3.29	100.0	V	328.0	10.1
6000.000000	57.24	---	74.00	16.76	100.0	V	65.0	15.7
6000.000000	---	49.91	54.00	4.09	100.0	V	65.0	15.7

Test Report

EUT Information

EUT Name: Qi Wireless Charging Dual Pad
Model: UNIQT-1084
Test Mode: WPT
Test Voltage:: 230V/50Hz
Remark: Temp 23 Humi:55%
Test Standard: EN 303 417
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10363.925000	---	33.59	54.00	20.41	100.0	H	325.0	11.8
10364.416667	43.18	---	74.00	30.82	100.0	H	298.0	11.8

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch36
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10361.466667	---	33.79	54.00	20.21	100.0	V	110.0	11.8
10371.300000	44.36	---	74.00	29.64	100.0	V	0.0	11.8

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch40
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10408.666667	---	35.76	54.00	18.24	100.0	H	99.0	11.9
10411.125000	45.49	---	74.00	28.51	100.0	H	317.0	11.9

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch40
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10399.816667	44.88	---	74.00	29.12	100.0	V	98.0	11.9
10403.750000	---	36.03	54.00	17.97	100.0	V	205.0	11.9

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch48
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
8499.525000	45.38	---	74.00	28.62	100.0	H	1.0	8.9
8500.016667	---	37.45	54.00	16.55	100.0	H	236.0	8.8
10000.091667	49.29	---	74.00	24.71	100.0	H	22.0	11.1
10000.091667	---	42.46	54.00	11.54	100.0	H	22.0	11.1
10481.925000	44.52	---	74.00	29.48	100.0	H	110.0	12.0
10485.366667	---	35.91	54.00	18.09	100.0	H	110.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch48
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10479.466667	45.47	---	74.00	28.53	100.0	V	355.0	12.0
10489.300000	---	36.20	54.00	17.80	100.0	V	306.0	12.0

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n20M_Ch52
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6749.683333	---	39.75	54.00	14.25	100.0	H	333.0	8.6
6750.175000	47.62	---	74.00	26.38	100.0	H	193.0	8.6
10000.091667	49.58	---	74.00	24.42	100.0	H	18.0	11.1
10000.091667	---	44.15	54.00	9.85	100.0	H	18.0	11.1
10517.325000	---	36.17	54.00	17.83	100.0	H	257.0	12.0
10522.241667	45.74	---	74.00	28.26	100.0	H	333.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch52
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10535.025000	46.81	---	74.00	27.19	100.0	V	32.0	12.0
10535.516667	---	37.09	54.00	16.91	100.0	V	132.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch56
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6749.683333	47.57	---	74.00	26.43	100.0	H	313.0	8.6
6749.683333	---	39.60	54.00	14.40	100.0	H	313.0	8.6
9999.600000	48.92	---	74.00	25.08	100.0	H	104.0	11.1
10000.091667	---	42.79	54.00	11.21	100.0	H	0.0	11.1
10554.691667	44.94	---	74.00	29.06	100.0	H	79.0	12.0
10568.950000	---	36.70	54.00	17.30	100.0	H	5.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch56
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10559.608333	---	36.20	54.00	17.80	100.0	V	168.0	12.0
10562.558333	45.42	---	74.00	28.58	100.0	V	206.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6749.683333	47.85	---	74.00	26.15	100.0	H	305.0	8.6
6749.683333	---	40.37	54.00	13.63	100.0	H	305.0	8.6
10000.091667	48.90	---	74.00	25.10	100.0	H	193.0	11.1
10000.091667	---	42.92	54.00	11.08	100.0	H	193.0	11.1
10645.158333	---	37.16	54.00	16.84	100.0	H	205.0	12.0
10645.158333	46.60	---	74.00	27.40	100.0	H	205.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9999.600000	45.66	---	74.00	28.34	100.0	V	35.0	11.1
10000.091667	---	38.88	54.00	15.12	100.0	V	1.0	11.1
10639.258333	46.03	---	74.00	27.97	100.0	V	97.0	12.0
10642.700000	---	36.85	54.00	17.15	100.0	V	35.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch100
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10999.650000	---	36.20	54.00	17.80	100.0	H	300.0	12.2
11006.041667	46.20	---	74.00	27.80	100.0	H	312.0	12.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch100
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10992.766667	46.42	---	74.00	27.58	100.0	V	300.0	12.2
11001.616667	---	36.10	54.00	17.90	100.0	V	13.0	12.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch120
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11200.633333	46.04	---	74.00	27.96	100.0	H	108.0	12.2
11205.550000	---	35.90	54.00	18.10	100.0	H	170.0	12.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch120
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11203.091667	45.53	---	74.00	28.47	100.0	V	140.0	12.2
11203.091667	---	36.54	54.00	17.47	100.0	V	140.0	12.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11398.391667	46.26	---	74.00	27.74	100.0	H	342.0	12.8
11400.358333	---	37.12	54.00	16.88	100.0	H	47.0	12.8

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11395.933333	46.95	---	74.00	27.05	100.0	V	123.0	12.7
11425.433333	---	37.35	54.00	16.65	100.0	V	0.0	13.1

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch144
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11432.316667	---	37.47	54.00	16.53	100.0	H	0.0	13.1
11437.725000	46.19	---	74.00	27.81	100.0	H	47.0	13.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch144
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11438.708333	46.44	---	74.00	27.56	100.0	V	311.0	13.2
11442.641667	---	37.14	54.00	16.86	100.0	V	3.0	13.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch149
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11491.808333	---	36.44	54.00	17.56	100.0	H	191.0	13.7
11494.266667	45.60	---	74.00	28.40	100.0	H	128.0	13.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch149
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11487.875000	46.24	---	74.00	27.76	100.0	V	345.0	13.7
11489.841667	---	37.02	54.00	16.98	100.0	V	78.0	13.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch157
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11568.508333	46.20	---	74.00	27.80	100.0	H	58.0	13.4
11568.508333	---	37.31	54.00	16.69	100.0	H	58.0	13.4

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch157
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11569.000000	46.22	---	74.00	27.78	100.0	V	63.0	13.4
11569.491667	---	36.62	54.00	17.38	100.0	V	255.0	13.4

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch165
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11650.125000	---	36.80	54.00	17.20	100.0	H	216.0	13.3
11657.500000	46.28	---	74.00	27.72	100.0	H	0.0	13.3

1.5 WiFi, 5GHz, 802.11n-HT20, Bandedge

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch36
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5122.000000	52.19	---	74.00	21.81	100.0	H	55.0	13.5
5122.888889	---	40.35	54.00	13.65	100.0	H	6.0	13.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch36
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5127.166667	---	41.18	54.00	12.82	100.0	V	220.0	13.5
5127.555556	53.87	---	74.00	20.13	100.0	V	236.0	13.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5386.700000	---	40.97	54.00	13.03	100.0	H	291.0	14.3
5386.700000	53.47	---	74.00	20.53	100.0	H	291.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch64
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5372.800000	---	42.60	54.00	11.40	100.0	V	251.0	14.3
5372.800000	53.53	---	74.00	20.47	100.0	V	251.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch100
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5447.173611	53.34	---	74.00	20.66	100.0	H	252.0	14.3
5447.513889	---	43.26	54.00	10.74	100.0	H	10.0	14.3
5466.083333	---	43.89	68.20	24.31	100.0	H	108.0	14.3
5466.812500	54.82	---	68.20	13.38	100.0	H	269.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch100
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5447.270833	53.09	---	74.00	20.91	100.0	V	293.0	14.3
5447.368056	---	43.33	54.00	10.67	100.0	V	293.0	14.3
5465.062500	56.89	---	68.20	11.31	100.0	V	276.0	14.3
5465.645833	---	43.93	68.20	24.27	100.0	V	235.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5726.316667	65.77	---	74.00	8.23	100.0	H	311.0	14.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch140
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5737.468056	62.14	---	74.00	11.86	100.0	V	318.0	14.6

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch149
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5638.020833	53.32	---	68.20	14.88	100.0	H	252.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch149
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5646.666667	53.78	---	68.20	14.42	100.0	V	26.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch165
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	DET 2 (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5950.534722	54.62	---	68.20	13.58	100.0	H	202.0	15.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n20M_Ch165
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	DET 2 (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5943.215278	53.83	---	68.20	14.37	100.0	V	351.0	15.5

1.6 WiFi, 5GHz, 802.11n-HT40, above 1GHz

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch38
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3982.650000	53.49	---	74.00	20.51	100.0	H	110.0	10.1
4000.075000	---	46.74	54.00	7.26	100.0	H	37.0	10.1
4999.500000	---	43.76	54.00	10.24	100.0	H	60.0	13.1
5000.000000	52.72	---	74.00	21.28	100.0	H	12.0	13.1
5500.000000	53.88	---	74.00	20.12	100.0	H	46.0	14.3
5500.000000	---	45.59	54.00	8.41	100.0	H	46.0	14.3
6000.000000	---	49.89	54.00	4.11	100.0	H	89.0	15.7
6000.500000	56.06	---	74.00	17.94	100.0	H	89.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch38
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2500.037500	49.98	---	74.00	24.02	100.0	V	354.0	7.4
2500.037500	---	42.70	54.00	11.30	100.0	V	354.0	7.4
3999.862500	53.77	---	74.00	20.23	100.0	V	304.0	10.1
4000.075000	---	47.72	54.00	6.28	100.0	V	50.0	10.1
4999.500000	53.82	---	74.00	20.18	100.0	V	312.0	13.1
5000.000000	---	44.03	54.00	9.97	100.0	V	312.0	13.1
6000.000000	---	48.68	54.00	5.32	100.0	V	96.0	15.7
6000.500000	55.38	---	74.00	18.62	100.0	V	326.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch46
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	52.60	---	74.00	21.40	100.0	H	309.0	10.1
4000.287500	---	47.02	54.00	6.98	100.0	H	45.0	10.1
5000.000000	52.35	---	74.00	21.65	100.0	H	22.0	13.1
5000.000000	---	44.16	54.00	9.84	100.0	H	22.0	13.1
6000.000000	55.36	---	74.00	18.64	100.0	H	77.0	15.7
6000.000000	---	47.65	54.00	6.35	100.0	H	77.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch46
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	---	41.91	54.00	12.09	100.0	V	355.0	6.0
1999.812500	48.53	---	74.00	25.47	100.0	V	355.0	6.0
2499.825000	51.46	---	74.00	22.54	100.0	V	0.0	7.4
2500.250000	---	43.63	54.00	10.37	100.0	V	0.0	7.4
4000.287500	53.52	---	74.00	20.48	100.0	V	325.0	10.1
4000.287500	---	47.29	54.00	6.71	100.0	V	325.0	10.1
6000.000000	---	50.27	54.00	3.73	100.0	V	64.0	15.7
6000.000000	56.57	---	74.00	17.43	100.0	V	64.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch54
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4499.500000	52.44	---	74.00	21.56	100.0	H	327.0	13.7
4499.500000	---	45.09	54.00	8.91	100.0	H	327.0	13.7
5500.000000	---	46.87	54.00	7.13	100.0	H	45.0	14.3
5500.000000	54.75	---	74.00	19.25	100.0	H	45.0	14.3
6000.000000	56.48	---	74.00	17.52	100.0	H	72.0	15.7
6000.000000	---	49.87	54.00	4.13	100.0	H	72.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch54
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	---	42.28	54.00	11.72	100.0	V	350.0	6.0
2000.237500	48.94	---	74.00	25.06	100.0	V	350.0	6.0
4000.287500	---	51.08	54.00	2.92	100.0	V	329.0	10.1
4000.287500	54.89	---	74.00	19.11	100.0	V	329.0	10.1
6000.000000	---	48.87	54.00	5.13	100.0	V	341.0	15.7
6000.000000	55.64	---	74.00	18.36	100.0	V	341.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch62
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	---	47.35	54.00	6.65	100.0	H	40.0	10.1
4000.500000	53.13	---	74.00	20.87	100.0	H	40.0	10.1
5000.000000	---	45.23	54.00	8.77	100.0	H	6.0	13.1
5000.500000	52.43	---	74.00	21.57	100.0	H	6.0	13.1
5500.000000	---	46.56	54.00	7.44	100.0	H	42.0	14.3
5500.000000	55.11	---	74.00	18.89	100.0	H	42.0	14.3
6000.000000	---	51.11	54.00	2.89	100.0	H	64.0	15.7
6000.500000	57.83	---	74.00	16.17	100.0	H	334.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch62
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2499.825000	---	43.35	54.00	10.65	100.0	V	356.0	7.4
2500.250000	51.11	---	74.00	22.89	100.0	V	0.0	7.4
3997.950000	53.09	---	74.00	20.91	100.0	V	195.0	10.1
4000.075000	---	46.76	54.00	7.24	100.0	V	0.0	10.1
4999.500000	52.96	---	74.00	21.04	100.0	V	347.0	13.1
5000.000000	---	44.56	54.00	9.44	100.0	V	61.0	13.1
6000.000000	---	48.21	54.00	5.79	100.0	V	40.0	15.7
6000.500000	56.06	---	74.00	17.94	100.0	V	6.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch102
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3000.050000	49.65	---	74.00	24.35	100.0	H	333.0	8.5
3000.050000	---	43.94	54.00	10.06	100.0	H	333.0	8.5
5000.000000	52.53	---	74.00	21.47	100.0	H	13.0	13.1
5000.000000	---	44.44	54.00	9.56	100.0	H	13.0	13.1
6000.000000	---	48.74	54.00	5.26	100.0	H	169.0	15.7
6000.500000	56.30	---	74.00	17.70	100.0	H	70.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch102
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.812500	48.71	---	74.00	25.29	100.0	V	0.0	6.0
2000.025000	---	42.25	54.00	11.75	100.0	V	352.0	6.0
2499.825000	---	43.08	54.00	10.92	100.0	V	0.0	7.4
2500.462500	49.87	---	74.00	24.13	100.0	V	359.0	7.4
4000.075000	---	47.92	54.00	6.08	100.0	V	316.0	10.1
4000.287500	54.56	---	74.00	19.44	100.0	V	62.0	10.1
6000.000000	---	48.22	54.00	5.78	100.0	V	5.0	15.7
6000.000000	55.70	---	74.00	18.30	100.0	V	5.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch118
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3999.862500	53.03	---	74.00	20.97	100.0	H	132.0	10.1
3999.862500	---	45.98	54.00	8.02	100.0	H	132.0	10.1
4499.500000	---	44.49	54.00	9.51	100.0	H	293.0	13.7
4500.000000	53.13	---	74.00	20.87	100.0	H	329.0	13.7
4999.500000	53.28	---	74.00	20.72	100.0	H	2.0	13.1
5000.000000	---	44.56	54.00	9.44	100.0	H	2.0	13.1
6000.000000	---	48.82	54.00	5.18	100.0	H	205.0	15.7
6000.000000	56.57	---	74.00	17.43	100.0	H	205.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch118
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2499.825000	---	43.36	54.00	10.64	100.0	V	0.0	7.4
2500.462500	49.75	---	74.00	24.25	100.0	V	357.0	7.4
3999.650000	53.41	---	74.00	20.59	100.0	V	0.0	10.1
4000.075000	---	47.06	54.00	6.94	100.0	V	328.0	10.1
5000.000000	52.71	---	74.00	21.29	100.0	V	350.0	13.1
5000.000000	---	44.95	54.00	9.05	100.0	V	350.0	13.1
6000.000000	---	48.91	54.00	5.09	100.0	V	32.0	15.7
6000.000000	56.16	---	74.00	17.84	100.0	V	32.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch134
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	---	46.59	54.00	7.41	100.0	H	46.0	10.1
4000.075000	54.96	---	74.00	19.04	100.0	H	46.0	10.1
5000.000000	---	44.47	54.00	9.53	100.0	H	1.0	13.1
5000.000000	52.78	---	74.00	21.22	100.0	H	1.0	13.1
5500.000000	54.16	---	74.00	19.84	100.0	H	26.0	14.3
5500.000000	---	44.85	54.00	9.15	100.0	H	26.0	14.3
6000.000000	---	49.31	54.00	4.69	100.0	H	220.0	15.7
6000.000000	56.16	---	74.00	17.84	100.0	H	220.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch134
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	48.21	---	74.00	25.79	100.0	V	327.0	6.0
2000.025000	---	40.89	54.00	13.11	100.0	V	327.0	6.0
4000.075000	54.80	---	74.00	19.20	100.0	V	327.0	10.1
4000.075000	---	49.41	54.00	4.59	100.0	V	327.0	10.1
5000.000000	---	45.77	54.00	8.23	100.0	V	282.0	13.1
5000.500000	52.75	---	74.00	21.25	100.0	V	282.0	13.1
6000.000000	---	48.70	54.00	5.30	100.0	V	62.0	15.7
6000.000000	56.91	---	74.00	17.09	100.0	V	62.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch142
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4999.500000	53.32	---	74.00	20.68	100.0	H	3.0	13.1
5000.000000	---	45.10	54.00	8.90	100.0	H	3.0	13.1
5500.000000	54.31	---	74.00	19.69	100.0	H	44.0	14.3
5500.000000	---	46.68	54.00	7.32	100.0	H	44.0	14.3
6000.000000	55.78	---	74.00	18.22	100.0	H	73.0	15.7
6000.000000	---	49.21	54.00	4.79	100.0	H	73.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch142
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	---	41.88	54.00	12.12	100.0	V	322.0	6.0
2000.237500	48.38	---	74.00	25.62	100.0	V	359.0	6.0
4000.075000	54.41	---	74.00	19.59	100.0	V	333.0	10.1
4000.075000	---	49.18	54.00	4.82	100.0	V	333.0	10.1
5500.000000	53.38	---	74.00	20.62	100.0	V	272.0	14.3
5500.000000	---	46.04	54.00	7.96	100.0	V	272.0	14.3
6000.000000	---	49.81	54.00	4.19	100.0	V	356.0	15.7
6000.500000	56.44	---	74.00	17.56	100.0	V	356.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch151
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	---	47.39	54.00	6.61	100.0	H	79.0	10.1
4000.075000	54.15	---	74.00	19.85	100.0	H	79.0	10.1
5000.000000	52.31	---	74.00	21.69	100.0	H	48.0	13.1
5000.000000	---	43.53	54.00	10.47	100.0	H	48.0	13.1
5500.000000	54.09	---	74.00	19.91	100.0	H	28.0	14.3
5500.000000	---	46.07	54.00	7.93	100.0	H	28.0	14.3
6000.000000	---	50.33	54.00	3.67	100.0	H	71.0	15.7
6000.000000	55.94	---	74.00	18.06	100.0	H	71.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch151
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1999.600000	48.57	---	74.00	25.43	100.0	V	0.0	6.0
2000.025000	---	42.64	54.00	11.36	100.0	V	0.0	6.0
4000.075000	54.34	---	74.00	19.66	100.0	V	297.0	10.1
4000.075000	---	48.40	54.00	5.60	100.0	V	297.0	10.1
5000.000000	---	45.14	54.00	8.86	100.0	V	348.0	13.1
5000.000000	53.21	---	74.00	20.79	100.0	V	348.0	13.1
6000.000000	---	48.34	54.00	5.66	100.0	V	29.0	15.7
6000.500000	56.53	---	74.00	17.47	100.0	V	29.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch159
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4000.075000	---	47.96	54.00	6.04	100.0	H	40.0	10.1
4000.500000	53.01	---	74.00	20.99	100.0	H	40.0	10.1
5000.000000	52.52	---	74.00	21.48	100.0	H	62.0	13.1
5000.000000	---	44.61	54.00	9.39	100.0	H	62.0	13.1
5500.000000	---	45.68	54.00	8.32	100.0	H	41.0	14.3
5500.500000	53.34	---	74.00	20.66	100.0	H	41.0	14.3
6000.000000	---	50.55	54.00	3.45	100.0	H	318.0	15.7
6000.000000	56.77	---	74.00	17.23	100.0	H	318.0	15.7

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch159
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2000.025000	47.73	---	74.00	26.27	100.0	V	0.0	6.0
2000.025000	---	41.91	54.00	12.09	100.0	V	0.0	6.0
3999.862500	53.27	---	74.00	20.73	100.0	V	38.0	10.1
4000.075000	---	47.24	54.00	6.76	100.0	V	6.0	10.1
5000.000000	53.41	---	74.00	20.59	100.0	V	350.0	13.1
5000.000000	---	44.96	54.00	9.04	100.0	V	350.0	13.1
6000.000000	56.59	---	74.00	17.41	100.0	V	67.0	15.7
6000.500000	---	50.17	54.00	3.83	100.0	V	344.0	15.7

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch38
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10380.641667	44.74	---	74.00	29.26	100.0	H	65.0	11.9
10386.541667	---	36.41	54.00	17.59	100.0	H	4.0	11.9

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch38
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10379.658333	---	35.47	54.00	18.53	100.0	V	257.0	11.9
10380.641667	44.80	---	74.00	29.20	100.0	V	112.0	11.9
17695.658333	---	49.62	54.00	4.38	100.0	V	307.0	22.9
17695.658333	---	49.62	54.00	4.38	100.0	V	307.0	22.9

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch46
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10448.983333	46.42	---	74.00	27.58	100.0	H	150.0	11.9
10461.275000	---	35.83	54.00	18.17	100.0	H	0.0	12.0

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch46
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10455.866667	---	35.64	54.00	18.36	100.0	V	314.0	12.0
10460.783333	44.70	---	74.00	29.30	100.0	V	41.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch54
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10537.975000	---	35.89	54.00	18.11	100.0	H	152.0	12.0
10547.316667	44.91	---	74.00	29.09	100.0	H	14.0	12.0

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch54
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10540.433333	---	35.96	54.00	18.04	100.0	V	289.0	12.0
10546.333333	45.41	---	74.00	28.59	100.0	V	319.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch62
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10619.100000	46.19	---	74.00	27.81	100.0	H	199.0	12.0
10625.983333	---	36.95	54.00	17.05	100.0	H	275.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch62
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9965.183333	45.31	---	74.00	28.69	100.0	V	146.0	11.0
10000.091667	---	37.77	54.00	16.23	100.0	V	313.0	11.1
10618.116667	46.48	---	74.00	27.52	100.0	V	286.0	12.0
10624.508333	---	36.68	54.00	17.32	100.0	V	222.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch102
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
6499.916667	---	39.05	54.00	14.95	100.0	H	359.0	8.8
6504.833333	46.16	---	74.00	27.84	100.0	H	326.0	8.8
11016.366667	45.78	---	74.00	28.22	100.0	H	326.0	12.2
11023.741667	---	36.58	54.00	17.42	100.0	H	276.0	12.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch102
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
9999.600000	45.32	---	74.00	28.68	100.0	V	328.0	11.1
10000.091667	---	37.51	54.00	16.49	100.0	V	14.0	11.1
11019.316667	---	35.75	54.00	18.25	100.0	V	274.0	12.2
11021.775000	44.84	---	74.00	29.16	100.0	V	179.0	12.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch118
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11150.100000	---	37.31	54.00	16.69	100.0	H	41.0	12.5
11190.908333	46.57	---	74.00	27.43	100.0	H	195.0	12.6

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch118
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11176.158333	46.65	---	74.00	27.35	100.0	V	0.0	12.5
11181.075000	---	36.13	54.00	17.87	100.0	V	227.0	12.6

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch134
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11342.341667	---	36.43	54.00	17.57	100.0	H	229.0	12.5
11343.816667	46.43	---	74.00	27.57	100.0	H	153.0	12.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch134
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11343.816667	45.96	---	74.00	28.04	100.0	V	342.0	12.5
11347.258333	---	36.86	54.00	17.14	100.0	V	64.0	12.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch142
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11417.075000	46.75	---	74.00	27.25	100.0	H	99.0	13.0
11429.366667	---	36.81	54.00	17.19	100.0	H	281.0	13.1

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch142
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11429.366667	---	36.72	54.00	17.28	100.0	V	185.0	13.1
11432.808333	46.05	---	74.00	27.95	100.0	V	185.0	13.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch151
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11507.541667	46.19	---	74.00	27.81	100.0	H	0.0	13.7
11513.933333	---	37.33	54.00	16.67	100.0	H	156.0	13.6

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch151
Test Voltage:: Battery
Remark: Temp 23 Humi:55%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11512.458333	---	36.84	54.00	17.16	100.0	V	356.0	13.6
11513.933333	46.12	---	74.00	27.88	100.0	V	91.0	13.6

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch159
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
10598.941667	---	36.34	54.00	17.66	100.0	H	103.0	12.1
10611.233333	47.90	---	74.00	26.10	100.0	H	245.0	12.0

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch159
Test Voltage::	Battery
Remark:	Temp 23 Humi:55%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
11600.466667	46.08	---	74.00	27.92	100.0	V	264.0	13.3
11602.925000	---	37.33	54.00	16.67	100.0	V	65.0	13.3

Final Result


Frequency (MHz)	QuasiPeak (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---		---	---

1.7 WiFi, 5GHz, 802.11n-HT40, Bandedge

Test Report

EUT Information

EUT Name: Android POS
Model: APOLLO
Test Mode: Wi-Fi 5G 11n40M_Ch38
Test Voltage:: Battery
Remark: Temp 23 Humi:45%
Test Standard: FCC 15.407
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5074.277778	52.00	---	74.00	22.00	100.0	H	295.0	13.3
5074.444445	---	40.00	54.00	14.00	100.0	H	163.0	13.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch38
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5071.722222	51.96	---	74.00	22.04	100.0	V	35.0	13.3
5072.277778	---	39.88	54.00	14.12	100.0	V	95.0	13.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch62
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5352.150000	52.14	---	74.00	21.86	100.0	H	2.0	14.2
5352.900000	---	41.11	54.00	12.89	100.0	H	122.0	14.2

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch62
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5360.200000	53.29	---	74.00	20.71	100.0	V	172.0	14.3
5362.850000	---	40.97	54.00	13.03	100.0	V	154.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch102
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5421.166667	---	41.16	54.00	12.84	100.0	H	53.0	14.3
5421.361111	52.80	---	74.00	21.20	100.0	H	175.0	14.3
5464.381945	52.75	---	68.20	15.45	100.0	H	175.0	14.3
5464.430556	---	41.04	68.20	27.16	100.0	H	292.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch102
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5394.479167	---	40.77	54.00	13.23	100.0	V	125.0	14.3
5394.770833	53.01	---	74.00	20.99	100.0	V	285.0	14.3
5465.743056	52.83	---	68.20	15.37	100.0	V	354.0	14.3
5466.715278	---	41.09	68.20	27.11	100.0	V	251.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch134
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5739.793056	60.30	---	74.00	13.70	100.0	H	51.0	14.6

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch134
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5733.033333	62.63	---	74.00	11.37	100.0	V	257.0	14.6

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch151
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	DET 2 (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5615.625000	54.29	---	68.20	13.91	100.0	H	164.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch151
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5635.572917	53.32	---	68.20	14.88	100.0	V	0.0	14.3

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch159
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical_Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	DET 2 (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5955.965278	54.46	---	68.20	13.74	100.0	H	153.0	15.5

Test Report

EUT Information

EUT Name:	Android POS
Model:	APOLLO
Test Mode:	Wi-Fi 5G 11n40M_Ch159
Test Voltage::	Battery
Remark:	Temp 23 Humi:45%
Test Standard:	FCC 15.407
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	DET 2 (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5939.083333	54.12	---	68.20	14.08	100.0	V	174.0	15.4