



No.198 Kezhu Road, Science Town Economic& Technology
Development District Guangzhou, China 510663
Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: sgs_internet_operations@sgs.com

FEDERAL COMMUNICATIONS COMMISSION
Registration number: 282399

Report No.: GLEMR080100223RFT
Page: 1 of 20
FCC ID:VX5270NC

TEST REPORT

Application No. : GLEMR080100223RF

Applicant: Thermor Ltd.

FCC ID: VX5270NC

Fundamental Frequency : 433.842MHz

Equipment Under Test (EUT):

Name: 433MHz Wireless In/Outdoor Thermometer

Model No.: 270NC,270NU,270BC, 270BU, 275NC, 275NU, 275BC, 275BU, 276NC, 276NU, 276BC, 276BU ♦

Serial No.: Not supplied by client.

♣ Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.

Standards: FCC PART 15, SUBPART C : 2007
Section 15.231(e)

Date of Receipt: 21 January 2008

Authorized Signature:



Stephen Guo
2008-Feb.

Stephen Guo
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at http://www.sgs.com/terms_and_conditions.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.



SGS-CSTC Standards Technical Services Ltd.

Report No.: GLEMR070601768RFT
Page: 2 of 20
FCC ID:VX5270NC

Date of Test: 21 January to 01 February 2008

Date of Issue: 02 February 2008

| | |
|----------------------|---------------|
| Test Result : | PASS * |
|----------------------|---------------|

- * In the configuration tested, the EUT complied with the standards specified above.

2 Test Summary

| The customer requested FCC tests for a 433MHz Wireless In/Outdoor Thermometer. | | | |
|--|-------------------|---------------------|--------|
| Test | Test Requirement | Stanadard Paragraph | Result |
| Radiated Emission (30MHz to 1000MHz) | FCC PART 15 :2007 | Section 15.231(e) | PASS |
| Occupied Bandwidth | FCC PART 15 :2007 | Section 15.231(c) | PASS |
| Dwell Time | FCC PART 15 :2007 | Section 15.231(e) | PASS |

Remark:

♣Item No.: 270NC,270NU,270BC, 270BU, 275NC, 275NU, 275BC, 275BU, 276NC, 276NU, 276BC, 276BU ♣

Only the Item 270NC was tested, since the electrical circuit design, PCB layout, components used and internal wiring were identical for the above items, only the logo imprinted on the plastic casing ,the color of the plastic casing and item numbers were different acrodding to the conformation from the applicant (manufacturer).

3 Contents

| | Page |
|---|--------------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 3 |
| 3 CONTENTS | 4 |
| 4 GENERAL INFORMATION | 5 |
| 4.1 CLIENT INFORMATION | 5 |
| 4.2 DETAILS OF E.U.T | 5 |
| 4.3 DESCRIPTION OF SUPPORT UNITS | 5 |
| 4.4 TEST LOCATION | 5 |
| 4.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 5 |
| 4.6 TEST FACILITY | 6 |
| 5 TEST RESULTS | 7 |
| 5.1 TEST INSTRUMENTS | 7 |
| 5.2 E.U.T. OPERATION | 8 |
| 5.3 TEST PROCEDURE & MEASUREMENT DATA | 8 |
| 5.3.1 Radiated Emissions | 8 |
| 5.3.2 Occupied Bandwidth | 14 |
| 5.3.3 Dwell Time | 15 |
| 6 PHOTOGRAPHS - TEST SETUP | 17 |
| 7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS | 18-19 |

4 General Information

4.1 Client Information

Applicant Name: Thermor Ltd.
Applicant Address: 16975 Leslie Street, Newmarket, Ontario, L3Y 9A1, Canada.

4.2 Details of E.U.T.

Name: 433MHz Wireless In/Outdoor Thermometer
Model No.: 270NC, 270NU, 270BC, 270BU, 275NC, 275NU, 275BC, 275BU, 276NC, 276NU, 276BC, 276BU
Power Supply: DC3V (2x1.5V "AAA" size battery)
Power Cord: N/A-

4.3 Description of Support Units

The EUT was tested as an independent unit: a 433.842MHz radio transmitter.

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory, No.198 Kezhu Road, Science Town Economic & Technology Development District, Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Other Information Requested by the Customer

None.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002. With the above and NVLAP's accreditation, SGS-CSTC is an authorized test laboratory for the DoC process.

5 Test Results

5.1 Test Instruments

| RE in Chamber/OATS | | | | | | |
|--------------------|-------------------------------|-------------------|---------------|-------------|----------------------|-------------------------|
| No: | Test Equipment | Manufacturer | Model No. | Serial No. | Cal. Date (dd-mm-yy) | Cal.Due date (dd-mm-yy) |
| EMC0525 | Compact Semi-Anechoic Chamber | ChangZhou ZhongYu | N/A | N/A | 06-03-2007 | 06-03-2008 |
| EMC0522 | EMI Test Receiver | Rohde & Schwarz | ESIB26 | 100249 | 05-12-2007 | 05-12-2008 |
| N/A | EMI Test Software | Audix | E3 | N/A | N/A | N/A |
| EMC0514 | Coaxial cable | SGS | N/A | N/A | 04-12-2007 | 04-12-2008 |
| EMC0524 | Bi-log Type Antenna | Schaffner -Chase | CBL6112B | 2966 | 12-08-2007 | 12-08-2008 |
| EMC0519 | Bilog Type Antenna | Schaffner -Chase | CBL6143 | 5070 | 12-08-2007 | 12-08-2008 |
| EMC0517 | Horn Antenna | Rohde & Schwarz | HF906 | 100095 | 12-08-2007 | 12-08-2008 |
| EMC0040 | Spectrum Analyzer | Rohde & Schwarz | FSP30 | 100324 | 05-12-2007 | 05-12-2008 |
| EMC0520 | 0.1-1300 MHz Pre-Amplifier | HP | 8447D OPT 010 | 2944A0625 2 | 28-03-2007 | 28-03-2008 |
| EMC0521 | 1-26.5 GHz Pre-Amplifier | Agilent | 8449B | 3008A0164 9 | 28-03-2007 | 28-03-2008 |
| EMC0523 | Active Loop Antenna | EMCO | 6502 | 00042963 | 09-08-2006 | 09-08-2008 |
| EMC0530 | 10m Semi- Anechoic Chamber | ETS | N/A | N/A | 10-08-2007 | 10-08-2008 |

| General used equipment | | | | | | |
|------------------------|-------------------------|-------------------|-----------|------------|----------------------|-------------------------|
| No: | Test Equipment | Manufacturer | Model No. | Serial No. | Cal. Date (dd-mm-yy) | Cal.Due date (dd-mm-yy) |
| EMC0050- EMC0053 | Temperature, & Humidity | ZHENGZHOU BO YANG | WSB | N/A | 05-12-2007 | 05-12-2008 |
| EMC0006 | DMM | Fluke | 73 | 70681569 | 27-09-2007 | 27-09-2008 |
| EMC0007 | DMM | Fluke | 73 | 70671122 | 27-09-2007 | 27-09-2008 |

5.2 E.U.T. Operation

| | |
|------------------------|------------------------------------|
| Input voltage: | DC3V (2×1.5V“AAA”size battery) |
| Operating Environment: | |
| Temperature: | 25.0 °C |
| Humidity: | 56 % RH |
| Atmospheric Pressure: | 1011 mbar |
| EUT Operation: | Test the EUT in transmitting mode. |

5.3 Test Procedure & Measurement Data

5.3.1 Radiated Emissions

| Test Requirement: | FCC Part15 C 15.231(e) | |
|------------------------------|--|--|
| Test Method: | ANSI C63.4 section 8 & 13 | |
| Test Date: | January 31 2008 | |
| Measurement Distance: | 3m (Semi-Anechoic Chamber) | |
| Requirements: | the field strength of emissions from intentional radiators operated under this Section shall not exceed the following: | |
| Fundamental Frequency MHz | Field Strength of Fundamental (dB μ V/m @ 3m) | Field Strength of Harmonics and Spurious Emissions (dB μ V/m @ 3m) |
| 40.66 to 40.70 | 60.0 | 40.0 |
| 70 to 130 | 54.0 | 34.0 |
| 130 to 174 | 54.0 to 63.5 | 34.0 to 43.5 |
| 174 to 260 | 63.5 | 43.5 |
| 260 to 470 | 63.5 to 74.0 | 43.5 to 54.0 |
| 470 and above | 74.0 | 54.0 |
| Detector: | Peak for pre-scan Peak and Average: 30-1000MHz:120kHz resolution bandwidth 1GHz-5GHz: 1MHz resolution bandwidth | |

** linear interpolations

[Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, uV/m at 3 meters = 22.72727(F) - 2454.545; for the band 260-470 MHz, uV/m at 3 meters = 16.6667(F) - 2833.3333. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

Since the device is a pulsed transmission with a periodic rate less than 20 pulses per second (20Hz).

The fundamental frequency of the EUT is 433.842MHz.

The limit for average field strength dB μ V/m for the fundamental emission= 72.9 dB μ V/m

No fundamental is allowed in the restricted bands.

The limit for average field strength dB μ V/m for the spurious emission=52.9 dB μ V/m. Spurious in the restricted bands must be less than 52.9dB μ V/m or 15.209.Whichever limit permits a higher field strength.

And according 15.35(a)

15.35(a) On any frequency or frequencies below or equal to 1000 MHz, the limits shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified. The specifications for the measuring instrument using the CISPR quasi-peak detector can be found in Publication 16 of the International Special Committee on Radio Interference (CISPR) of the International Electrotechnical Commission. As an alternative to CISPR quasi-peak measurements, the responsible party, at its option, may demonstrate compliance with the emission limits using measuring equipment employing a peak detector function, properly adjusted for such factors as pulse desensitization, as long as the same bandwidths as indicated for CISPR quasi-peak measurements are employed.

Note: For pulse modulated devices with a pulse-repetition frequency of 20 Hz or less and for which CISPR quasi-peak measurements are specified, compliance with the regulations shall be demonstrated using measuring equipment employing a peak detector function, properly adjusted for such factors as pulse desensitization, using the same measurement bandwidths that are indicated for CISPR quasi-peak measurements.

According to 15.35 (b) Unless otherwise specified, on any frequency or frequencies above 1000 MHz, the radiated emission limits are based on the use of measurement instrumentation employing an average detector function. Unless otherwise specified, measurements above 1000 MHz shall be performed using a minimum resolution bandwidth of 1 MHz. When average radiated emission measurements are specified in this part, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. Unless otherwise specified, e.g., see §§ 15.250, 15.252, 15.255, and 15.509-15.519 of this part, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device, e.g., the total peak power level. Note that the use of a pulse desensitization correction factor may be needed to determine the total peak emission level. The instruction manual or application note for the measurement instrument should be consulted for determining pulse desensitization factors, as necessary.


The average correction factor is computed by analyzing the "worst case" on time in any 100 msec time period. Analysis of the remote transmitter worst case on time in any 100 msec time period is an on time of 100 msec, therefore the average value of fundamental frequency is: Average = Peak value + 20log (Duty cycle), where the duty factor is calculated from following formula:

$$20\log (\text{Duty cycle}) = 20\log(T_{pulse}/100\text{ms}) = 20\log(66.2/100) = -3.6$$


Where $T_{pulse} = (\text{Pulse 1}) \times 8 + (\text{Pulse 2}) \times 12 + (\text{Pulse 3}) \times 5 + (\text{Pulse 4}) \times 11 = 66.2$

Please refer to below pictures for more details.



Report No.: GLEMR070601768RFT
 Page: 10 of 20
 FCC ID:VX5270NC

Pulse 1=2.8ms

Pulse 2=0.4ms


Pulse 3=3.4ms

Pulse 4=2ms

Report No.: GLEMR070601768RFT
Page: 12 of 20
FCC ID:VX5270NC

Test Procedure: The procedure used was ANSI

Standard C63.4-2003. The receive was scanned from 30MHz to 5.0GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes with two new batteries.

The field strength is calculated by adding the Antenna Factor, Cable Factor & Peramplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Peramplifier Factor

An initial pre-scan was performed in the 3m chamber using the spectrum analyser in peak detection mode. Peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bilog antenna with 2 orthogonal polarities and Horn antenna.

The following test results were performed on the EUT on 31 January 2008.

1. Fundamental emission& Spurious Emissions
(a) Antenna polarization: Horizontal

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Remark |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------|
| 433.831 | 79.3 | 16.5 | 2.5 | 25.3 | 72.9 | 92.9 | -20.0 | PEAK |
| 433.831 | 75.7 | 16.5 | 2.5 | 25.3 | 69.3 | 72.9 | -3.6 | AVERAG |
| 866.140 | 45.7 | 20.4 | 3.8 | 25.2 | 44.8 | 72.9 | -28.1 | PEAK |
| 866.140 | 42.1 | 20.4 | 3.8 | 25.2 | 41.2 | 52.9 | -11.7 | AVERAG |
| 1296.000 | 62.5 | 24.7 | 3.3 | 35.6 | 55.0 | 72.9 | -17.9 | PEAK |
| 1296.000 | 58.9 | 24.7 | 3.3 | 35.6 | 51.4 | 52.9 | -1.5 | AVERAG |
| 2092.000 | 50.1 | 27.7 | 4.4 | 35.0 | 47.3 | 72.9 | -25.6 | PEAK |
| 2092.000 | 46.5 | 27.7 | 4.4 | 35.0 | 43.7 | 52.9 | -9.2 | AVERAG |

(b) Antenna polarization: Vertical

| Frequency (MHz) | Read Level (dBuV) | Antenna Factor (dB/m) | Cable Loss (dB) | Preamp Factor (dB) | Level (dBuV/m) | Limit Line (dBuV/m) | Over Limit (dB) | Remark |
|-----------------|-------------------|-----------------------|-----------------|--------------------|----------------|---------------------|-----------------|--------|
| 433.839 | 76.2 | 22.9 | 0.7 | 25.3 | 69.9 | 92.9 | -23.0 | PEAK |
| 433.839 | 72.6 | 22.9 | 0.7 | 25.3 | 66.3 | 72.9 | -6.6 | AVERAG |
| 867.658 | 39.9 | 16.5 | 2.5 | 25.3 | 39.4 | 72.9 | -33.5 | PEAK |
| 867.658 | 36.3 | 16.5 | 2.5 | 25.3 | 35.8 | 52.9 | -17.1 | AVERAG |
| 1296.000 | 62.5 | 20.4 | 3.8 | 25.2 | 55.0 | 72.9 | -17.9 | PEAK |
| 1296.000 | 58.9 | 20.4 | 3.8 | 25.2 | 51.4 | 52.9 | -1.5 | AVERAG |
| 2092.000 | 40.9 | 24.7 | 3.3 | 35.6 | 38.1 | 72.9 | -34.8 | PEAK |
| 2092.000 | 37.3 | 24.7 | 3.3 | 35.6 | 34.5 | 52.9 | -18.4 | AVERAG |

Remark:

According to 15.35 (b) When average radiated emission measurements are specified in the regulations, including emission measurements below 1000 MHz, there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules, e.g., see Section 15.255.

TEST RESULTS: The unit does meet the FCC Part 15 C Section 15.231 requirements.

5.3.2 Occupied Bandwidth

Test Requirement: FCC Part 15 C Section 15.231(c)

Test Method: ANSI C63.4 section 13.

Test Date: 02 February 2008


Requirements: 15.231 (c) The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

The fundamental frequency is 433.842MHz, so the limit for 20dB bandwidth is 1.08MHz.

Method of measurement: The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector. The vertical Scale is set to 10dB per division. The horizontal scale is set to 100KHz per division.

20dB Bandwidth: 132KHz

The graph as below, represents the emissions take for this device.



Date: 2.FEB.2008 12:12:34

The results: The unit does meet the FCC Part 15 C Section 15.231 requirements.

5.3.3 Dwell Time

Test Requirement: FCC Part 15 C Section 15.231(e)

Test Method: FCC Part15 C Section 15.231(e)

Test Date: 02 February 2008


Requirements:

1. Regulation 15.231 (e) In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

Result:

The duration of the EUT transmission is 960ms, and the silent period between transmissions is about 39.2s greater than 30 times the duration of the transmission and greater than 10 seconds.


Duration time of transmissions



Date: 18.FEB.2008 12:08:03

Silent period between transmissions

Report No.: GLEMR070601768RFT
Page: 16 of 20
FCC ID:VX5270NC



Date: 2.FEB.2008 12:04:31

The results: The unit does meet the FCC Part 15 C Section 15.231 requirements.

6 Photographs - Test Setup

Radiated Emission

7 Photographs - EUT Constructional Details





Report No.: GLEMR070601768RFT
Page: 20 of 20
FCC ID:VX5270NC

