

InterLab Final Report on GSM Desktop Phone Model GDP-04Ai

Report Reference: MDE_JABLO_0903_FCCa

Test Specification FCC 24

Date: January 21, 2010

Test Laboratory:

7 layers AG Borsigstr. 11 40880 Ratingen Germany



DGA-PL-192/99-02

Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7 layers AG Borsigstrasse 11 40880 Ratingen, Germany Phone: +49 (0) 2102 749 0 Fax: +49 (0) 2102 749 350 www.7Layers.com Aufsichtsratsvorsitzender • Chairman of the Supervisory Board: Markus Becker Vorstand • Board: Dr. Hermann Buitkamp Wilfried Klassmann

Registergericht • registered in: Düsseldorf, HRB 44096 USt-IdNr • VAT No.: DE 203159652 TAX No. 147/5869/0385



Test Specification FCC 24

1 Administrative Data

1.1 Project Data

Project Responsible:

Mr. René Houx

Date Of Test Report:

2010/01/21

Date of first test:

2009/11/26

Date of last test:

2009/11/26

1.2 Applicant Data

Company Name:

JabloCOM s.r.o.

Street:

V Nivách 12

City:

466 01 Jablonec nad Nisou

Country:

Czech Republic

Contact Person:

Mr. Ing. Filip Kopriva

Function:

Hardware Engineer +420 483 559 711

Phone: Fax:

+420 483 559 713

E-Mail:

kopriva@jablocom.com

1.3 Test Laboratory Data

The following list shows all places and laboratories involved for test result generation:

7 layers DE

Company Name :

7 layers AG

Street :

Borsigstrasse 11

City:

40880 Ratingen

Country:

Germany

Contact Person:

Mr. Michael Albert

Phone:

+49 2102 749 201

Fax :

+49 2102 749 444

E Mail :

michael.albert@7Layers.de

Laboratory Details

Lab ID

Identification

Responsible

Accreditation Info

Lab 1

Radiated Emissions

Mr. Robert Machulec Mr. Andreas Petz DAR-Registration no. DGA-PL-192/99-02

1.4 Signature of the Testing Responsible

Tad which

Robert Machulec

responsible for tests performed in: Lab 1



Test Specification FCC 24

1.5 Signature of the Accreditation Responsible

Accreditation scope responsible person responsible for Lab 1

2 **Test Object Data**

2.1 General OUT Description

The following section lists all OUTs (Object's Under Test) involved during testing.

OUT: GDP-04Ai

Type / Model / Family:

GSM Desktop Phone

Model GDP-04Ai

Product Category:

Others

Manufacturer:

Company Name:

JabloCOM s.r.o.

Street:

V Nivách 12 466 01 Jablonec nad Nisou

City: Country:

Czech Republic

Company URL:

http://www.jablocom.com

Contact Person: Function:

Mr. Ing. Filip Kopriva Hardware Engineer +420 483 559 711

Phone: Fax:

+420 483 559 713

E-Mail:

kopriva@jablocom.com

Parameter List:

Parameter name

Value

AC Power Supply

periphery equipment: 120 (V)

Antenna gain 1900 band

not specified (dBi) not specified (dBi)

Antenna gain 850 band DC Power Supply

periphery equipment: 6

highest channel

(V)

lowest channel

mid channel

251 (848.8MHz) for GSM850, 810 (1909.8MHz) for GSM1900 128 (824.2MHz) for GSM850, 512 (1850.2MHz) for GSM1900 190 (836.6MHz) for GSM850, 661 (1880.0MHz) for GSM1900

Ancillary Equipment: AC Adapter UP0121A-06PE

Type / Model / Family:

Accessory Made by UMEC

Product Category:

Others

Parameter List:

Parameter name

Value

AC Power Supply

INPUT: AC 100 - 240~ / 50/60Hz / 0.4A MAX.

OUTPUT: DC +6V / 2A / 12W MAX.



-10 °C

Test Specification FCC 24

2.2 **Detailed Description of OUT Samples**

Sample: a01

OUT Identifier GDP-04Ai Sample Description sample #01 Serial No. 356614020036602 HW Status XC13003

SW Status XC609.2.1.15 Date of Receipt 2009/11/20

Low Temp. High Temp. +55 °C Nominal Voltage 120 V Normal Temp. +23 °C

Sample: AC/DC01

AC Adapter UP0121A-06PE **OUT Identifier** AC/DC Adapter #01 Sample Description Date of Receipt 2009/11/20

OUT Features 2.3

Features for OUT: GDP-04Ai

Allowed Values Designation Description Supported Value(s) Features for scope: FCC_v2 AC The OUT is powered by or connected to AC Mains GSM850 EUT supports GSM850 band 824MHz - 849MHz Integral Antenna: permanent fixed antenna, Iant which may be built-in, designed as an indispensable part of the equipment EUT supports PCS1900 band 1850MHz -PCS1900

1910MHz

2.4 **Setups used for Testing**

For each setup a relation is given to determine if and which samples and auxiliary equipment is used. The left side list all OUT samples and the right side lists all auxiliary equipment for the given setup.

Setup No. List of OUT samples List of auxiliary equipment AE No. AE Description Sample No. Sample Description

A01ACDC (sample #01 with AC/DC Adapter No.1)

Sample: AC/DC01 AC/DC Adapter #01

Sample: a01 sample #01



Test Specification FCC 24

3 Results

3.1 General

Documentation of tested

devices:

Available at the test laboratory.

Interpretation of the

test results:

The results of the inspection are described on the following pages, where 'Conformity' or 'Passed' means that the certification criteria were verified and that the tested device is conform to the applied standard.

In cases where 'Declaration' is printed, the required documents

are available in the manufacturers product documentation.

In cases where 'not applicable' is printed, the test case requirements are not relevant to the specific equipment

implementation.

3.2 List of the Applicable Body

(Body for Scope: FCC_v2)

Designation Description

FCC47CFRChIPART24PERSONAL COMMUNICATIONS SERVICES

Part 24, Subpart E - Broadband PCS

3.3 List of Test Specification

Test Specification: FCC part 2 and 24

Date / Version 2009/03/26 Version: 10-1-08 Edition
Title: PART 2 - GENERAL RULES AND REGULATIONS

PART 24 - PERSONAL COMMUNICATIONS SERVICES



Test Specification FCC 24

3.4 Summary

Test Case Identifier / Name			Lab	
Test (condition)	Result	Date of Test	Ref.	Setup
24.1 RF Power Output §2.1046, §24.232				
24.1; Frequency Band = 1900, Mode = GSM, Channel = 512, Frequency = 1850.2MHz, Method = radiated	Passed	2009/11/26	Lab 1	A01ACDC
24.1; Frequency Band = 1900, Mode = GSM, Channel = 661, Frequency = 1880.0MHz, Method = radiated	Passed	2009/11/26	Lab 1	A01ACDC
24.1; Frequency Band = 1900, Mode = GSM, Channel = 810, Frequency = 1909.8MHz, Method = radiated	Passed	2009/11/26	Lab 1	A01ACDC
24.4 Field strength of spurious radiation §2.1	053, §24.238			
24.4; Frequency Band = 1900, Mode = GSM, Channel = 661, Frequency = 1880.0MHz	Passed	2009/11/26	Lab 1	A01ACDC



Test Specification FCC 24

3.5 Detailed Results

3.5.1 24.1 RF Power Output §2.1046, §24.232

Test: 24.1; Frequency Band = 1900, Mode = GSM, Channel = 512, Frequency = 1850.2MHz, Method = radiated

Result: Passed


Setup No.: A01ACDC

Date of Test: 2009/11/26 8:56

Body: FCC47CFRChIPART24PERSONAL COMMUNICATIONS SERVICES

Test Specification: FCC part 2 and 24

Detailed Results:



detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	300	1850.28	31.60	33.00	1.40	-150.0	horizontal	vertical	passed

no further values have been found with a margin of less than 30 dB



Test Specification FCC 24

Test: 24.1; Frequency Band = 1900, Mode = GSM, Channel = 661, Frequency = 1880.0MHz, Method = radiated

Result:

Passed

Setup No.:

A01ACDC

Date of Test:

2009/11/26 8:10


Body:

FCC47CFRChIPART24PERSONAL COMMUNICATIONS SERVICES

Test Specification:

FCC part 2 and 24

Detailed Results:



detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	300	1879.93	32.83	33.00	0.17	-135.0	horizontal	vertical	passed

no further values have been found with a margin of less than 30 dB

Test: 24.1; Frequency Band = 1900, Mode = GSM, Channel = 810, Frequency = 1909.8MHz, Method = radiated

Result: Passed
Setup No.: A01ACDC

Date of Test: 2009/11/26 9:23


Body: FCC47CFRChIPART24PERSONAL COMMUNICATIONS SERVICES

Test Specification: FCC part 2 and 24



Test Specification FCC 24

Detailed Results:



detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	300	1909.87	31.22	33.00	1.78	-120.0	horizontal	vertical	passed

no further values have been found with a margin of less than 30 dB



Test Specification FCC 24

3.5.2 24.4 Field strength of spurious radiation §2.1053, §24.238

Test: 24.4; Frequency Band = 1900, Mode = GSM, Channel = 661, Frequency = 1880.0MHz

Result: Passed


Setup No.: A01ACDC

Date of Test: 2009/11/26 7:17

Body: FCC47CFRChIPART24PERSONAL COMMUNICATIONS SERVICES

Test Specification: FCC part 2 and 24

Detailed Results:



detector	trace	resolution bandwidth /kHz	frequency /MHz	peak value /dBm	limit /dBm	margin to limit /dB	azimuth /°	antenna polarization	EUT orientation	verdict
peak	maxhold	1000	18653.3	-21.48	-13.00	8.48	45.0	vertical	vertical	passed
peak	maxhold	1000	19214.4	-18.64	-13.00	5.64	120.0	vertical	horizontal	passed
peak	maxhold	1000	19312.6	-18.92	-13.00	5.92	45.0	horizontal	vertical	passed
peak	maxhold	1000	19326.7	-17.92	-13.00	4.92	90.0	vertical	vertical	passed
peak	maxhold	1000	19340.7	-19.34	-13.00	6.34	0.0	vertical	horizontal	passed

no further values have been found with a margin of less than 20 dB



Test Specification FCC 24

4 Test Equipment Details

4.1 List of Used Test Equipment

The calibration, hardware and software states are shown for the testing period.

Test Equipment Anechoic Chamber

Lab 1
Manufacturer: Lab 1
Frankonia

Description: Anechoic Chamber for radiated testing

Type: 10.58x6.38x6

 Calibration Details
 Last Execution
 Next Exec.

 FCC renewal
 2006/12/19
 2009/12/19

 IC renewal
 2009/01/21
 2011/01/20

 FCC renewal
 2009/01/07
 2011/01/06

Single Devices for Anechoic Chamber

Single Device Name	Туре	Serial Number	Manufacturer
Air compressor	none	-	Atlas Copco
Anechoic Chamber	10.58 x 6.38 x 6 Calibration Details	none	Frankonia Last Execution Next Exec.
	FCC listing 96716 3m Part15/18 ANSI C64.3 NSA		2009/01/07 2011/01/06 2009/01/21 2011/01/20
Controller Innco 2000	CO 2000	CO2000/328/124 70406/L	Innco innovative constructions GmbH
EMC camera	CE-CAM/1	-	CE-SYS
EMC camera Nr.2	CCD-400E	0005033	Mitsubishi
Filter ISDN	B84312-C110-E1		Siemens&Matsushita
Filter Universal 1A	BB4312-C30-H3	-	Siemens&Matsushita



Test Specification FCC 24

Test Equipment Auxiliary Equipment for Radiated emissions

Lab ID: Lab 1

Description: Equipment for emission measurements

Serial Number: see single devices

Single Devices for Auxiliary Equipment for Radiated emissions

Single Device Name	Туре	Serial Number	Manufacturer	
Antenna mast	AS 620 P		HD GmbH	
Biconical dipole	VUBA 9117	9117108	Schwarzbeck	
	Calibration Details		Last Execution Nex	t Exec.
	Standard Calibration		2008/10/27 2013	3/10/26
Broadband Amplifier 18MHz-26GHz	JS4-18002600-32-5P	849785	Miteq	
	Calibration Details		Last Execution Nex	t Exec.
	Path Calibration		2009/11/16 2010)/05/15
Broadband Amplifier 1GHz-4GHz	AFS4-01000400-1Q-10P-4	-	Miteq	
	Calibration Details		Last Execution Nex	t Exec.
	Path Calibration		2009/11/16 2010)/05/15
Broadband Amplifier BOMHz-18GHz	JS4-00101800-35-5P	896037	Miteq	
	Calibration Details		Last Execution Nex	t Exec.
	Path Calibration		2009/11/16 2010)/05/15
Cable "ESI to EMI Antenna"	EcoFlex10	W18.01- 2+W38.01-2	Kabel Kusch	
	Calibration Details		Last Execution Nex	t Exec.
	Path Calibration		2009/11/16 2010)/05/15
Cable "ESI to Horn Antenna"	UFB311A+UFB293C	W18.02- 2+W38.02-2	Rosenberger Micro-Coa	ЭX
	Calibration Details		Last Execution Nex	t Exec.
	Path Calibration		2009/11/16 2010)/05/15
Double-ridged horn	HF 906	357357/001	Rohde & Schwarz Gmb Co. KG	Н &
	Calibration Details		Last Execution Nex	t Exec.
	Standard Calibration		2009/04/16 2012	2/04/15
Double-ridged horn	HF 906	357357/002	Rohde & Schwarz Gmb	Н &
	Calibration Details			t Exec.
	Standard Calibration		2009/04/28 2012	2/04/27
Dreheinheit	DE 325		HD GmbH	
High Pass Filter	4HC1600/12750-1.5-KK	9942011	Trilithic	
	Calibration Details	55.2011		t Exec.
	Path Calibration)/05/15
High Pass Filter	5HC2700/12750-1.5-KK	9942012	Trilithic	
ngn russ rnter	Calibration Details	J J ¬ Z U I Z		t Exec.
	Path Calibration			0/05/15
High Pass Filter	5HC3500/12750-1.2-KK	200035008	Trilithic	-
	0 111 11 5 1 11		Last Execution Nex	t Exec.
	Calibration Details			
	Path Calibration		2009/11/16 2010)/05/15
_ogper. Antenna		830547/003	2009/11/16 2010 Rohde & Schwarz Gmb Co. KG	



Test Specification FCC 24

Single Devices for Auxiliary Equipment for Radiated emissions (continued)

Single Device Name	Туре	Serial Number	Manufacturer
	Standard Calibration		2009/05/27 2012/05/26
Loop Antenna	HFH2-Z2	829324/006	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	DKD calibration		2008/10/07 2011/10/06
Pyramidal Horn Antenna 26,5 GHz	3160-09	00083069	EMCO Elektronik GmbH
Pyramidal Horn Antenna 40 GHz	3160-10	00086675	EMCO Elektronik GmbH

Test Equipment Auxiliary Test Equipment

Lab ID: Lab 1

Manufacturer: see single devices

Description: Single Devices for various Test Equipment

Type: various
Serial Number: none

Single Devices for Auxiliary Test Equipment

Single Device Name	Туре	Serial Number	Manufacturer
AC Power Source	Chroma 6404	64040001304	Chroma ATE INC.
Broadband Power Divider N (Aux)	1506A / 93459	LM390	Weinschel Associates
Broadband Power Divider SMA	WA1515	A855	Weinschel Associates
Digital Multimeter 01 (Multimeter)	Voltcraft M-3860M	IJ096055	Conrad Electronics
Digital Multimeter 03 (Multimeter)	Fluke 177	86670383	Fluke Europe B.V.
,	Calibration Details		Last Execution Next Exec.
	Standard calibration		2009/10/07 2011/10/06
Digital Oscilloscope [SA2] (Aux)	TDS 784C	B021311	Tektronix GmbH
Fibre optic link Satellite (Aux)	FO RS232 Link	181-018	Pontis
Fibre optic link Transceiver (Aux)	FO RS232 Link	182-018	Pontis
Isolating Transformer	LTS 604	1888	Thalheimer Transformatorenwerke GmbH
Notch Filter Ultra Stable (Aux)	WRCA800/960-6EEK	24	Wainwright
Spectrum Analyser	FSP3	836722/011	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	DKD calibration		2008/10/06 2011/10/05



Test Specification FCC 24

Test Equipment Digital Signalling Devices

Lab ID: Lab 1

Description: Signalling equipment for various wireless technologies.

Single Devices for Digital Signalling Devices

Single Device Name	Туре	Serial Number	Manufacturer
Bluetooth Signalling Unit CBT	CBT	100589	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2008/08/14 2011/08/13
Digital Radio Communication Tester	CMD 55	831050/020	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard calibration		2008/10/07 2010/10/06
Digital Radio Test Set	6103E	2359	Racal Instruments, Ltd.
Universal Radio Communication Tester	CMU 200	102366	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard calibration		2009/02/16 2011/02/15
	HW/SW Status		Date of Start Date of End
	Software: K21 4v21, K22 4v21, K23 4v21, K24 4v21, K K43 4v21, K53 4v21, K56 4v22, K57 4v22, K	·	
	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06	64 4v22,	
Universal Radio	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware:	64 4v22,	Rohde & Schwarz GmbH &
	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06	64 4v22, 69 4v22	Rohde & Schwarz GmbH & Co. KG <i>Last Execution Next Exec.</i>
	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06 	64 4v22, 69 4v22	Co. KG
Universal Radio Communication Tester	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06 CMU 200	64 4v22, 69 4v22	Co. KG Last Execution Next Exec.
	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06 CMU 200 Calibration Details Standard calibration HW/SW Status HW options: B11, B21V14, B21-2, B41, B52V14, B52-2, B B54V14, B56V14, B68 3v04, B95, PCMCIA, U SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K K28 4v10, K42 4v11, K43 4v11, K53 4v10, K K66 4v10, K68 4v10, Firmware: μP1 8v40 01.12.05	837983/052 837983/052 853-2, 165V02	Co. KG <i>Last Execution</i> Next Exec. 2008/12/01 2011/11/30
	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06 CMU 200 Calibration Details Standard calibration HW/SW Status HW options: B11, B21V14, B21-2, B41, B52V14, B52-2, B B54V14, B56V14, B68 3v04, B95, PCMCIA, U SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K K28 4v10, K42 4v11, K43 4v11, K53 4v10, K K66 4v10, K68 4v10, Firmware:	837983/052 837983/052 853-2, 165V02	Co. KG Last Execution Next Exec. 2008/12/01 2011/11/30 Date of Start Date of End
Communication Tester	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06 CMU 200 Calibration Details Standard calibration HW/SW Status HW options: B11, B21v14, B21-2, B41, B52v14, B52-2, B B54v14, B56v14, B68 3v04, B95, PCMCIA, U SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K K28 4v10, K42 4v11, K43 4v11, K53 4v10, K K66 4v10, K68 4v10, Firmware: μP1 8v40 01.12.05 SW:	837983/052 837983/052 853-2, 165V02	Co. KG
Communication Tester	K59 4v22, K61 4v22, K62 4v22, K63 4v22, K K65 4v22, K66 4v22, K67 4v22, K68 4v22, K Firmware: μP1 8v50 02.05.06 CMU 200 Calibration Details Standard calibration HW/SW Status HW options: B11, B21v14, B21-2, B41, B52v14, B52-2, B B54v14, B56v14, B68 3v04, B95, PCMCIA, U SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v11, K K28 4v10, K42 4v11, K43 4v11, K53 4v10, K K66 4v10, K68 4v10, Firmware: μP1 8v40 01.12.05 SW: K62, K69	837983/052 837983/052 837983/052 853-2, 865V02 827 4v10,	Co. KG Last Execution Next Exec. 2008/12/01 2011/11/30 Date of Start Date of End 2007/01/02



Test Specification FCC 24

Test Equipment Emission measurement devices

Lab ID: Lab 1

Description: Equipment for emission measurements

Serial Number: see single devices

Single Devices for Emission measurement devices

Single Device Name	Туре	Serial Number	Manufacturer
Personal Computer	Dell	30304832059	Dell
Signal Generator	SMR 20	846834/008	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2007/12/05 2010/12/04
Spectrum Analyzer	ESIB 26	830482/004	Rohde & Schwarz GmbH &
			Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2007/12/06 2009/12/05

4.2 Laboratory Environmental Conditions

Laboratory	Date	Temperature	Humidity	Air Pressure
Lab 1	2009/11/26	24 °C	38 %	1003 hPa



Test Specification FCC 24

5 Annex

5.1 **Additional Information for OUT Description**



front view



Test Specification FCC 24




back view



Test Specification FCC 24

5.2 Additional Information for Test Plan



setup for radiated testing



Test Specification FCC 24

5.3 Additional Information for Report



	Reference: MDE_JABLO_0903_FCCa
Summary of Test Results	Test Specification FCC 24
The EUT complied with all performed tests as listed in the summary section of this report.	
Technical Report Summary	
Type of Authorization :	
Certification for a GSM cellular radiotelephone device	
Applicable FCC Rules	
Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 0 to 69. The following subparts are applicable to the results in this test report.	
Part 2, Subpart J - Equipment Authorization Procedures, Certification	
§ 2.1046 Measurement required: RF power output § 2.1049 Measurement required: Occupied bandwidth § 2.1051 Measurement required: Spurious emissions at antenna terminals § 2.1053 Measurement required: Field strength of spurious radiation § 2.1055 Measurement required: Frequency stability § 2.1057 Frequency spectrum to be investigated	
Part 24, Subpart E - Broadband PCS	
§ 24.232 Power and antenna height limits § 24.235 Frequency stability § 24.236 Field strength limits § 24.238 Emission limitations for Broadband PCS equipment	
additional documents	
ANSI TIA-603-C-2004	
Description of Methods of Measurements	
RF Power Output	
Standard: FCC Part 24, Subpart E	
The test was performed according to: FCC §2.1046	

Test Description (conducted measurement procedure)



Test Specification FCC 24

- 1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".
- 2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.
- 3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester. Important Settings:
- Channel (Frequency): please refer to the detailed results
- 4) The transmitted power of the EUT was recorded by using a spectrum analyser.

Test Description (radiated measurement procedure)

- 1) The EUT was placed inside an anechoic chamber. Refer to chapter "Setup Drawings". The EUT was coupled to a Digital Communication Tester which was located outside the chamber via a small signalling antenna.
- 2) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester. Important Settings:
- Output Power: Maximum
- Channel: please refer to the detailed results
- 3) A substitution procedure is used so that the readings from the spectrum analyser are corrected and represent directly the equivalent radiated power (related to a lamda/2 dipole).
- 4) The output power was measured in both vertical and horizontal antenna polarisation during the call is established on the lowest channel, mid channel and on the highest channel. To find the worst case power all orientations (X, Y, Z) of the EUT have been measured.
- 5) The test procedure according to TIA-603-C-2004 has been considered.

Test Requirements / Limits

- §2.1046 Measurements Required: RF Power Output
- (a) For transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in § 2.1033(c)(8). The electrical characteristics of the output terminals when this test is made shall be stated. §24.232 Power and antenna height limits
- (c) Mobile/portable stations are limited to 2 watts EIRP peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.
- (e) Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

Emission and Occupied Bandwidth

Standard: FCC Part 24, Subpart E

The test was performed according to: FCC §2.1049

Test Description

- 1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".
- 2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.
- 3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester. Important Settings:
- Output Power: Maximum
- Channel: please refer to the detailed results
- 4) Important Analyser Settings:
- Resolution Bandwidth: >1% of the manufacturer's stated occupied bandwidth
- 5) The maximum spectral level of the modulated signal was recorded as the reference.
- 6) The emission bandwidth is measured as follows:

the two furthest frequencies above and below the frequency of the maximum reference level where the



Test Specification FCC 24

spectrum is -26 dB down have to be found.

7) The occupied bandwidth (99% Bandwidth) is measured as follows:

the occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 percent of the total mean power.

Test Requirements / Limits

§ 2.1049 Measurements required: Occupied bandwidth

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured under the following conditions (as applicable):

(h) Transmitters employing digital modulation techniques - when modulated by an input signal such that its amplitude and symbol rate represent the maximum rated conditions under which the equipment will be operated. The signal shall be applied through any filter networks, pseudo-random generators or other devices required in normal service. Additionally, the occupied bandwidth shall be shown for operation with any devices used for modifying the spectrum when such devices are optional at the discretion of the user.

Spurious emissions at antenna terminals

Standard: FCC Part 24, Subpart E

The test was performed according to FCC §2.1051

Test Description

- 1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".
- 2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.
- 3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester. Important Settings:
- Output Power: Maximum
- Channel: please refer to the detailed results
- 4) Important Analyser Settings
- [Resolution Bandwidth]:
- a) [>=1% of wanted signal bandwidth] in the Span of 1 MHz directly below and above the Band,
- b) otherwise [1 MHz]
- c) [reduced resolution bandwidth] in case the curve of the analyser IF-Filter or the wanted EUT signal leads to an exceeding of the limit, in this case a correction factor was used
- Sweep Time: depending on the transmitting signal, the span and the resolution bandwidth
- 5) The spurious emissions peaks were measured in the frequency range from 9 kHz to 20 GHz (up to the 10th harmonic) during the call was established

Test Requirements / Limits

§ 2.1051 Spurious emissions at antenna terminals

The radio frequency voltage or power generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in Sec. 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

§ 2.1057 Frequency spectrum to be investigated.

- (a) In all of the measurements set forth in Secs. 2.1051 and 2.1053, the spectrum shall be investigated from the lowest radio frequency signal generated in the equipment, without going below 9 kHz, up to at least the frequency shown below:
- (1) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or



Test Specification FCC 24

to 40 GHz, whichever is lower.

- (b) Particular attention should be paid to harmonics and subharmonics of the carrier frequency as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.
- (c) The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.
- (d) Unless otherwise specified, measurements above 40 GHz shall be performed using a minimum resolution bandwidth of 1 MHz.
- § 24.238 Emission limitations for Broadband PCS equipment
- (a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P) dB$. Remark of the test laboratory: This is calculated to be -13 dBm.
- (b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (c) Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas [...].
- (d) If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

For reporting only spurious emission levels reaching to the 20dB margin to limit were noted.

Field strength of spurious radiation

Standard: FCC Part 24, Subpart E

The test was performed according to: FCC §2.1053

Test Description

- 1) The EUT was placed inside an anechoic chamber. Refer to chapter "Setup Drawings". The EUT was coupled to a Digital Communication Tester which was located outside the chamber via a small signalling antenna.
- 2) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester. Important Settings:
- Output Power: Maximum
- Channel: please refer to the detailed results
- 3) A pre-calibration procedure is used so that the readings from the spectrum analyser are corrected and represent directly the equivalent radiated power (related to a lamda/2 dipole).
- 4) All spurious radiation measurements were made with spectrum analyser and the appropriate calibrated antennas for the frequency range of 30 MHz to 20 GHz (up to the 10th harmonic of the transmit frequency). The frequency range from 9 kHz to 30 MHz has been examined during the conducted spurious emission measurements.
- 5) Important Analyser Settings
- [Resolution Bandwidth / Video Bandwidth]:
- a) [3 kHz / 10 kHz] in the Span of 1 MHz directly below and above the Band,
- b) [10 kHz / 30 kHz] in case the curve of the analyser IF-Filter leads to an exceeding of the limit, in this case a worst case correction factor of 20 dB (1 MHz -> 10 kHz) was used
- c) [1 MHz / 3 MHz] otherwise
- Sweep Time: depending on the transmitting signal, the span and the resolution bandwidth
- 6) The spurious emissions peaks were measured in both vertical and horizontal antenna polarisation during the call is established on the lowest channel, mid channel and on the highest channel. To find the worst case peaks all orientations (X, Y, Z) of the EUT have been measured.

Test Requirements / Limits



Test Specification FCC 24

§ 2.1053 Measurements required: Field strength of spurious radiation.

Measurements shall be made to detect spurious emissions that may be radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of Sec. 2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required, with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from halfwave dipole antennas.

- (b) The measurements specified in paragraph (a) of this section shall be made for the following equipment:
- (2) All equipment operating on frequencies higher than 25 MHz.
- § 2.1057 Frequency spectrum to be investigated.
- (a) In all of the measurements set forth in Secs. 2.1051 and 2.1053, the spectrum shall be investigated from the lowest radio frequency signal generated in the equipment, without going below 9 kHz, up to at least the frequency shown below:
- (1) If the equipment operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (b) Particular attention should be paid to harmonics and subharmonics of the carrier frequency as well as to those frequencies removed from the carrier by multiples of the oscillator frequency. Radiation at the frequencies of multiplier stages should also be checked.
- (c) The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.
- (d) Unless otherwise specified, measurements above 40 GHz shall be performed using a minimum resolution bandwidth of 1 MHz.
- \S 24.238 Emission limitations for Broadband PCS equipment
- (a) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. This is calculated to be -13 dBm (effective radiated power) which corresponds to 84.6 dB μ V/m (field strength) in a distance of 3 m.
- (b) Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (c) Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas [...].
- (d) If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

For reporting only spurious emission levels reaching to the 20dB margin to limit were noted.

Frequency stability

Standard: FCC Part 24, Subpart E

The test was performed according to FCC §2.1055

Test Description



Test Specification FCC 24

- 1) The EUT was placed inside a temperature chamber.
- 2) The EUT was coupled to a Digital Communication Tester. Refer to chapter "Setup Drawings".
- 3) The climatic chamber was cycled down/up to a certain temperature, starting with the EUT minimum temperature.
- 4) After the temperature was stabilized the EUT was switched on and a call was established on a Traffic Channel between the EUT and the Digital Communication Tester.

 Important Settings:
- Output Power: Maximum
- Mid Channel
- 5) The frequency error of the EUT was recorded by using an internal measurement function of the Digital Communication Tester immediately after the call was established, five minutes after the call was established and ten minutes after the call was established.
- 6) This measurement procedure was performed for temperature variation from -30°C to +50°C in increments of 10°C, if not otherwise stated in the detailed results.

When the EUT did not operate at certain temperature levels, these measurements were left out.

Test Requirements / Limits

§2.1055 Measurements required: Frequency stability

- (a) The frequency stability shall be measured with variation of ambient temperature as follows:
- (1) From -30° to +50° centigrade for all equipment except that specified in paragraphs
- (a) (2) and (3) of this section.
- (b) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10° centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.
- (d) The frequency stability shall be measured with variation of primary supply voltage as follows:
- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.
- (3) The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided. Effects on frequency of transmitter keying (except for broadcast transmitters) and any heating element cycling at the nominal supply voltage and at each extreme also shall be shown.

§24.235 Frequency stability

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

7Layers interpretation of limit:

To ensure that the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block following limit was used:

+/- 2.5 ppm = 4700 Hz for a frequency of 1880.0 MHz

in accordance with FCC Part 22, Subpart H, §22.355, table C-1: Frequency tolerance for the carrier frequency of mobile transmitters in the Public Mobile Service in the frequency range 821 to 896 MHz.

Band edge compliance

Standard: FCC Part 24, Subpart E

The test was performed according to: FCC §24.238

Test Description



Test Specification FCC 24

Standard: FCC Part 24, Subpart E

The test was performed according to: FCC §24.238

Test Description


- 1) The EUT was coupled to a Spectrum Analyser and a Digital Communication Tester through a Power Divider. Refer to chapter "Setup Drawings".
- 2) The total insertion losses for signal path 1 and signal path 2 were measured. The values were used to correct the readings from the Spectrum Analyser and the Digital Communication Tester.
- 3) A call was established on a Traffic Channel between the EUT and the Digital Communication Tester. Important Settings:
- Output Power: Maximum
- Channel: please refer to the detailed results
- 4) Important Analyser Settings:
- Resolution Bandwidth = Video Bandwidth: >1% of the manufacturer's stated occupied bandwidth

Test Requirements / Limits

§ 24.238 Effective radiated power limits

Refer to chapter "Field strength of spurious radiation".

Setup Drawings




Remark: Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

Principle set-up for radiated measurements




Test Specification FCC 24



<u>Remark:</u> Depending on the frequency range suitable attenuators and/or filters and/or amplifiers are used.

Principle set-up for conducted measurements under nominal conditions



Principle set-up for tests under extreme test conditions



Test Specification FCC 24

6 Index

1 Administrative Data	2
1.1 Project Data	2
1.2 Applicant Data	2
1.3 Test Laboratory Data	2
1.4 Signature of the Testing Responsible	
1.5 Signature of the Accreditation Responsible	
2 Test Object Data	
2 Test object bala	
2.1 General OUT Description	3
2.2 Detailed Description of OUT Samples	4
2.3 OUT Features	4
2.4 Setups used for Testing	4
3 Results	5
3.1 General	5
3.2 List of the Applicable Body	5
3.3 List of Test Specification	5
3.4 Summary	6
3.5 Detailed Results	
3.5.1 24.1 RF Power Output §2.1046, §24.232	
3.5.2 24.4 Field strength of spurious radiation §2.1053, §24.238	
4 Test Equipment Details	
4.1 List of Used Test Equipment	
4.2 Laboratory Environmental Conditions	
5 Annex	
3 Alliex	
5.1 Additional Information for OUT Description	16
5.2 Additional Information for Test Plan	18
5.3 Additional Information for Report	19
6 Index	28