



849 NW STATE ROAD 45  
NEWBERRY, FL 32669 USA  
PH: 888.472.2424 OR  
352.472.5500  
FAX: 352.472.2030  
EMAIL: [INFO@TIMCOENGR.COM](mailto:INFO@TIMCOENGR.COM)  
[HTTP://WWW.TIMCOENGR.COM](http://WWW.TIMCOENGR.COM)

---

## RF Exposure Evaluation Report

|                            |  |
|----------------------------|--|
| <b>APPLICANT</b>           | GUIDANCE MARINE LIMITED  |
|                            | 5 TIBER WAY<br>MERIDIAN BUSINESS PARK<br>LEICESTER LE19 1QP UNITED KINGDOM |
| <b>FCC ID</b>              | VYMVALIDATOR   |
| <b>MODEL NUMBER</b>        | VALIDATOR  |
| <b>PRODUCT DESCRIPTION</b> | X BAND RADAR   |
| <b>STANDARD APPLIED</b>    | CFR 47 Part 2.1091   |
| <b>PREPARED BY</b>         | CHRISTIAN PAWLAK   |

We, TIMCO ENGINEERING, INC. would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and meets the requirements.

The attached report shall not be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

## GENERAL REMARKS

### Attestations

This equipment has been evaluated in accordance with the standards identified in this report. To the best of my knowledge and belief, these evaluations were performed using the procedures described in this report.

I attest that the necessary evaluations were made, under my supervision, at:

**Timco Engineering Inc.**  
**849 NW State Road 45**  
**Newberry, FL 32669**



**Authorized Signatory Name:**

Christian Pawlak

Project Manager

**Date: 3/21/2017**

Applicant: GUIDANCE MARINE LIMITED  
FCC ID: VYMVALIDATOR  
Report: 2171BUT16RF EXP MPE RPT REV2.DOCX

## RF Exposure Requirements

### General information

Device type: X BAND RADAR

### Antenna

The manufacturer does not specify an antenna, but a typical antenna has a gain of 0 dBi.

| Configuration | Antenna p/n | Type | Max. Gain (dBi) |
|---------------|-------------|------|-----------------|
| Fixed mounted | Any         | omni | 0               |

### MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for general uncontrolled exposure environment is shown in FCC rule Part 1.11310, Table 1.

| Insert values in yellow highlighted boxes to determine Minimum Separation Distance |                    |                    |        |                 |          |         |
|--|--------------------|--------------------|--------|-----------------|----------|---------|
| Max Power  | 0.024              | W                  | equals | Max Power       | 24       | mW      |
| Duty Cycle   | 100                | %                  | equals | Duty Factor     | 1        | numeric |
| Antenna Gain   | 6                  | dBi                | equals | Gain numeric    | 3.981072 | numeric |
| Coax Loss  | 0                  | dB                 |        | Gain - Coax Los | 3.981072 | numeric |
| Power Density  | 1                  | mW/cm <sup>2</sup> |        |                 |          |         |
| Enter power Density from the chart to the right                                    |                    |                    |        |                 |          |         |
| Frequency  | 9230               | MHz                |        |                 |          |         |
| Rule Part 1.1310, Table 1 (B)  |                    |                    |        |                 |          |         |
| Frequency rang   | Power der          | Enter this value   |        |                 |          |         |
| MHz  | mW/cm <sup>2</sup> | mW/cm <sup>2</sup> |        |                 |          |         |
| 0.3-1.34   | 100                | 100                |        |                 |          |         |
| 1.34-30  | 180/f <sup>2</sup> | 0.0                |        |                 |          |         |
| 30-300   | 0.2                | 0.2                |        |                 |          |         |
| 300-1,500  | f/1500             | 6.2                |        |                 |          |         |
| 1,500-100,000  | 1                  | 1                  |        |                 |          |         |

f = frequency in MHz

| Minimum Separation Distance | 3 cm | 0.03 m |
|-----------------------------|------|--------|
|-----------------------------|------|--------|

Minimum Separation in Inches      1.084763 Inches