

# RF Exposure Evaluation declaration

Product Name	802.11a CPE
Model No.	CPE2618; CPE2514
FCC ID	VYXWIFI-005

Applicant	ARGtek Communication Inc.
Address	8F-9, NO. 4, LANE 609, SEC. 5, CHUNG HSIN RD., SAN CHUNG CITY, TAIPEI HSIEN TAIWAN R.O.C.

Date of Receipt	Aug. 31, 2009
Date of Declaration	Nov. 06, 2009
Report No.	099058R-RFUSP05V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.  
This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

**LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in  $\text{mW/cm}^2$

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1  $\text{mW/cm}^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : 802.11a CPE  
Test Item : RF Exposure Evaluation  
Test Site : No.3 OATS

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 18 dBi in logarithm scale.

#### 802.11a

##### Output Power Into Antenna & RF Exposure Evaluation Distance (18 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
149	5745.00	35.0752	0.440282
157	5785.00	33.5738	0.421435
165	5825.00	40.7380	0.511364

#### 802.11n(20M)

##### Output Power Into Antenna & RF Exposure Evaluation Distance (18 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
149	5745.00	42.7563	0.536699
157	5785.00	35.2371	0.442314
165	5825.00	38.1944	0.479436

#### 802.11n(40M)

##### Output Power Into Antenna & RF Exposure Evaluation Distance (18 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
151	5755.00	39.5367	0.496284
159	5795.00	29.1743	0.366210

The distance r (4<sup>th</sup> column) calculated from the Friis transmission formula is far shorter than 20 cm separation requirement.