

RF EXPOSURE REPORT

REPORT NO.: SA990716E07

MODEL NO.: ARG-1005

FCC ID: VYXWIFI-008

ACCORDING: FCC Guidelines for Human Exposure

IEEE C95.1

APPLICANT: Argtek Communication Inc.

ADDRESS: 8F-9, No. 4, Lane 609, Sec. 5, Chung Hsin Rd. San

Chung City, Taipei Hsien

ISSUED BY: Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen,

Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan

Report No.: SA990716E07 Report Format Version 3.0.1



RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in our lab, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2.RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency	Electric Field	Magnetic Field	Power Density	Average Time	
Range	Strength (V/m)	Strength (A/m)	(mW/cm ²)	(minutes)	
(MHz)					
	(A)Limits For Occupational / Control Exposures				
300-1500		•••	F/300	6	
1500-100,000		•••	5	6	
(B)L	(B)Limits For General Population / Uncontrolled Exposure				
300-1500	•••	•••	F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

Report No.: SA990716E07



3. Friis Formula

Friis transmission formula : $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref.: David K. Cheng, *Field and Wave Electromagnetics*, Second Edition, Page 640, Eq. (11-133).

4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. Classification

Report No.: SA990716E07

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**



6.TEST RESULTS

6.1 Antenna Gain

The maximum Gain measured in Fully Anechoic Chamber is 7dBi or 5.011872 (numeric) for panel antenna and 5dBi or 3.16228 (numeric) for dipole antenna.

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

For Panel Antenna:

802.11b:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm²)
1	2412	74.1	0.074	1.0
6	2437	95.5	0.095	1.0
11	2462	102.3	0.102	1.0

802.11g:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm²)	Limit of Power Density (mW/cm²)
1	2412	691.8	0.690	1.0
6	2437	758.6	0.756	1.0
11	2462	758.6	0.756	1.0

802.11n (20MHz):

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm²)
1	2412	631.0	0.629	1.0
6	2437	660.7	0.659	1.0
11	2462	707.9	0.706	1.0

802.11n (40MHz):

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm²)	Limit of Power Density (mW/cm ²)
1	2422	524.8	0.523	1.0
4	2437	660.7	0.659	1.0
7	2452	562.3	0.561	1.0

Report No.: SA990716E07



For Dipole Antenna:

802.11b:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm²)
1	2412	74.1	0.047	1.0
6	2437	95.5	0.060	1.0
11	2462	102.3	0.064	1.0

802.11g:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm²)
1	2412	691.8	0.435	1.0
6	2437	758.6	0.477	1.0
11	2462	758.6	0.477	1.0

802.11n (20MHz):

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm²)
1	2412	631.0	0.397	1.0
6	2437	660.7	0.416	1.0
11	2462	707.9	0.445	1.0

802.11n (40MHz):

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm²)	Limit of Power Density (mW/cm ²)
1	2422	524.8	0.330	1.0
4	2437	660.7	0.416	1.0
7	2452	562.3	0.354	1.0

--- END ---

Report No.: SA990716E07