



RF Exposure Estimation

1. Introduction

Applicant:	NINGBO DOOYA MECHANIC & ELECTRONIC TECHNOLOGY CO., LTD.
Address:	No.168 Shengguang Road, Luotuo, Zhenhai, Ningbo ZHEJIANG,China
FCC ID:	VYYDV24WES0634V0
Product:	DC Venetian Blinds Drive
Model No.:	DVQ24WE/S-0.6/34, DV24WE/S-0.6/34, DVQ24WE/S-0.2/28, DV24WE/S-0.2/28
Reference RF report #	709502501815-00B

2. 447498 D04 Interim General RF Exposure Guidance v01

B.2 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance. The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A). The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

3. RF Exposure Evaluation

Per the test report included herein, for 433.92MHz

According to C63.10-2020 Annex G

$$\text{EIRP} = \text{pt} \times \text{gt} = (\text{E} \times \text{d})^2 / 30 \quad (\text{G.1})$$

where

pt is the transmitter output power in watts

gt is the numeric gain of the transmitting antenna (dimensionless)

E is the electric field strength in V/m

d is the measurement distance in meters (m)

$$\text{ERP} = \text{EIRP} / 1.64 = (\text{E} \times \text{d})^2 / (30 \times 1.64) = (\text{E} \times \text{d})^2 / 49.2 \quad (\text{G.2})$$

Transmitter output power for 433.92MHz Function

Field Strength (EMeas):	91.10(dBuV/m)=0.0359V/m (f=433.92 MHz)
Measurement Distance(dMeas):	3 (m)
ERP (W):	0.0002357W
ERP (mW):	0.2357mW




We used the maximum ERP/EIRP to perform RF exposure exemption evaluation.

	Evaluation method	Exempt Limit (mW)	Verdict
■	Blanket 1 mW Blanket Exemption	1mW	Yes
□	MPE-based Exemption (ERP)	7mW (ERP)	N/A
□	SAR-based Exemption (Pth)	3060mW	N/A

So, the device is qualified for SAR test exemption, the exemption report is in lieu of the SAR report.

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
Reviewed by: Prepared by: Tested by:

		
		
Jiaxi XU Reviewer Engineer Date: 2025-04-15	Hui TONG Project Engineer Date: 2025-04-15	Tianji XU Test Engineer Date: 2025-04-15

-----End of Test Report-----