

RF Exposure Report

Report No.: SA170809E07A

FCC ID: VZ9170001

Test Model: EAP738

Series Model: HSG328

Received Date: Aug. 09, 2017

Test Date: Sep. 06, 2017

Issued Date: Mar. 29, 2018

Applicant: 4IPNET, INC.

Address: 5F., No.367, Fuxing N. Rd., Songshan Dist., Taipei City 105, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,

Taiwan R.O.C.

FCC Registration / Designation Number:

723255 / TW2022





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



Table of Contents

Rele	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.1	Limits for Maximum Permissible Exposure (MPE)	5
2.2	MPE Calculation Formula	5
2.3	Classification	5
	Antenna Gain	
2.5	Calculation Result of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA170809E07A	Original release.	Mar. 29, 2018

Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SA170809E07A Reference No.: 180108E07



1 Certificate of Conformity

Product: Enterprise Access Point

Brand: 4ipnet

Test Model: EAP738

Series Model: HSG328

Sample Status: ENGINEERING SAMPLE

Applicant: 4IPNET, INC.

Test Date: Sep. 06, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : , **Date:** Mar. 29, 2018

Mary Ko / Specialist

May Chen / Manager



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)					
Limits For General Population / Uncontrolled Exposure									
0.3-1.34	614	1.63	(100)*	30					
1.34-30	824/f	2.19/f	(180/f ²)*	30					
30-300	27.5	0.073	0.2	30					
300-1500			f/1500	30					
1500-100,000			1.0	30					

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 28cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN antenna Spec.												
Antenna No.	Brand	d Model		Antenna Gain(d		rai	uency nge Hz)	Antenna Type		Connecter Type		Cable Length (mm)
Antenna 1 Acctor		n 120G000001	600000153A 4.17 5.83				2.4835 ~5.85	Monopole		i-pex		180
Antenna 2 Accto		120G00000153A		4.27		2.4~2	2.4835	Monopole		i-pex		160
				8.18 Bluetooth anter			5.15~5.85 nna Spec.		<u> </u>			
Brand	rand Model Antenna Net Frequency range Antenna Type		а Туре	Connecter Type		Ca	able Length (mm)					
Accton		20G00000153A		4.09	2.4~2.4835		PIFA		i-pex		80	

Report No.: SA170809E07A Reference No.: 180108E07



2.5 Calculation Result of Maximum Conducted Power

For WLAN:

Frequency Band (MHz)	Max. Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)
2412-2462	864.046	7.23	28	0.46346	1
5180-5240	349.188	10.09	28	0.36185	1
5745-5825	417.679	10.09	28	0.43283	1

NOTE:

2.4 GHz: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 7.23$ dBi 5 GHz: Directional gain = $10 \log[(10^{G0/20} + 10^{G1/20})^2 / 2] = 10.09$ dBi

For Bluetooth:

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	1.225	4.09	28	0.00032	1

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz + Bluetooth = 0.46346 / 1 + 0.43283 / 1 + 0.00032 / 1 = 0.89661Therefore the maximum calculations of above situations are less than the "1" limit.

--- END ---