MPE CALCULATION

FCC ID: W22-ATH

RF Exposure Requirements: 47 CFR §1.1307(b)
RF Radiation Exposure Limits: 47 CFR §1.1310

RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65

EUT Frequency Band: 2401.5-2479.5 MHz, Limits for General Population/Uncontrolled Exposure in the band of: 1500-100,000 MHz

Power Density Limit: 1 mW / cm²

Equation: $S = PG / 4\pi R^2 \text{ or } R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

EUT: Wireless Large display tag, Model No.: ATH100ES

PIFA Antenna

Prediction distance 20cm

(FHSS 2.4GHz): Power = 19.96 dBm, Antenna Gain = 0 dBi, Power density = 0.0248 mW/cm²

Туре	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Directional Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm²)	MPE Limit (mW/cm²)	Pass/ Fail
FHSS 2.4GHz	2401.5	19.96	0	0	±1dB	20.96	20	0.0248	1	Pass

The Above Result had shown that the device complied with MPE requirement at a prediction distance of 20cm.

Dem

Completed By: Deon Dai

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: 08/28/2018