



User Guide

Product Overview

The devices Mini PCI-e adapter cards contain an Atheros chip for Wireless LAN applications. The mini PCI-e adapter cards support key security features like Wi-Fi Protected Access (WPA), WPA2, WEP and 802.1x.

Typical application of the card is integration into other wireless products such as AP/ Router which is used distance 20 cm away human body.

Packaging Contents

The mini PCI-e card package contains the following item(s):

1 x Wireless Mini PCI-e Adapter

Installation guide

- Shut down the power of the platform
- Align the Mini PCI-e adapter with the Mini PCI-e socket on the platform
- Adjust and push down the Mini PCI-e adapter gently until the metal locking levers on the Mini PCI-e socket is latched. (Please take note that the Mini PCI-e adapter can only fit in one direction due to the keyed notch. Wrong orientation will cause improper installation and may damage the Mini PCI-e socket)
- Connect the antenna(s) on the mini PCI-e module
- Reboot on the platform
- Install drivers if necessary

Frequency

2412 ~ 2462 MHz

5180 ~ 5240MHz, 5745 ~ 5825MHz

Connector: Reverse U.FL PLUG

FCC Statement



This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

FCC Caution: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate this equipment.

This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

FCC Caution

For product available in the USA/Canada market, only channel 1~11 can be operated. Selection of other channels is not possible.

FCC Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20 cm between the radiator & your body.

This device is intended only for OEM integrators under the following conditions:

- 1) The antenna must be installed such that 20 cm is maintained between the antenna and users, and the maximum antenna gain allowed for use with this device is 2dBi.
- 2) The transmitter module may not be co-located with any other transmitter or antenna.

As long as 2 conditions above are met, further transmitter test will not be required. However, the OEM integrator is still responsible for testing their end-product for any additional compliance requirements required with this module installed

Important Notes

In the event that these conditions can not be met (for example certain laptop configurations or co-location with another transmitter), then the FCC authorization is no longer considered valid and the FCC ID can not be used on the final product. In these circumstances, the OEM integrator will be responsible for re-evaluating the end product (including the transmitter) and obtaining a separate FCC authorization.

Label for end product must include

This transmitter module is authorized only for use in device where the antenna may be installed such that 20 cm may be maintained between the antenna and users. The final end product must be labeled in a visible area with the following: "Contains FCC ID: **W23-JWX5556**". The grantee's FCC ID can be used only when all FCC compliance requirements are met.

Manual Information To the End User

The OEM integrator has to be aware not to provide information to the end user regarding how to install or remove this RF module in the user's manual of the end product which integrates this module.

The end user manual shall include all required regulatory information/warning as show in this manual.

Appendix

The antenna information for certification is listed as below;

- Frequency : 2400 ~ 2500 MHz, 5150 ~ 5850 MHz
- Gain : 2 dBi
- VSWR : ≤ 2.0
- Type : Omni-directional
- Impedance : 50 Ohm
- Connector Type : SMA Male Reverse

CE Mark Warning



This device complies with **Directive 2014/53/EU** issued by the Commission of the European Community.

A minimum separation distance of 20 cm must be maintained between the user's body and the device, including the antenna during body-worn operation to comply with the RF exposure requirements in Europe.

Frequency bands and Powers

a. Frequency :

2412 ~ 2462 MHz

5180 ~ 5240MHz, 5745 ~ 5825MHz

b. Maximum output power

JWX6082/JWX6083: 19 dBm @ 1 ~ 11Mbps

JWX6052/JWX6053: 18 dBm @ 1 ~ 11Mbps

JWX6055/JWX6056: 20 dBm @ 1 ~ 11Mbps

Components and accessories

The module is delivered without an antenna, the suggest antenna information is listed as below:

- Frequency : 2400 ~ 2500 MHz, 5150 ~ 5850 MHz
- Type : Omni, Directional
- Impedance : 50 Ohm
- Connector Type : SMA Male Reverse

The module must be installed at host device and installed with proper driver before to use it

Operating temperature

Temperature Range	-20°C ~ +70°C	-40°C ~ +85°C
Model name	JWX6083, JWX6052, JWX6055	JWX6082, JWX6053, JWX6056

Warning:

The over temperature could let module stop functioning or function abnormally.

Safety Information

- Don't power on module without antenna installed
- Don't disassemble the product, or make repairs yourself. You run the risk of electric shock and voiding the limited warranty
- Avoid water and wet locations

Simplified DoC

Hereby, jjPlus CORP. declares that the radio equipment is in compliance with Directive 2014/53/EU

The full text of the EU declaration of conformity is available at the following internet address:
http://www.jjplus.com/?page_id=3320

Importer Information



Requirements

in AT/BE/BG/CZ/DK/EE/FR/DE/IS/IE/IT/EL/ES/CY/LV/LI/LT/LU/HU/MT/NL/NO/PL/PT/RO/SI/
SK/TR/FI/SE/CH/UK/HR. 5150MHz~5350MHz is for indoor use only.

jjPlus CORP.

13F-3, No.120, Qiaohe Rd., Zhonghe Dist., New Taipei City 235, Taiwan