

## FCC TEST REPORT

**FCC ID** : W2IAM-14P

**Applicant** : Adomax Electronic Technology Co., (Z.Q.) Ltd.  
**Address** : East Side of Qiancun, Yingbin Road, Zhaoqing,  
Guangdong, China

**Equipment Under Test (EUT) :**

**Product Name** : Mouse  
**Model No.** : AM-14P(USB),AM-14P(USB+PS/2)

**Standards** : FCC PART15 SUBPART B

**Date of Test** : July 22, 2009

**Test Engineer** : Zero.Zhou

**Reviewed By** : 

<b>Test Result :</b>	PASS *
----------------------	--------

\* The sample detailed above has been tested to the requirements of Council Directives ANSI C63.4:2003. The test results have been reviewed against the Directives above and found to meet their essential requirements.

**Prepared By:**

**Waltek Services (Shenzhen) Co., Ltd.**

1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District,  
Shenzhen 518105, China

Tel :+86-755-27553488  
Fax:+86-755-27553868

## 1 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Radiated Emission (30MHz to 1GHz)	FCC PART 15, SUBPART B: 2007	ANSI C63.4: 2003	Class B	PASS
Conducted Emission (150KHz to 30MHz)	FCC PART 15, SUBPART B: 2007	ANSI C63.4: 2003	Class B	PASS

## 2 Contents

<b>1</b>	<b>COVER PAGE</b>	<b>1</b>
<b>1</b>	<b>TEST SUMMARY</b>	<b>2</b>
<b>2</b>	<b>CONTENTS</b>	<b>3</b>
<b>3</b>	<b>GENERAL INFORMATION</b>	<b>4</b>
3.1	CLIENT INFORMATION .....	4
3.2	GENERAL DESCRIPTION OF E.U.T. ....	4
3.3	DETAILS OF E.U.T. ....	4
3.4	DESCRIPTION OF SUPPORT UNITS .....	4
3.5	STANDARDS APPLICABLE FOR TESTING .....	4
3.6	TEST FACILITY .....	5
3.7	TEST LOCATION .....	5
<b>4</b>	<b>EQUIPMENT USED DURING TEST</b>	<b>6</b>
<b>5</b>	<b>EMISSIONS TEST RESULTS</b>	<b>8</b>
5.1	CONDUCTED EMISSION DATA .....	8
5.1.1	<i>E.U.T. Operation</i> .....	8
5.1.2	<i>EUT Setup</i> .....	9
5.1.3	<i>Conducted Emission Test Result</i> .....	10
5.1.4	<i>Photograph- Test Setup for Conducted Emission</i> .....	12
5.2	RADIATION EMISSION DATA .....	13
5.2.1	<i>Measurement Uncertainty</i> .....	13
5.2.2	<i>EUT Setup</i> .....	13
5.2.3	<i>Spectrum Analyzer Setup</i> .....	14
5.2.4	<i>Test Procedure</i> .....	14
5.2.5	<i>Corrected Amplitude &amp; Margin Calculation</i> .....	14
5.2.6	<i>Summary of Test Results</i> .....	15
5.2.7	<i>Photograph – Radiation Emission Test Setup</i> .....	17
<b>6</b>	<b>PHOTOGRAPHS - CONSTRUCTIONAL DETAILS</b>	<b>18</b>
6.1	EUT – FRONT VIEW .....	18
6.2	EUT - BACK VIEW .....	18
6.3	EUT – OPEN VIEW .....	19
6.4	EUT – PCB-FRONT VIEW .....	19
6.5	EUT – PCB -BACK VIEW .....	20
<b>7</b>	<b>FCC LABEL</b> .....	<b>21</b>

### 3 General Information

#### 3.1 Client Information

Applicant:

Address of Applicant:

Adomax Electronic Technology Co., (Z.Q.) Ltd.

East Side of Qiancun, Yingbin Road, Zhaoqing,  
Guangdong, China

Manufacturer:

Address of Manufacturer:

Adomax Electronic Technology Co., (Z.Q.) Ltd.

East Side of Qiancun, Yingbin Road, Zhaoqing,  
Guangdong, China

#### 3.2 General Description of E.U.T.

Product Name:

Mouse

Model No. :

AM-14P(USB),AM-14P(USB+PS/2)

#### 3.3 Details of E.U.T.

Power supply:

USB or PS/2 input

#### 3.4 Description of Support Units

The EUT has been tested as independent unit.

#### 3.5 Standards Applicable for Testing

The customer requested FCC tests for a mouse. The standards used were FCC PART 15  
SUBPART B.

### **3.6 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **IC – Registration No.:7760A**

Waltek Services(Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration No.:7760A,July 24,2008.

- **FCC – Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, July 9, 2008

### **3.7 Test Location**

All Emission test were performed at:-

Waltek Services(Shenzhen) Co., Ltd. at 1/F, Fukangtai Building, West Baima Rd.,Songgang Street, Baoan District, Shenzhen, China

## 4 Equipment Used during Test

Equipment Name	Manufacturer Model	Equipment No	Internal No	Specification	Cal. Date	Due Date	Cert. No	Uncertainty
EMC Analyzer	Agilent/ E7405A	MY45114 943	W2008001	9k-26.5GHz	Aug-08	Aug-09	Wws20 081596	±1dB
Trilog Broadband Antenne 30-3000 MHz	SCHWARZ BECK MESS-ELEKTROM / VULB9163	336	W2008002	30-3000 MHz	Aug-08	Aug-09		±1dB
Broad-band Horn Antenna 1-18 GHz	SCHWARZ BECK MESS-ELEKTROM / VULB9163	667	W2008003	1-18GHz	Aug-08	Aug-09		f<10 GHz: ±1dB 10GHz<f <18 GHz: ±1.5dB
Broadband Preamplifier 0.5-18 GHz	SCHWARZ BECK MESS-ELEKTROM / BBV 9718	9718-148	W2008004	0.5-18GHz	Aug-08	Aug-09		±1.2dB
10m Coaxial Cable with N-male Connectors usable up to 18GHz,	SCHWARZ BECK MESS-ELEKTROM / AK 9515 H	-	-	-	Aug-08	Aug-09		-
10m 50 Ohm Coaxial Cable with N-plug,individual length,usable up to 3(5)GHz, Connector	SCHWARZ BECK MESS-ELEKTROM / AK 9513				Aug-08	Aug-09		
Positioning Controller	C&C LAB/ CC-C-IF				N/A	N/A		
Color Monitor	SUNSPO/ SP-14C				N/A	N/A		
Test Receiver	ROHDE&SC HWARZ/ ESPI	101155	W2005001	9k-3GHz	Aug-08	Aug-09	Wws20 080942	±1dB
EMI Receiver	Beijingkehuan	KH3931		9k-1GHz	Aug-08	Aug-09		
Two-Line V-Network	ROHDE&SC HWARZ/ ENV216	100115	W2005002	50Ω/50μ H	Aug-08	Aug-09	Wws20 080941	±10%

Equipment Name	Manufacturer Model	Equipment No	Internal No	Specification	Cal. Date	Due Date	Cert. No	Uncertainty
V—LISN	SCHWARZ BECK MESS — ELEKTRON IK	NSLK 8128	8128-259	9k-30MHz	Aug-08	Aug-09		
Absorbing Clamp	ROHDE&SC HWARZ/ MDS-21	100205	W2005003	impandance 50Ω loss : 17 dB	Aug-08	Aug-09	Wws20 080943	±1dB
10m 50 Ohm Coaxial Cable with N- plug,indivi dual length,usa ble up to 3(5)GHz, Connec tors	SCHWARZ BECK MESS- ELEKTROM / AK 9514				Aug-08	Aug-09		
PC	accer	AG1720	-	-	Aug-08	Aug-09		±1dB

## 5 Emissions Test Results

### 5.1 Conducted Emission Data

Test Requirement:	FCC Part15.107
Test Method:	ANSI C63.4:2003
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class:	Class B
Limit:	66-56 dB $\mu$ V between 0.15MHz & 0.5MHz 56 dB $\mu$ V between 0.5MHz & 5MHz 60 dB $\mu$ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit

#### 5.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.5 °C

Humidity: 51 % RH

Atmospheric Pressure: 1012 mbar


EUT Operation :

The EUT was tested according to ANSI C63.4:2003. The frequency spectrum from 150kHz to 30MHz was investigated.

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

### 5.1.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.4:2003, The specification used in this report was the FCC Part15 B 15.107 limits.




The EUT was placed on the test table in working mode and connected with PC system, we pretest USB connector and PS/2 connector, the max. emission was detected using USB connector, so the data were shown as follow.


### 5.1.3 Conducted Emission Test Result

An initial pre-scan was performed on the live and neutral lines.

Live line:



Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.2460	19.76	10.64	30.40	61.89	-31.49	QP	
2	0.2460	10.58	10.64	21.22	51.89	-30.67	AVG	
3	0.3220	16.75	10.67	27.42	59.65	-32.23	QP	
4	0.3220	9.76	10.67	20.43	49.65	-29.22	AVG	
5	0.6820	16.86	11.05	27.91	56.00	-28.09	QP	
6	0.6820	8.62	11.05	19.67	46.00	-26.33	AVG	

#### 5.1.4 Photograph- Test Setup for Conducted Emission



## 5.2 Radiation Emission Data

Test Requirement:	FCC Part15.109
Test Method:	ANSI C63.4:2003
Test Result:	PASS
Frequency Range:	30MHz to 1GHz
Measurement Distance:	3m
Class:	Class B
Limit:	40.0 dB $\mu$ V/m between 30MHz & 88MHz 43.5 dB $\mu$ V/m between 88MHz & 216MHz 46.0 dB $\mu$ V/m between 216MHz & 960MHz 54.0 dB $\mu$ V/m zbove 960MHz
Detector:	Peak for pre-scan (120kHz resolution bandwidth) Quasi-Peak if maximised peak within 6dB of limit

### 5.2.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in the field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Waltek EMC Lab is  $\pm 5.03$ dB.

### 5.2.2 EUT Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4:2003, The specification used in this report was the FCC Part15 B limits.

The EUT was placed on the test table in working mode and connected with PC system, we pretest USB connector and PS/2 connector, the max.emission was detected using USB connector, so the data were shown as follow.

### 5.2.3 Spectrum Analyzer Setup

According to FCC Part15 B Rules, the system was tested 30 to 1000MHz.

Start Frequency.....	30 MHz
Stop Frequency.....	1000MHz
Sweep Speed Auto	
IF Bandwidth.....	120 KHz
Video Bandwidth.....	100 KHz
Quasi-Peak Adapter Bandwidth .....	120 KHz
Quasi-Peak Adapter Mode .....	Normal
Resolution Bandwidth .....	100 KHz

### 5.2.4 Test Procedure

The radiated emissions test.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB $\mu$ V of specification limits), and are distinguished with a "Qp" in the data table.

The EUT was under normal mode during the final qualification test and the configuration was used to represent the worst case results.

### 5.2.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$


The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB $\mu$ V means the emission is 7dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Class B Limit}$$


### 5.2.6 Summary of Test Results

According to the data in this section, the EUT complied with the FCC Part15 B standards.

Antenna polarization:Horizontal



Antenna polarization:Vertical



### 5.2.7 Photograph – Radiation Emission Test Setup



## 6 Photographs - Constructional Details

### 6.1 EUT – Front View




### 6.2 EUT - Back View




### 6.3 EUT – Open View



### 6.4 EUT – PCB-Front View



## 6.5 EUT – PCB -Back View



## 7 FCC Label

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:(1)this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

The Label must not be a stick-on paper. The Label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Proposed Label Location on EUT

EUT Bottom View/proposed FCC Mark Location

