

TEST REPORT

Reference No...... : WTF20S04018829W003 V1
FCC ID : W2X-AUR524
Applicant..... : HANGZHOU LINGFENG ELECTRONIC Co.,LTD
Address..... : No.1 Hetai Road, ZhongTai Street, Yuhang District, Hangzhou, Zhejiang, China
Manufacturer : The same as above
Address..... : The same as above
Product..... : STAGE ROUTER
Model(s) : AUR524/WRC-1
Brand Name..... : N/A
Standards..... : FCC Part 2.1091
Date of Receipt sample : 2020-04-14
Date of Test : 2020-04-15 to 2020-05-25
Date of Issue..... : 2020-06-05
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Approved by:

Ford Wang

Ford Wang / Project Engineer



Philip Zhong

Philip Zhong / Manager

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF E.U.T.	4
4.2 DETAILS OF E.U.T.	4
4.3 TEST FACILITY	4
5 TEST SUMMARY	5
6 RF EXPOSURE.....	6
6.1 PROCEDURES AND REQUIREMENTS	6
6.2 TEST RESULT	7

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTF20S04018 829W003	2020-04-14	2020-04-15 to 2020-05-25	2020-05-26	original	-	Replaced
WTF20S04018 829W003 V1	2020-04-14	2020-04-15 to 2020-05-25	2020-06-05	Version 1	Updated	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	STAGE ROUTER
Model(s):	AUR524/WRC-1
Model Description:	N/A
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40 5G-802.11a/n/ac HT20 /n/ac HT40 /ac HT80
Hardware Version:	we1326v05
Software Version:	19.1101

4.2 Details of E.U.T.

Ratings:	AC 120V 60Hz
----------	--------------

4.3 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Services(Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	2.1091	PASS

6 RF Exposure

Test Requirement: FCC Part 2.1091

Test Mode: The EUT work in test mode(Tx).

6.1 Procedures and Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

FCC Part 1.1307:

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ;

*Plane-wave equivalent power density

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, d=20cm, as well as the gain of the used antenna, the RF power density can be obtained

6.2 Test Result

FCC Part 2.1091:

A distance of 20cm normally can be maintained between the user and the device.

Mode	Antenna Gain (dBi)	Antenna Gain (numeric)	Max.Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
2.4G WIFI	3.00	1.995	22.28	169.04	0.067100	1
5G WIFI	3.00	1.995	20.01	100.23	0.039785	1

=====End of Report=====