



FCC PART 15.249 MEASUREMENT AND TEST REPORT

For

Videotech Technology Development Co., Ltd.

Bldg 12, Section B, BaoSheng Industrial Area, BaiNiKeng, PingHu Town, Shenzhen, Guangdong, China.

FCC ID: W3DVT-6106

Report Type:		Product Type:
Original Report		i Ball Wireless Trailer Hitch Camera.
Test Engineer:	Chris Peng	Chris bug
	RSZ081114	401
Report Date:	2009-01-15	
	Green Xu	Green. Thu
Reviewed By:	EMC Manag	ger
Prepared By:	6/F, the 3rd ShiHua Roa Shenzhen, C Tel: +86-755	ompliance Laboratories Corp. (Shenzhen) Phase of WanLi Industrial Building, ad, FuTian Free Trade Zone Guangdong, China 5-33320018 55-33320008

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government. * This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*"

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
MECHANICAL DESCRIPTION OF EUT	3
EUT PHOTOGRAPH	
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
Test Methodology	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
JUSTIFICATION	5
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
CONFIGURATION OF TEST SETUP	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
	_
§15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	7
§15.205 §15.209 §15.249(A) §15.249(D) - RADIATED EMISSIONS	8
APPLICABLE STANDARD	8
MEASUREMENT UNCERTAINTY	8
TEST EQUIPMENT SETUP	
EUT SETUP	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	
§15.249(D) – OUT OF BAND EMISSIONS	13
APPLICABLE STANDARD	
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	14
DECLARATION LETTER	15

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *Videotech Technology Development Co., Ltd.*'s product, model: *VT-C6106* or the "EUT" as referred to in this report is a *i ball wireless trailer hitch camera*., rated input voltage: DC 12V power supply source.

Mechanical Description of EUT

The *Videotech Technology Development Co., Ltd.*'s product, model number: *VT-C6106*, measures approximately 10.0 cm L x 10.0 cm W x 4.5 cm H.

*Note: The series products, model VT-C6106 and HITCH VU i ball camera, we select VT-C6106 to test, the all model have same circuit diagram, PCB, which was explained in the attached Declaration Letter.

* All measurement and test data in this report was gathered from production sample serial number: 0811037 (Assigned by BACL, Shenzhen). The EUT was received on 2008-11-14.

EUT Photograph



Please see additional photos in Exhibit B & C

Objective

This Type approval report is prepared on behalf of *Videotech Technology Development Co.,Ltd.* in accordance with Part 2, Subpart J, and Part 15, Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

No Related Submittals.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 04, 2004. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at http://ts.nist.gov/Standards/scopes/2007070.htm

SYSTEM TEST CONFIGURATION

Justification

The system was configured for testing in a typical fashion (as normally used by a typical user).

Special Accessories

N/A


Equipment Modifications

No modifications were made to the unit tested.

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conduction Emissions	N/A *
\$15.205, \$15.209, 15.249(a), \$15.249(c)	Radiated Emissions	Compliant**
§15.249(d)	Out of Band Emissions	Compliant

Note: *DC power operation.
** Within measurement uncertainty.

§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to \$15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Antenna Connector Construction

The EUT antenna is a permanently attached antenna, the maximum of antenna gain is 0dBi, which in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.

Result: Compliant.

Please refer to the EUT photos.

§15.205 §15.209 §15.249(a) §15.249(d) - RADIATED EMISSIONS

Applicable Standard

As per §15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per §15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Shenzhen) is ± 4.0 dB.

Test Equipment Setup

The spectrum analyzer or receiver is set as:

Below 1000MHz:


$$RBW = 100 \text{ kHz} / VBW = 300 \text{ kHz} / Sweep = Auto$$

Above 1000MHz:

(1) Peak: RBW = 1MHz / VBW = 1MHz / Sweep = Auto

(2) Average: RBW = 1MHz / VBW = 10Hz / Sweep = Auto

EUT Setup



The radiated emission and out of band emission tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209 and FCC 15.249 limits.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	8447E	1937A01046	2008-11-15	2009-11-15
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2008-10-16	2009-10-16
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2008-08-14	2009-08-14
HP	Amplifier	8449B	3008A00277	2008-09-29	2009-09-29
Sunol Sciences	Horn Antenna	DRH-118	A052604	2008-09-25	2009-09-25
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-05-09	2009-05-09

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Procedure

For the radiated emissions test, the EUT, and all support equipment power cords was connected to the AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 mete, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 & 15.249, with the worst margin reading of:

Below 1GHz:

16.4 dB at **336.9492 MHz** in the **Horizontal** polarization

Above 1GHz:

1.36 dB at **4828 MHz** in the **Vertical** polarization

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Chris Peng on 2009-01-14.

Test Mode: Transmitting

Below 1GHz:



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna Height (cm)	Antenna Polarity (H/V)	Turntable Position (deg)	Correction Factor (dB)	Limit (dBµV/m)	Margin (dB)
336.949200	29.6	99.0	Н	67.0	-23.9	46.0	16.4
377.381250	28.9	99.0	Н	10.0	-22.7	46.0	17.1
301.493975	27.8	99.0	Н	76.0	-24.8	46.0	18.2
31.576250	18.9	120.0	V	145.0	-12.0	40.0	21.1
171.741250	21.8	99.0	Н	98.0	-2.3	43.5	21.7
183.987500	18.7	99.0	Н	135.0	-6.8	43.5	24.8

Above 1GHz:

Freq.	Fred S.A. De		Detector Table		Antenna			Pre-	Cord.	FCC	FCC 15.249/15.209		
(MHz)	Reading (dBµV)	PK/QP/AV	Direction Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Loss (dB)	Amp. Gain (dB)	Amp. (dBμV/m)	Limit (dBµV/m)	Margin (dB)	Remarks	
4828	43.78	AV	139	1.0	V	35.00	7.56	33.70	52.64	54	1.36*	Harmonic	
9656	29.20	AV	211	1.2	Н	41.40	10.79	34.00	47.39	54	6.61	Harmonic	
4828	36.70	AV	46	1.2	Н	36.30	7.56	33.70	46.86	54	7.14	Harmonic	
9656	29.10	AV	156	1.2	V	40.10	10.79	34.00	45.99	54	8.01	Harmonic	
2414	80.66	AV	140	1.6	Н	30.90	7.90	33.90	85.56	94	8.44	Fund.	
7242	30.38	AV	336	1.0	Н	39.20	9.12	33.60	45.10	54	8.9	Harmonic	
7242	30.40	AV	38	1.0	V	38.00	9.12	33.60	43.92	54	10.08	Harmonic	
4828	52.61	PK	139	1.0	V	35.00	7.56	33.70	61.47	74	12.53	Harmonic	
9656	41.20	PK	211	1.2	Н	41.40	10.79	34.00	59.39	74	14.61	Harmonic	
7242	43.77	PK	336	1.0	Н	39.20	9.12	33.60	58.49	74	15.51	Harmonic	
9656	41.10	PK	156	1.2	V	40.10	10.79	34.00	57.99	74	16.01	Harmonic	
4828	47.37	PK	46	1.2	Н	36.30	7.56	33.70	57.53	74	16.47	Harmonic	
2414	73.10	AV	80	1.0	V	30.30	7.90	33.90	77.40	94	16.6	Fund.	
7242	43.14	PK	38	1.0	V	38.00	9.12	33.60	56.66	74	17.34	Harmonic	
2414	85.79	PK	140	1.6	Н	30.90	7.90	33.90	90.69	114	23.31	Fund.	
2414	78.19	PK	80	1.0	V	30.30	7.90	33.90	82.49	114	31.51	Fund.	

 $^{*\} Within\ measurement\ uncertainty.$

§15.249(d) – OUT OF BAND EMISSIONS

Applicable Standard

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Test Procedure

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 mete, and the EUT is placed on a turntable, which is 0.8 meter above ground plane, the table shall be rotated for 360 degrees to find out the highest emission at the band edge. The receiving antenna should be changed the polarization both of horizontal and vertical.

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier 8447E		1937A01046	2008-11-15	2009-11-15
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2008-10-16	2009-10-16
Sunol Sciences	Bilog Antenna	JB1	A040904-2	2008-08-14	2009-08-14
НР	Amplifier	8449B	3008A00277	2008-09-29	2009-09-29
Sunol Sciences	unol Sciences Horn Antenna		A052604	2008-09-25	2009-09-25

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) Corp. attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C			
Relative Humidity:	56 %			
ATM Pressure:	100.0 kPa			

The testing was performed by Chris Peng on 2008-12-23.

Test Mode: Transmitting

Freq.	S.A.	Detector	Table	Ant.	Ant.	Ant.	Cable	Pre- Amp.	Cord.	FCC 1	5.209
(MHz)	Reading (dBµV)	(PK/AV)	Degree	Height (m)	Polar (H/V)	Factor (dB/m)	Loss (dB)	Gain (dB)	Amp. (dBμV/m)	Limit (dBµV/m)	Margin (dB)
	Out of Left Side Band (2310 – 2390 MHz)										
2358.25	32.57	AV	230	1.5	Н	30.7	7.3	33.9	36.67	54	17.33
2375.25	32.15	AV	145	1.0	V	30.2	7.5	33.9	35.95	54	18.05
2358.25	45.51	PK	230	1.5	Н	30.7	7.3	33.9	49.61	74	24.39
2375.25	45.50	PK	145	1.0	V	30.2	7.5	33.9	49.3	74	24.70
			Out	of Right S	Side Band	1 (2483.5	– 2500 M	Hz)			
2485.81	32.20	AV	176	1.4	Н	31.1	8.03	33.9	37.43	54	16.57
2495.20	32.45	AV	98	1.0	V	30.5	8.05	33.9	37.1	54	16.90
2485.81	45.44	PK	176	1.4	Н	31.1	8.03	33.9	50.67	74	23.33
2495.20	45.00	PK	98	1.0	V	30.5	8.05	33.9	49.65	74	24.35

DECLARATION LETTER

VIDE® TECH Videotech Technology Development Co.,Ltd.

Bldg 12, Section B, BaoSheng Industrial Area, BaiNiKeng, PingHu Town, ShenZhen, China.

Product Similarity Declaration

To Whom It May Concern,

We, Videotech Technology Development Co.,Ltd., hereby declare our product: i ball wireless trailer hitch camera. Model number: VT-C6106 is electrically identical with the Model Number: HITCH VU i ball camera, They are named differently due to marketing purposes.

Please contact me if you have any question.

Signature:

Print Name: Zou YuLan

Title: Manager
Date:2009-1-16

***** END OF REPORT *****