

RF Exposure Measured

Maximum Permissible Exposure at 20 cm

1. Declaration of RF exposure compliance

Transmitter(s) Installed	902-928 MHz Digital Transmission System / Hybrid Digital Transmission System
Model number:	121-33089
Client	Cypress Envirosystems
Judgement of Compliance	Compliant
Compliance Distance	20 cm
Radiated Transmitter Power (V/m) Conducted Transmitter Power (dBm)	902-928 MHz transmitter: 18.4 dBm maximum
Antenna Gain (dBi)	P/N: 0915AT43A0026: -1.0 dBi peak gain
4.3.1. Maximum Permissible Exposure considerations are:	During normal operation, user and user extremities must be at least 20 cm removed from any transmitting antenna. The Requirements for MPE are set by:
Verdict	Compliant with 20 cm zone

2. Attestation

ATTESTATION: I attest that the calculations were performed or supervised by me; that the calculations were based on the worst-case power output at the worst-case frequency of the transmitting device. All possible configurations have been considered when calculating the worst case Maximum Permissible Exposure requirements as detailed below.

Signature:	
Date:	April 16, 2020
Name:	James Cunningham, Wireless Supervisor

Both the MPE limits listed in Table 1 of paragraph (e) of this section and the SAR limits as set forth in paragraph (a) through (c) of this section and in §2.1093 of this chapter are for continuous exposure, that is, for indefinite time periods. Exposure levels higher than the limits are permitted for shorter exposure times, as long as the average exposure over the specified averaging time in Table 1 is less than the limits. Detailed information on our policies regarding procedures for evaluating compliance with all of these exposure limits can be found in the FCC's *OET Bulletin 65*, "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields," and in supplements to *Bulletin 65*, all available at the FCC's Internet Web site: <http://www.fcc.gov/oet/rlsafety>.

Table 1 below sets forth limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Measured and Calculated Result



Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

TX Type 1
RN2903 900 MHz

Maximum peak output power at device output terminal: **18.4 dBm**

Cable and Jumper loss: **0 dB**

Maximum peak output power at antenna input terminal (dBm): **18.4 dBm**

Maximum peak output power at antenna input terminal (mW): **69.18 mW**

Single Antenna gain (typical): **-1 dBi**

Number of Antennae: **1**

Total Antenna gain (typical) (dBi): **-1 dBi**

Total Antenna gain (typical) (linear): **0.79 (numeric)**

Prediction distance: **20 cm**

Prediction frequency: **902 MHz**

MPE limit for uncontrolled exposure at prediction frequency: **0.60133333 mW/cm²**

Power density at prediction frequency: **0.01093277 mW/cm²**

0.10932768 W/m²

Tx On time: **1 ms**

Tx period time: **1 ms**

Average Factor: **100 %**

Average Power density at prediction frequency: **0.10932768 W/m²**

Maximum allowable antenna gain: **16.4038513 dBi**

Margin of Compliance: **17.4038513 dB**

902 MHz TX

0.01818 <1.0