

Date: 2016-05-06 Page 1 of 29

: HM170231 No.

Gatekeeper System (HK) Ltd. **Applicant:**

Unit 2305, Level 23, Tower 2, Metroplaza, No. 223 Hing Fong

Road, Kwai Fong, N.T., Hong Kong

Manufacturer: Gatekeeper System (HK) Ltd.

Unit 2305, Level 23, Tower 2, Metroplaza, No. 223 Hing Fong

Road, Kwai Fong, N.T., Hong Kong

Description of Sample(s): Product: Remote Controlled Locking Wheel

> Brand Name: Gatekeeper Systems

Model Number: W-9470A FCC ID: W3Z-W9470A

2016-04-12 Date Sample(s) Received:

Date Tested: 2016-04-25

Perform ElectroMagnetic Interference measurement in accordance **Investigation Requested:**

with FCC 47CFR [Codes of Federal Regulations] Part 15: 2014 and

ANSI C63.10:2013 for FCC Certification.

The submitted product COMPLIED with the requirements of Conclusion(s):

Federal Communications Commission [FCC] Rules and

Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test

Report.

Remark(s):

CHEUNG Chi. Kennett Authorized Signatory ElectroMagnetic Compatibility Department For and on behalf of

The Hong Kong Standards and Testing Centre Ltd.



Date : 2016-05-06 Page 2 of 29

No. : HM170231

CONTENT:

	Cover Content	Page 1 of 29 Page 2 of 29
<u>1.0</u>	General Details	
1.1	Equipment Under Test [EUT] Description of EUT operation	Page 3 of 29
1.2	Description of EUT Operation	
1.3	Date of Order	Page 3 of 29
1.4	Submitted Sample	Page 3 of 29
1.5	Test Duration	Page 3 of 29
1.6	Country of Origin	Page 3 of 29
<u>2.0</u>	<u>Technical Details</u>	
2.1	Investigations Requested	Page 4 of 29
2.2	Test Standards and Results Summary	Page 4 of 29
<u>3.0</u>	<u>Test Results</u>	
3.1	Emission	Page 5-29 of 29

Appendix A

List of Measurement Equipment Page 30 of 29

Appendix B

Photographs Page 31-29 of 29



Date : 2016-05-06 Page 3 of 29

No. : HM170231

1.0 General Details

1.1 Equipment Under Test [EUT] Description of Sample(s)

Product: Remote Controlled Locking Wheel
Manufacturer: Gatekeeper System (HK) Ltd.

Unit 2305, Level 23, Tower 2, Metroplaza, No. 223 Hing Fong Road,

Kwai Fong, N.T., Hong Kong

Brand Name: Gatekeeper Systems

Model Number: W-9470A

Rating: 3Vd.c. ("CR17450" Lithium Battery x 1)

1.2 Description of EUT Operation

The Equipment Under Test (EUT) is a Remote Controlled Locking Wheel of Gatekeeper System (HK) Ltd., it consist with two 2.4GHz transceivers.

The W-9470A has two modes which affect the characteristics of its RF emissions operational mode and program download mode. Operational mode transmissions are modulated at 20kbps FSK (Frequency Shift Keying), with a deviation of 19 kHz (Carson's rule bandwidth about 80 kHz). Program download mode transmissions are modulated with 500 kbps MSK (Minimum Shift Keying)

1.3 Date of Order

2016-04-12

1.4 Submitted Sample(s):

3 Sample(s)

1.5 Test Duration

2016-04-25

1.6 Country of Origin

China



Date : 2016-05-06 Page 4 of 29

No. : HM170231

2.0 Technical Details

2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2015 Regulations and ANSI C63.10:2013 for FCC Certification.

2.2 Test Standards and Results Summary Tables

	EMISSION Results Summary								
Test Condition	Test Requirement	Test Method	Class /	Test I	Result				
			Severity	Pass	Fail				
Field Strength of Fundamental & Harmonics Emissions	FCC 47CFR 15.249	ANSI C63.10:2013	N/A	\boxtimes					
Radiated Emissions	FCC 47CFR 15.209	ANSI C63.10:2013	N/A						

Note: N/A - Not Applicable



Date : 2016-05-06 Page 5 of 29

No. : HM170231

3.0 Test Results

3.1 Emission

3.1.1 Field Strength of Fundamental & Harmonics Emissions

Test Requirement: FCC 47CFR 15.249
Test Method: ANSI C63.10:2013
Test Date: 2016-04-25

Mode of Operation: On Mode

Test Method:

The sample was placed 0.8m above the ground plane on a standard radiated emission test site. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. In the frequency range of 9kHz to 30MHz, The center of the loop antenna shall be 1 meter above the ground and rotated loop axis for maximum reading. The emissions worst-case are shown in Test Results of the following pages.

Remark: 3 orthogonal axis apply to hand-held device only.

*: Semi-anechoic chamber located on the G/F of The Hong Kong Standards and Testing Centre Ltd. with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.



Date : 2016-05-06 Page 6 of 29

No. : HM170231

Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av) RBW: 10kHz

VBW: 30kHz Sweep: Auto

Span: Fully capture the emissions being measured

Trace: Max. hold

30MHz – 1GHz (QP) RBW: 120kHz

VBW: 120kHz Sweep: Auto

Span: Fully capture the emissions being measured

Trace: Max. hold


Above 1GHz (Pk & Av) RBW: 3MHz

VBW: 3MHz Sweep: Auto

Span: Fully capture the emissions being measured

Trace: Max. hold

Test Setup:



Absorbers placed on top of the ground plane are for measurements above 1000MHz only.



Date : 2016-05-06 Page 7 of 29

No. : HM170231

Limits for Field Strength of Fundamental & Harmonics Emissions [FCC 47CFR 15.249]:

Fundamental frequency [MHz]	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

Result of Data mode, (Channel 2), (Above 1GHz): Pass

Res	Result of Data mode, (Channel 2), (Above IGHz): Pass									
	Field Strength of Fundamental and Harmonics Emissions									
	Peak Value									
F	requency	Measured	Correction	Field	Field	Limit @3m	E-Field			
		Level @3m	Factor	Strength	Strength		Polarity			
	MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$				
	2401.4	56.4	27.9	84.3	16,405.9	500,000	Vertical			
*	4802.7	15.1	32.1	47.2	229.1	5,000	Vertical			
	7204.3	2.5	38.6	41.1	113.5	5,000	Vertical			
	9605.6					5,000	Vertical			
*	12007.0					5,000	Vertical			
	14408.4					5,000	Vertical			
	16809.8	Е	missions detec	cted are more	than	5,000	Vertical			
* 19211.2 20 dB below the FCC Limits 5,0					5,000	Vertical				
	21612.6 5,000 Vertical						Vertical			
	24014.0					5,000	Vertical			

	Field Strength of Fundamental and Harmonics Emissions								
	Average Value								
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Factor	Strength	Strength		Polarity			
MHz	dBμV/m	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$				
2401.4	54.4	27.9	82.3	13,031.7	50,000	Vertical			
* 4802.7	9.2	32.1	41.3	116.1	500	Vertical			
7204.3	-0.8	38.6	37.8	77.6	500	Vertical			
9605.6					500	Vertical			
* 12007.0					500	Vertical			
14408.4					500	Vertical			
16809.8	Е	missions detec	cted are more	than	500	Vertical			
* 19211.2	20 dB below the FCC Limits 500 Vertical								
21612.6	500 Vertical								
24014.0									



Date : 2016-05-06 Page 8 of 29

No. : HM170231

Result of Data mode, (Channel 126), (Above 1GHz): Pass

Kes	Result of Data mode, (Channel 126), (Above 1GHz): Pass								
	Field Strength of Fundamental and Harmonics Emissions								
				Peak Value					
F	requency	Measured	Correction	Field	Field	Limit @3m	E-Field		
		Level @3m	Factor	Strength	Strength		Polarity		
	MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$			
	2426.2	55.2	27.9	83.1	14,288.9	500,000	Vertical		
*	4852.3	15.0	32.1	47.1	226.5	5,000	Vertical		
*	7278.4	2.3	38.6	40.9	110.9	5,000	Vertical		
	9704.8					5,000	Vertical		
*	12131.0					5,000	Vertical		
	14557.2					5,000	Vertical		
	16983.4	Е	missions dete	cted are more	than	5,000	Vertical		
*	* 19409.6 20 dB below the FCC Limits 5,000					5,000	Vertical		
	21835.8 5,000 Vertical						Vertical		
	24262.0					5,000	Vertical		

	Field Strength of Fundamental and Harmonics Emissions								
		A	Average Valu	e					
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Factor	Strength	Strength		Polarity			
MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$				
2426.2	53.8	27.9	81.7	12,161.9	50,000	Vertical			
* 4852.3	9.2	32.1	41.3	116.1	500	Vertical			
* 7278.4	0.1	38.6	38.7	86.1	500	Vertical			
9704.8					500	Vertical			
* 12131.0					500	Vertical			
14557.2					500	Vertical			
16983.4	Е	missions dete	cted are more	than	500	Vertical			
* 19409.6		20 dB below	500	Vertical					
21835.8	500 Vertical								
24262.0		500	Vertical						



Date : 2016-05-06 Page 9 of 29

No. : HM170231

Result of Data mode, (Channel 254), (Above 1GHz): Pass

Res	Result of Data mode, (Channel 254), (Above 1GHz): Pass								
	Field Strength of Fundamental and Harmonics Emissions								
				Peak Value					
F	requency	Measured	Correction	Field	Field	Limit @3m	E-Field		
		Level @3m	Factor	Strength	Strength		Polarity		
	MHz	dBμV/m	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	μV/m			
	2451.8	56.4	27.9	84.3	16,405.9	500,000	Vertical		
*	4903.5	14.0	32.1	46.1	201.8	5,000	Vertical		
*	7355.3	3.5	38.6	42.1	127.4	5,000	Vertical		
	9807.2					5,000	Vertical		
*	12259.0					5,000	Vertical		
	14710.8					5,000	Vertical		
	17162.6	Е	missions dete	cted are more	than	5,000	Vertical		
*	19614.4 20 dB below the FCC Limits					5,000	Vertical		
	22066.2				5,000	Vertical			
	24518.0	1				5,000	Vertical		

	Field Strength of Fundamental and Harmonics Emissions								
		A	Average Valu	e					
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field			
	Level @3m	Factor	Strength	Strength		Polarity			
MHz	dBμV/m	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$				
2451.8	54.2	27.9	82.1	12,735.0	50,000	Vertical			
* 4903.5	8.2	32.1	40.3	103.5	500	Vertical			
* 7355.3	0.1	38.6	38.7	86.1	500	Vertical			
9807.2					500	Vertical			
* 12259.0					500	Vertical			
14710.8					500	Vertical			
17162.6	Е	missions dete	cted are more	than	500	Vertical			
* 19614.4		20 dB below	500	Vertical					
22066.2	500 Vertical								
24518.0									



Date : 2016-05-06 Page 10 of 29

No. : HM170231

Result of Announce mode (Channel 8), (Above 1GHz): Pass

Kes	Result of Announce mode (Channel 8), (Above 1GHz): Pass								
	Field Strength of Fundamental and Harmonics Emissions								
				Peak Value					
I	requency	Measured	Correction	Field	Field	Limit @3m	E-Field		
		Level @3m	Factor	Strength	Strength		Polarity		
	MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$			
	2403.5	55.2	27.9	83.1	14,288.9	500,000	Vertical		
*	4807.3	10.2	32.1	42.3	130.3	5,000	Vertical		
	7211.3	1.7	38.6	40.3	103.5	5,000	Vertical		
	9614.0					5,000	Vertical		
*	12017.5					5,000	Vertical		
	14421.0					5,000	Vertical		
	16824.5	Е	missions dete	cted are more	than	5,000	Vertical		
* 19228.0 20 dB below the FCC Limits 5,0					5,000	Vertical			
	21631.5 5,000 Vertical								
	24035.0								

	Field Strength of Fundamental and Harmonics Emissions							
	Average Value							
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	dBμV/m	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$			
2403.5	48.6	27.9	76.5	6,683.4	50,000	Vertical		
* 4807.3	3.3	32.1	35.4	58.9	500	Vertical		
7211.3	-1.0	38.6	37.6	75.9	500	Vertical		
9614.0					500	Vertical		
* 12017.5					500	Vertical		
14421.0					500	Vertical		
16824.5	Е	missions detec	cted are more	than	500	Vertical		
* 19228.0	2228.0 20 dB below the FCC Limits					Vertical		
21631.5	500 Vertical							
24035.0								



Date : 2016-05-06 Page 11 of 29

No. : HM170231

Result of Announce mode (Channel 120), (Above 1GHz): Pass

Res	Result of Announce mode (Channel 120), (Above 1GHz): Pass								
	Field Strength of Fundamental and Harmonics Emissions								
				Peak Value					
F	requency	Measured	Correction	Field	Field	Limit @3m	E-Field		
		Level @3m	Factor	Strength	Strength		Polarity		
	MHz	dBμV/m	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$			
	2438.7	54.2	27.9	82.1	12,735.0	500,000	Vertical		
*	4877.7	8.3	32.1	40.4	104.7	5,000	Vertical		
*	7316.5	1.5	38.6	40.1	101.2	5,000	Vertical		
	9754.8					5,000	Vertical		
*	12193.5					5,000	Vertical		
	14632.2					5,000	Vertical		
	17070.9	Е	missions dete	cted are more	than	5,000	Vertical		
*	19509.6	09.6 20 dB below the FCC Limits					Vertical		
	21948.3	5,000 Vertical							
	24387.0]				5,000	Vertical		

	Field Strength of Fundamental and Harmonics Emissions					
	Average Value					
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field
	Level @3m	Factor	Strength	Strength		Polarity
MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$	
2438.7	48.4	27.9	76.3	6,531.3	50,000	Vertical
* 4877.7	2.2	32.1	34.3	51.9	500	Vertical
* 7316.5	-0.5	38.6	38.1	80.4	500	Vertical
9754.8					500	Vertical
* 12193.5				500	Vertical	
14632.2					500	Vertical
17070.9	Emissions detected are more than 500 Verti			Vertical		
* 19509.6	20 dB below the FCC Limits 500 Vertical			Vertical		
21948.3	500 Vertical			Vertical		
24387.0]				500	Vertical



Date : 2016-05-06 Page 12 of 29

No. : HM170231

Result of Announce mode (Channel 247), (Above 1GHz): Pass

Kes	Result of Announce mode (Channel 24/), (Above 1GHz): Pass						
	Field Strength of Fundamental and Harmonics Emissions						
	Peak Value						
F	requency	Measured	Correction	Field	Field	Limit @3m	E-Field
		Level @3m	Factor	Strength	Strength		Polarity
	MHz	dBμV/m	$dB\mu V/m$	dBμV/m	$\mu V/m$	$\mu V/m$	
	2478.6	54.0	27.9	81.9	12,445.1	500,000	Vertical
*	4957.1	8.2	32.1	40.3	103.5	5,000	Vertical
*	7436.1	2.5	38.6	41.1	113.5	5,000	Vertical
	9914.4					5,000	Vertical
*	12393.0				5,000	Vertical	
	14871.6	5,000 Vertical			Vertical		
	17350.2	Emissions detected are more than 5,000 Vertical					
*	19828.8	20 dB below the FCC Limits 5,000 Vertical			Vertical		
	22307.4	5,000 Vertical					
	24786.0	5,000 Vertical					

Field Strength of Fundamental and Harmonics Emissions						
	Average Value					
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field
	Level @3m	Factor	Strength	Strength		Polarity
MHz	dBμV/m	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$	
2478.6	47.4	27.9	75.3	5,821.0	50,000	Vertical
* 4957.1	0.1	32.1	32.2	40.7	500	Vertical
* 7436.1	0.2	38.6	38.8	87.1	500	Vertical
9914.4					500	Vertical
* 12393.0				500	Vertical	
14871.6				500	Vertical	
17350.2	Emissions detected are more than 500			Vertical		
* 19828.8	20 dB below the FCC Limits 500 Vertical 500 Vertical			Vertical		
22307.4				Vertical		
24786.0					500	Vertical

Remarks:

No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz

*: Denotes restricted band of operation.

Measurements were made using a peak detector. Any emission less than 1000 MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Calculated measurement uncertainty : 9kHz to 30MHz 2.4dB

30MHz to 1GHz 4.9dB 1GHz to 6GHz 4.02dB 6GHz to 18GHz 4.03dB




Date : 2016-05-06 Page 13 of 29

No. : HM170231

Limits for 20dB Bandwidth of Fundamental Emission:

Frequency Range	20dB Bandwidth
[MHz]	[MHz]
2401.6	0.571

Data mode - Channel 2






Date: 2016-05-06 Page 14 of 29

No. : HM170231

Frequency Range	20dB Bandwidth
[MHz]	[MHz]
2426.1	0.553

Data mode - Channel 126






Date : 2016-05-06 Page 15 of 29

No. : HM170231

Frequency Range	20dB Bandwidth
[MHz]	[MHz]
2451.7	0.550

Data mode - Channel 254






Date: 2016-05-06 Page 16 of 29

No. : HM170231

Frequency Range	20dB Bandwidth
[MHz]	[MHz]
2403.5	1.468

Announce mode - Channel 8






Date : 2016-05-06 Page 17 of 29

No. : HM170231

Frequency Range	20dB Bandwidth	
[MHz]	[MHz]	
2438.7	1.459	

Announce mode - Channel 120






Date: 2016-05-06 Page 18 of 29

No. : HM170231

Frequency Range	20dB Bandwidth
[MHz]	[MHz]
2478.6	1.447

Announce mode - Channel 247






Date : 2016-05-06 Page 19 of 29

No. : HM170231

Frequency Range	Radiated Emission Attenuated below the Fundamental
[MHz]	[dB]
Data mode – Lowest Fundamental	35.9






Date : 2016-05-06 Page 20 of 29

No. : HM170231

Frequency Range	Radiated Emission Attenuated below the Fundamental
[MHz]	[dB]
Data mode – Highest Fundamental	53.8






Date : 2016-05-06 Page 21 of 29

No. : HM170231

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
Announce mode – Lowest Fundamental	39.5






Date : 2016-05-06 Page 22 of 29

No. : HM170231

Frequency Range	Radiated Emission Attenuated below the Fundamental
[MHz]	[dB]
Announce mode – Highest Fundamental	44.8





Date : 2016-05-06 Page 23 of 29

No. : HM170231

Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Result of On mode, (9kHz - 30MHz): PASS

Emissions detected are more than 20 dB below the FCC Limits

Result of On mode, (30MHz - 1GHz): PASS

	Field Strength of Fundamental and Harmonics Emissions								
		Qı	ıasi-Peak Va	lue					
Frequency	Frequency Measured Correction Field Field Limit @3m E-Field								
	Level @3m Factor Strength Strength								
MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$				
63.4	0.3	9.2	9.5	3.0	100	Vertical			
101.7	0.1	10.3	10.4	3.3	150	Vertical			
210.4	0.2	14.0	14.2	5.1	150	Horizontal			
246.5	246.5 0.7 15.7 16.4 6.6 200								
337.9	9 0.5 18.6 19.1 9.0 200 Horizo								
421.3	0.5	21.1	21.6	12.0	200	Horizontal			



Date : 2016-05-06 Page 24 of 29

No. : HM170231

Result of On mode (Data mode, Band-edge measurement), (1GHz – 18GHz): PASS

Field Strength of Fundamental and Harmonics Emissions								
	Peak Value							
Frequency	Frequency Measured Correction Field Field Limit @3m E-Field							
	Level @3m	Factor	Strength	Strength		Polarity		
MHz $dB\mu V/m$ $dB\mu V/m$ $dB\mu V/m$ $\mu V/m$ $\mu V/m$								
2399.1	22.4	27.9	50.3	327.3	5,000	Vertical		
2485.1	12.3	28.0	40.3	103.5	5,000	Vertical		

Field Strength of Fundamental and Harmonics Emissions							
		A	Average Valu	e			
Frequency	Frequency Measured Correction Field Field Limit @3m E-Field						
	Level @3m	el @3m Factor Strength Strength			Polarity		
MHz $dB\mu V/m$ $dB\mu V/m$ $dB\mu V/m$ $\mu V/m$ $\mu V/m$							
2399.1	16.9	27.9	44.8	173.8	500	Vertical	
2485.1	5.8	28.0	33.8	49.0	500	Vertical	

Result of On mode (Announce mode, Band-edge measurement), (1GHz - 18GHz): PASS

Field Strength of Fundamental and Harmonics Emissions						
			Peak Value			
Frequency	Frequency Measured Correction Field Field Limit @3m E-Field					
	Level @3m	Factor	Strength	Strength		Polarity
MHz	dBμV/m	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$	
2399.1	21.2	27.9	49.1	285.1	5,000	Vertical
2484.6	21.3	28.0	49.3	291.7	5,000	Vertical

Field Strength of Fundamental and Harmonics Emissions Average Value							
		F	Average valu				
Frequency	Measured Correction Field Field Limit @3m E-Fie						
	Level @3m	Factor	Strength	Strength		Polarity	
MHz	MHz $dB\mu V/m$ $dB\mu V/m$ $dB\mu V/m$ $\mu V/m$ $\mu V/m$						
2399.1	12.4	27.9	40.3	103.5	500	Vertical	
2484.6	12.6	28.0	40.6	107.2	500	Vertical	



Date : 2016-05-06 Page 25 of 29

No. : HM170231

Result of Receiver mode, (9kHz – 30MHz): PASS Emissions detected are more than 20 dB below the Limits

Result of Receiver mode, (30MHz – 1GHz): PASS Emissions detected are more than 20 dB below the Limits

Result of Receiver mode, (1GHz – 18GHz): PASS

Nesult of Receiver mode, (IGHz – 18GHz): FASS								
Field Strength of Fundamental and Harmonics Emissions								
Peak Value								
Frequency	Measured	Correction	Field	Field	Limit @3m	E-Field		
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$			
2437.2	6.2	27.9	34.1	50.7	5,000	Vertical		

Field Strength of Fundamental and Harmonics Emissions								
Average Value								
Frequency	equency Measured Correction Field Field Limit @3m E-Field							
	Level @3m	Factor	Strength	Strength		Polarity		
MHz	$dB\mu V/m$	$dB\mu V/m$	$dB\mu V/m$	$\mu V/m$	$\mu V/m$			
2437.2	5.1	27.9	33.0	44.7	500	Vertical		

Remarks:

No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty : 30MHz to 1GHz 4.9dB

1GHz to 6GHz 4.02dB 6GHz to 18GHz 4.03dB



Date : 2016-05-06 Page 26 of 29

No. : HM170231

Appendix A

LIST OF MEASUREMENT EQUIPMENT

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EMD062	DOUBLE-RIDGED WAVEGUIDE HORN ANTENNA	ETS-LINDGREN	3117	00075933	2014/11/15	2016/11/15
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM216	MINI MAST SYSTEM	EMCO	2075	00026842	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-LINDGREN	FACT-3		2016/04/19	2017/04/19
EM320	BICONILOG ANTENNA	ETS-LINDGREN	3142D	00094856	2014/08/06	2016/08/06
EM229	EMI TEST RECEIVER	R&S	ESIB40	100248	2015/06/01	2016/06/01
EM358	LOOP ANTENNA	ETS_LINDGREN	6502	00206533	2016/03/16	2018/03/16
EM299	DOUBLE-RIDGED WAVEGUIDE HORN ANTENNA	ETS-LINDGREN	3115	00114120	2016/04/27	2018/04/27
EM302	PRECISION OMNIDIRECTIONAL DIPOLE (1 – 6GHZ)	SEIBERSDORF LABORATORIES	POD 16	161806/L	2016/05/11	2018/05/11
EM303	PRECISION OMNIDIRECTIONAL DIPOLE (6 – 18GHZ)	SEIBERSDORF LABORATORIES	POD 618	6181908/L	2016/05/11	2018/05/11

Remarks:

CM Corrective Maintenance

N/A Not Applicable or Not Available

TBD To Be Determined




Date : 2016-05-06 Page 27 of 29

No. : HM170231

Appendix B

Photographs of EUT





Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View







Date : 2016-05-06 Page 28 of 29

No. : HM170231

Photographs of EUT





The Hong Kong Standards and Testing Centre Limited 10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong



Date : 2016-05-06 No. : HM170231

Photographs of EUT

Measurement of Radiated Emission Test Set Up

***** End of Test Report *****



Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by the Company as a result of this application for testing service (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. The Report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
- 5. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 6. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 7. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
- 10. Issuance records of the Report are available on the internet at www.stc-group.org. Further enquiry of validity or verification of the Reports should be addressed to the Company.