

## RF Exposure Report

**Report No.:** SA160606E02

**FCC ID:** W59XWOBAP1

**Test Model:** XWO-BAP1

**Received Date:** June 06, 2016

**Test Date:** June 29 to 30, 2016

**Issued Date:** July 26, 2016

**Applicant:** Luxul Wireless

**Address:** 14203 Minuteman Dr Suite 201 Draper UT 84020 USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1      Certificate of Conformity.....</b>	<b>4</b>
<b>2      RF Exposure.....</b>	<b>5</b>
2.1    Limits For Maximum Permissible Exposure (MPE).....	5
2.2    MPE Calculation Formula .....	5
2.3    Classification .....	5
2.4    Antenna Gain .....	5
2.5    Calculation Result Of Maximum Conducted Power .....	6

### Release Control Record

Issue No.	Description	Date Issued
SA160606E02	Original release.	July 26, 2016

## 1 Certificate of Conformity

**Product:** High Power AC1200 Dual-Band Outdoor Bridging AP

**Brand:** Luxul

**Test Model:** XWO-BAP1

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** Luxul Wireless


**Test Date:** June 29 to 30, 2016

**Standards:** FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :**   
\_\_\_\_\_, **Date:** July 26, 2016

Wendy Wu / Specialist

**Approved by :**   
\_\_\_\_\_, **Date:** July 26, 2016

May Chen / Manager

## 2 RF Exposure

### 2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

### 2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

### 2.3 Classification

The antenna of this product, under normal use condition, is at least 40cm away from the body of the user.

So, this device is classified as **Mobile Device**.

### 2.4 Antenna Gain

<b>2.4GHz</b>				
Transmitter Circuit	Antenna Gain(dBi)	Frequency range (MHz ~ MHz)	Antenna Type	Connector Type
Chain (0)	6	2400~2483.5	Patch	NA
Chain (1)	6			
<b>5GHz</b>				
Transmitter Circuit	Antenna Gain(dBi)	Frequency range (MHz ~ MHz)	Antenna Type	Connector Type
Chain (0)	10	5150~5875	Patch	NA
Chain (1)	10			

## 2.5 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
2412-2462	747.622	9.01	40	0.29604	1
5180-5240	97.338	13.01	40	0.09682	1
5745-5825	395.908	13.01	40	0.39379	1

NOTE:

2.4GHz: Directional gain = 6dBi + 10log(2) = 9.01dBi

5GHz: Directional gain = 10dBi + 10log(2) = 13.01dBi

### Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = 0.29604 / 1 + 0.39379 / 1 = 0.68983

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---