

# A Test Lab Techno Corp.

Changan Lab: No. 140-1, Changan Street, Bade City, Taoyuan County, Taiwan R.O.C.

Tel: 886-3-271-0188 / Fax: 886-3-271-0190

# SAR EVALUATION REPORT





Test Report No. : 1304FS16

Applicant : Tobii Technology AB

Product Type : Tobii I-12

Trade Name : Tobii

Model Number : I-12 ETR, I-12 R

Date of Received : Jan. 08, 2013

Test Period : Apr. 23, 2013

Date of Issued : May 20, 2013

Test Environment : Ambient Temperature :  $22 \pm 2 \circ C$ 

Relative Humidity: 40 - 70 %

Standard : ANSI/IEEE C95.1-1999

IEEE Std. 1528-2003

IEEE Std. 1528a-2005

47 CFR Part §2.1093;

FCC/OET Bulletin 65 Supplement C [July 2001]

RSS-102 Issue 4, March 2010

Max. SAR : 0.501 W/kg Body SAR

Test Lab Location : Chang-an Lab



 The test operations have to be performed with cautious behavior, the test results are as attached.

 The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.

3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. The test results in the report only apply to the tested sample.

Approved By

` Tested By

(Bill Hu)

Report Number: 1304FS16 Page 1 of 66



# **Contents**

1.	Desc	4	
2.	Introd	duction	5
	2.1	SAR Definition	5
3.	SAR	Measurement Setup	6
	3.1	DASY E-Field Probe System	7
	3.2	Data Acquisition Electronic (DAE) System	10
	3.3	Robot	10
	3.4	Measurement Server	10
	3.5	Device Holder	11
	3.6	Phantom - SAM v4.0	11
	3.7	Oval Flat Phantom - ELI 4.0	12
	3.8	Data Storage and Evaluation	12
4.	Tissu	e Simulating Liquids	15
	4.1	Ingredients	16
	4.2	Recipes	16
	4.3	Liquid Depth	17
5.	SAR	Testing with RF Transmitters	18
	5.1	SAR Testing with 802.11 Transmitters	18
	5.2	General Device Setup	18
	5.3	Conducted Power	19
	5.4	Antenna location	21
	5.5	Stand-alone SAR Evaluate	22
	5.6	Simultaneous Transmitting Evaluate	23
	5.7	SAR test reduction according to KDB	25
6.	Syste	em Verification and Validation	26
	6.1	Symmetric Dipoles for System Verification	26
	6.2	Liquid Parameters	27
	6.3	Verification Summary	28
	6.4	Validation Summary	28
7.	Test I	Equipment List	29
8.	Meas	surement Uncertainty	30
9.	Meas	surement Procedure	32
	9.1	Spatial Peak SAR Evaluation	32
	9.2	Area & Zoom Scan Procedures	33
	9.3	Volume Scan Procedures	33
	9.4	SAR Averaged Methods	33
	9.5	Power Drift Monitoring	33



10. SAR Test Results Summary	34
10.1 Head Measurement SAR	34
10.2 Body Measurement SAR	34
10.3 Hot-spot mode Measurement SAR	34
10.4 Extremity Measurement SAR	34
10.5 SAR Measurement Variability	34
10.6 Std. C95.1-1999 RF Exposure Limit	35
11. Conclusion	
12. References	
13. SAR Measurement Guidance	36
Appendix A - System Performance Check	
Appendix B - SAR Measurement Data	38
Appendix C - Calibration	42



# 1. Description of Equipment under Test (EUT)

Applicant	Tobii Technology AB				
Applicant Address	Karlsrovägen 2D,182 53 Danderyd, SWEDEN				
Manufacture	ONYX Healthcare				
Manufacture Address	2F., No.135, Ln. 235, Baoqiao Rd., Xindian Dist., No. Taiwan (R.O.C.)	ew Taipei City 231,			
Product Type Tobii I-12					
Trade Name	Tobii				
Model Number	I-12 ETR, I-12 R				
Model Difference	I-12 ETR (with Eyetrack ,with Radio) I-12 R (without Eyetrack ,with Radio)				
FCC ID	W5M-TOBIII12A				
RF Function	IEEE 802.11b / 802.11g / IEEE 802.11n (2.4GHz) 20MHz & 40MHz				
	Bluetooth v3.0 + EDR				
Tx Frequency	Band	Operate Frequency (MHz)			
	IEEE 802.11b / 802.11g / IEEE 802.11n 20MHz	2412 - 2462			
	IEEE 802.11n 40MHz	2422 - 2452			
	Bluetooth v3.0 + EDR	2402 - 2480			
RF Conducted Power	Band	Power (W / dBm)			
(Avg.)	IEEE 802.11b	0.057 / 17.54			
	IEEE 802.11g	0.029 / 14.65			
	IEEE 802.11n (2.4GHz) 20MHz	0.030 / 14.83			
	IEEE 802.11n (2.4GHz) 40MHz	0.030 / 14.74			
	Bluetooth v3.0 + EDR	0.002 / 1.98			
Max. SAR Measurement	0.501 W/kg Body SAR				
Device Category	Portable Device				
RF Exposure Environment	General Population / Uncontrolled				
Application Type	Certification				
	•				

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment / general population exposure limits specified in Standard C95.1-1999 and had been tested in accordance with the measurement procedures specified in IEEE Std. 1528-2003 and IEEE Std. 1528a-2005.

Report Number: 1304FS16 Page 4 of 66



### 2. Introduction

The A Test Lab Techno Corp. has performed measurements of the maximum potential exposure to the user of **Tobii Technology AB Trade Name : Tobii Model(s) : I-12 ETR, I-12 R**. The test procedures, as described in American National Standards, Institute C95.1-1999 [1], FCC/OET Bulletin 65 Supplement C [July 2001] were employed and they specify the maximum exposure limit of 1.6mW/g as averaged over any 1 gram of tissue for portable devices being used within 20cm between user and EUT in the uncontrolled environment. A description of the product and operating configuration, detailed summary of the test results, methodology and procedures used in the equipment used are included within this test report.

#### 2.1 SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dw) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Figure 2).

$$SAR = \frac{d}{dt} \left( \frac{dw}{dm} \right) = \frac{d}{dt} \left( \frac{dw}{\rho dv} \right)$$

Figure 2. SAR Mathematical Equation

SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma E^2}{\rho}$$

Where:


σ = conductivity of the tissue (S/m)
 ρ = mass density of the tissue (kg/m3)
 E = RMS electric field strength (V/m)

#### \*Note:

The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane [2]



# 3. SAR Measurement Setup



The DASY5 system for performing compliance tests consists of the following items:

- 1. A standard high precision 6-axis robot (Stäubli TX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- 2. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- 4. The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- 5. A probe alignment unit which improves the (absolute) accuracy of the probe positioning.
- 6. A computer operating Windows 2000 or Windows XP.
- 7. DASY5 software.
- 8. Remote controls with teach pendant and additional circuitry for robot safety such as warning lamps, etc.
- 9. The SAM twin phantom enabling testing left-hand and right-hand usage.
- 10. The device holder for handheld mobile phones.
- 11. Tissue simulating liquid mixed according to the given recipes.
- 12. Validation dipole kits allowing validating the proper functioning of the system.

Report Number: 1304FS16 Page 6 of 66



## 3.1 DASY E-Field Probe System

The SAR measurements were conducted with the dosimetric probe (manufactured by SPEAG), designed in the classical triangular configuration [3] and optimized for dosimetric evaluation. The probes is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting. The approach is stopped when reaching the maximum.

Report Number: 1304FS16 Page 7 of 66



#### 3.1.1 E-Field Probe Specification

Construction Symmetrical design with triangular core

Built-in optical fiber for surface detection System

Built-in shielding against static charges

PEEK enclosure material (resistant to organic solvents, e.q., glycol)

Calibration In air from 10 MHz to 6 GHz

In brain and muscle simulating tissue at frequencies of 2450MHz (accuracy ±8%)

Calibration for other liquids and frequencies upon request

Frequency ±0.2 dB (30 MHz to 6 GHz)

Directivity ±0.3 dB in brain tissue (rotation around probe axis)

±0.5 dB in brain tissue (rotation normal probe axis)

Dynamic Range  $10\mu W/g$  to > 100mW/g; Linearity:  $\pm 0.2dB$ 

Dimensions Overall length: 337mm


Tip length: 9mm Body diameter: 10mm Tip diameter: 2.5mm

Distance from probe tip to dipole centers: 1.0mm

Application General dosimetry up to 6GHz

Compliance tests of mobile phones

Fast automatic scanning in arbitrary phantoms



Report Number: 1304FS16 Page 8 of 66



### 3.1.2 E-Field Probe Calibration process

#### Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter.

#### Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm<sup>2</sup>.

#### **Temperature Assessment**

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

 $\Delta t$  = Exposure time (30 seconds),

C = Heat capacity of tissue (head or body),

**Δ T** = Temperature increase due to RF exposure.

Or SAR = 
$$\frac{|E|^2 \sigma}{\rho}$$

Where:

**σ** = Simulated tissue conductivity,

 $\rho$  = Tissue density (kg/m<sup>3</sup>).



# 3.2 Data Acquisition Electronic (DAE) System

**Cell Controller** 

Processor: Intel Core(TM)2 CPU

Clock Speed: @ 1.86GHz

Operating System: Windows XP Professional

**Data Converter** 

Features: Signal Amplifier, multiplexer, A/D converter, and control logic Software: DASY5 v5.0 (Build 125) & SEMCAD X Version 13.4 Build 125

Connecting Lines: Optical downlink for data and status info

Optical uplink for commands and clock

3.3 Robot

Positioner: Stäubli Unimation Corp. Robot Model: TX90XL

Repeatability: ±0.02 mm

No. of Axis: 6

#### 3.4 Measurement Server

Processor: PC/104 with a 400MHz intel ULV Celeron

I/O-board: Link to DAE4 (or DAE3)

16-bit A/D converter for surface detection system

Digital I/O interface Serial link to robot


Direct emergency stop output for robot

Report Number: 1304FS16 Page 10 of 66



#### 3.5 Device Holder

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon$ =3 and loss tangent  $\delta$ =0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



3.6 Phantom - SAM v4.0

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness	2 ±0.2 mm		
Filling Volume	Approx. 25 liters		
Dimensions	1000×500 mm (LxW)		
Table 1. Specification of SAM v4.0			



Figure 6. SAM Twin Phantom

Report Number: 1304FS16 Page 11 of 66



#### 3.7 Oval Flat Phantom - ELI 4.0

The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (Oval Flat) phantom defined in IEEE 1528-2003, IEEE Std. 1528a-2005, CENELEC 50361 and IEC 62209. It enables the dosimetric evaluation of wireless portable device usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points with the robot.

Shell Thickness	2 ±0.2 mm	
Filling Volume	Approx. 30 liters	
Dimensions	190×600×400 mm (H×L×W)	
Table 2. Spe	cification of ELI 4.0	




Figure 7. Oval Flat Phantom

### 3.8 Data Storage and Evaluation

### 3.8.1 Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension DA4 or DA5. The post processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

Report Number: 1304FS16 Page 12 of 66



#### 3.8.2 Data Evaluation

The DASY post processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters: - Sensitivity Normi, ai0, ai1, ai2

- Conversion factor ConvFi

- Diode compression point dcpi

Device parameters: - Frequency #

- Crest factor cf

Media parameters : - Conductivity of

- Density ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

With Vi = compensated signal of channel i (i = x, y, z)

Ui = input signal of channel i (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcpi = diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

E-field probes : 
$$E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$



$$H_{i} = \sqrt{V_{i}} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^{2}}{f}$$

H-field probes :

with Vi = compensated signal of channel i (i = x, y, z)

Normi = sensor sensitivity of channel i (i = x, y, z)

μV/(V/m)2 for E-field Probes

ConvF = sensitivity enhancement in solution

aij = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

Ei = electric field strength of channel i in V/m

Hi = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with SAR = local specific absorption rate in mW/g

Etot = total field strength in V/m

 $\sigma$  = conductivity in [mho/m] or [Siemens/m]

= equivalent tissue density in g/cm3

\*Note: That the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

The power flow density is calculated assuming the excitation field to be a free space field.

$$P_{pwe} = \frac{E_{tot}^2}{3770}$$
 or  $P_{pwe} = \frac{H_{tot}^2}{37.7}$ 

with Ppwe = equivalent power density of a plane wave in mW/cm2

Etot = total electric field strength in V/m

Htot = total magnetic field strength in A/m



# 4. Tissue Simulating Liquids

The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue. The dielectric parameters of the liquids were verified prior to the SAR evaluation using an 85070C Dielectric Probe Kit and an E5071B Network Analyzer.

#### IEEE SCC-34/SC-2 in 1528 recommended Tissue Dielectric Parameters

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in 1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in human head. Other head and body tissue parameters that have not been specified in 1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equation and extrapolated according to the head parameter specified in 1528.

Target Frequency	Head		Во	ody			
(MHz)	εr	σ (S/m)	εr	σ (S/m)			
150	52.3	0.76	61.9	0.80			
300	45.3	0.87	58.2	0.92			
450	43.5	0.87	56.7	0.94			
835	41.5	0.90	55.2	0.97			
900	41.5	0.97	55.0	1.05			
915	41.5	0.98	55.0	1.06			
1450	40.5	1.20	54.0	1.30			
1610	40.3	1.29	53.8	1.40			
1800 - 2000	40.0	1.40	53.3	1.52			
2450	39.2	1.80	52.7	1.95			
3000	38.5	2.40	52.0	2.73			
5800	35.3	5.27	48.2	6.00			
	( $\epsilon r$ = relative permittivity, $\sigma$ = conductivity and $\rho$ = 1000 kg/m3 )						

Table 3. Tissue dielectric parameters for head and body phantoms

Report Number: 1304FS16 Page 15 of 66



## 4.1 Ingredients

The following ingredients are used:

- Water: deionized water (pure  $H_20$ ), resistivity  $\geq$  16 M  $\Omega$  -as basis for the liquid
- Sugar: refied white sugar (typically 99.7 % sucrose, available as crystal sugar in food shops)
   to reduce relative permittivity
- Salt: pure NaCl -to increase conductivity
- Cellulose: Hydroxyethyl-cellulose, medium viscosity (75-125 mPa.s, 2% in water, 20 C), CAS # 54290 -to increase viscosity and to keep sugar in solution.
- Preservative: Preventol D-7 Bayer AG, D-51368 Leverkusen, CAS # 55965-84-9 -to prevent the spread of bacteria and molds
- DGBE: Diethylenglycol-monobuthyl ether (DGBE), Fluka Chemie GmbH, CAS # 112-34-5 -to reduce relative permittivity

## 4.2 Recipes

The following tables give the recipes for tissue simulating liquids to be used in different frequency bands. Note: The goal dielectric parameters (at 22  $^{\circ}$ C) must be achieved within a tolerance of ±5% for  $\epsilon$  and ±5% for  $\sigma$ .

Ingredients	Frequency (MHz)											
(% by weight)	7!	50	83	35	17	50	19	00	24	50	26	00
Tissue Type	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body	Head	Body
Water	39.28	51.30	41.45	52.40	54.50	40.20	54.90	40.40	62.70	73.20	60.30	71.40
Salt (NaCl)	1.47	1.42	1.45	1.50	0.17	0.49	0.18	0.50	0.50	0.10	0.60	0.20
Sugar	58.15	46.18	56.00	45.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
HEC	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Bactericide	0.10	0.10	0.10	0.10	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
DGBE	0.00	0.00	0.00	0.00	45.33	59.31	44.92	59.10	36.80	26.70	39.10	28.40
Dielectric Constant	41.88	54.60	42.54	56.10	40.10	53.60	39.90	54.00	39.80	52.50	39.80	52.50
Conductivity (S/m)	0.90	0.97	0.91	0.95	1.39	1.49	1.42	1.45	1.88	1.78	1.88	1.78

Salt:  $99^+\%$  Pure Sodium Chloride Sugar:  $98^+\%$  Pure Sucrose Water: De-ionized,  $16\ M\Omega^+$  resistivity HEC: Hydroxyethyl Cellulose DGBE:  $99^+\%$  Di(ethylene glycol) butyl ether, [2-(2-butoxyethoxy)ethanol]

Triton X-100 (ultra pure): Polyethylene glycol mono [4-(1,1, 3, 3-tetramethylbutyl)phenyl]ether


Page 16 of 66



# 4.3 Liquid Depth

The liquid level was during measurement 15cm  $\pm 0.5$ cm.

According to KDB865664 ,the depth of tissue-equivalent liquid in a phantom must be  $\geq$  15.0 cm  $\pm$ 0.5 cm for SAR measurements  $\leq$  3 GHz and  $\geq$  10.0 cm  $\pm$ 0.5 cm for measurements > 3 GHz.



Report Number: 1304FS16 Page 17 of 66



# 5. SAR Testing with RF Transmitters

# 5.1 SAR Testing with 802.11 Transmitters

Normal network operating configurations are not suitable for measuring the SAR of 802.11 b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

### 5.2 General Device Setup

©2013 A Test Lab Techno Corp.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

#### **Frequency Channel Configurations**

802.11 a/b/g and 4.9 GHz operating modes are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz §15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. 4.9 GHz is tested on channels 1, 10 and 5 or 6, whichever has the higher output power, for 5 MHz channels; channels 11, 15 and 19 for 10 MHz channels; and channels 21 and 25 for 20 MHz channels. These are referred to as the "default test channels". 802.11g mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.

IEEE 802.11 Test Channels per FCC Requirement									
				Default Test "Channels"					
Mode	GHz	Channel	Turbo Channel	§15.247		UNII			
				802.11b	802.11g	OI	OINII		
	2412	1		✓	$\nabla$				
802.11 b/g	2437	6	6	✓	$\nabla$				
	2462	11		✓	$\nabla$				



## 5.3 Conducted Power

Band	Data Rate	СН	Frequency (MHz)	Average (dBı	
			(1711 12)	Aux	Main
	1 M	1	2412.0	17.36	17.21
		6	2437.0	17.49	17.29
IEEE 802.11b		11	2462.0	17.54	17.31
IEEE 002.110	2 M	6	2437.0	17.39	17.25
	5.5 M	6	2437.0	17.31	17.19
	11 M	6	2437.0	17.29	17.16
		1	2412.0	14.46	14.36
	6 M	6	2437.0	14.57	14.42
		11	2462.0	14.65	14.52
	9 M	6	2437.0	14.55	14.42
IEEE 002 11 a	12 M	6	2437.0	14.51	14.39
IEEE 802.11g	18 M	6	2437.0	14.48	14.36
	24 M	6	2437.0	14.45	14.34
	36 M	6	2437.0	14.42	14.32
	48 M	6	2437.0	14.38	14.27
	54 M	6	2437.0	14.35	14.22
	6.5 M	1	2412.0	14.40	14.21
		6	2437.0	14.70	14.53
IEEE 802.11n (2.4 GHz) 20MHz		11	2462.0	14.83	14.66
	13.0 M	6	2437.0	14.66	14.49
	19.5 M	6	2437.0	14.60	14.46
	26.0 M	6	2437.0	14.54	14.41
	39.0 M	6	2437.0	14.46	14.31
	52.0 M	6	2437.0	14.40	14.25
	58.5 M	6	2437.0	14.34	14.23
	65.0 M	6	2437.0	14.28	14.19
		1	2412.0	14.47	14.21
	13.5 M	6	2437.0	14.64	14.38
		11	2462.0	14.74	14.48
	27 M	6	2437.0	14.60	14.35
IEEE 802.11n (2.4 GHz)	40.5 M	6	2437.0	14.54	14.29
(2.4 GHZ) 40MHz	54 M	6	2437.0	14.48	14.26
	81 M	6	2437.0	14.40	14.22
	108 M	6	2437.0	14.34	14.19
	121.5 M	6	2437.0	14.28	14.13
	135 M	6	2437.0	14.22	14.09

Report Number: 1304FS16 Page 19 of 66




Band	СН	Frequency (MHz)	Packet Type	Average Power (dBm)
			DH1	-1.54
	0	2402	DH3	1.45
			DH5	1.98
Bluetooth v3.0			DH1	-1.92
	39	2441	DH3	1.04
GFSK			DH5	1.68
			DH1	-2.85
	78	2480	DH3	0.11
			DH5	0.75
	0	2402	DH1	-5.68
			DH3	-3.16
			DH5	-2.63
Bluetooth v3.0			DH1	-6.14
	39	2441	DH3	-3.67
$\pi$ /4-DQPSK			DH5	-3.14
	78	2480	DH1	-7.20
			DH3	-4.76
			DH5	-4.22
			DH1	-5.06
	0	2402	DH3	-3.13
			DH5	-2.59
Bluetooth v3.0			DH1	-6.09
	39	2441	DH3	-3.61
8DPSK			DH5	-3.09
			DH1	-7.14
	78	2480	DH3	-4.71
			DH5	-4.19

Report Number: 1304FS16 Page 20 of 66




# 5.4 Antenna location

Antenna to User					
Distance of Aux Anteni (mm)	na to edge	Distance of Main Antenna to edge (mm)			
Ant. to Side 1	3.40	Ant. to Side 1	3.40		
Ant. to Side 2	86.83	Ant. to Side 2	94.34		
Ant. to Side 3	Ant. to Side 3 249.41		239.31		
Ant. to Side 4	Ant. to Side 4 8.53		18.81		
Ant. to Side 5	Ant. to Side 5 16.90		246.90		
Ant. to Side 6	Ant. to Side 6 248.16		18.16		
Antenna to Antenna					
Antenna accou	ınt	Distance (cm)			
Aux Antenna to Main	Antenna	18.84			







#### 5.5 Stand-alone SAR Evaluate

There have no exclusion issue for transmitters.

Transmitter and antenna implementation as below:

Band	Aux antenna	Main antenna
WLAN V		V
Bluetooth	V	Х

Note: This device supports antenna diversity.

Stand-alone transmission configurations as below:

Band	Antenna	Side 1	Side 2	Side 3	Side 4	Side 5	Side 6
IEEE 802.11 b/g/n	Aux antenna				٧	V	
IEEE 802.11 b/g/n	Main antenna				V		V

Note: 1. The test reduction for distance less than 50mm. Use the max power to make sure minimum distance by evaluated for SAR testing.

- 2. The device should be test when the actual distance of antenna to edge less than power as above. (SAR test is required when the wlan antenna to edge < 30mm & the Bluetooth antenna to edge < 2 mm)
- 3. The side 1 (front surface) generally not required.

Report Number: 1304FS16 Page 22 of 66



Band	Channel	Power (dBm)	Frequency (GHz)	Distance (mm)	Power (mW)	Result	Limit	Exclusion Considerations SAR <sup>1g</sup>	Limit
IEEE 802.11 b	11	17.54	2.462	29	57	3.1	3	SAR is required	7.5
Bluetooth	0	1.98	2.402	1	2	3.1	3	SAR is required	7.5

Note: 1. The test reduction for distance less than 50mm. Use the max power to make sure minimum distance by evaluated for SAR testing.

2. The device should be test when the actual distance of antenna to edge less than power as above. (SAR test is required when the wlan antenna to edge < 30mm & the BT antenna to edge < 2 mm)

Band	Channel	Power (dBm)	Frequency (GHz)	Distance (mm)	Power (mW)	Power Thresholds SAR <sup>1g</sup> (mW)	Exclusion Considerations SAR <sup>1g</sup>
IEEE 802.11 b	11	17.54	2.462	51	57	106	SAR is not required
Bluetooth	0	1.98	2.402	51	2	107	SAR is not required

Note: The test reduction for distance more than 50mm. Use the max power to make sure minimum distance by evaluated for SAR testing.

For antenna to edge more than 50 mm that sar test is not required when the minimun distance(worst case) evaluated by results of above.

# 5.6 Simultaneous Transmitting Evaluate

Simultaneous transmission configurations as below:

Condition	Side		Frequency Band								
Condition	Side	WLAN (Aux antenna) WLAN (Main antenna) B		Bluetooth (Aux antenna)							
1	4	V	Х	V							
2	4	X	V	V							
3	5	Х	V	V							

Note: This device supports antenna diversity, therefore main antenna and aux antenna should be tested separate

#### 5.6.1 Estimated SAR

Side	Band	Channel	Power-Tune up (dBm)	Frequency (GHz)	Distance (mm)	Power (mW)	Estimated SAR <sup>1g</sup> (mW/g)
4	Bluetooth	0	4	2.402	8.53	3	0.07
5	Bluetooth	0	4	2.402	16.9	3	0.04

Page 23 of 66



#### 5.6.2 Sum of 1-g or 10-g SAR of all simultaneously transmitting

When the sum of 1-g or 10-g SAR of all simultaneously transmitting antennas in and operating mode and exposure condition combination is within the SAR limit, SAR test exclusion applies to that simultaneous transmission configuration.

Sum of 1-g SAR of summary as below:

	Phantom Position			Simult Tx 1		Simult Tx		Σ	_
Phanto	m Position	Spacing (mm)	ASSY	Band	SAR <sup>1g</sup> (mW/g)	Band	SAR <sup>1g</sup> (mW/g)	(mW/g)	Event
Flat	Side 4	0	N/A	Bluetooth	0.070	WLAN	0.501	0.571	<1.6
I lat	Side 5	0	N/A	Bluetooth	0.040	WLAN	0.037	0.077	<1.6

Note: 1. Since Bluetooth SAR test is not required that evaluated by test reduction, therefore estimated SAR is required in order to evaluate simultaneous transmission.

2. The test reduction for distance less than 50mm. Use the max power to make sure minimum distance by evaluated for SAR testing.

#### 5.6.3 SAR to peak location separation ratio (SPLSR)

When the sum of SAR is larger than the limit, SAR test exclusion is determined by the SAR to peak location separation ratio. The ratio is determined by  $(SAR1 + SAR2)^1.5/Ri$ , rounded to two decimal digits, and must be  $\leq 0.04$  for all antenna pairs in the configuration to qualify for 1-g SAR test exclusion.

All of sum of SAR < 1.6 W/Kg, therefore SPLSR is not required.

Report Number: 1304FS16 Page 24 of 66



### 5.7 SAR test reduction according to KDB

#### General:

- The test data reported are the worst-case SAR value with the position set in a typical configuration.
   Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001], IEEE1528-2003 and IEEE Std. 1528a-2005.
- All modes of operation were investigated, and worst-case results are reported.
- Tissue parameters and temperatures are listed on the SAR plots.
- Batteries are fully charged for all readings.
- When the Channel's SAR 1g of maximum conducted power is > 0.8 mW/g, low, middle and high channel are supposed to be tested.

#### KDB 447498:

The test data reported are the worst-case SAR value with the position set in a typical configuration.
 Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001], IEEE1528-2003 and IEEE Std. 1528a-2005.

#### KDB 865664:

- Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg.</li>
- When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
- Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg.
- Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5
   W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

#### KDB 248227:

• If the conducted power of (802.11g and 802.11n) are higher than 802.11b 0.25dB,(802.11g and 802.11n) are supposed to be tested.

Report Number: 1304FS16 Page 25 of 66



# 6. System Verification and Validation

# 6.1 Symmetric Dipoles for System Verification

Construction Symmetrical dipole with I/4 balun enables measurement of feed point impedance with NWA

matched for use near flat phantoms filled with head simulating solutions Includes distance holder and tripod adaptor Calibration Calibrated SAR value for specified position and input

power at the flat phantom in head simulating solutions.


Frequency 2450 MHz

Return Loss > 20 dB at specified verification position Power Capability > 100 W (f < 1GHz); > 40 W (f > 1GHz)

Options Dipoles for other frequencies or solutions and other calibration conditions are available upon

request

Dimensions D2450V2: dipole length 51.5 mm; overall height 300 mm



Report Number: 1304FS16 Page 26 of 66



# 6.2 Liquid Parameters

Liquid Verif	y										
Ambient Temperature: 22 ± 2 °C; Relative Humidity: 40 -70%											
Liquid Type	iquid Type Frequency Temp (°C) Parameters Target Value Measured Deviation (%) Measured Date										
	2400MHz	22.0	٤r	52.77	52.13	-1.21	± 5				
		22.0	σ	1.902	1.889	-0.68	± 5				
2450MHz	245014117	22.0	٤r	52.70	51.92	-1.48	± 5	Apr 22 2012			
(Body)	2450MHz	lz 22.0	σ	1.950	1.964	0.72	± 5	Apr. 23, 2013			
	2500MHz	500MHz 22.0	٤r	52.64	51.77	-1.65	± 5				
	2500MHz		σ	2.021	2.038	0.84	± 5				

Table 4. Measured Tissue dielectric parameters for body phantoms

Report Number: 1304FS16 Page 27 of 66



### 6.3 Verification Summary

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm$  7%. The verification was performed at 2450MHz.

Mixture Frequency Type (MHz)		Power	SAR <sub>1g</sub>	SAR <sub>10g</sub>	Drift		rence ntage	Probe	Dipole	1W T	arget	Date
	(MHz)		(mW/g)	(mW/g)	(dB)	1g	10g	Model / Serial No.	Model / Serial No.	SAR <sub>1g</sub> (mW/g)	SAR <sub>10g</sub> (mW/g)	Dute
	0.450	250 mW	12.8	5.98	0.40	1 000/	1 000/	EX3DV3	D2450V2	<b>50.00</b>		
Body 2450	Normalize to 1 Watt	51.20	23.92	0.12	1.80%	1.80%	SN:3519 SN:712		50.30	23.50	Apr. 23, 2013	

### 6.4 Validation Summary

Per FCC KDB 865664 D02v01, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in IEEE 1528-2003 and FCC KDB 865664 D01v01. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters as below.

Probe Type	Prob Cal.	Lload /	Cond.	Perm.	C'	W Validation	1	Мо	od. Validati	on	
Model / Point		" Head / Body	er	σ	Sensitivity	Probe	Probe	Mod.	Duty	PAR	Date
Serial No.	(IVII IZ)		CI		Schsilivity	Linearity	Isotropy	Туре	Factor	FAR	
EX3DV3 SN:3519	2450	Body	51.92	1.964	Pass	Pass	Pass	OFDM	N/A	Pass	Apr. 23, 2013



# 7. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calib	ration	
Iviaridiacidiei	Name of Equipment	i ype/iviodei	Serial Number	Last Cal.	Due Date	
SPEAG	2450MHz System Validation Kit	D2450V2	712	Feb. 19, 2013	Feb. 19, 2014	
SPEAG	Dosimetric E-Field Probe	EX3DV3	3519	Feb. 20, 2013	Feb. 20, 2014	
SPEAG	Data Acquisition Electronics	DAE4	779	Feb. 13, 2013	Feb. 13, 2014	
SPEAG	Device Holder	N/A	N/A	NO	CR	
SPEAG	Measurement Server	SE UMS 011 AA	1025	NO	CR	
SPEAG	Phantom	ELI v5.0	TP-1133	NO	CR	
SPEAG	Robot	Staubli TX90XL	F07/564ZA1/C/01	NO	CR	
SPEAG	Software	DASY5 V5.0 Build 125	N/A	NCR		
SPEAG	Software	SEMCAD V13.4 Build 125	N/A	NO	CR	
Agilent	Dielectric Probe Kit	85070C	US99360094	NO	CR	
Agilent	ENA Series Network Analyzer	E5071B	MY42404655	Apr. 05, 2012	Apr. 05, 2014	
R&S	Power Sensor	NRP-Z22	100179	May 16, 2012	May 16, 2013	
Agilent	MXG Vector Signal Generator	N5182A	MY47420962	May 24, 2012	May 24, 2014	
Agilent	Dual Directional Coupler	778D	50334	NCR		
Mini-Circuits	Power Amplifier	ZHL-42W-SMA	D111103#5	NO	CR	
Mini-Circuits	Power Amplifier	ZVE-8G-SMA	D042005 671800514	NO	CR	
Aisi	Attenuator	IEAT 3dB	N/A	NO	CR	

Table 5. Test Equipment List

Report Number: 1304FS16 Page 29 of 66



# 8. Measurement Uncertainty

Measurement uncertainties in SAR measurements are difficult to quantify due to several variables including biological, physiological, and environmental. However, we estimate the measurement uncertainties in SAR to be less than  $\pm 19.62~\%$  [ 8 ] . The frequency range of the measurement uncertainty is 750  $\sim$  5800MHz  $\pm 10.1~\%$ 

According to Std. C95.3 [9], the overall uncertainties are difficult to assess and will vary with the type of meter and usage situation. However, accuracy's of  $\pm$  1 to 3 dB can be expected in practice, with greater uncertainties in near-field situations and at higher frequencies (shorter wavelengths), or areas where large reflecting objects are present. Under optimum measurement conditions, SAR measurement uncertainties of at least  $\pm$  2dB can be expected.

According to CENELEC ( 10 ) , typical worst-case uncertainty of field measurements is  $\pm$  5 dB. For well-defined modulation characteristics the uncertainty can be reduced to  $\pm$  3 dB.

Report Number: 1304FS16 Page 30 of 66



Item	Uncertainty Component	Uncertainty Value	Prob. Dist	Div.	<i>c<sub>i</sub></i> (1g)	<i>c<sub>i</sub></i> (10g)	Std. Unc. (1-g)	Std. Unc. (10-g)	$egin{array}{c} oldsymbol{V_i} \ oldsymbol{V_{eff}} \end{array}$
Meas	urement System								
u1	Probe Calibration (k=1)	±5.05%	Normal	1	1	1	±5.05%	±5.05%	8
u2	Probe Isotropy	±7.6%	Rectangular	$\sqrt{3}$	0.7	0.7	±3.1%	±3.1%	8
u3	Boundary Effect	±1.0%	Rectangular	$\sqrt{3}$	1	1	±0.6%	±0.6%	8
u4	Linearity	±4.7%	Rectangular	$\sqrt{3}$	1	1	±2.7%	±2.7%	8
u5	System Detection Limit	±1.0%	Rectangular	$\sqrt{3}$	1	1	±0.58%	±0.58%	8
u6	Readout Electronics	±0.3%	Normal	1	1	1	±0.3%	±0.3%	8
u7	Response Time	±0.8%	Rectangular	$\sqrt{3}$	1	1	±0.5%	±0.5%	8
u8	Integration Time	±2.6%	Rectangular	$\sqrt{3}$	1	1	±1.5%	±1.5%	8
u9	RF Ambient Conditions	±0%	Rectangular	$\sqrt{3}$	1	1	±0%	±0%	8
u10	RF Ambient Reflections	±0%	Rectangular	$\sqrt{3}$	1	1	±0%	±0%	8
u11	Probe Positioner Mechanical Tolerance	±0.4%	Rectangular	$\sqrt{3}$	1	1	±0.2%	±0.2%	8
u12	Probe Positioning with respect to Phantom Shell	±2.9%	Rectangular	$\sqrt{3}$	1	1	±1.7%	±1.7%	8
u13	Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	±1.0%	Rectangular	$\sqrt{3}$	1	1	±0.6%	±0.6%	80
Test s	ample Related								
u14	Test sample Positioning	±3.6%	Normal	1	1	1	±3.6%	±3.6%	89
u15	Device Holder Uncertainty	±3.5%	Normal	1	1	1	±3.5%	±3.5%	5
u16	Output Power Variation - SAR drift measurement	±5.0%	Rectangular	$\sqrt{3}$	1	1	±2.9%	±2.9%	8
Phant	tom and Tissue Parameters								
u17	Phantom Uncertainty ( shape and thickness tolerances)	±4.0%	Rectangular	$\sqrt{3}$	1	1	±2.3%	±2.3%	8
u18	Liquid Conductivity - deviation from target values	±5.0%	Rectangular	$\sqrt{3}$	0.64	0.43	±1.8%	±1.2%	8
u19	Liquid Conductivity - measurement uncertainty	±1.93%	Normal	1	0.64	0.43	±1.24%	±0.83%	69
u20	Liquid Permittivity - deviation from target values	±5.0%	Rectangular	$\sqrt{3}$	0.6	0.49	±1.7%	±1.4%	8
u21	Liquid Permittivity - measurement uncertainty	±1.4%	Normal	1	0.6	0.49	±0.84%	±1.69%	69
	Combined standard uncertaint	RSS				±9.81%	±9.62%	313	
	Expanded uncertainty (95% CONFIDENCE LEVEL)	1	<i>k</i> =2				±19.62%	±19.24%	

Table 6. Uncertainty Budget of DASY

Report Number: 1304FS16 Page 31 of 66



#### 9. Measurement Procedure

The measurement procedures are as follows:

- For WLAN function, engineering testing software installed on Notebook can provide continuous transmitting signal.
- 2. Measure output power through RF cable and power meter
- 3. Set scan area, grid size and other setting on the DASY software
- 4. Find out the largest SAR result on these testing positions of each band
- 5. Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- 1. Power reference measurement
- 2. Area scan
- 3. Zoom scan

©2013 A Test Lab Techno Corp.

4. Power drift measurement

#### 9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages

- 1. Extraction of the measured data (grid and values) from the Zoom Scan
- 2. Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- 3. Generation of a high-resolution mesh within the measured volume
- 4. Interpolation of all measured values form the measurement grid to the high-resolution grid
- 5. Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- 6. Calculation of the averaged SAR within masses of 1g and 10g



#### 9.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures points and step size follow as below. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

Grid Type	Frequ	Frequency		Step size (mm)		X*Y*Z	(	Cube size	Ċ.	Step size		
	$\leq 3 \text{GHz}$ uniform grid		Χ	Υ	Z	(Point)	Χ	Υ	Z	Χ	Υ	Z
		≦2GHz	≤8	≤8	≤ 5	5*5*7	32	32	30	8	8	5
uniform grid		2G - 3G	≤ 5	≤ 5	≤ 5	7*7*7	30	30	30	5	5	5
uniionn gna		3 - 4GHz	≤ 5	≤ 5	≤ 4	7*7*8	30	30	28	5	5	4
3 - 6GHz	3 - 6GHz	4 - 5GHz	≤ 4	≤ 4	≤ 3	8*8*10	28	28	27	4	4	3
		5 - 6GHz	≤ 4	≤ 4	≤ 2	8*8*12	28	28	22	4	4	2

(Our measure settings are refer KDB Publication 865664 D01v01)

#### 9.3 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the DUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

#### 9.4 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

### 9.5 Power Drift Monitoring

All SAR testing is under the DUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of DUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

Report Number: 1304FS16 Page 33 of 66



# 10. SAR Test Results Summary

#### 10.1 Head Measurement SAR

Evaluated head SAR is not available.

## 10.2 Body Measurement SAR

Index.	Position	Band	Ch.	Data Rate or Sub-Test	Side to Phantom	Spacing (mm)	SAR <sub>1g</sub> (mW/g)	Power Drift	Burst Avg Power	Max. Tune-Up	Reported SAR <sub>1g</sub>
#1	Flat	IEEE 802.11b	11	1M	4 (Main Ant.)	0	0.159	-0.020	17.31	18.5	0.209
#2	Flat	IEEE 802.11b	11	1M	5 (Main Ant.)	0	0.028	-0.090	17.31	18.5	0.037
#3	Flat	IEEE 802.11b	11	1M	4 (Aux Ant.)	0	0.402	0.140	17.54	18.5	0.501
#4	Flat	IEEE 802.11b	11	1M	6 (Aux Ant.)	0	0.017	-0.040	17.54	18.5	0.021

Note: 1. According KDB 447498 D01 V05 section 4.1.4, the "Reported" explanation as below: 
"When SAR or MPE is measured at or scaled to the maximum tune-up tolerance limit, the results are referred to as reported."

- 2. If actual power less than tune-up power that Scaling SAR is required.
- 3. The formula of Reported SAR, that represent as below:

  Reported SAR = Original SAR \* 10^[(Tune-up power Actual power)/10]
- 4. If the Channel's SAR 1g of maximum conducted power is > 0.8 mW/g, low, middle and high channel are supposed to be tested.

## 10.3 Hot-spot mode Measurement SAR

Hot-spot mode measurement SAR is not available.

### 10.4 Extremity Measurement SAR

Evaluated extremity SAR is not available.

### 10.5 SAR Measurement Variability

©2013 A Test Lab Techno Corp.

Detailed evaluations please refer KDB 865664 on "SAR test reduction according to KDB" section. Variability SAR is not available.



# 10.6 Std. C95.1-1999 RF Exposure Limit

	Population	Occupational		
Human Exposure	Uncontrolled	Controlled		
Truman Exposure	Exposure	Exposure		
	( W/kg ) or (mW/g)	( W/kg ) or (mW/g)		
Spatial Peak SAR*	1.60	8.00		
(head)	1.00			
Spatial Peak SAR**	0.08	0.40		
(Whole Body)	0.00	0.40		
Spatial Peak SAR***	1.60	8.00		
(Partial-Body)	1.00			
Spatial Peak SAR****	4.00	20.00		
(Hands / Feet / Ankle / Wrist )	4.00	20.00		

Table 7. Safety Limits for Partial Body Exposure

#### Notes:

- \* The Spatial Peak value of the SAR averaged over any 1 gram of tissue.( defined as a tissue volume in the shape of a cube ) and over the appropriate averaging time.
- \*\* The Spatial Average value of the SAR averaged over the whole body.
- \*\*\* The Spatial Average value of the SAR averaged over the partial body.
- \*\*\*\* The Spatial Peak value of the SAR averaged over any 10 grams of tissue.

  ( defined as a tissue volume in the shape of a cube ) and over the appropriate averaging time.

**Population / Uncontrolled Environments:** are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

**Occupational / Controlled Environments:** are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

Report Number: 1304FS16 Page 35 of 66



## 11. Conclusion

The SAR test values found for the portable mobile phone **Tobii Technology AB Trade Name : Tobii Model(s) : I-12 ETR, I-12 R** is below the maximum recommended level of 1.6 W/kg (mW/g).

#### 12. References

- [1] Std. C95.1-1999, "American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300KHz to 100GHz", New York.
- [2] NCRP, National Council on Radiation Protection and Measurements, "Biological Effects and Exposure Criteria for Radio frequency Electromagnetic Fields", NCRP report NO. 86, 1986.
- [3] T. Schmid, O. Egger, and N. Kuster, "Automatic E-field scanning system for dosimetric assessments", IEEE Transactions on Microwave Theory and Techniques, vol. 44, pp, 105-113, Jan. 1996.
- [4] K. Pokovi<sup>c</sup>, T. Schmid, and N. Kuster, "Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequency", in ICECOM'97, Dubrovnik, October 15-17, 1997, pp.120-124.
- [5] K. Pokovi<sup>c</sup>, T. Schmid, and N. Kuster, "E-field probe with improved isotropy in brain simulating liquids", in Proceedings of the ELMAR, Zadar, Croatia, 23-25 June, 1996, pp.172-175.
- [6] N. Kuster, and Q. Balzano, "Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz", IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [7] Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148.
- [8] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [9] Std. C95.3-1991, "IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields RF and Microwave, New York: IEEE, Aug. 1992.
- [10] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10KHz-300GHz, Jan. 1995.
- [11] IEEE Std 1528™-2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head From Wireless Communications Devices: Measurement Techniques
- [12] IEEE Std 1528a<sup>™</sup>-2005 (Amendment to IEEE Std 1528<sup>™</sup>-2003), IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques

#### 13. SAR Measurement Guidance

©2013 A Test Lab Techno Corp.

- [1] KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01
- [2] KDB 447498 D01 General RF Exposure Guidance v05
- [3] KDB 248227 D01 SAR meas for 802 11 a b g v01r02.
- [4] KDB 616217 D04 SAR for laptop and tablets v01.



## Appendix A - System Performance Check

Date/Time: 4/23/2013 1:25:42 PM

System Performance Check at 2450MHz\_20130423\_Body

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:712

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: f = 2450 MHz;  $\sigma = 1.96 \text{ mho/m}$ ;  $\varepsilon_r = 51.9$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

**DASY5** Configuration:

• Area Scan setting - Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg

Probe: EX3DV3 - SN3519; ConvF(7.88, 7.88, 7.88); Calibrated: 2/20/2013

Sensor-Surface: 2mm (Mechanical Surface Detection)

• Electronics: DAE4 Sn779; Calibrated: 2/13/2013

Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1133

• Measurement SW: DASY5, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

#### System Performance Check at 2450MHz/Area Scan (91x91x1):

Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 19.5 mW/g

#### System Performance Check at 2450MHz/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.4 V/m; Power Drift = 0.120 dB

Peak SAR (extrapolated) = 26.3 W/kg

SAR(1 g) = 12.8 mW/g; SAR(10 g) = 5.98 mW/g

Maximum value of SAR (measured) = 19.5 mW/g



0 dB = 19.5 mW/g

Report Number: 1304FS16 Page 37 of 66



## Appendix B - SAR Measurement Data

Test Laboratory: A Test Lab Techno Corp. Date/Time: 4/23/2013 3:57:45 PM

#1\_Flat\_802.11b CH11\_1M\_Side 4 to phantom 0mm\_Main Antenna

DUT: I-12 ETR; Type: Tobii I-12 ; FCC ID: W5M-TOBIII12A

Communication System: IEEE 802.11b; Frequency: 2462 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2462 MHz;  $\sigma = 1.98$  mho/m;  $\epsilon r = 51.9$ ;  $\rho = 1000$  kg/m3

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV3 SN3519; ConvF(7.88, 7.88, 7.88); Calibrated: 2/20/2013
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 2/13/2013
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1133
- Measurement SW: DASY5, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

## Flat/Area Scan (181x151x1):


Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (interpolated) = 0.260 mW/g

## Flat/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 0.451 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 0.319 W/kg

SAR(1 g) = 0.159 mW/g; SAR(10 g) = 0.077 mW/g Maximum value of SAR (measured) = 0.233 mW/g





0 dB = 0.233 mW/g

Report Number: 1304FS16 Page 38 of 66



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 4/23/2013 7:43:28 PM

#2\_Flat\_802.11b CH11\_1M\_Side 5 to phantom 0mm\_Main Antenna

DUT: I-12 ETR; Type: Tobii I-12; FCC ID: W5M-TOBIII12A

Communication System: IEEE 802.11b; Frequency: 2462 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2462 MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV3 SN3519; ConvF(7.88, 7.88, 7.88); Calibrated: 2/20/2013
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 2/13/2013
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1133
- Measurement SW: DASY5, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

## Flat/Area Scan (181x151x1):

Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (interpolated) = 0.042 mW/g


## Flat/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 0.298 V/m; Power Drift = -0.09 dB

Peak SAR (extrapolated) = 0.052 W/kg

SAR(1 g) = 0.028 mW/g; SAR(10 g) = 0.014 mW/g Maximum value of SAR (measured) = 0.038 mW/g





0 dB = 0.038 mW/g

Report Number: 1304FS16 Page 39 of 66



 ${\sf Test\ Laboratory:\ A\ Test\ Lab\ Techno\ Corp.}$ 

Date/Time: 4/23/2013 4:55:01 PM

#3\_Flat\_802.11b CH11\_1M\_Side 4 to phantom 0mm\_Aux Antenna

DUT: I-12 ETR; Type: Tobii I-12; FCC ID: W5M-TOBIII12A

Communication System: IEEE 802.11b; Frequency: 2462 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2462 MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV3 SN3519; ConvF(7.88, 7.88, 7.88); Calibrated: 2/20/2013
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 2/13/2013
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1133
- Measurement SW: DASY5, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

## Flat/Area Scan (181x151x1):

Measurement grid: dx=10mm, dy=10mm


Maximum value of SAR (interpolated) = 0.625 mW/g


## Flat/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 0.537 V/m; Power Drift = 0.14 dB

Peak SAR (extrapolated) = 0.893 W/kg

SAR(1 g) = 0.402 mW/g; SAR(10 g) = 0.177 mW/gMaximum value of SAR (measured) = 0.627 mW/g





0 dB = 0.627 mW/g

Report Number: 1304FS16 Page 40 of 66



Test Laboratory: A Test Lab Techno Corp.

Date/Time: 4/23/2013 8:54:39 PM

#4\_Flat\_802.11b CH11\_1M\_Side 6 to phantom 0mm\_Aux Antenna

DUT: I-12 ETR; Type: Tobii I-12 ; FCC ID: W5M-TOBIII12A

Communication System: IEEE 802.11b; Frequency: 2462 MHz;Duty Cycle: 1:1 Medium parameters used: f = 2462 MHz;  $\sigma = 1.98$  mho/m;  $\epsilon_r = 51.9$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Area Scan setting Find Secondary Maximum Within: 2.0dB and with a peak SAR value greater than 0.5 W/Kg
- Probe: EX3DV3 SN3519; ConvF(7.88, 7.88, 7.88); Calibrated: 2/20/2013
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn779; Calibrated: 2/13/2013
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1133
- Measurement SW: DASY5, V5.0 Build 125;SEMCAD X Version 13.4 Build 125

## Flat/Area Scan (181x151x1):

Measurement grid: dx=10mm, dy=10mm

Maximum value of SAR (interpolated) = 0.024 mW/g


## Flat/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 1.13 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 0.036 W/kg

## SAR(1 g) = 0.017 mW/g; SAR(10 g) = 0.00888 mW/g

Maximum value of SAR (measured) = 0.026 mW/g





0 dB = 0.026 mW/g

Report Number: 1304FS16 Page 41 of 66



## Appendix C - Calibration

All of the instruments Calibration information are listed below.

- Dipole \_ D2450V2 SN:712 Calibration No.D2450V2-712\_Feb13
- Probe \_ EX3DV3 SN:3519 Calibration No.EX3-3519\_Feb13
- DAE \_ DAE4 SN:779 Calibration No.DAE4-779\_Feb13

Report Number: 1304FS16 Page 42 of 66



## Calibration Laboratory of Schmid & Partner

Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Client ATL (Auden)

Accreditation No.: SCS 108

Certificate No: D2450V2-712\_Feb13

## CALIBRATION CERTIFICATE

Object D2450V2 - SN: 712

Calibration procedure(s) QA CAL-05.v9

Calibration procedure for dipole validation kits above 700 MHz

Calibration date: February 19, 2013

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).

The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	1D #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter EPM-442A	GB37480704	01-Nov-12 (No. 217-01640)	Oct-13
Power sensor HP 8481A	US37292783	01-Nov-12 (No. 217-01640)	Oct-13
Reference 20 dB Attenuator	SN: 5058 (20k)	27-Mar-12 (No. 217-01530)	Apr-13
Type-N mismatch combination	SN: 5047.3 / 06327	27-Mar-12 (No. 217-01533)	Apr-13
Reference Probe ES3DV3	SN: 3205	28-Dec-12 (No. ES3-3205_Dec12)	Dec-13
DAE4	SN: 601	27-Jun-12 (No. DAE4-601_Jun12)	Jun-13
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (in house check Oct-11)	In house check: Oct-13
RF generator R&S SMT-06	100005	04-Aug-99 (in house check Oct-11)	In house check: Oct-13
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (in house check Oct-12)	In house check: Oct-13
	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	Sel War
Approved by:	Katja Pokovic	Technical Manager	00 111

Issued: February 20, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



## Calibration Laboratory of Schmid & Partner

Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst C Service suisse d'étalonnage

Servizio svizzero di taratura Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL tissue simulating liquid

ConvF sensitivity in TSL / NORM x,y,z N/A not applicable or not measured

## Calibration is Performed According to the Following Standards:

 a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003

 IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

#### Additional Documentation:

d) DASY4/5 System Handbook

## Methods Applied and Interpretation of Parameters:

- Measurement Conditions: Further details are available from the Validation Report at the end
  of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL: The dipole is mounted with the spacer to position its feed
  point exactly below the center marking of the flat phantom section, with the arms oriented
  parallel to the body axis.
- Feed Point Impedance and Return Loss: These parameters are measured with the dipole
  positioned under the liquid filled phantom. The impedance stated is transformed from the
  measurement at the SMA connector to the feed point. The Return Loss ensures low
  reflected power. No uncertainty required.
- Electrical Delay: One-way delay between the SMA connector and the antenna feed point.
   No uncertainty required.
- SAR measured: SAR measured at the stated antenna input power.
- SAR normalized: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Certificate No: D2450V2-712\_Feb13

Page 2 of 8



## **Measurement Conditions**

DASY system configuration, as far as not given on page 1.

DASY Version	DASY5	V52.8.5
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz ± 1 MHz	

## Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 ± 0.2) °C	37.9 ± 6 %	1.85 mho/m ± 6 %
Head TSL temperature change during test	< 0.5 °C		

## SAR result with Head TSL

SAR averaged over 1 cm <sup>2</sup> (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.4 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.5 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL	condition	
SAR measured	250 mW input power	6.20 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.5 W/kg ± 16.5 % (k=2)

## Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 ± 0.2) °C	50.9 ± 6 %	2.02 mho/m ± 6 %
Body TSL temperature change during test	< 0.5 °C		****

## SAR result with Body TSL

SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.9 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	50.3 W/kg ± 17.0 % (k=2)

SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL	condition	
SAR measured	250 mW input power	5.95 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.5 W/kg ± 16.5 % (k=2)



## Appendix

## Antenna Parameters with Head TSL

Impedance, transformed to feed point	$54.8 \Omega + 1.3 j\Omega$	
Return Loss	- 26.5 dB	

## Antenna Parameters with Body TSL

Impedance, transformed to feed point	$49.4 \Omega + 5.0 j\Omega$	
Return Loss	- 25.9 dB	

## General Antenna Parameters and Design

Electrical Delay (one direction)	1.158 ns

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

## **Additional EUT Data**

Manufactured by	SPEAG	
Manufactured on	July 05, 2002	



## DASY5 Validation Report for Head TSL

Date: 19.02.2013

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 712

Communication System: CW; Frequency: 2450 MHz.

Medium parameters used: f = 2450 MHz;  $\sigma = 1.85 \text{ S/m}$ ;  $\varepsilon_r = 37.9$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

#### DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(4.52, 4.52, 4.52); Calibrated: 28.12.2012;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 27.06.2012


Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001

DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

## Dipole Calibration for Head Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 99.359 V/m; Power Drift = 0.05 dB Peak SAR (extrapolated) = 28.2 W/kg


SAR(1 g) = 13.4 W/kg; SAR(10 g) = 6.2 W/kg Maximum value of SAR (measured) = 17.1 W/kg



0 dB = 17.1 W/kg = 12.33 dBW/kg



## Impedance Measurement Plot for Head TSL





## DASY5 Validation Report for Body TSL

Date: 18.02.2013

Test Laboratory; SPEAG, Zurich, Switzerland

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 712

Communication System: CW; Frequency: 2450 MHz

Medium parameters used: f = 2450 MHz;  $\sigma = 2.02 \text{ S/m}$ ;  $\varepsilon_r = 50.9$ ;  $\rho = 1000 \text{ kg/m}^3$ 

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

## DASY52 Configuration:

Probe: ES3DV3 - SN3205; ConvF(4.42, 4.42, 4.42); Calibrated: 28.12.2012;

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn601; Calibrated: 27.06.2012

Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002


DASY52 52.8.5(1059); SEMCAD X 14.6.8(7028)

## Dipole Calibration for Body Tissue/Pin=250 mW, d=10mm/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 93.989 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 27.1 W/kg


SAR(1 g) = 12.9 W/kg; SAR(10 g) = 5.95 W/kg Maximum value of SAR (measured) = 16.8 W/kg



0 dB = 16.8 W/kg = 12.25 dBW/kg



## Impedance Measurement Plot for Body TSL





Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA

Multilateral Agreement for the recognition of calibration certificates

Client

ATL (Auden)

Certificate No: EX3-3519\_Feb13

Accreditation No.: SCS 108

## CALIBRATION CERTIFICATE

Object EX3DV3 - SN:3519

Calibration procedure(s) QA CAL-01.v8, QA CAL-12.v7, QA CAL-14.v3, QA CAL-23.v4,

QA CAL-25.v4

Calibration procedure for dosimetric E-field probes

Calibration date: February 20, 2013

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Philosophy Philosophy and Company	um.	The case of the Color of the Color	
Primary Standards	1D	Cal Date (Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-12 (No. 217-01508)	Apr-13
Power sensor E4412A	MY41498087	29-Mar-12 (No. 217-01508)	Apr-13
Reference 3 dB Attenuator	SN: S5054 (3c)	27-Mar-12 (No. 217-01531)	Apr-13
Reference 20 dB Attenuator	SN: S5086 (20b)	27-Mar-12 (No. 217-01529)	Apr-13
Reference 30 dB Attenuator	SN: S5129 (30b)	27-Mar-12 (No. 217-01532)	Apr-13
Reference Probe ES3DV2	SN: 3013	28-Dec-12 (No. ES3-3013_Dec12)	Dec-13
DAE4	SN: 660	31-Jan-13 (No. DAE4-660_Jan13)	Jan-13
Secondary Standards	ID.	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (in house check Apr-11)	In house check: Apr-13
Network Analyzer HP 8753E	US37390585	18-Oct-01 (in house check Oct-12)	In house check: Oct-13

Name Function Signature

Calibrated by: Jeton Kastrati Laboratory Technician

Approved by: Katja Pokovic Technical Manager

Issued: February 22, 2013

This calibration certificate shall not be reproduced except in full without written approval of the laboratory

Certificate No: EX3-3519\_Feb13 Page 1 of 11



#### Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





S

Schweizerischer Kalibrierdienst Service suisse d'étalonnage C Servizio svizzero di taratura Swiss Calibration Service

Accreditation No.: SCS 108

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL tissue simulating liquid NORMx,y,z sensitivity in free space ConvF sensitivity in TSL / NORMx,y,z DCP diode compression point

crest factor (1/duty\_cycle) of the RF signal modulation dependent linearization parameters CF A, B, C, D

Polarization @ o rotation around probe axis

9 rotation around an axis that is in the plane normal to probe axis (at measurement center), Polarization 9

i.e., 8 = 0 is normal to probe axis

#### Calibration is Performed According to the Following Standards:

IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement

Techniques", December 2003
b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

#### Methods Applied and Interpretation of Parameters:

- NORMx,y,z: Assessed for E-field polarization 9 = 0 (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not affect the E2-field uncertainty inside TSL (see below ConvF)
- NORM(f)x,y,z = NORMx,y,z \* frequency\_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCPx,y,z: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- Ax.y.z; Bx,y.z; Cx,y.z; Dx,y.z; VRx,y.z: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters: Assessed in flat phantom using E-field (or Temperature Transfer Standard for f ≤ 800 MHz) and inside waveguide using analytical field distributions based on power measurements for f > 800 MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORMx,y,z \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100
- Spherical isotropy (3D deviation from isotropy): in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Certificate No: EX3-3519 Feb13

Page 2 of 11



# Probe EX3DV3

SN:3519

Manufactured: March 8, 2004 Calibrated:

February 20, 2013

Calibrated for DASY/EASY Systems (Note: non-compatible with DASY2 system!)

Certificate No: EX3-3519\_Feb13

Page 3 of 11



## DASY/EASY - Parameters of Probe: EX3DV3 - SN:3519

## **Basic Calibration Parameters**

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm (µV/(V/m) <sup>2</sup> ) <sup>A</sup>	0.82	0.70	0.72	± 10.1 %
DCP (mV) <sup>II</sup>	100.2	99.1	102.5	

## Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√μV	С	D dB	VR mV	Unc* (k=2)
0	CW	X	0.0	0.0	1.0	0.00	112.7	±3.0 %
		Y	0.0	0.0	1.0		116.6	
		Z	0.0	0.0	1.0		142.1	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

Numerical linearization parameter: uncertainty not required.

Uncertainty is determined using the max, deviation from linear response applying rectangular distribution and is expressed for the square of the</sup> 



## DASY/EASY - Parameters of Probe: EX3DV3 - SN:3519

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) <sup>C</sup>	Relative Permittivity	Conductivity (S/m) F	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
450	43.5	0.87	10.80	10.80	10.80	0.13	1.43	± 13.4 9
750	41.9	0.89	11.12	11.12	11.12	0.18	1.41	± 12.0 9
835	41.5	0.90	10.73	10.73	10.73	0.12	1.92	± 12.0 9
900	41.5	0.97	10.72	10.72	10.72	0.31	0.90	± 12.0 9
1750	40.1	1,37	9.03	9.03	9.03	0.30	0.91	± 12.0 9
1810	40.0	1.40	8.85	8.85	8.85	0.46	0.72	± 12.0 9
1900	40.0	1.40	8.79	8.79	8.79	0.34	0.83	± 12.0 9
2000	40.0	1.40	8.76	8.76	8.76	0.38	0.83	± 12.0 9
2100	39.8	1.49	8.93	8.93	8.93	0.76	0.57	± 12.0 9
2300	39.5	1.67	8.40	8.40	8.40	0.39	0.80	± 12.0 9
2450	39.2	1.80	7.94	7.94	7.94	0.31	0.92	± 12.0 9
2600	39.0	1.96	7.69	7.69	7.69	0.36	0.89	± 12.0 9
5200	36.0	4.66	4.99	4.99	4.99	0.41	1.80	± 13.1 9
5300	35.9	4.76	4.86	4.86	4.86	0.42	1.80	± 13.1 9
5500	35.6	4.96	4.51	4.51	4.51	0.45	1.80	± 13.1 9
5600	35.5	5,07	4.31	4,31	4.31	0.45	1.80	± 13.1 9
5800	35.3	5.27	4.28	4.28	4.28	0.48	1.80	± 13.1 9

Certificate No: EX3-3519\_Feb13

<sup>&</sup>lt;sup>C</sup> Frequency validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

At frequencies below 3 GHz, the validity of tissue parameters (c and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (c and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.



## DASY/EASY - Parameters of Probe: EX3DV3 - SN:3519

## Calibration Parameter Determined in Body Tissue Simulating Media


f (MHz) <sup>C</sup>	Relative Permittivity <sup>F</sup>	Conductivity (S/m) <sup>F</sup>	ConvF X	ConvF Y	ConvF Z	Alpha	Depth (mm)	Unct. (k=2)
450	56.7	0.94	11.79	11.79	11.79	0.05	1.25	± 13.4 9
750	55.5	0.96	10.78	10.78	10.78	0.42	0.86	± 12.0 9
835	55.2	0.97	10.56	10.56	10.56	0.20	1.37	± 12.0 9
900	55.0	1.05	10.46	10.46	10.46	0.36	0.93	± 12.0 9
1750	53.4	1.49	8.99	8.99	8.99	0.49	0.69	± 12.0 %
1810	53.3	1.52	8.79	8.79	8.79	0.54	0.68	± 12.0 9
1900	53.3	1.52	8.58	8.58	8.58	0.26	1.00	± 12.0 9
2000	53.3	1.52	8.61	8.61	8.61	0.38	0.80	± 12.0 9
2100	53.2	1.62	8.72	8.72	8.72	0.24	1.09	± 12.0 9
2300	52.9	1.81	8.13	8.13	8.13	0.57	0.67	± 12.0 9
2450	52.7	1.95	7.88	7.88	7.88	0.80	0.50	± 12.0 9
2600	52.5	2.16	7.61	7.61	7.61	0.62	0.50	± 12.0 9
3500	51.3	3.31	7.14	7.14	7.14	0.33	1.24	± 13.1 9
5200	49.0	5.30	4.49	4.49	4.49	0.50	1.90	± 13.1 9
5300	48.9	5.42	4.27	4.27	4.27	0.50	1.90	± 13.1 9
5500	48.6	5.65	3.96	3.96	3,96	0.55	1.90	± 13.1 9
5600	48.5	5.77	3.63	3.63	3.63	0.60	1.90	± 13.1 9
5800	48.2	6.00	3.88	3.88	3.88	0.59	1.90	±13.19

<sup>&</sup>lt;sup>C</sup> Frequency validity of  $\pm$  100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to  $\pm$  50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

<sup>c</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to  $\pm$  10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to  $\pm$  5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target base parameters.



## Frequency Response of E-Field (TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)


Certificate No: EX3-3519\_Feb13

Page 7 of 11





## Receiving Pattern (\$\phi\$), \$\theta = 0^\circ\$





f=600 MHz,TEM






Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)


Certificate No: EX3-3519\_Feb13

Page 8 of 11



## Dynamic Range f(SAR<sub>head</sub>) (TEM cell , f = 900 MHz)






Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Certificate No: EX3-3519\_Feb13


Page 9 of 11



## Conversion Factor Assessment



## Deviation from Isotropy in Liquid Error (\$\phi\$, \$\text{8}\$), f = 900 MHz



Certificate No: EX3-3519\_Feb13

Page 10 of 11



EX3DV3-SN:3519

February 20, 2013

## DASY/EASY - Parameters of Probe: EX3DV3 - SN:3519

## Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-93.4
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	2 mm

Certificate No: EX3-3519\_Feb13

Page 11 of 11



## Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland





Schweizerischer Kallbrierdienst S Service suisse d'étalonnage C Servizio svizzero di taratura Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS) The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Object	DAE4 - SD 000 D	04 BJ - SN: 779	
Calibration procedure(s)	QA CAL-06.v25 Calibration proces	lure for the data acquisition electron	onics (DAE)
Calibration date:	February 13, 2013	Transfer for the state of the s	
		nal standards, which realize the physical units obability are given on the following pages and a	
		facility: environment temperature (22 $\pm$ 3)°C a	and humidity < 70%.
Calibration Equipment used (M&	TE critical for callbration)	Cal Date (Certificate No.)	and humidity < 70%.  Scheduled Calibration
Calibration Equipment used (M&	TE critical for calibration)		
Calibration Equipment used (M& Primary Standards Keithley Multimeter Type 2001 Secondary Standards	ID # SN: 0810278	Cal Date (Certificate No.) 02-Oct-12 (No:12728) Check Date (in house)	Scheduled Calibration
All calibrations have been conducted.  Calibration Equipment used (M& Primary Standards  Keithley Multimeter Type 2001  Secondary Standards  Auto DAE Calibration Unit  Calibrator Box V2.1	ID # SN: 0810278 ID # SE UWS 053 AA 1001	Cal Date (Certificate No.) 02-Oct-12 (No:12728)	Scheduled Calibration Oct-13
Calibration Equipment used (M& Primary Standards Keithley Multimeter Type 2001 Secondary Standards Auto DAE Calibration Unit	ID # SN: 0810278 ID # SE UWS 053 AA 1001	Cal Date (Certificate No.) 02-Oct-12 (No:12728) Check Date (in house) 07-Jan-13 (in house check)	Scheduled Calibration Oct-13 Scheduled Check In house check: Jan-14
Calibration Equipment used (M& Primary Standards Keithley Multimeter Type 2001 Secondary Standards Auto DAE Calibration Unit	ID # SN: 0810278 ID # SE UWS 053 AA 1001	Cal Date (Certificate No.) 02-Oct-12 (No:12728) Check Date (in house) 07-Jan-13 (in house check)	Scheduled Calibration Oct-13 Scheduled Check In house check: Jan-14 In house check: Jan-14
Calibration Equipment used (M& Primary Standards Keithley Multimeter Type 2001 Secondary Standards Auto DAE Calibration Unit	ID # SN: 0810278  ID # SE UWS 053 AA 1001 SE UMS 006 AA 1002	Cal Date (Certificate No.) 02-Oct-12 (No:12728) Check Date (in house) 07-Jan-13 (in house check) 07-Jan-13 (in house check)	Scheduled Calibration Oct-13 Scheduled Check In house check: Jan-14 In house check: Jan-14

Certificate No: DAE4-779\_Feb13

Page 1 of 5



#### Calibration Laboratory of Schmid & Partner Engineering AG Zeughausstrasse 43, 8004 Zurich, Switzerland

lac w



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

## Glossary

DAE data acquisition electronics

Connector angle information used in DASY system to align probe sensor X to the robot

coordinate system.

#### Methods Applied and Interpretation of Parameters

- DC Voltage Measurement: Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- Connector angle: The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
  - DC Voltage Measurement Linearity: Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
  - Common mode sensitivity: Influence of a positive or negative common mode voltage on the differential measurement.
  - Channel separation: Influence of a voltage on the neighbor channels not subject to an input voltage.
  - AD Converter Values with inputs shorted: Values on the internal AD converter corresponding to zero input voltage
  - Input Offset Measurement: Output voltage and statistical results over a large number of zero voltage measurements.
  - Input Offset Current: Typical value for information; Maximum channel input offset current, not considering the input resistance.
  - Input resistance: Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
  - Low Battery Alarm Voltage: Typical value for information. Below this voltage, a battery alarm signal is generated.
  - Power consumption: Typical value for information. Supply currents in various operating modes.

Certificate No: DAE4-779\_Feb13

Page 2 of 5



## DC Voltage Measurement

A/D - Converter Resolution nominal High Range: 1LSB = full range = -100...+300 mV full range = -1......+3mV 6.1µV, Low Range: 1LSB = 61nV, DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	404.452 ± 0.02% (k=2)	403.694 ± 0.02% (k=2)	403.914 ± 0.02% (k=2)
Low Range	3.96902 ± 1.55% (k=2)	3.97887 ± 1.55% (k=2)	3.99319 ± 1.55% (k=2)

## **Connector Angle**

ELECTRIC STREET, COLUMN TO STREET, THE
156.5°±1°

Certificate No: DAE4-779\_Feb13



## Appendix

1. DC Voltage Linearity

High Range	Reading (µV)	Difference (µV)	Error (%)
Channel X + Input	199996,96	1.92	0.00
Channel X + Input	20001.89	1.69	0.01
Channel X - Input	-19996.92	3.97	-0.02
Channel Y + Input	199996.16	1.24	0.00
Channel Y + Input	19999.20	-0.93	-0.00
Channel Y - Input	-20000,26	0.76	-0.00
Channel Z + Input	199997.40	2.46	0.00
Channel Z + Input	20001.63	1.50	0.01
Channel Z - Input	~19998.30	2.69	-0.01

Low Range	Reading (µV)	Difference (µV)	Error (%)
Channel X + Input	2001.21	0.58	0.03
Channel X + Input	201.35	0.31	0.15
Channel X - Input	-198.61	0.26	-0.13
Channel Y + Input	2000.66	0.18	0.01
Channel Y + Input	200,39	-0.58	-0.29
Channel Y - Input	-199.01	0.03	-0.01
Channel Z + Input	2000.62	0.22	0.01
Channel Z + Input	200.34	-0.52	-0.26
Channel Z - Input	-199.81	-0.83	0.42

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	-2.78	-4.73
	-200	5.70	4.22
Channel Y	200	14.58	13.79
	- 200	-15.41	-15.51
Channel Z	200	2.91	3.09
	- 200	-4.86	-4.74

## 3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (µV)	Channel Y (µV)	Channel Z (μV)
Channel X	200		-2.01	-3.72
Channel Y	200	10.67		-0.58
Channel Z	200	7.80	8.55	_

Certificate No: DAE4-779\_Feb13

Page 4 of 5



## 4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	15602	13837
Channel Y	15845	15843
Channel Z	16202	15651

## 5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10MΩ

	Average (μV)	min. Offset (μV)	max. Offset (μV)	Std. Deviation (µV)
Channel X	0.26	-0.87	2.39	0.52
Channel Y	-0.70	-2.45	1.01	0.66
Channel Z	-0.84	-1.90	0.45	0.44

## 6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)	
Supply (+ Vcc)	+7.9	
Supply (- Vcc)	-7.6	

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9

Certificate No: DAE4-779\_Feb13