



## Plots of Input Occupied Bandwidth for 1900 PCS LTE Band




## Plots of Input Occupied Bandwidth for 1900 PCS LTE Band

### LTE 20 MHz


#### Low Channel AGC threshold




#### Middle Channel AGC threshold



#### High Channel AGC threshold



## Plots of Input Occupied Bandwidth for 1900 PCS Band



## Plots of Input Occupied Bandwidth for 1900 PCS Band

### GSM

#### Low Channel AGC threshold



#### Middle Channel AGC threshold



#### High Channel AGC threshold




**[Downlink Output\_AWS 2100 Band]**

| AWS 2100 Band                               | Channel | Frequency (MHz) | OBW (MHz) |
|---------------------------------------------|---------|-----------------|-----------|
| LTE 5 MHz<br>AGC threshold                  | Low     | 2112.50         | 4.5117    |
|                                             | Middle  | 2145.00         | 4.5155    |
|                                             | High    | 2177.50         | 4.5161    |
| LTE 5 MHz<br>+3 dB above the AGC threshold  | Low     | 2112.50         | 4.5087    |
|                                             | Middle  | 2145.00         | 4.5151    |
|                                             | High    | 2177.50         | 4.5105    |
| LTE 10 MHz<br>AGC threshold                 | Low     | 2115.00         | 8.9953    |
|                                             | Middle  | 2145.00         | 9.0016    |
|                                             | High    | 2175.00         | 8.9944    |
| LTE 10 MHz<br>+3 dB above the AGC threshold | Low     | 2115.00         | 8.9915    |
|                                             | Middle  | 2145.00         | 9.0062    |
|                                             | High    | 2175.00         | 8.9951    |
| LTE 20 MHz<br>AGC threshold                 | Low     | 2120.00         | 17.990    |
|                                             | Middle  | 2145.00         | 18.039    |
|                                             | High    | 2170.00         | 18.017    |
| LTE 20 MHz<br>+3 dB above the AGC threshold | Low     | 2120.00         | 18.007    |
|                                             | Middle  | 2145.00         | 18.030    |
|                                             | High    | 2170.00         | 18.010    |
| WCDMA<br>AGC threshold                      | Low     | 2112.50         | 4.1601    |
|                                             | Middle  | 2145.00         | 4.1599    |
|                                             | High    | 2177.50         | 4.1873    |
| WCDMA<br>+3 dB above the AGC threshold      | Low     | 2112.50         | 4.1752    |
|                                             | Middle  | 2145.00         | 4.1717    |
|                                             | High    | 2177.50         | 4.1778    |
| CDMA<br>AGC threshold                       | Low     | 2111.25         | 1.2421    |
|                                             | Middle  | 2145.00         | 1.2423    |
|                                             | High    | 2178.75         | 1.2449    |
| CDMA<br>+3 dB above the AGC threshold       | Low     | 2111.25         | 1.2392    |
|                                             | Middle  | 2145.00         | 1.2464    |
|                                             | High    | 2178.75         | 1.2398    |


**[Downlink Input\_AWS 2100 Band]**

| AWS 2100 Band               | Channel | Frequency (MHz) | OBW (MHz) |
|-----------------------------|---------|-----------------|-----------|
| LTE 5 MHz<br>AGC threshold  | Low     | 2112.50         | 4.5093    |
|                             | Middle  | 2145.00         | 4.5086    |
|                             | High    | 2177.50         | 4.5108    |
| LTE 10 MHz<br>AGC threshold | Low     | 2115.00         | 9.0053    |
|                             | Middle  | 2145.00         | 8.9911    |
|                             | High    | 2175.00         | 9.0012    |
| LTE 20 MHz<br>AGC threshold | Low     | 2120.00         | 18.019    |
|                             | Middle  | 2145.00         | 18.025    |
|                             | High    | 2170.00         | 18.016    |
| WCDMA<br>AGC threshold      | Low     | 2112.50         | 4.1697    |
|                             | Middle  | 2145.00         | 4.1663    |
|                             | High    | 2177.50         | 4.1673    |
| CDMA<br>AGC threshold       | Low     | 2111.25         | 1.2440    |
|                             | Middle  | 2145.00         | 1.2435    |
|                             | High    | 2178.75         | 1.2398    |


## Plots of Output Occupied Bandwidth for AWS 2100 Band LTE 5 MHz




## Plots of Output Occupied Bandwidth for AWS 2100 Band LTE 10 MHz




## Plots of Output Occupied Bandwidth for AWS 2100 Band LTE 20 MHz




## Plots of Output Occupied Bandwidth for AWS 2100 Band WCDMA




## Plots of Output Occupied Bandwidth for AWS 2100 Band CDMA




## Plots of Input Occupied Bandwidth for AWS 2100 LTE Band



## Plots of Input Occupied Bandwidth for AWS 2100 LTE Band



## Plots of Input Occupied Bandwidth for AWS 2100 Band



## 7. INPUT VERSUS OUTPUT SPECTRUM

### ISED Rules

#### Test Requirements:

##### RSS-131

**5. Equipment standard specifications for zone enhancers working with equipment certified in RSSs listed in section 1 except RSS-119**

##### 5.2 Industrial Zone Enhancers

##### 5.2.2 Input-versus-output spectrum

The spectral growth of the 26 dB bandwidth of the output signal shall be less than 5% of the input signal spectrum.

#### Test Procedures:

##### RSS-Gen

#### 6 General administrative and technical requirements

##### 6.7 Occupied bandwidth (or 99% emission bandwidth) and x dB bandwidth

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

**Note:** It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

#### Note :

1. We tested using the automatic bandwidth measurement capability of a spectrum analyzer. X dB is set 26 dB.
2. Plots of results are the same as Section 6.

**Test Results:**
**[Downlink Output\_700 LTE]**

| 700 LTE Band                                | Channel | Frequency (MHz) | 26 dB BW (MHz) | Growth (%) |
|---------------------------------------------|---------|-----------------|----------------|------------|
| LTE 5 MHz<br>AGC threshold                  | Low     | 731.50          | 5.039          | -0.14      |
|                                             | Middle  | 742.00          | 5.032          | -0.16      |
|                                             | High    | 753.50          | 5.045          | 0.24       |
| LTE 5 MHz<br>+3dBm above the AGC threshold  | Low     | 731.50          | 5.044          | -0.04      |
|                                             | Middle  | 742.00          | 5.040          | 0.00       |
|                                             | High    | 753.50          | 5.045          | 0.24       |
| LTE 10 MHz<br>AGC threshold                 | Low     | 734.00          | 10.000         | 0.00       |
|                                             | Middle  | 741.00          | 9.982          | -0.18      |
|                                             | High    | 751.00          | 9.991          | -0.29      |
| LTE 10 MHz<br>+3dBm above the AGC threshold | Low     | 734.00          | 9.988          | -0.12      |
|                                             | Middle  | 741.00          | 10.020         | 0.20       |
|                                             | High    | 751.00          | 10.000         | -0.20      |

**[Downlink Output\_FirstNet]**

| FirstNet Band                               | Channel | Frequency (MHz) | 26 dB BW (MHz) | Growth (%) |
|---------------------------------------------|---------|-----------------|----------------|------------|
| LTE 5 MHz<br>AGC threshold                  | Low     | 760.50          | 5.035          | -0.08      |
|                                             | High    | 765.50          | 5.031          | -0.04      |
| LTE 5 MHz<br>+3dBm above the AGC threshold  | Low     | 760.50          | 5.058          | 0.38       |
|                                             | High    | 765.50          | 5.032          | -0.02      |
| LTE 10 MHz<br>AGC threshold                 | Middle  | 763.00          | 9.995          | -0.15      |
| LTE 10 MHz<br>+3dBm above the AGC threshold | Middle  | 763.00          | 9.952          | -0.58      |

**[Downlink Output\_800 IDEN]**

| 800 IDEN Band                              | Channel | Frequency (MHz) | 26 dB BW (MHz) | Growth (%) |
|--------------------------------------------|---------|-----------------|----------------|------------|
| LTE 5 MHz<br>AGC threshold                 | Low     | 864.50          | 5.038          | -0.02      |
|                                            | High    | 866.50          | 5.026          | -0.24      |
| LTE 5 MHz<br>+3dBm above the AGC threshold | Low     | 864.50          | 5.041          | 0.04       |
|                                            | High    | 866.50          | 5.015          | -0.46      |
| CDMA<br>AGC threshold                      | Low     | 863.25          | 1.373          | 0.07       |
|                                            | Middle  | 865.50          | 1.367          | -0.15      |
|                                            | High    | 867.75          | 1.373          | 0.07       |
| CDMA<br>+3dBm above the AGC threshold      | Low     | 863.25          | 1.368          | -0.29      |
|                                            | Middle  | 865.50          | 1.367          | -0.15      |
|                                            | High    | 867.75          | 1.369          | -0.22      |

**[Downlink Output\_850 CEL]**

| 850 CEL Band                                | Channel | Frequency (MHz) | 26 dB BW (MHz) | Growth (%) |
|---------------------------------------------|---------|-----------------|----------------|------------|
| LTE 5 MHz<br>AGC threshold                  | Low     | 871.50          | 5.033          | 0.26       |
|                                             | Middle  | 881.50          | 5.046          | 0.16       |
|                                             | High    | 891.50          | 5.027          | -0.36      |
| LTE 5 MHz<br>+3dBm above the AGC threshold  | Low     | 871.50          | 5.049          | 0.58       |
|                                             | Middle  | 881.50          | 5.043          | 0.10       |
|                                             | High    | 891.50          | 5.010          | -0.69      |
| LTE 10 MHz<br>AGC threshold                 | Low     | 874.00          | 10.010         | -0.10      |
|                                             | Middle  | 881.50          | 9.996          | -0.24      |
|                                             | High    | 889.00          | 9.971          | -0.59      |
| LTE 10 MHz<br>+3dBm above the AGC threshold | Low     | 874.00          | 10.010         | -0.10      |
|                                             | Middle  | 881.50          | 10.010         | -0.10      |
|                                             | High    | 889.00          | 9.967          | -0.63      |
| WCDMA<br>AGC threshold                      | Low     | 871.50          | 4.692          | -0.13      |
|                                             | Middle  | 881.50          | 4.684          | 0.06       |
|                                             | High    | 891.50          | 4.684          | -0.04      |
| WCDMA<br>+3dBm above the AGC threshold      | Low     | 871.50          | 4.675          | -0.49      |
|                                             | Middle  | 881.50          | 4.697          | 0.34       |
|                                             | High    | 891.50          | 4.686          | 0.00       |
| CDMA<br>AGC threshold                       | Low     | 870.25          | 1.368          | -0.15      |
|                                             | Middle  | 881.50          | 1.376          | 0.29       |
|                                             | High    | 892.75          | 1.365          | -0.36      |
| CDMA<br>+3dBm above the AGC threshold       | Low     | 870.25          | 1.372          | 0.15       |
|                                             | Middle  | 881.50          | 1.370          | -0.15      |
|                                             | High    | 892.75          | 1.363          | -0.51      |

[Downlink Output\_1900 PCS Band]

| 1900 PCS Band                               | Channel | Frequency (MHz) | 26 dB BW (MHz) | Growth (%) |
|---------------------------------------------|---------|-----------------|----------------|------------|
| LTE 5 MHz<br>AGC threshold                  | Low     | 1932.50         | 5.026          | -0.44      |
|                                             | Middle  | 1962.50         | 5.045          | 0.00       |
|                                             | High    | 1992.50         | 5.048          | 0.10       |
| LTE 5 MHz<br>+3dBm above the AGC threshold  | Low     | 1932.50         | 5.014          | -0.67      |
|                                             | Middle  | 1962.50         | 5.037          | -0.16      |
|                                             | High    | 1992.50         | 5.033          | -0.20      |
| LTE 10 MHz<br>AGC threshold                 | Low     | 1935.00         | 9.977          | -0.33      |
|                                             | Middle  | 1962.50         | 10.010         | -0.10      |
|                                             | High    | 1990.00         | 9.982          | -0.48      |
| LTE 10 MHz<br>+3dBm above the AGC threshold | Low     | 1935.00         | 9.978          | -0.32      |
|                                             | Middle  | 1962.50         | 10.010         | -0.10      |
|                                             | High    | 1990.00         | 9.976          | -0.54      |
| LTE 20 MHz<br>AGC threshold                 | Low     | 1940.00         | 20.010         | -0.15      |
|                                             | Middle  | 1962.50         | 20.030         | -0.15      |
|                                             | High    | 1985.00         | 20.080         | 0.15       |
| LTE 20 MHz<br>+3dBm above the AGC threshold | Low     | 1940.00         | 20.080         | 0.20       |
|                                             | Middle  | 1962.50         | 20.080         | 0.10       |
|                                             | High    | 1985.00         | 19.990         | -0.30      |
| WCDMA<br>AGC threshold                      | Low     | 1932.50         | 4.676          | -0.40      |
|                                             | Middle  | 1962.50         | 4.677          | -0.23      |
|                                             | High    | 1992.50         | 4.680          | -0.13      |
| WCDMA<br>+3dBm above the AGC threshold      | Low     | 1932.50         | 4.666          | -0.62      |
|                                             | Middle  | 1962.50         | 4.680          | -0.17      |
|                                             | High    | 1992.50         | 4.694          | 0.17       |

| 1900 PCS Band                         | Channel | Frequency (MHz) | 26 dB BW (MHz) | Growth (%) |
|---------------------------------------|---------|-----------------|----------------|------------|
| CDMA<br>AGC threshold                 | Low     | 1931.25         | 1.407          | 0.36       |
|                                       | Middle  | 1962.50         | 1.409          | 0.50       |
|                                       | High    | 1993.75         | 1.406          | 0.21       |
| CDMA<br>+3dBm above the AGC threshold | Low     | 1931.25         | 1.402          | 0.00       |
|                                       | Middle  | 1962.50         | 1.412          | 0.71       |
|                                       | High    | 1993.75         | 1.408          | 0.36       |
| 1900 PCS Band                         | Channel | Frequency (MHz) | 26 dB BW (kHz) | Growth (%) |
| GSM<br>AGC threshold                  | Low     | 1930.20         | 311.9          | -0.29      |
|                                       | Middle  | 1962.50         | 313.8          | 1.29       |
|                                       | High    | 1994.80         | 305.1          | -1.80      |
| GSM<br>+3dBm above the AGC threshold  | Low     | 1930.20         | 319.8          | 2.24       |
|                                       | Middle  | 1962.50         | 304.2          | -1.81      |
|                                       | High    | 1994.80         | 308.6          | -0.68      |

[Downlink Output\_AWS 2100 Band]

| AWS 2100 Band                               | Channel | Frequency (MHz) | 26 dB BW (MHz) | Growth (%) |
|---------------------------------------------|---------|-----------------|----------------|------------|
| LTE 5 MHz<br>AGC threshold                  | Low     | 2112.50         | 5.038          | 0.34       |
|                                             | Middle  | 2145.00         | 5.039          | 0.22       |
|                                             | High    | 2177.50         | 5.042          | 0.62       |
| LTE 5 MHz<br>+3dBm above the AGC threshold  | Low     | 2112.50         | 5.034          | 0.26       |
|                                             | Middle  | 2145.00         | 5.045          | 0.34       |
|                                             | High    | 2177.50         | 5.034          | 0.46       |
| LTE 10 MHz<br>AGC threshold                 | Low     | 2115.00         | 10.020         | 0.00       |
|                                             | Middle  | 2145.00         | 10.010         | -0.10      |
|                                             | High    | 2175.00         | 10.010         | 0.00       |
| LTE 10 MHz<br>+3dBm above the AGC threshold | Low     | 2115.00         | 9.966          | -0.54      |
|                                             | Middle  | 2145.00         | 10.030         | 0.10       |
|                                             | High    | 2175.00         | 10.000         | -0.10      |
| LTE 20 MHz<br>AGC threshold                 | Low     | 2120.00         | 20.060         | 0.35       |
|                                             | Middle  | 2145.00         | 20.060         | -0.10      |
|                                             | High    | 2170.00         | 20.050         | -0.15      |
| LTE 20 MHz<br>+3dBm above the AGC threshold | Low     | 2120.00         | 19.980         | -0.05      |
|                                             | Middle  | 2145.00         | 20.100         | 0.10       |
|                                             | High    | 2170.00         | 20.060         | -0.10      |
| WCDMA<br>AGC threshold                      | Low     | 2112.50         | 4.692          | -0.04      |
|                                             | Middle  | 2145.00         | 4.689          | 0.28       |
|                                             | High    | 2177.50         | 4.692          | -0.04      |
| WCDMA<br>+3dBm above the AGC threshold      | Low     | 2112.50         | 4.685          | -0.19      |
|                                             | Middle  | 2145.00         | 4.683          | 0.15       |
|                                             | High    | 2177.50         | 4.691          | -0.06      |
| CDMA<br>AGC threshold                       | Low     | 2111.25         | 1.369          | 0.00       |
|                                             | Middle  | 2145.00         | 1.367          | 0.15       |
|                                             | High    | 2178.75         | 1.370          | -0.07      |
| CDMA<br>+3dBm above the AGC threshold       | Low     | 2111.25         | 1.370          | 0.07       |
|                                             | Middle  | 2145.00         | 1.373          | 0.59       |
|                                             | High    | 2178.75         | 1.382          | 0.80       |

## 8. OUT OF BAND REJECTION & MEAN OUTPUT POWER AND ZONE ENHANCER GAIN

### FCC Rules

#### Test Requirements:

##### KDB 935210 D05 v01r02

Out of Band Rejection – Test for rejection of out of band signals. Filter freq. response plots are acceptable.

### ISED Rules

#### Test Requirements:

##### RSS-131

**5. Equipment standard specifications for zone enhancers working with equipment certified in RSSs listed in section 1 except RSS-119**

#### 5.2 Industrial Zone Enhancers

##### 5.2.1 Out-of-band rejection

The gain-versus-frequency response and the 20 dB bandwidth of the zone enhancer shall be reported. The zone enhancer shall reject amplification of other signals outside the passband of the zone enhancer.

##### 5.2.3 Mean output power and zone enhancer gain

The zone enhancer gain shall not exceed the nominal gain by more than 1.0 dB. Outside of the 20 dB bandwidth, the gain shall not exceed the gain at the 20 dB point.

### Test Procedures:

Measurements were in accordance with the test methods section 3.3, 4.3 of KDB 935210 D05 v01r02.

#### 3.3 EUT out-of-band rejection

- a) Connect a signal generator to the input of the EUT.
- b) Configure a swept CW signal with the following parameters:
  - 1) Frequency range =  $\pm 250$  % of the passband from the center of the passband.
  - 2) Level = a sufficient level to affirm that the out-of-band rejection is  $> 20$  dB above the noise floor and will not engage the AGC during the entire sweep.
  - 3) Dwell time = approx. 10 ms.
  - 4) Number of points =  $\text{SPAN}/(\text{RBW}/2)$ .
- c) Connect a spectrum analyzer to the output of the EUT using appropriate attenuation.
- d) Set the span of the spectrum analyzer to the same as the frequency range of the signal generator.
- e) Set the resolution bandwidth of the spectrum analyzer to be 1 % to 5 % of the passband and

the video bandwidth shall be set to  $\geq 3 \times \text{RBW}$ .

f) Set the detector to Peak Max-Hold and wait for the spectrum analyzer's spectral display to fill.

g) Place a marker to the peak of the frequency response and record this frequency as  $f_0$ .

h) Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the  $-20$  dB down amplitude to determine the 20 dB bandwidth. Capture the frequency response of the EUT.

#### 4.3 PLMRS device out-of-band rejection

Adjust the internal gain control of the equipment under test to the maximum gain for which equipment certification is sought.

a) Connect a signal generator to the input of the EUT.

b) Configure a swept CW signal with the following parameters:

c) Frequency range =  $\pm 250$  % of the manufacturer's pass band.

d) The CW amplitude will be 3 dB below the AGC threshold (see 4.2) and but not activate the AGC threshold throughout the test.

e) Dwell time = approx. 10 ms.

f) Frequency step = 50 kHz.

g) Connect a spectrum analyzer to the output of the EUT using appropriate attenuation.

h) Set the resolution bandwidth of the spectrum analyzer between 1 % and 5 % of the manufacturer's pass band with the video bandwidth set to  $3 \times \text{RBW}$ .

i) Set the detector to Peak and the trace to Max-Hold.

j) After the trace is completely filled, place a marker at the peak amplitude, which is designated as  $f_0$ , and with two additional markers (use the marker-delta method) at the 20 dB bandwidth (i.e., at the points where the gain has fallen by 20 dB).

k) Capture the frequency response plot and for inclusion in the test report.


#### Test Results:

| Input Signal                                                            | Input Level<br>Input Signal : Sinusoidal | Maximum Amp Gain |
|-------------------------------------------------------------------------|------------------------------------------|------------------|
| 700LTE, FirstNet<br>800IDEN, 850CEL<br>800 MHz PLMR<br>1900PCS<br>AWS13 | -20 dBm                                  | 53 dB            |

[Downlink]

| Band                | 20 dB point frequency<br>(MHz)  | Output power<br>(dBm) | Gain<br>(dB) |
|---------------------|---------------------------------|-----------------------|--------------|
| 700 LTE<br>FirstNet | 726.700 MHz<br>~<br>770.200 MHz | 33.159                | 53.159       |

Plot of Out of Band Rejection & Mean Output Power and Zone Enhancer Gain




\* MRDU\_700LTE\_FN module amplifies 700 LTE band (729 ~ 758 MHz) and FirstNet band (758 ~ 768 MHz) together.

### [Downlink]

| Band                                | 20 dB point frequency<br>(MHz)  | Output power<br>(dBm) | Gain<br>(dB) |
|-------------------------------------|---------------------------------|-----------------------|--------------|
| 800 IDEN<br>850 CEL<br>800 MHz PLMR | 860.000 MHz<br>~<br>895.950 MHz | 32.974                | 52.974       |

### Plot of Out of Band Rejection & Mean Output Power and Zone Enhancer Gain




\* MRDU\_800I\_850C module amplifies 800 IDEN band (PLMR Band, 862 ~ 869 MHz) and 850 CEL band (869 ~ 894 MHz) together.

**[Downlink]**

| Band     | 20 dB point frequency<br>(MHz)      | Output power<br>(dBm) | Gain<br>(dB) |
|----------|-------------------------------------|-----------------------|--------------|
| 1900 PCS | 1 926.290 MHz<br>~<br>1 998.370 MHz | 33.033                | 53.033       |

**Plot of Out of Band Rejection & Mean Output Power and Zone Enhancer Gain**



[Downlink]

| Band     | 20 dB point frequency<br>(MHz)      | Output power<br>(dBm) | Gain<br>(dB) |
|----------|-------------------------------------|-----------------------|--------------|
| AWS 2100 | 2 102.300 MHz<br>~<br>2 191.025 MHz | 32.929                | 52.929       |

Plot of Out of Band Rejection & Mean Output Power and Zone Enhancer Gain



## 9. NOISE FIGURE

### FCC Rules

#### Test Requirements:

##### § 90.219 Use of signal boosters:

(e) (2) The noise figure of a signal booster must not exceed 9 dB in either direction.

### ISED Rules

#### Test Requirements:

##### RSS-131

#### 6. Equipment standard specifications for zone enhancers working with equipment certified under RSS-119

##### 6.4 Noise

The ERP of noise within the passband should not exceed -43 dBm in a 10 kHz measurement bandwidth.

The ERP of noise in spectrum more than 1 MHz outside of the passband should not exceed -70 dBm in a 10 kHz measurement bandwidth.

The noise figure of a zone enhancer shall not exceed 9 dB in either direction.

#### Test Procedures:

The EUT was tested using Agilent Application Note 57-1, 'The direct noise measurement method'

##### 1. GAIN measurement

EUT in the maximum gain of the repeater state.

The signal generator was connected to RF input port at a maximum level as determined by the spectrum analyzer was connected to RF output port depending on the circuitry being measured.

$EUT\ GAIN = Output\ signal\ level - Input\ signal\ level$

##### 2. Output Noise level measurement

EUT in the maximum gain of the repeater state.

Without input signal.

Spectrum analyzer was connected to RF output port

Measured to Noise power.

$NF = NP - G - BCF - PNAD$

$NF = NP - G - 60 + 174$

$NF = NP - G + 114$

NF=Noise Figure (dB)

NP=Noise power (dBm/MHz)

G=Maximum gain

BCF=Bandwidth Correction Factor= $10 \log(1 \text{ MHz}/1 \text{ Hz})=60$

PNAD=Noise Power Density=-174 dBm/Hz


### Test Results:

| Input Signal                    | Input Level | Maximum Amp Gain |
|---------------------------------|-------------|------------------|
| 800IDEN, 850CEL<br>800 MHz PLMR | -20 dBm     | 53 dB            |

\* For reason of filter setting, noise figure is measured at all frequencies of par 22 and part 90 band.

$$\text{Noise Figure} = -52.108 - 53 + 114 = 8.892 \text{ dB}$$

### Plot of Noise power



## 10. SPURIOUS AND HARMONIC EMISSION AT ANTENNA TERMINAL

### FCC Rules

#### Test Requirements:

##### **§ 2.1051 Measurements required: Spurious emissions at antenna terminals:**

The radio frequency voltage or powers generated within the equipment and appearing on a spurious frequency shall be checked at the equipment output terminals when properly loaded with a suitable artificial antenna. Curves or equivalent data shall show the magnitude of each harmonic and other spurious emission that can be detected when the equipment is operated under the conditions specified in § 2.1049 as appropriate. The magnitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be specified.

##### **§ 22.917 Emission limitations for cellular equipment.**

The rules in this section govern the spectral characteristics of emissions in the Cellular Radiotelephone Service.

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a reference bandwidth as follows:

(1) In the spectrum below 1 GHz, instrumentation should employ a reference bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided that the measured power is integrated over the full required reference bandwidth (i.e., 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(2) In the spectrum above 1 GHz, instrumentation should employ a reference bandwidth of 1 MHz.

(c) Alternative out of band emission limit. Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) Interference caused by out of band emissions. If any emission from a transmitter operating in

this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

#### **§ 24.238 Emission limitations for Broadband PCS equipment.**

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(a) *Out of band emissions.* The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

(b) *Measurement procedure.* Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (*i.e.* 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) *Alternative out of band emission limit.* Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) *Interference caused by out of band emissions.* If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

#### **§ 27.53 Emission limits.**

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least  $43 + 10 \log (P)$  dB;

- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;
- (6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.
- (f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to  $-70$  dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and  $-80$  dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.
- (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least  $43 + 10 \log (P)$  dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.
- (h) *AWS emission limits*
- (1) *General protection levels.* Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10} (P)$  dB.
- (2) *Additional protection levels.* Notwithstanding the foregoing paragraph (h)(1) of this section:
- (i) Operations in the 2180-2200 MHz band are subject to the out-of-band emission requirements set forth in §27.1134 for the protection of federal government operations operating in the 2200-2290 MHz band.
- (ii) For operations in the 2000-2020 MHz band, the power of any emissions below 2000 MHz shall be attenuated below the transmitter power (P) in watts by at least  $70 + 10 \log_{10}(P)$  dB.
- (iii) For operations in the 1915-1920 MHz band, the power of any emission between 1930-1995 MHz shall be attenuated below the transmitter power (P) in watts by at least  $70 + 10$