

On your side



TEST REPORT

FCC MPE Test for N20-HRDU_600
Certification

APPLICANT
SOLiD, Inc.

REPORT NO.
HCT-RF-1907-FC026

DATE OF ISSUE
July 31, 2019


HCT Co., Ltd.

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 F ax. +82 31 645 6401



HCT Co., Ltd.

74, Seocheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383 KOREA
Tel. +82 31 634 6300 Fax. +82 31 645 6401



REPORT NO.
HCT-RF-1907-FC026

DATE OF ISSUE
July 31, 2019

Other ID
-

Applicant	SOLiD, Inc. 10, 9th Floor, SOLiD Space, Pangyoek-ro 220, Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, South Korea
Eut Type	ALLIANCE_N20
Model Name	N20-HRDU_600
FCC ID	W6UNH600

Tested by
Kwang Il Yoon

(signature)

Technical Manager
Jong Seok Lee

(signature)

HCT CO., LTD.

SooChan Lee

/ CEO

REVISION HISTORY

The revision history for this test report is shown in table.

Revision No.	Date of Issue	Description
0	July 31, 2019	Initial Release

The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules under normal use and maintenance.

RF Exposure Statement

1. LIMITS

According to § 1.1310 and § 2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

- 600 MHz Service

Max Peak output Power at antenna input terminal	44.00	dBm
Max Peak output Power at antenna input terminal	25118.86	mW
Prediction distance	690.00	cm
Prediction frequency	617.00	MHz
Antenna Gain(typical)	17.000	dBi
Antenna Gain(numeric)	50.119	-
Power density at prediction frequency(S)	0.210	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	0.411	mW/cm ²