



243 Jubug-Ri, Yangji-Myeon, Yongin-Si, Gyeonggi-Do, Korea 17159
 Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

Dates of Tests: April 01, 2019 ~ April 24, 2019
 Test Report S/N: LR500111904S
 Test Site : LTA CO., LTD.

CERTIFICATION OF COMPLIANCE

FCC ID.

W6YPT400TWR

APPLICANT

PASSTECH CO., LTD.

Equipment Class	:	Digital Transmission System (DTS)
Manufacturing Description	:	LOCKER LOCK
Manufacturer	:	PASSTECH CO., LTD.
Model name	:	PT400TWR
Varient Model name	:	PT200TWR, PT600TWR
Test Device Serial No.:	:	Identical prototype
Rule Part(s)	:	FCC Part 15.247 Subpart C ; ANSI C63.10 - 2013
Frequency Range	:	2402 ~ 2480 MHz - BLE 2405 ~ 2480 MHz - Zigbee
Max. Output Power	:	Max 3.77 dBm (BLE) – Conducted Max 1.96 dBm (Zigbee) - Conducted
Data of issue	:	April 24, 2019

This test report is issued under the authority of:

The test was supervised by:

Ja-Beom, Koo / Director

Hee-Cheon, Kwon, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

NVLAP LAB Code.: 200723-0

TABLE OF CONTENTS

1. GENERAL INFORMATION	-----	3
2. INFORMATION ABOUT TEST ITEM	-----	4
3. TEST REPORT	-----	5
3.1 SUMMARY OF TESTS	-----	5
3.2 TECHNICAL CHARACTERISTICS TEST	-----	6
3.2.1 6 dB BANDWIDTH	-----	6
3.2.2 PEAK OUTPUT POWER	-----	11
3.2.3 POWER SPECTRAL DENSITY	-----	16
3.2.4 BAND EDGE	-----	20
3.2.5 CONDUCTED SPURIOUS EMISSIONS	-----	24
3.2.6 RADIATED SPURIOUS EMISSIONS	-----	28
APPENDIX		
APPENDIX TEST EQUIPMENT USED FOR TESTS	-----	46

1. General information

1-1 Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Youngin-Si, Kyunggi-Do, Korea. 17159
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which is the “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2019-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	Updating	FCC CAB
VCCI	JAPAN	C-4948, T-2416, R-4483(10 m), G-847	2020-09-10 2020-09-10 2020-10-15 2022-06-13	VCCI registration
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

2. Information about test item

2-1 Client & Manufacturer

Company name : PASSTECH CO., LTD.
 Address : #1305 Kranz Techno, 5442-1, Sangdaewon-dong, Jungwon-gu,
 Seongnam-si, Gyeonggi-do, South Korea
 Tel / Fax : +82-31-743-7277 / +82-31-743-7276

2-2 Equipment Under Test (EUT)

Model name : PT400TWR
 Variant Model name : PT200TWR, PT600TWR
 Serial number : Identical prototype
 Date of receipt : April 01, 2019
 EUT condition : Pre-production, not damaged
 Antenna type : Chip Antenna (Max Gain : 3.5 dBi)
 Frequency Range : 2402 ~ 2480 MHz (BLE)
 2405 ~ 2480 MHz (Zigbee)
 RF output power : Max 3.77 dBm – Conducted (BLE)
 Max 1.96 dBm – Conducted (Zigbee)
 Number of channels : 40 (BLE), 16 (Zigbee)
 Type of Modulation : GFSK, OQPSK
 Power Source : 6.0 Vdc

2-3 Tested frequency

	LOW	MID	HIGH
Frequency (MHz) - BLE	2402	2440	2480
Frequency (MHz) – Zigbee	2405	2440	2480

2-4 Ancillary Equipment

Equipment	Model No.	Serial No.	Manufacturer
Notebook	CR720	MS-1736	MSI

3. Test Report

3.1 Summary of tests

FCC Part Section(s)	Parameter	Limit	Test Condition	Status (note 1)
15.247(a)	6 dB Bandwidth	> 500 kHz	Conducted	C
15.247(b)	Transmitter Peak Output Power	< 1 Watt		C
15.247(d)	Transmitter Power Spectral Density	< 8 dBm @ 3 kHz		C
15.247(d)	Band Edge	> 20 dBc		C
15.209	Field Strength of Harmonics	Emission	Radiated	C
15.207	AC Conducted Emissions	Emissions	Conducted	N/A
15.203	Antenna requirement	-	-	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

The above equipment was tested by LTA Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247. The test results of this report relate only to the tested sample identified in this report.

→ Antenna Requirement

PASSTECH CO., LTD. FCC ID: W6YPT400TWR unit complies with the requirement of §15.203. The antenna type is Chip Antenna.

3.2 Technical Characteristics Test

3.2.1 6 dB Bandwidth

Procedure:

The bandwidth at 6 dB below the highest in-band spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 6 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 100 kHz Span = 5 MHz

VBW = 300 kHz (VBW \geq RBW) Sweep = auto

Measurement Data : Complies

BLE Mode

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2402	1.418	Complies
2440	1.425	Complies
2480	1.563	Complies

Zigbee Mode

Frequency (MHz)	Test Results	
	Measured Bandwidth (MHz)	Result
2405	1.584	Complies
2440	1.628	Complies
2480	1.613	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:

6 dB Bandwidth > 500 kHz



Measurement Setup


Figure 1: Measurement setup for the carrier frequency separation

Low Channel - BLE




Date: 24.APR.2019 04:21:52

Middle Channel - BLE




Date: 24.APR.2019 04:30:41

High Channel - BLE




Date: 24.APR.2019 04:35:45

Low Channel - Zigbee




Date: 24.APR.2019 04:00:14

Middle Channel - Zigbee



Date: 24.APR.2019 04:11:30

High Channel - Zigbee



Date: 24.APR.2019 04:14:08

3.2.2 Peak Output Power Measurement

Procedure:

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The spectrum analyzer's internal channel power integration function is used to integrate the power over a bandwidth greater than or equal to the 99 % bandwidth. The EUT was operating in transmit mode at the appropriate center frequency.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

RBW = 1 MHz

Span = auto

VBW = 3 MHz (VBW \geq RBW)

Sweep = auto

Detector function = peak

Measurement Data : Complies

BLE Mode

Frequency (MHz)	Test Results		
	Measured Data (dBm)	mW	Result
2402	-2.19	0.60	Complies
2440	3.77	2.38	Complies
2480	0.35	1.08	Complies

Zigbee Mode

Frequency (MHz)	Test Results		
	Measured Data (dBm)	mW	Result
2402	-0.35	0.92	Complies
2440	1.96	1.57	Complies
2480	-1.67	0.68	Complies

- See next pages for actual measured spectrum plots.


Minimum Standard:

Peak output power	< 1 W
-------------------	-------

Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

Low Channel - BLE




Date: 24.APR.2019 04:24:16

Middle Channel - BLE




Date: 24.APR.2019 04:32:36

High Channel - BLE




Date: 24.APR.2019 04:36:16

Low Channel - Zigbee




Date: 24.APR.2019 04:03:41

Middle Channel - Zigbee



Date: 24.APR.2019 04:12:09

High Channel - Zigbee



Date: 24.APR.2019 04:14:48

3.2.3 Power Spectral Density

Procedure:

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

The spectrum analyzer is set to:

RBW = 3 kHz (3 kHz \leq RBW \leq 100 kHz) Span = 1.5 times the DTS bandwidth

VBW = 10 kHz (3 X RBW) Sweep = auto

Detector function = peak Trace = max hold

Measurement Data : Complies

BLE Mode

Frequency (MHz)	Test Results	
	dBm/ 3 kHz BW	Result
2402	-19.96	Complies
2440	-15.83	Complies
2480	-18.32	Complies

Zigbee Mode

Frequency (MHz)	Test Results	
	dBm/ 3 kHz BW	Result
2405	-17.81	Complies
2440	-17.03	Complies
2480	-18.57	Complies

- See next pages for actual measured spectrum plots.

Minimum Standard:


Power Spectral Density	< 8 dBm @ 3 kHz BW
------------------------	--------------------

Measurement Setup

Same as the Chapter 3.2.1 (Figure 1)


Power Density Measurement

Low Channel - BLE




Date: 24.APR.2019 04:07:01

Middle Channel - BLE




Date: 24.APR.2019 04:12:34

High Channel - BLE




Date: 24.APR.2019 04:15:08

Low Channel - Zigbee




Date: 24.APR.2019 04:07:01

Middle Channel - Zigbee



Date: 24.APR.2019 04:12:34

High Channel - Zigbee



Date: 24.APR.2019 04:15:08

3.2.4 Band Edge

Procedure:

The bandwidth at 20 dB down from the highest inband spectral density is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate frequencies.

After the trace being stable, Use the marker-to-peak function to measure 20 dB down both sides of the intentional emission.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

Span = 40 MHz, 100 MHz Detector function = peak

Radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a)

The spectrum analyzer is set to:

Center frequency = the highest, the lowest channels

PEAK: RBW = VBW = 1 MHz, Sweep=Auto

Average: RBW = 1 MHz, VBW = 10 Hz, Sweep=Auto


Measurement Distance: 3 m

Polarization: Horizontal / Vertical


Measurement Data: Complies

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


Minimum Standard:	> 20 dBc
--------------------------	----------

Lower edge - BLE


Date: 24.APR.2019 04:27:49

Upper edge- BLE

Date: 24.APR.2019 04:37:23

Lower edge - Zigbee

Date: 24.APR.2019 04:08:57

Upper edge- Zigbee

Date: 24.APR.2019 04:18:29

BLE Mode**Radiated Band-edges in the restricted band 2310-2390 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak			AV	Peak	AV	Peak	AV	Peak
2395.48	44.19	48.42	H	-9.37	54.0	74.0	34.82	39.05	19.18	34.95
2399.37	44.02	48.11	H	-9.37	54.0	74.0	34.65	38.74	19.35	35.26
2399.16	44.31	48.30	H	-9.37	54.0	74.0	34.94	38.93	19.06	35.07

Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak			AV	Peak	AV	Peak	AV	Peak
2483.94	47.29	51.17	H	-9.24	54.0	74.0	38.05	41.93	15.95	32.07
2483.44	47.02	50.96	H	-9.24	54.0	74.0	37.78	41.72	16.22	32.28
2490.91	48.03	51.13	H	-9.24	54.0	74.0	38.79	41.89	15.21	32.11

Zigbee Mode**Radiated Band-edges in the restricted band 2310-2390 MHz measurement**

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak			AV	Peak	AV	Peak	AV	Peak
2396.23	42.93	46.23	H	-9.37	54.0	74.0	33.56	36.86	20.44	37.14
2399.48	43.62	47.03	H	-9.37	54.0	74.0	34.25	37.66	19.75	36.34
2399.95	42.15	46.48	H	-9.37	54.0	74.0	32.78	37.11	21.22	36.89

Radiated Band-edges in the restricted band 2483.5-2500 MHz measurement

Frequency [MHz]	Reading [dBuV/m]		Pol.	Correction Factor	Limits [dBuV/m]		Result [dBuV/m]		Margin [dB]	
	AV	Peak			AV	Peak	AV	Peak	AV	Peak
2483.89	48.19	52.28	H	-9.24	54.0	74.0	38.95	43.04	15.05	30.96
2483.12	48.95	52.32	H	-9.24	54.0	74.0	39.71	43.08	14.29	30.92
2490.25	48.41	52.46	H	-9.24	54.0	74.0	39.17	43.22	14.83	30.78

Note : This EUT was tested in 3 orthogonal positions and the worst-case data was presented

3.2.5 Conducted Spurious Emissions

Procedure:

The test follows KDB558074. The conducted spurious emissions were measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function disabled at the highest, middle and the lowest available channels.

After the trace being stable, set the marker on the peak of any spurious emission recorded.

The spectrum analyzer is set to:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions

RBW = 100 kHz Sweep = auto

VBW = 100 kHz Detector function = peak

7 Trace = max hold


Measurement Data: Complies

- All conducted emission in any 100 kHz bandwidth outside of the spread spectrum band was at least 20 dB lower than the highest inband spectral density. Therefore the applying equipment meets the requirement.
- See next pages for actual measured spectrum plots.


Minimum Standard:	> 20 dBc
--------------------------	----------

Measurement Setup


Same as the Chapter 3.2.1 (Figure 1)

Unwanted Emission – Low Channel -BLEFrequency Range = 30 MHz ~ 26.5 GHz


Date: 24.APR.2019 04:26:32

Unwanted Emission – Middle Channel - BLEFrequency Range = 30 MHz ~ 26.5 GHz


Date: 24.APR.2019 04:33:16

Unwanted Emission – High Channel - BLEFrequency Range = 30 MHz ~ 26.5 GHz


Date: 24.APR.2019 04:36:42

Unwanted Emission – Low Channel - ZigbeeFrequency Range = 30 MHz ~ 26.5 GHz

Date: 24.APR.2019 04:09:46

Unwanted Emission – Middle Channel - ZigbeeFrequency Range = 30 MHz ~ 26.5 GHz

Date: 24.APR.2019 04:13:04

Unwanted Emission – High Channel - ZigbeeFrequency Range = 30 MHz ~ 26.5 GHz

Date: 24.APR.2019 04:15:25

3.2.6 Radiated Spurious Emissions

Procedure:

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defined in ANSI C63.10-2013.

The EUT is placed on a turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.

The spectrum analyzer is set to:

Center frequency = the worst channel

Frequency Range = 9 kHz ~ 10th harmonic.

RBW = 100 kHz (30 MHz \approx 1 GHz)

$$\text{VBW} \geq \text{RBW}$$


$\equiv 1 \text{ MHz}$ (1 GHz $\sim 10^{\text{th}}$ harmonic)



Detector function = peak

Trace = max hold

Sweep = auto

below 50 MHz



below 1 GHz (30 MHz to 1 GHz)**above 1 GHz****Measurement Data: Complies**

- See next pages for actual measured data.
- No other emissions were detected at a level greater than 20 dB below limit include from 9 kHz to 30MHz.

Minimum Standard: FCC Part 15.209(a)

Frequency (MHz)	Limit (uV/m) @ 3 m
0.009 ~ 0.490	2400/F(kHz) (@ 300 m)
0.490 ~ 1.705	24000/F(kHz) (@ 30 m)
1.705 ~ 30	30(@ 30 m)
30 ~ 88	100 **
88 ~ 216	150 **
216 ~ 960	200 **
Above 960	500

** Except as provided in 15.209(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

Radiated Emissions (Below 1 GHz) – Operating mode - BLE


4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: PT400TWR

Temp/Humi: 23 / 36

Test Mode : Bluetooth mode

Tested by: Kwon H C



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
120.09	51.32	-14.95	36.37	43.50	7.13	100	264	vertical
167.86	43.43	-12.68	30.75	43.50	12.75	100	289	vertical
408.06	44.57	-8.89	35.68	46.00	10.32	100	360	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) – Operating mode - BLE


4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: PT400TWR

Temp/Humi: 23 / 36

Test Mode : Bluetooth mode

Tested by: Kwon H C



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
143.98	51.68	-12.85	38.83	43.50	4.67	188	360	horizontal
156.10	52.69	-12.32	40.37	43.50	3.13	100	336	horizontal
167.98	52.76	-12.69	40.07	43.50	3.43	100	346	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) – Operating mode - Zigbee


4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: PT400TWR

Temp/Humi: 23 / 36

Test Mode : Zigbee mode

Tested by: Kwon H C



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
216.12	48.51	-15.10	33.41	46.00	12.59	100	323	vertical
408.06	43.08	-8.89	34.19	46.00	11.81	100	334	vertical
600.00	40.67	-4.81	35.86	46.00	10.14	100	253	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) – Operating mode - Zigbee


4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: PT400TWR

Temp/Humi: 23 / 36

Test Mode : Zigbee mode

Tested by: Kwon H C



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	deg	
155.98	52.86	-12.32	40.54	43.50	2.96	100	346	horizontal
167.98	52.81	-12.69	40.12	43.50	3.38	100	346	horizontal
600.00	48.24	-4.81	43.43	46.00	2.57	100	333	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Above 1 GHz) – BLE (LOW) mode



EMI I Chamber of LTA CO.,LTD.
4, Songju-ro 236 Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP
Tel : +82-31-3236008, 9 www.ltalab.com
Fax : +82-31-3236010

EUT/Model No.: PT400TWR


Test Mode: wireless (BLE) L

Tested by : Kwon H C

Temp/Humi:

Data: 66 Level (dBuV/m)

Date: 2019-04-24



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
<hr/>						
1 2109.43	42.31	2.14	44.45	74.00	29.55	VERTICAL
2 2109.43	30.83	2.14	32.97	74.00	41.03	VERTICAL
3 4772.83	28.11	17.63	45.74	54.00	8.26	VERTICAL
4 4772.83	13.33	17.63	30.96	74.00	43.04	VERTICAL
5 7213.00	33.83	28.02	61.85	74.00	12.15	VERTICAL
6 7213.00	18.81	28.02	46.83	54.00	7.17	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (BLE)_L


Tested by : Kwon H C

Temp/Humi:

Data: 67

Level (dBuV/m)

Date: 2019-04-24



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						Horizontal
1 2109.41	39.27	1.24	40.51	74.00	33.49	HORIZONTAL
2 2109.41	21.48	2.14	23.62	54.00	30.38	HORIZONTAL
3 4772.84	26.64	17.63	44.27	74.00	29.73	HORIZONTAL
4 4772.84	10.64	17.63	28.27	54.00	25.73	HORIZONTAL
5 7213.01	31.07	28.02	59.09	74.00	14.91	HORIZONTAL
6 7213.01	14.17	28.02	42.19	54.00	11.81	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

BLE (MID) mode


EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (BLE)_M

Tested by : Kwon H C

Temp/Humi:



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit	Margin dB	Polarity
				PK dBuV/m		
1 2134.89	42.03	2.21	44.24	74.00	29.76	HORIZONTAL
2 2134.89	31.72	2.21	33.93	54.00	20.07	HORIZONTAL
3 4848.43	28.31	17.96	46.27	74.00	27.73	HORIZONTAL
4 4848.43	17.22	17.96	35.18	54.00	18.82	HORIZONTAL
5 7327.02	30.27	29.85	60.12	74.00	13.88	HORIZONTAL
6 7327.02	17.32	29.85	47.17	54.00	6.83	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal



EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (BLE) _M


Tested by : Kwon H C

Temp/Humi:

Data: 69

Level (dBuV/m)

Date: 2019-04-24



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						PK
1 2134.88	40.68	2.21	42.89	74.00	31.11	VERTICAL
2 2134.88	31.02	2.21	33.23	54.00	20.77	VERTICAL
3 4848.43	26.38	17.96	44.34	74.00	29.66	VERTICAL
4 4848.43	14.95	17.96	32.91	54.00	21.09	VERTICAL
5 7327.03	28.95	29.85	58.80	74.00	15.20	VERTICAL
6 7327.03	17.83	29.85	47.68	54.00	6.32	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

BLE (HIGH) mode


EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (BLE)_H

Tested by : Kwon H C

Temp/Humi:



Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
 Blue : Vertical Black : Horizontal



EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (BLE)_H


Tested by : Kwon H C

Temp/Humi:

Data: 71

Level (dBuV/m)

Date: 2019-04-24



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						PK
1 2104.88	41.89	2.13	44.02	74.00	29.98	VERTICAL
2 2104.88	30.12	2.13	32.25	54.00	21.75	VERTICAL
3 4924.31	27.35	18.04	45.39	74.00	28.61	VERTICAL
4 4924.31	17.42	18.04	35.46	54.00	18.54	VERTICAL
5 7442.23	26.35	31.18	57.53	74.00	16.47	VERTICAL
6 7442.23	16.42	31.18	47.60	54.00	6.40	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal


Radiated Emissions (Above 1 GHz) – Zigbee (LOW) mode



EMI I Chamber of LTA CO.,LTD.
4, Songju-ro 236 Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP
Tel : +82-31-3236008, 9 www.ltalab.com
Fax : +82-31-3236010

EUT/Model No.: PT400TWR Test Mode: wireless (Zigbee)_L

Tested by : Kwon H C Temp/Humi:



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1 2105.73	45.73	2.13	47.86	74.00	26.14	HORIZONTAL
2 2105.73	37.12	2.13	39.25	54.00	14.75	HORIZONTAL
3 4848.07	30.22	17.95	48.17	74.00	25.83	HORIZONTAL
4 4848.07	21.00	17.95	38.95	54.00	15.05	HORIZONTAL
5 7212.04	31.04	28.00	59.04	74.00	14.96	HORIZONTAL
6 7212.04	20.95	28.00	48.95	54.00	5.05	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal




EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (Zigbee)_L

Tested by : Kwon H C

Temp/Humi:



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						PK
1 2105.73	43.12	2.13	45.25	74.00	28.75	VERTICAL
2 2105.73	33.20	2.13	35.33	54.00	18.67	VERTICAL
3 4848.06	29.34	17.95	47.29	74.00	26.71	VERTICAL
4 4848.06	18.67	17.95	36.62	54.00	17.38	VERTICAL
5 7212.04	29.95	28.00	57.95	74.00	16.05	VERTICAL
6 7212.04	20.02	28.00	48.02	54.00	5.98	VERTICAL


Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

Zigbee (MID) mode

EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR Test Mode: wireless (Zigbee)_M

Tested by : Kwon H C Temp/Humi:



Freq	Reading	C.F	Result	Limit	Margin	Polarity
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1 2107.77	40.30	2.14	42.44	74.00	31.56	HORIZONTAL
2 2107.77	31.00	2.14	33.14	54.00	20.86	HORIZONTAL
3 4902.24	26.52	18.07	44.59	74.00	29.41	HORIZONTAL
4 4902.24	17.63	18.07	35.70	54.00	18.30	HORIZONTAL
5 7327.11	30.89	29.85	60.74	74.00	13.26	HORIZONTAL
6 7327.11	18.63	29.85	48.48	54.00	5.52	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal




EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (Zigbee)_M

Tested by : Kwon H C

Temp/Humi:



Freq MHz	Reading dBuV	C.F. dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						PK
1 2107.78	38.25	2.14	40.39	74.00	33.61	VERTICAL
2 2107.78	28.28	2.14	30.42	54.00	23.58	VERTICAL
3 4902.06	23.41	18.07	41.48	74.00	32.52	VERTICAL
4 4902.06	12.99	18.07	31.06	54.00	22.94	VERTICAL
5 7327.13	28.82	29.85	58.67	74.00	15.33	VERTICAL
6 7327.13	18.12	29.85	47.97	54.00	6.03	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

Zigbee (HIGH) mode


EMI I Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho. by NVLAP
Tel:+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (Zigbee)_H

Tested by : Kwon H C

Temp/Humi:



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						PK
1 2110.12	44.02	2.14	46.16	74.00	27.84	HORIZONTAL
2 2110.12	33.89	2.14	36.03	54.00	17.97	HORIZONTAL
3 4924.07	31.04	18.04	49.08	74.00	24.92	HORIZONTAL
4 4924.07	20.12	18.04	38.16	54.00	15.84	HORIZONTAL
5 7442.30	29.83	31.18	61.01	74.00	12.99	HORIZONTAL
6 7442.30	17.53	31.18	48.71	54.00	5.29	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal




EMI Chamber of LTA CO.,LTD.
4, Songjuro236Beon-gil, Yangji-myeon,
Yongin-si, Gyeonggi-do, Korea Autho by NVLAP
Tel :+82-31-3236008,9 www.ltalab.com
Fax:+82-31-3236010

EUT/Model No.: PT400TWR

Test Mode: wireless (Zigbee)_H

Tested by : Kwon H C

Temp/Humi:



Freq MHz	Reading dBuV	C.F dB	Result PK dBuV/m	Limit dBuV/m	Margin dB	Polarity
						PK
1 2110.14	41.00	2.14	43.14	74.00	30.86	VERTICAL
2 2110.14	30.98	2.14	33.12	54.00	20.88	VERTICAL
3 4924.06	30.23	18.04	48.27	74.00	25.73	VERTICAL
4 4924.06	20.17	18.04	38.21	54.00	15.79	VERTICAL
5 7442.33	26.43	31.18	57.61	74.00	16.39	VERTICAL
6 7442.33	16.31	31.18	47.49	54.00	6.51	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain
Blue : Vertical Black : Horizontal

APPENDIX
TEST EQUIPMENT USED FOR TESTS

	Use	Description	Model No.	Serial No.	Manufacturer	Interval	Last Cal. Date
1	■	Signal Analyzer (9 kHz ~ 30 GHz)	FSV30	100757	R&S	1 year	2018-09-06
2		SYNTHESIZED CW GENERATOR	83711B	US34490456	HP	1 year	2019-03-16
3		Attenuator (3 dB)	8491A	37822	HP	1 year	2018-09-06
4		Attenuator (10 dB)	8491A	63196	HP	1 year	2018-09-06
5	■	EMI Test Receiver (~7 GHz)	ESCI7	100722	R&S	1 year	2018-09-06
6	■	RF Amplifier (~1.3 GHz)	8447D OPT 010	2944A07684	HP	1 year	2018-09-06
7	■	RF Amplifier (1~26.5 GHz)	8449B	3008A02126	HP	1 year	2019-03-16
8	■	Horn Antenna (1~18 GHz)	3115	00114105	ETS	2 year	2018-08-04
9		DRG Horn (Small)	3116B	81109	ETS-Lindgren	2 year	2018-05-03
10	■	DRG Horn (Small)	3116B	133350	ETS-Lindgren	2 year	2018-05-03
11	■	TRILOG Antenna	VULB 9160	9160-3237	SCHWARZBECK	2 year	2019-03-16
12		DC Power Supply	6674A	3637A01657	Agilent	-	-
13	■	Power Meter	EPM-441A	GB32481702	HP	1 year	2019-03-16
14	■	Power Sensor	8481A	3318A94972	HP	1 year	2018-09-06
15		Audio Analyzer	8903B	3729A18901	HP	1 year	2018-09-06
16		Modulation Analyzer	8901B	3749A05878	HP	1 year	2018-09-06
17		TEMP & HUMIDITY Chamber	YJ-500	LTAS06041	JinYoung Tech	1 year	2018-09-06
18		Stop Watch	HS-3	812Q08R	CASIO	2 year	2018-03-21
19	■	LISN	KNW-407	8-1430-1	Kyoritsu	1 year	2018-09-06
20		Two-Lime V-Network	ESH3-Z5	893045/017	R&S	1 year	2019-03-16
21		Highpass Filter	WHKX1.5/15G-10SS	74	Wainwright Instruments	1 year	2019-03-16
22		Highpass Filter	WHKX3.0/18G-10SS	118	Wainwright Instruments	1 year	2019-03-16
23		OSP120 BASE UNIT	OSP120	101230	R&S	1 year	2019-03-16
24	■	Signal Generator(100 kHz ~ 40 GHz)	SMB100A	177621	R&S	1 year	2019-03-16
25		Vector Signal Generator(9kHz ~ 6 GHz)	SMBV100A	255081	R&S	1 year	2019-03-16
26		Signal Analyzer (10 Hz ~ 40 GHz)	FSV40	101367	R&S	1 year	2019-03-16
27	■	RF Cable	SUCOFLEX	-	Huber+suhner	-	-