Product Name: BT Remote

Model Number: ERF6D60, ERF6\*60

FCCID:W9HBRCB0008

## RADIO FRREQUENCY EXPOSURE COMPLIANCE RESULT:

Test Standard: FCC KDB Publication 447498 D01V06 Clause 4.3.1,

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f_{(GHz)}}$ ]  $\leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR,where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- · Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

According to the actual measurement, max. power of channel, including tune-up tolerance =2.77mW min. test separation distance=5mm  $\sqrt{f_{\text{(GHz)}}} = 1.55$ 

The test result is 0.8597≤3.0 for 1-g SAR≤ 7.5 for 10-g SAR, hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01:General RF Exposure Guidance V06.