



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

RF Exposure evaluation

Report Reference No.: GTS20200812003-1-3

FCC ID.: W9V-DA725-GP

Compiled by

(position+printed name+signature) : File administrators Peter Xiao

Supervised by

(position+printed name+signature) : Test Engineer Moon Tan

Approved by

(position+printed name+signature) : Manager Simon Hu

Date of issue: Sep.02, 2020



Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address : No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

Applicant's name: Green Packet Berhad, Taiwan

Address : 2F, NO.23, LANE 583 RUEIGUANG RD, NEIHU DISTRICT, Taipei City, Taiwan

Test specification :

47CFR §1.1310

Standard : 47CFR §2.1091

KDB447498 v06

TRF Originator : Shenzhen Global Test Service Co.,Ltd.

Master TRF : Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description : LTE CPE

Trade Mark : GreenPacket

Manufacturer : Green Packet Berhad, Taiwan

Model/Type reference : DA-725

Listed Models : N/A

Modulation Type : 802.11b: DSSS; 802.11g/n: OFDM, QPSK, 16QAM

Operation Frequency : From 2412MHz to 2462MHz;
LTE:band 41

Hardware Version : V1.0

Software Version : V1.0

Rating : DC 12.0V /1.0A by Adapter

Result : PASS

TEST REPORT

Test Report No. :	GTS20200812003-1-3	Sep.02, 2020 Date of issue
-------------------	--------------------	-------------------------------

Equipment under Test : LTE CPE

Model /Type : DA-725

Listed model : N/A

Applicant : **Green Packet Berhad, Taiwan**

Address : 2F, NO.23, LANE 583 RUEIGUANG RD, NEIHU DISTRICT, Taipei City,Taiwan

Manufacturer : **Green Packet Berhad, Taiwan**

Address : 2F, NO.23, LANE 583 RUEIGUANG RD, NEIHU DISTRICT, Taipei City,Taiwan

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY	4
1.1. EUT configuration	4
1.2. Product Description	4
2. TEST ENVIRONMENT	5
2.1. Address of the test laboratory	5
2.2. Test Facility.....	5
2.3. Environmental conditions.....	5
2.4. Statement of the measurement uncertainty.....	5
3. METHOD OF MEASUREMENT	6
3.1. Applicable Standard.....	6
3.2. Requirement	6
3.3. Limit	6
3.4. MPE Calculation Method	7
3.5. Antenna Information	7
4. Conducted Power	8
5. Manufacturing Tolerance	9
6. EVALUATION RESULT	10
6.1. Standalone MPE.....	10
6.2. Simultaneous transmission MPE Considerations	10
7. CONCLUSION.....	11

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

● /	Length (m) :	/
	Shield :	/
	Detachable :	/

1.2. Product Description

Product Name	LTE CPE
Trade Mark	GreenPacket
Model/Type reference	DA-725
List Models	N/A
Model Declaration	N/A
Power supply:	DC 12.0V /1.0A by Adapter
Sample ID	GTS20200812003-1-1-1# & GTS20200812003-1-1-2#
WIFI(2.4G Band)	
Frequency Range	2412MHz ~ 2462MHz
Channel Spacing	5MHz
Channel Number	11 Channel for 20MHz bandwidth(2412~2462MHz) 7 channels for 40MHz bandwidth(2422~2452MHz)
Modulation Type	802.11b: DSSS; 802.11g/n: OFDM
Antenna Description	Two same Internal Antenna, support MIMO technology ANT0 used for WIFI TX/RX, 2.0dBi(Max.) for 2.4G Band ANT1 used for WIFI TX/RX, 2.0dBi(Max.) for 2.4G Band
LTE	
LTE Operation Frequency Band	LTE Band 41
LTE Release Version	R9
Type Of Modulation	QPSK/16QAM
Antenna Description	External Antenna; 1.0dBi (max.)

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is 165725.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, r =20cm, as well as the gain of the used antenna is 0.0dBi for BT, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained..

3.5. Antenna Information

DA-725 can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 0	2.4GWLAN	Internal antenna	2.4 – 2.4835 GHz	2.0dBi(Max.)
Antenna 1	2.4GWLAN	Internal antenna	2.4 – 2.4835 GHz	2.0dBi(Max.)
Antenna 2	LTE	External antenna	0.8 – 3GHz	1.0dBi(Max)

4. Conducted Power

Antenna 0:

2.4G WLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	16.02
	06	2437	16.10
	11	2462	16.68
802.11g	01	2412	16.17
	06	2437	16.22
	11	2462	16.27
802.11n(HT20)	01	2412	16.99
	06	2437	16.31
	11	2462	16.82
802.11n(HT40)	03	2422	15.10
	06	2437	15.93
	09	2452	15.13

Antenna 1:

2.4G WLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	16.90
	06	2437	16.81
	11	2462	16.75
802.11g	01	2412	16.11
	06	2437	16.13
	11	2462	16.36
802.11n(HT20)	01	2412	16.30
	06	2437	16.22
	11	2462	16.50
802.11n(HT40)	03	2422	15.85
	06	2437	15.30
	09	2452	15.09

Antenna 2:

<LTE Max Conducted Power>

Test Mode		Channel	Frequency (MHz)	Max Conducted Power (dBm)
LTE	Band 41	LCH	2562.5	22.46
		MCH	2605.0	22.50
		HCH	2647.5	22.48

5. Manufacturing Tolerance

Antenna 0:

2.4G WLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	15.0	15.0	15.0
Tolerance \pm (dB)	1.0	1.0	1.0

Antenna 1:

2.4G WLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	16.0	16.0	16.0
Tolerance \pm (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	15.0	15.0	15.0
Tolerance \pm (dB)	1.0	1.0	1.0

Antenna 2:

LTE

Test Mode		Channel	Max Conducted Power (dBm)	ANT Max. Tune Up Power (dBm)
LTE	Band 41	LCH	22.46	22.0 \pm 1.0
		MCH	22.50	22.0 \pm 1.0
		HCH	22.48	22.0 \pm 1.0

6. EVALUATION RESULT

6.1. Standalone MPE

Antenna 0:

2.4GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	17.00	50.1187	2.00	1.5849	0.0158	1.0000
802.11g	17.00	50.1187	2.00	1.5849	0.0158	1.0000
802.11n(HT20)	17.00	50.1187	2.00	1.5849	0.0158	1.0000
802.11n(HT40)	16.00	39.8107	2.00	1.5849	0.0126	1.0000

Antenna 1:

2.4GWLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	17.00	50.1187	2.00	1.5849	0.0158	1.0000
802.11g	17.00	50.1187	2.00	1.5849	0.0158	1.0000
802.11n(HT20)	17.00	50.1187	2.00	1.5849	0.0158	1.0000
802.11n(HT40)	16.00	39.8107	2.00	1.5849	0.0126	1.0000

Antenna 2:

LTE

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
LTE Band 41	23.00	199.5262	1.00	1.2589	0.0500	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;
3. The sample support one WLAN <E modular and two WLAN antennas, and two LTE antennas, WLAN support MIMO, Need consider simultaneous transmission ;

6.2. Simultaneous transmission MPE Considerations

According to KDB447498 :For mobile exposure host platform to qualify for simultaneous transmission MPE test exclusion, all transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

\sum of MPE ratios ≤ 1.0

6.2.1 Summary simultaneous transmission information

Modulation Type	Work Frequency Band	Transmit Antenna		Antenna 0 Antenna 1 Synchronization transmit
		Antenna 0	Antenna 1	
802.11b	2.4G WLAN	Yes	Yes	No
802.11g	2.4G WLAN	Yes	Yes	No
802.11n(HT20)	2.4G WLAN	Yes	Yes	Yes
802.11n(HT40)	2.4G WLAN	Yes	Yes	Yes

6.2.2 Summary simultaneous transmission results

Maximum Simultaneous transmission MPE Ratios for **Antenna 0, Antenna 1, Antenna 2** .

Maximum MPE ratio Ant. 0	Maximum MPE ratio Ant. 1	Maximum MPE ratio Ant. 2	Σ MPE ratios	Limit	Results
0.0158	0.0158	0.0500	0.0816	1.0	PASS

7. CONCLUSION

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

.....End of Report.....