

ROGERS LABS, INC.

4405 West 259th Terrace
Louisburg, KS 66053
Phone / Fax (913) 837-3214

Application For Grant of Certification

Product Marketing Name (PMN): Aranet4 PRO
2400-2483.5 Digital Transmission System

FCC ID: W9Z-A4MK2PRO
IC: 8855A-A4MK2PRO


SAF Tehnika AS

24a, Ganibu dambis
Riga Latvia LV-1005

FCC Designation: US5305
IC Test Site Registration: 3041A-1

Test Report Number: 210415

Test Date: April 15, 2021

Authorized Signatory: 

Scot D. Rogers
Rogers Labs, Inc.
4405 West 259th Terrace
Louisburg, KS 66053
Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.
This report must not be used by the client to claim product certification, approval, or
endorsement by NVLAP, NIST, or any agency of the U.S. Government.

Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911

FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021

Page 1 of 36

Table of Contents

TABLE OF CONTENTS.....	2	
REVISIONS.....	4	
EXECUTIVE SUMMARY	5	
OPINION / INTERPRETATION OF RESULTS	5	
EQUIPMENT TESTED.....	5	
Equipment Function	6	
Equipment Operations.....	7	
Equipment Configuration.....	7	
APPLICATION FOR CERTIFICATION.....	8	
APPLICABLE STANDARDS & TEST PROCEDURES	9	
TESTING PROCEDURES	9	
AC Line Conducted Emission Test Procedure	9	
Radiated Emission Test Procedure.....	9	
Antenna-Port Conducted Emission Test Procedure	9	
Diagram 1 Test arrangement for radiated emissions of tabletop equipment.....	10	
Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)	11	
Diagram 3 Test arrangement for Antenna Port Conducted emissions	12	
TEST SITE LOCATIONS	12	
UNITS OF MEASUREMENTS	13	
ENVIRONMENTAL CONDITIONS.....	13	
STATEMENT OF MODIFICATIONS AND DEVIATIONS	13	
INTENTIONAL RADIATORS	14	
Antenna Requirements	14	
Rogers Labs, Inc.	SAF Tehnika AS	S/N's: 00913 / 00911
4405 W. 259th Terrace	M/N: Aranet4 Pro	FCC ID: W9Z-A4MK2PRO
Louisburg, KS 66053	Test: 210415	IC: 8855A-A4MK2PRO
Phone/Fax: (913) 837-3214	Test to: 47CFR 15C, RSS-Gen RSS-247	Date: May 28, 2021
Revision 1	File: SAF Aranet4 PRO DTS TstRpt 210415	Page 2 of 36

Restricted Bands of Operation	14
Table 1 BLE Radiated Emissions Data in Restricted Frequency Bands	15
Summary of Results for Radiated Emissions in Restricted Bands	15
AC Line Conducted Emissions Procedure	16
General Radiated Emissions Procedure	16
Table 2 General Radiated Emissions Data	17
Summary of Results for General Radiated Emissions	17
Operation in the Band 2400 – 2483.5 MHz (BLE).....	18
Figure 1 BLE (1Mb) Plot of Transmitter Emissions in Operational Frequency Band.....	19
Figure 2 BLE (1Mb) Plot of Transmitter Emissions Low Band Edge.....	20
Figure 3 BLE (1Mb) Plot of Transmitter Emissions High Band Edge	20
Figure 4 BLE (1Mb) Plot of Transmitter Emissions 6-dB Occupied Bandwidth.....	21
Figure 5 BLE (1Mb) Plot of Transmitter Emissions 99% dB Occupied Bandwidth.....	22
Figure 6 BLE (2Mb) Plot of Transmitter Emissions in Operational Frequency Band.....	23
Figure 7 BLE (2Mb) Plot of Transmitter Emissions Low Band Edge	24
Figure 8 BLE (2Mb) Plot of Transmitter Emissions High Band Edge	25
Figure 9 BLE (2Mb) Plot of Transmitter Emissions 6-dB Occupied Bandwidth.....	26
Figure 10 BLE (2Mb) Plot of Transmitter Emissions 99% Occupied Bandwidth.....	27
Transmitter Emissions Data.....	28
Table 3 BLE Transmitter Radiated Emission Worst-case Data.....	28
Table 4 Transmitter Antenna Port Data	29
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator	30
ANNEX.....	31
Annex A Measurement Uncertainty Calculations	32
Annex B Additional Test Equipment.....	33

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214 Revision 1	SAF Tehnika AS M/N: Aranet4 Pro Test: 210415 Test to: 47CFR 15C, RSS-Gen RSS-247 File: SAF Aranet4 PRO DTS TstRpt 210415	S/N's: 00913 / 00911 FCC ID: W9Z-A4MK2PRO IC: 8855A-A4MK2PRO Date: May 28, 2021 Page 3 of 36
--	--	--

Annex C Rogers Qualifications35

Annex D Laboratory Certificate of Accreditation..........36

Revisions

Revision 1 Issued May 28, 2021

Rogers Labs, Inc.	SAF Tehnika AS	S/N's: 00913 / 00911
4405 W. 259th Terrace	M/N: Aranet4 Pro	FCC ID: W9Z-A4MK2PRO
Louisburg, KS 66053	Test: 210415	IC: 8855A-A4MK2PRO
Phone/Fax: (913) 837-3214	Test to: 47CFR 15C, RSS-Gen RSS-247	Date: May 28, 2021
Revision 1	File: SAF Aranet4 PRO DTS TstRpt 210415	Page 4 of 36

Executive Summary

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Hybrid Digital Transmission System Intentional Radiator operating under Title 47 Code of Federal Regulations (47CFR) Paragraph 15.247 and Industry Canada RSS-GEN, Issue 5, and RSS-247 Issue 2, operation in the 2402-2480 MHz band.

Name of Applicant: SAF Tehnika AS
 24a, Ganibu dambis
 Riga Latvia LV-1005

FCC ID: W9Z-A4MK2PRO IC: 8855A-A4MK2PRO

PMN: Aranet4 PRO HVIN: TDSPC0U3.002, TDSPC0U3.003, TDSPC0U3.004

Antenna: 2.4 GHz PIFA (0 dBi)

Frequency Range: 2402-2480 MHz

BLE (1 Mb) Output Power 0.002 W, 99% Occupied bandwidth 1,070.3 kHz

BLE (2 Mb) Output Power 0.002 W, 99% Occupied bandwidth 2,089.3 kHz

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Restricted Bands Emissions per 47CFR 15.205, RSS-GEN	-6.0	Complies
AC Line Emissions per 47CFR 15.207, RSS-GEN	N/A	Complies
General Emissions as per 47CFR 15.209, RSS-GEN	-12.6	Complies
Harmonic Emissions per 47CFR 15.247, RSS-247	-3.0	Complies
Power Spectral Density per 47CFR 15.247, RSS-247	-6.1	Complies

Equipment Tested

Equipment	Model / PN	Serial Number
EUT #1 (Integral Antenna)	Aranet4 Pro	00913
EUT #2 (Antenna port connector)	Aranet4 Pro	00911

Test results in this report relate only to the items tested.

- Software version of “typical” Aranet4 Pro: v0.4.5 and higher
- Software version of “modified for testing” Aranet4 Pro: v0.4.4-4-gc220537

Equipment Function

The Equipment Under Test (EUT) provides sensor circuitry to monitor environmental conditions. The design may be provided using different CO₂ sensors interfaced with the identical transmitter board. Identification of the different sensors are provided under the different Hardware Version Identification Numbers (HVIN): TDSPC0U3.002, TDSPC0U3.003, and TDSPC0U3.004 (note: Numbers “0” are numeric zeros). The design incorporates radio transceivers providing wireless interface operation with compatible 902-928 MHz LoRa (Long Range) devices and 2402-2480 MHz BLE (Bluetooth[®] Low Energy) equipment. The LoRa transmitter was tested for compliance as a Hybrid Digital Transmission System employing a combination of both frequency hopping and digital modulation techniques and the BLE system as Digital Transmission System. Two test samples were provided for testing. One sample representative of end product with integral antenna systems. The second sample was modified by replacing the integral antennas with 50-ohm RF connection ports. Both samples operated with special test software which provided testing personnel the capability to operate the transmitters in defined modes. The LoRa transmitter may operate one of two modes, either M-mode (500 kHz wide channel) or P-mode (125 kHz wide channel). The BLE transmitter provides either 1 or 2 MB data rates. LoRa operation in the M-mode operates as a Digital Modulation Transmission System and P-Mode employs a combination of both frequency hopping and Digital Modulation Techniques. BLE operates as Digital Transmission System across the 2402-2480 MHz band. Each operational mode was tested for compliance as documented in this report. The design operates from two (2) LR6 (AA) replaceable batteries only and offers no provision for alternate power source. Test samples were provided with test software to enable transmit operation on lowest, middle, and highest operating channels. The test software provided operation of the transmitter at 100% duty cycle for testing. For testing purposes, each test sample received power from new replaceable LR6 batteries and configured to operate in available modes. The equipment was tested for emissions compliance using the available configurations with the worst-case data presented. Test results in this report relate only to the products described in this report.



Equipment Operations

The Aranet products have distinct operation modes, which use the following radio frequency channels:

- Pairing mode utilized by all of the products (TX and RX) (M-mode)
 - 923.2 MHz @ 500 kHz
- Aranet4 PRO system mode utilized by sensors (TX) and Aranet Pro (RX) (P-mode)
 - 917.3 MHz; 922.9 MHz @ 125kHz
 - 917.5 MHz; 923.1 MHz @ 125kHz
 - 917.7 MHz; 923.3 MHz @ 125kHz
 - 917.9 MHz; 923.5 MHz @ 125kHz


Aranet4 PRO base stations choose their initial operational channel randomly when the device is first powered up.

Equipment Configuration

- 1) EUT #1 operating from replaceable LR6 (AA) internal battery



- 2) EUT #2 (Antenna Port Unit) operating from replaceable LR6 (AA) internal battery



Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911

FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021

Page 7 of 36

Application for Certification

(1) Manufacturer: SAF Tehnika AS
24a, Ganibu dambis
Riga Latvia LV-1005

(2) Identification: M/N: Aranet4 Pro, HVIN: TDSPC0U3.002, TDSPC0U3.003, TDSPC0U3.004
FCC ID: W9Z-A4MK2PRO IC: 8855A-A4MK2PRO

(3) Instruction Book:
Refer to Exhibit for Instruction Manual.

(4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.

(5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.

(6) Report of Measurements:
Report of measurements follows in this Report.

(7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.

(8) List of Peripheral Equipment Necessary for operation. The equipment operates from direct current power supplied from replaceable LR6 (AA) batteries and provides no other interface options as presented in this filing. The EUT offers no other connection ports than those presented in this filing.

(9) Transition Provisions of 47CFR 15.37 are not requested.

(10) Not Applicable. The unit is not a scanning receiver.

(11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.

(12) The equipment is not software defined and this section is not applicable.

(13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.

(14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards & Test Procedures

The following information is submitted in accordance with the eCFR Federal Communications Code of Federal Regulations, dated April 15, 2021, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.247, and Industry Canada RSS-247 Issue 2, and RSS-GEN Issue 5. This equipment operates as Digital Transmission System. Test procedures used are as defined in 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10-2013.

Testing Procedures

AC Line Conducted Emission Test Procedure

The design operates solely from direct current power provided from LR6 (AA) 1.5-volt batteries. The design offers no provision for connection with Utility AC power system and is therefore exempt from AC Line conducted emissions testing.

Radiated Emission Test Procedure

Radiated emissions testing was performed as required in 47CFR 15, RSS-247 and specified in ANSI C63.10-2013. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. The frequency spectrum from 9 kHz to 25,000 MHz was searched during preliminary investigation. Refer to diagrams one and two showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Antenna-Port Conducted Emission Test Procedure

The EUT was assembled as required for operation and placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed as presented in the regulations and specified in ANSI C63.10-2013. Antenna port conducted emissions testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram three showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911


FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021


Page 9 of 36

Diagram 1 Test arrangement for radiated emissions of tabletop equipment




1. A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).
 - 1.1—LISN spaced at least 80 cm from the nearest part of the EUT chassis.
2. Antenna can be integral or detachable, depending on the EUT (see 6.3.1).
3. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).
4. For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 2 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)



AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

Diagram 3 Test arrangement for Antenna Port Conducted emissions



Test Site Locations

Conducted EMI	AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Antenna port	Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS
Radiated EMI	The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 West 259 th Terrace, Louisburg, KS

Registered Site information: FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096

NVLAP Accreditation Lab code 200087-0

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

SAF Tehnika AS
M/N: Aranet4 Pro
Test: 210415
Test to: 47CFR 15C, RSS-Gen RSS-247
File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911
FCC ID: W9Z-A4MK2PRO
IC: 8855A-A4MK2PRO
Date: May 28, 2021
Page 12 of 36

Units of Measurements

Conducted EMI Data presented in dB μ V; dB referenced to one microvolt

Antenna port Conducted Data is in dBm; dB referenced to one milliwatt

Radiated EMI Data presented in dB μ V/m; dB referenced to one microvolt per meter

Note: Radiated limit may be expressed for measurement in dB μ V/m when the measurement is taken at a distance of 3 or 10 meters. Data taken for this report was taken at distance of 3 meters.

Sample calculation demonstrates corrected field strength reading for Open Area Test Site using the measurement reading and correcting for receive antenna factor, cable losses, and amplifier gains.

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Losses = attenuators/cable losses, Gain = amplification gains

RFS (dB μ V/m @ 3m) = FSM (dB μ V) + A.F. (dB/m) + Losses (dB) - Gain (dB)

Environmental Conditions

Ambient Temperature 22.4° C

Relative Humidity 26%

Atmospheric Pressure 1025.4 mb

Statement of Modifications and Deviations

No modifications to the EUT were required for the design to demonstrate compliance with the 47CFR Part 15C, RSS-Gen, and RSS-247 emission requirements. There were no deviations to the specifications.

Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911

FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021

Page 13 of 36



Intentional Radiators

The following information is submitted for demonstration of compliance with the requirements of 47CFR Subpart C paragraph 15.247, and Industry Canada RSS-247 and RSS-Gen.

Antenna Requirements

The EUT incorporates integral antenna system and offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2013 paragraph 6 and KDB 558074 paragraph 12 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 BLE Radiated Emissions Data in Restricted Frequency Bands

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)	Horizontal Average Margin (dB)	Vertical Average Margin (dB)
2390.0	53.7	34.2	53.3	33.7	54.0	-19.8	-20.3
2483.5	61.9	38.7	64.5	41.2	54.0	-15.3	-12.8
4804.0	54.7	39.6	50.2	37.2	54.0	-14.4	-16.8
4880.0	55.5	37.7	49.1	35.7	54.0	-16.3	-18.3
4960.0	55.2	38.4	49.1	35.8	54.0	-15.6	-18.2
7206.0	52.6	39.5	52.6	39.6	54.0	-14.5	-14.4
7320.0	52.5	39.3	53.2	40.2	54.0	-14.7	-13.8
7440.0	52.9	39.3	52.5	39.7	54.0	-14.7	-14.3
12010.0	58.8	45.9	58.4	45.6	54.0	-8.1	-8.4
12200.0	59.4	46.0	60.6	48.0	54.0	-8.0	-6.0
12400.0	58.4	45.5	58.4	45.8	54.0	-8.5	-8.2

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C, RSS-Gen, and RSS-247 Intentional Radiators. The EUT demonstrated a worst-case minimum radiated emission in restricted bands providing a minimum margin of -6.0 dB below the radiated emissions requirements. Peak and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: S AF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911

FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021

Page 15 of 36



AC Line Conducted Emissions Procedure

The design operates solely from direct current power provided from replaceable LR6 (AA) batteries. The design offers no provision for connection with the Utility AC power system and is therefore exempt from AC Line conducted emissions testing.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available mode during testing. Both the LoRa and BLE transmitters were operating during testing. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated measurements were performed. Final data was taken with the EUT located on the OATS at 3 meters distance between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers above 1 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911

FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021

Page 16 of 36

Table 2 General Radiated Emissions Data

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Quasi-Peak (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Quasi-Peak (dB μ V/m)	Limit @ 3m (dB μ V/m)	Horizontal Average Margin (dB)	Vertical Average Margin (dB)
64.3	22.4	16.6	32.7	27.4	40.0	-23.4	-12.6
112.7	30.5	15.0	27.2	23.5	40.0	-25.0	-16.5
128.6	20.5	15.2	22.2	14.4	40.0	-24.8	-25.6
144.7	28.2	23.3	26.0	21.7	40.0	-16.7	-18.3
176.8	23.8	19.2	24.3	17.3	40.0	-20.8	-22.7
208.0	17.7	12.5	18.5	12.5	40.0	-27.5	-27.5
256.1	21.5	18.0	20.3	15.5	47.0	-29.0	-31.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.


Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C paragraph 15.209, RSS-247 and RSS-GEN Intentional Radiators. The EUT demonstrated a minimum margin of -12.6 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 2400 – 2483.5 MHz (BLE)

The requirements and demonstration of compliance with RSS-247 and 47CFR subpart 15.247 are addressed below and as specified in KDB 558074 D01 15.247 Meas Guidance v05r02. Test sample #1 was used during radiated emissions measurements. Both the LoRa and BLE transmitters were operating during testing. Test sample #2 was provided for testing antenna port conducted emissions. Test sample #2 was modified by replacing the internal antenna with a 50-ohm antenna port connector and attenuator for testing purposes. The transmitter peak and average power was measured at the antenna port using a wideband RF power meter as described in ANSI C63.10-2013 and KDB 558074. Average power measurements did not include any time intervals during which the transmitter was off or transmitting at a reduced power level. Emission measurements were taken as required in ANSI C63.10-2013 and KDB 558074. The amplitude of each harmonic and general radiated emission was measured on the OATS at distance of 3 meters from the FSM antenna (radiated emission testing was performed on sample #1 representative of production equipment with integral antenna). The EUT was positioned on supporting turntable elevated as required above the ground plane, at a distance of 3 meters from the FSM antenna. Radiated emission investigations were performed from 9 kHz to 25,000 MHz. Each radiated emission was maximized by varying the FSM antenna height and polarization, and by rotating the turntable. The worst-case amplitude of each emission was then recorded from the analyzer display. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Radiated Emissions were measured in dB μ V/m @ 3 meters. Plots were taken of transmitter performance (using sample #2) for reference in this and other documentation displaying compliance with the specifications.

Figure 1 BLE (1Mb) Plot of Transmitter Emissions in Operational Frequency Band



Type	Ref Trace	X-Value	Y-Value
M1	1	2.402 GHz	3.7 dBm
M2	2	2.44 GHz	3.6 dBm
M3	3	2.48 GHz	3.7 dBm

Figure 2 BLE (1Mb) Plot of Transmitter Emissions Low Band Edge




Figure 3 BLE (1Mb) Plot of Transmitter Emissions High Band Edge






Figure 4 BLE (1Mb) Plot of Transmitter Emissions 6-dB Occupied Bandwidth




Type	Ref Trace	X-Value	Y-Value	Function	Func Result
M1	1	2.44 GHz	2.1 dBm	ndB	6 dB
T1	1	2.44 GHz	-4 dBm	ndB down BW	807.2 kHz
T2	1	2.441 GHz	-3.9 dBm	Q Factor	3023

Figure 5 BLE (1Mb) Plot of Transmitter Emissions 99% dB Occupied Bandwidth



Type	Ref Trace	X-Value	Y-Value	Function	Func Result
M1	1	2.44 GHz	0.3 dBm	99% Occ Bw	1.07 MHz
T1	1	2.44 GHz	-15.3 dBm	Occ Bw Centroid	2.44 GHz
T2	1	2.441 GHz	-14.3 dBm	Occ Bw Freq Offset	131.1 kHz

Figure 6 BLE (2Mb) Plot of Transmitter Emissions in Operational Frequency Band



Type	Ref Trace	X-Value	Y-Value
M1	1	2.403 GHz	3.7 dBm
M2	2	2.44 GHz	3.6 dBm
M3	3	2.48 GHz	3.7 dBm

Figure 7 BLE (2Mb) Plot of Transmitter Emissions Low Band Edge




Figure 8 BLE (2Mb) Plot of Transmitter Emissions High Band Edge





Figure 9 BLE (2Mb) Plot of Transmitter Emissions 6-dB Occupied Bandwidth




Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

SAF Tehnika AS
M/N: Aranet4 Pro
Test: 210415
Test to: 47CFR 15C, RSS-Gen RSS-247
File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911
FCC ID: W9Z-A4MK2PRO
IC: 8855A-A4MK2PRO
Date: May 28, 2021
Page 26 of 36

Figure 10 BLE (2Mb) Plot of Transmitter Emissions 99% Occupied Bandwidth



Type	Ref Trace	X-Value	Y-Value	Function	Func Result
M1	1	2.44 GHz	0.7 dBm	Occ Bw	2.089 MHz
T1	1	2.439 GHz	-14.5 dBm	Occ Bw Centroid	2.44 GHz
T2	1	2.441 GHz	-14.6 dBm	Occ Bw Freq Offset	129.1 kHz

Transmitter Emissions Data

Table 3 BLE Transmitter Radiated Emission Worst-case Data

Frequency in MHz	Horizontal Peak (dB μ V/m)	Horizontal Average (dB μ V/m)	Vertical Peak (dB μ V/m)	Vertical Average (dB μ V/m)	Limit @ 3m (dB μ V/m)	Horizontal Average Margin (dB)	Vertical Average Margin (dB)
2402.0	--	--	--	--	--	--	--
4804.0	54.7	39.6	50.2	37.2	54.0	-14.4	-16.8
7206.0	52.6	39.5	52.6	39.6	54.0	-14.5	-14.4
9608.0	54.9	42.0	55.2	42.1	54.0	-12.0	-11.9
12010.0	58.8	45.9	58.4	45.6	54.0	-8.1	-8.4
14412.0	61.5	48.9	61.5	49.0	54.0	-5.1	-5.0
16814.0	63.6	50.6	63.0	50.5	54.0	-3.4	-3.5
2440.0	--	--	--	--	--	--	--
4880.0	55.5	37.7	49.1	35.7	54.0	-16.3	-18.3
7320.0	52.5	39.3	53.2	40.2	54.0	-14.7	-13.8
9760.0	54.8	42.1	56.7	43.7	54.0	-11.9	-10.3
12200.0	59.4	46.0	60.6	48.0	54.0	-8.0	-6.0
14640.0	62.0	48.8	62.0	48.9	54.0	-5.2	-5.1
17080.0	63.9	51.0	63.3	50.1	54.0	-3.0	-3.9
2480.0	--	--	--	--	--	--	--
4960.0	55.2	38.4	49.1	35.8	54.0	-15.6	-18.2
7440.0	52.9	39.3	52.5	39.7	54.0	-14.7	-14.3
9920.0	55.8	42.3	55.1	42.2	54.0	-11.7	-11.8
12400.0	58.4	45.5	58.4	45.8	54.0	-8.5	-8.2
14880.0	60.8	48.0	61.1	48.1	54.0	-6.0	-5.9
17360.0	63.9	50.7	63.8	50.9	54.0	-3.3	-3.1

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911

FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021

Page 28 of 36

Table 4 Transmitter Antenna Port Data

Frequency MHz	Antenna Port Output Power (Watts)	99% Occupied Bandwidth (kHz)	20-dB Occupied Bandwidth (kHz)	6-dB Occupied Bandwidth (kHz)	Peak Power Spectral Density (dBm/3kHz)
BLE 1Mb					
2402.0	0.002	1,062.1	N/A	795.2	-10.6
2440.0	0.002	1,070.3	N/A	807.2	-8.8
2480.0	0.002	1,070.1	N/A	769.2	-9.8
BLE 2Mb					
2402.0	0.002	2,082.0	N/A	1,523.5	-12.6
2440.0	0.002	2,089.3	N/A	1,428.6	-12.7
2480.0	0.002	2,085.7	N/A	1,458.5	-12.3

Rogers Labs, Inc.

4405 W. 259th Terrace

Louisburg, KS 66053

Phone/Fax: (913) 837-3214

Revision 1

SAF Tehnika AS

M/N: Aranet4 Pro

Test: 210415

Test to: 47CFR 15C, RSS-Gen RSS-247

File: SAF Aranet4 PRO DTS TstRpt 210415

S/N's: 00913 / 00911

FCC ID: W9Z-A4MK2PRO

IC: 8855A-A4MK2PRO

Date: May 28, 2021

Page 29 of 36

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15.247, RSS-GEN, and RSS-247 Digital Transmission Systems. The BLE (2402-2480 MHz) average antenna port conducted output power measured was 0.002 Watts. The BLE power spectral density measured at the antenna port presented a minimum margin of -16.8 dB below the requirements. The BLE transmitter demonstrated a minimum margin of -3.0 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. There were no other deviations or exceptions to the requirements.

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Additional Test Equipment
- Annex C Rogers Qualifications
- Annex D Laboratory Certificate of Accreditation

Rogers Labs, Inc. SAF Tehnika AS S/N's: 00913 / 00911
4405 W. 259th Terrace M/N: Aranet4 Pro FCC ID: W9Z-A4MK2PRO
Louisburg, KS 66053 Test: 210415 IC: 8855A-A4MK2PRO
Phone/Fax: (913) 837-3214 Test to: 47CFR 15C, RSS-Gen RSS-247 Date: May 28, 2021
Revision 1 File: SAF Aranet4 PRO DTS TstRpt 210415 Page 31 of 36

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16-4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.14
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Additional Test Equipment

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
<input type="checkbox"/> LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	4/21/2020	4/21/2021
<input type="checkbox"/> LISN	Compliance Design	FCC-LISN-2.Mod.cd,(126)	.15-30MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)9kHz-40 GHz	10/14/2020	10/14/2021	
<input type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)9kHz-40 GHz	10/14/2020	10/14/2021	
<input checked="" type="checkbox"/> Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303070)9kHz-40 GHz	10/14/2020	10/14/2021	
<input type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/14/2020	10/14/2021
<input type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Antenna	Com Power	AL-130 (121055)	.001-30 MHz	10/14/2020	10/14/2021
<input type="checkbox"/> Antenna:	EMCO	6509	.001-30 MHz	10/14/2020	10/14/2022
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/14/2020	10/14/2021
<input type="checkbox"/> Antenna:	Schwarzbeck Model	VHBB 9124 (9124-627)		4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/14/2020	10/14/2021
<input type="checkbox"/> Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	10/14/2020	10/14/2022
<input type="checkbox"/> Antenna:	Schwarzbeck Model:	VULP 9118 A (VULP 9118 A-534)		4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	4/21/2020	4/21/2022
<input type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/14/2020	10/14/2022
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	3/2/2021	3/2/2022
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/12/2021	1/12/2022
<input type="checkbox"/> Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/14/2020	10/14/2021
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	10/14/2020	10/14/2021
<input type="checkbox"/> Power Meter	Agilent	N1911A with N1921A	0.05-40 GHz	4/21/2020	4/21/2021
<input type="checkbox"/> Generator	Rohde & Schwarz	SMB100A6 (100150)	20Hz-6 GHz	4/21/2020	4/21/2021
<input type="checkbox"/> Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50114 (017)1.5G HPF	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	HPM50105 (059) 6G HPF	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Fairview	SA6NFNF100W-40 (1625)	30-18000 MHz	4/21/2020	4/18/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1436)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	4/21/2020	4/21/2021
<input type="checkbox"/> Attenuator	Mini-Circuits	VAT-6W2+ (1736)	30-6000 MHz	4/21/2020	4/21/2021
<input checked="" type="checkbox"/> Weather station	Davis	6312 (A81120N075)		11/4/2020	11/4/2021

List of Test Equipment		Calibration	Date (m/d/y)	Due
<input type="checkbox"/> Frequency Counter:	Leader LDC-825 (8060153)		4/21/2020	4/21/2021
<input type="checkbox"/> LISN:	Com-Power Model LI-220A		10/14/2020	10/14/2021
<input type="checkbox"/> LISN:	Com-Power Model LI-550C		10/14/2020	10/14/2021
<input type="checkbox"/> ISN:	Com-Power Model ISN T-8		4/21/2020	4/21/2021
<input type="checkbox"/> LISN:	Fischer Custom Communications Model: FCC-LISN-50-16-2-08		4/21/2020	4/21/2021
<input type="checkbox"/> Cable	Huber & Suhner Inc. Sucoflex102ea(1.5M)(303072) 9kHz-40 GHz	10/14/2020	10/14/2021	
<input type="checkbox"/> Cable	Huber & Suhner Inc. Sucoflex102ea(L1M)(281183) 9kHz-40 GHz	10/14/2020	10/14/2021	
<input type="checkbox"/> Cable	Huber & Suhner Inc. Sucoflex102ea(L4M)(281184) 9kHz-40 GHz	10/14/2020	10/14/2021	
<input type="checkbox"/> Cable	Huber & Suhner Inc. Sucoflex102ea(L10M)(317546)9kHz-40 GHz	10/14/2020	10/14/2021	
<input type="checkbox"/> Cable	Time Microwave 4M-750HF290-750 (4M) 9kHz-24 GHz	10/14/2020	10/14/2021	
<input type="checkbox"/> RF Filter	Micro-Tronics BRC17663 (001) 9.3-9.5 notch 30-1800 MHz	4/21/2020	4/21/2021	
<input type="checkbox"/> RF Filter	Micro-Tronics BRC19565 (001) 9.2-9.6 notch 30-1800 MHz	10/16/2018	4/21/2021	
<input type="checkbox"/> Analyzer	HP 8562A (3051A05950) 9kHz-125GHz	4/21/2020	4/21/2021	
<input type="checkbox"/> Analyzer	HP External Mixers11571, 11970 25GHz-110GHz	4/18/2015	4/18/2025	
<input type="checkbox"/> Analyzer	HP 8591EM (3628A00871)	4/21/2020	4/21/2021	
<input type="checkbox"/> Wave Form Generator	Keysight 33512B (MY57400128)	4/21/2020	4/21/2021	
<input type="checkbox"/> Antenna:	Solar 9229-1 & 9230-1	2/22/2021	2/22/2022	
<input type="checkbox"/> CDN:	Com-Power Model CDN325E	10/14/2020	10/14/2021	
<input type="checkbox"/> Injection Clamp	Luthi Model EM101	10/14/2020	10/14/2021	
<input type="checkbox"/> Oscilloscope	Scope: Tektronix MDO 4104	2/22/2021	2/22/2022	
<input type="checkbox"/> EMC Transient Generator	HVT TR 3000	2/22/2021	2/22/2022	
<input type="checkbox"/> AC Power Source	(Ametech, California Instruments)	2/22/2021	2/22/2022	
<input type="checkbox"/> Field Intensity Meter	EFM-018	2/22/2021	2/22/2022	
<input type="checkbox"/> ESD Simulator	MZ-15	2/22/2021	2/22/2022	
<input type="checkbox"/> R.F. Power Amp	ACS 230-50W	not required		
<input type="checkbox"/> R.F. Power Amp	EIN Model: A301	not required		
<input type="checkbox"/> R.F. Power Amp	A.R. Model: 10W 1010M7	not required		
<input type="checkbox"/> R.F. Power Amp	A.R. Model: 50U1000	not required		
<input type="checkbox"/> Tenney Temperature Chamber		not required		
<input checked="" type="checkbox"/> Shielded Room		not required		

Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has 35 years' experience in the field of electronics. Work experience includes working in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

Positions Held:

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background:

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University
- 2) Bachelor of Science Degree in Business Administration Kansas State University
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.

Annex D Laboratory Certificate of Accreditation

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

Rogers Labs, Inc.
Louisburg, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).*

2021-02-19 through 2022-03-31

Effective Dates



For the National Voluntary Laboratory Accreditation Program

Rogers Labs, Inc. 4405 W. 259th Terrace Louisburg, KS 66053 Phone/Fax: (913) 837-3214 Revision 1	SAF Tehnika AS M/N: Aranet4 Pro Test: 210415 Test to: 47CFR 15C, RSS-Gen RSS-247 File: SAF Aranet4 PRO DTS TstRpt 210415	S/N's: 00913 / 00911 FCC ID: W9Z-A4MK2PRO IC: 8855A-A4MK2PRO Date: May 28, 2021 Page 36 of 36
--	--	---