

# FCC Radio Test Report

## FCC ID: WA5WH65B

This report concerns (check one): Original Grant Class II Change

**Project No.** : 1612C276  
**Equipment** : Weather Station  
**Model Name** : WH65B  
**Applicant** : Fine Offset Electronics Co., LTD  
**Address** : 2/F., Building no.3, Ping Shan Mingqi Industrial Park, Xili Town, Nanshan Distri. Shenzhen, Guangdong, China

**Date of Receipt** : Dec. 29, 2016  
**Date of Test** : Dec. 29, 2016 ~ Jan. 12, 2017  
**Issued Date** : Jan. 13 2017  
**Tested by** : BTL Inc.

**Testing Engineer** : Nick Chen  
(Nick Chen)

**Technical Manager** : David Mao  
(David Mao)

**Authorized Signatory** : Steven Lu  
(Steven Lu)

**B T L I N C .**

No.3,Jinshagang 1st Road, Shixia,Dalang Town, Dongguan, Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

## **Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to international standard(s) and/or national standard(s).

**BTL**'s reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL**'s report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL**'s authorized written approval.

**BTL**'s laboratory quality assurance procedures are in compliance with the **ISO Guide17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

## **Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Table of Contents	Page
1 . CERTIFICATION	6
2 . SUMMARY OF TEST RESULTS	7
2.1 TEST FACILITY	8
2.2 MEASUREMENT UNCERTAINTY	8
3 .GENERAL INFORMATION	9
3.1 GENERAL DESCRIPTION OF EUT	9
3.2 DESCRIPTION OF TEST MODES	10
3.3 BLOCKDIAGRAMSHOWINGTHECONFIGURATIONOFSYSTEMTESTED	10
3.4 DESCRIPTION OF SUPPORT UNITS	10
4 . EMC EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.1.1 POWER LINE CONDUCTED EMISSION	11
4.1.2 TESTPROCEDURE	11
4.1.3 DEVIATIONFROMTESTSTANDARD	11
4.1.4 TESTSETUP	12
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 EUT TEST CONDITIONS	12
4.1.7 TEST RESULTS	12
4.2 RADIATED EMISSION MEASUREMENT	13
4.2.1 RADIATED EMISSION LIMITS	13
4.2.2 TESTPROCEDURE	14
4.2.3 DEVIATIONFROMTESTSTANDARD	14
4.2.4 TESTSETUP	15
4.2.5 EUT OPERATING CONDITIONS	16
4.2.6 EUT TEST CONDITIONS	16
4.2.7 TEST RESULTS (BELOW 30MHz)	16
4.2.8 TEST RESULTS (30 TO 1000 MHz)	16
4.2.9 TEST RESULTS(ABOVE1000 MHz)	16
5 . BANDWIDTH TEST	17
5.1 TEST PROCEDURE	17
5.2 DEVIATION FROM STANDARD	17
5.3 TEST SETUP	17
5.4 EUT OPERATION CONDITIONS	17
5.5 EUT TEST CONDITIONS	17
5.6 TEST RESULTS	17
6 . MEASUREMENT INSTRUMENTS LIST AND SETTING	18
7 . EUT TEST PHOTO	19

<b>Table of Contents</b>	<b>Page</b>
ATTACHMENT A - CONDUCTED EMISSION	22
ATTACHMENT B -RADIATED EMISSION (9KHZ to 30MHZ)	23
ATTACHMENT C -RADIATED EMISSION (30MHZ TO 1000MHZ)	28
ATTACHMENT D -RADIATED EMISSION (ABOVE 1000MHZ)	31
ATTACHMENT E - BANDWIDTH	36

**REPORT ISSUED HISTORY**

Issued No.	Description	Issued Date
BTL-FCCP-1-1612C276	Original Issue.	Jan. 13, 2017

## 1. CERTIFICATION

Equipment : Weather Station  
Brand Name : N/A  
Model Name : WH65B  
Applicant : Fine Offset Electronics Co., LTD  
Manufacturer : Fine Offset Electronics Co., LTD  
Address : 2/F., Building no.3, Ping Shan Mingqi Industrial Park, Xili Town, NanshanDistri. Shenzhen, Guangdong, China  
Date of Test : Dec. 29, 2016 ~ Jan. 12, 2017  
Test Sample : Engineering Sample  
Standard(s) : FCC Part15, Subpart C(15.249)/ ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FCCP-1-1612C276) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC Part15, Subpart C (15.249)			
StandardSection	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	Note (1)
15.209 15.249	Radiated Spurious Emission	PASS	
-	Bandwidth	PASS	

NOTE:

- (1)"N/A" denotes test is not applicable in this test report.
- (2) EUT is used new battery.

## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.3,Jinshagang 1st Road, Shixia, DalangTown,Dongguan, Guangdong, China.

BTL's test firm number for FCC: 319330

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. The BTL measurement uncertainty is less than the CISPR 16-4-2  $U_{cisp}$  requirement.

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

A. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U,(dB)
DG-CB03	CISPR	9KHz~30MHz	V	3.79
		9KHz~30MHz	H	3.57
		30MHz~200MHz	V	3.82
		30MHz~200MHz	H	3.78
		200MHz~ 1,000MHz	V	4.10
		200MHz~ 1,000MHz	H	4.06
		1GHz~18GHz	V	3.12
		1GHz~18GHz	H	3.68
		18GHz~40GHz	V	4.15
		18GHz~40GHz	H	4.14

### 3.GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Weather Station	
Brand Name	NA	
Model Name	WH65B	
Model Difference	N/A	
Product Description	Operation Frequency	915 MHz
	Modulation Technology	FSK
	Data rate	17.2Kbps
	Field Strength	92.85dBuV/m
PowerSource	2*AA Battery supplied	
Power Rating	DC 3V	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. Channel List:

Channe	Frequency (MHz)
01	915

Table for Filed Antenna:


Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	0

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode
Final Test Mode	Description
Mode 1	TX Mode

### 3.3 BLOCKDIAGRAMSHOWINGTHECONFIGURATIONOFSYSTEMTESTED



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.
-	-	-	-	-	-

Item	Shielded Type	Ferrite Core	Length	Note
-	-	-	-	-

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION (FREQUENCY RANGE 150KHZ-30MHZ)

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

(1) The limit of " \* " decreases with the logarithm of the frequency

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


#### 4.1.2 TESTPROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATIONFROMTESTSTANDARD

No deviation

#### 4.1.4 TESTSETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The EUT was programmed to be in continuously transmitting mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: N/A

Relative Humidity: N/A

Test Voltage: N/A

#### 4.1.7 TEST RESULTS

Please refer to the Attachment A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of **Note**. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a “\*” marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (FCC 15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Harmonic emissions limits comply with below 54dB<sub>UV</sub>/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dB<sub>UV</sub>/m)=20log Emission level (uV/m).

### LIMITS OF RADIATED EMISSION MEASUREMENT (FCC 15.209)

FREQUENCY (MHz)	(dB <sub>UV</sub> /m) (at 3m)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dB<sub>UV</sub>/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz for PK/AVG detector
Start ~ Stop Frequency	90kHz~110kHz for QP detector
Start ~ Stop Frequency	110kHz~490kHz for PK/AVG detector
Start ~ Stop Frequency	490kHz~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### **4.2.2 TESTPROCEDURE**


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m or 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### **4.2.3 DEVIATIONFROMTESTSTANDARD**


No deviation

#### 4.2.4 TESTSETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 24°C

Relative Humidity: 52%

Test Voltage: DC 3V

#### 4.2.7 TEST RESULTS (BELOW 30MHz)

Please refer to the Attachment B.

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);.
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor..

#### 4.2.8 TEST RESULTS (30 TO 1000 MHz)

Please refer to the Attachment C

#### 4.2.9 TEST RESULTS(ABOVE1000 MHz)

Please refer to the Attachment D

Remark:

- (1) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (2) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

## 5. BANDWIDTH TEST

### 5.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 3kHz, VBW=3kHz, Sweep time = Auto.

### 5.2 DEVIATION FROM STANDARD

No deviation.

### 5.3 TEST SETUP



### 5.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 unless otherwise a special operating condition is specified in the follows during the testing.

### 5.5 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: DC 3V

### 5.6 TEST RESULTS

Please refer to the Attachment E

## 6. MEASUREMENT INSTRUMENTS LIST AND SETTING

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarbeck	VULB9160	9160-3232	Mar. 27, 2017
2	Amplifier	HP	8447D	2944A09673	Oct. 20, 2017
3	Receiver	Agilent	N9038A	MY52130039	Sep. 04, 2017
4	Cable	emci	LMR-400(30MHz-1GHz)(8m+5m)	N/A	Jun. 27, 2017
5	Controller	CT	SC100	N/A	N/A
6	Controller	MF	MF-7802	MF780208416	N/A
7	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-01	N/A	N/A
8	Double Ridged Guide Antenna	ETS	3115	75789	Mar. 27, 2017
9	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Apr. 23, 2017
10	Amplifier	Agilent	8449B	3008A02274	Mar. 10, 2017
11	Microwave Preamplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Mar. 27, 2017
12	Receiver	Agilent	N9038A	MY52130039	Sep. 04, 2017
13	Antenna	EM	EM-6876-1	230	Jul. 08, 2017
14	Controller	CT	SC100	N/A	N/A
15	Controller	MF	MF-7802	MF780208416	N/A

Bandwidth					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP40	100185	Sep. 04, 2017
2	Test Cable	emci	EMC104-SM-SM-9000(0.01GHz—26.5GHz)	C-100	N/A

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
All calibration period of equipment list is one year.

## 7. EUT TEST PHOTO

### Radiated Measurement Photos

9KHz to 30MHz



## Radiated Measurement Photos

30MHz to 1000MHz



**Radiated Measurement Photos****Above 1000MHz**

## ATTACHMENT A - CONDUCTED EMISSION


**Test Mode: N/A**

Note: "N/A" denotes test is not applicable to this device.

## ATTACHMENT B -RADIATED EMISSION (9KHZ to 30MHZ)

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dB			
1	*	0.0116	33.90	24.02	57.92	126.32	-68.40	AVG	
2		0.0156	30.20	23.78	53.98	123.74	-69.76	AVG	
3		0.0214	27.90	23.35	51.25	121.00	-69.75	AVG	

Test Mode: TX Mode


Ant 0°



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		0.1750	24.50	18.72	43.22	102.75	-59.53	AVG
2	*	2.2486	29.50	17.59	47.09	69.54	-22.45	QP
3		3.7198	22.20	18.16	40.36	69.54	-29.18	QP

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Margin	
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1	*	0.0135	32.80	23.91	56.71	125.00	-68.29	AVG
2		0.0198	29.50	23.53	53.03	121.67	-68.64	AVG
3		0.0326	25.38	21.97	47.35	117.34	-69.99	AVG

Test Mode: TX Mode


Ant 90°



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		0.1835	23.80	18.71	42.51	102.33	-59.82	AVG	
2		2.1898	24.10	17.66	41.76	69.54	-27.78	QP	
3	*	3.6611	25.90	18.04	43.94	69.54	-25.60	QP	


## ATTACHMENT C -RADIATED EMISSION (30MHZ TO 1000MHZ)

Test Mode: TX Mode



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Comment
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	
1		46.490	28.46	-12.60	15.86	40.00	-24.14	peak
2		164.830	28.36	-12.20	16.16	43.50	-27.34	peak
3		301.600	28.13	-10.19	17.94	46.00	-28.06	peak
4		434.490	30.28	-7.94	22.34	46.00	-23.66	peak
5		549.920	31.76	-4.55	27.21	46.00	-18.79	peak
6 *		799.210	30.25	0.23	30.48	46.00	-15.52	peak

Test Mode: TX Mode

**Horizontal**


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		45.520	28.55	-12.60	15.95	40.00	-24.05	peak	
2		166.770	28.50	-12.21	16.29	43.50	-27.21	peak	
3		390.840	29.99	-8.41	21.58	46.00	-24.42	peak	
4		550.890	29.21	-4.59	24.62	46.00	-21.38	peak	
5		723.550	29.87	-2.04	27.83	46.00	-18.17	peak	
6 *		907.850	30.62	2.61	33.23	46.00	-12.77	peak	

## ATTACHMENT D -RADIATED EMISSION (ABOVE 1000MHZ)

Orthogonal Axis : X

Test Mode : TX Mode


## Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
			MHz	dBuV	dB	dBuV/m	dB		
1	*	902.000	33.48	2.64	36.12	46.00	-9.88	QP	
2		915.040	80.87	2.58	83.45	94.00	-10.55	QP	
3		928.000	33.34	2.52	35.86	46.00	-10.14	QP	

Orthogonal Axis :	X
Test Mode :	TX Mode


### Vertical



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		1828.000	54.07	-4.14	49.93	74.00	-24.07	peak	
2		2746.000	43.87	0.25	44.12	74.00	-29.88	peak	
3		3664.000	42.82	1.85	44.67	74.00	-29.33	peak	
4		4573.000	46.41	3.79	50.20	74.00	-23.80	peak	
5 *		5491.000	48.15	7.20	55.35	74.00	-18.65	peak	

Orthogonal Axis :	X
Test Mode :	TX Mode


### Horizontal



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Margin	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dB	Detector	Comment
1		902.000	33.49	2.64	36.13	46.00	-9.87	QP
2 *		915.000	90.27	2.58	92.85	94.00	-1.15	QP
3		928.000	33.38	2.52	35.90	46.00	-10.10	QP

Orthogonal Axis :	X
Test Mode :	TX Low Channel

### Horizontal




No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit	Margin	Detector	Comment
			Level dBuV	Factor dB	ment dBuV/m				
1		1828.000	48.29	-4.14	44.15	74.00	-29.85	peak	
2		2746.000	48.30	0.25	48.55	74.00	-25.45	peak	
3 *		3664.000	49.76	1.85	51.61	74.00	-22.39	peak	
4		4573.000	47.33	3.79	51.12	74.00	-22.88	peak	
5		5491.000	42.32	7.20	49.52	74.00	-24.48	peak	
6		6409.000	38.75	10.55	49.30	74.00	-24.70	peak	

## ATTACHMENT E - BANDWIDTH

Test Mode :	TX Mode
-------------	---------

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)
915	0.308	0.745

### TX Mode



Date: 6.JAN.2017 17:16:04