# Verykool USA INC.

# **Mobile Phone**

Main Model: S450 Serial Model: N/A

**January 17, 2014** 

Report No.: 13070615-FCC-R1



**Modifications made to the product: None** 

This Test Report is Issued Under the Authority of:

Fly Xu

Fly Xu

Compliance Engineer

Technical Manager

This test report may be reproduced in full only.

Test result presented in this test report is applicable to the representative sample only.

SIEMIC, INC.
Accessing global market

Issue Date: January 17, 2014
Page: 2 of 61
www.siemic.com.cn

Report No: 13070615-FCC-R1

# **Laboratory Introduction**

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to <u>testing</u> and <u>certification</u>, SIEMIC provides initial design reviews and <u>compliance</u> <u>management</u> through out a project. Our extensive experience with <u>China</u>, <u>Asia Pacific</u>, <u>North America</u>, <u>European</u>, <u>and international</u> compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

SIEMIC (Shenzhen - China) Laboratories Accreditations for Conformity Assessment

Country/Region	Scope		
USA	EMC, RF/Wireless, Telecom		
Canada	EMC, RF/Wireless, Telecom		
Taiwan	EMC, RF, Telecom, Safety		
Hong Kong	RF/Wireless ,Telecom		
Australia	EMC, RF, Telecom, Safety		
Korea	EMI, EMS, RF, Telecom, Safety		
Japan	EMI, RF/Wireless, Telecom		
Singapore	EMC, RF, Telecom		
Europe	EMC, RF, Telecom, Safety		



This page has been left blank intentionally.



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 4 of 61 www.siemic.com.cn

# **CONTENTS**

1.	EXECUTIVE SUMMARY & EUT INFORMATION	5
2.	TECHNICAL DETAILS	6
3	MODIFICATION	7
3.	TEST SUMMARY	8
4.	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
ANI	NEX A. TEST INSTRUMENT & METHOD	45
ANI	NEX B. EUT AND TEST SETUP PHOTOGRAPHS	48
ANI	NEX C. TEST SETUP AND SUPPORTING EQUIPMENT	57
ANI	NEX D.USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST	60
ANI	NEX E. DECLARATION OF SIMILARITY	61



#### 1. **EXECUTIVE SUMMARY & EUT INFORMATION**

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014

5 of 61

www.siemic.com.cn

Page:

The purpose of this test programmed was to demonstrate compliance of the Verykool USA INC., Mobile Phone and model: S450 against the current Stipulated Standards. The Mobile Phone has demonstrated compliance with the FCC Part 22(H) & FCC Part 24(E): 2013.

#### **EUT Information**

EUT

**Description** : Mobile Phone

Main Model : S450

Serial Model N/A

UMTS-FDD Band V/GSM850: -1.25 dBi

UMTS-FDD Band II/PCS1900: -0.73 dBi

Antenna Gain : Bluetooth/WIFI: -1.1 dBi

BLE: -1.1 dBi

**Battery:** 

Model: KLB175N267

Spec: 3.7V 1750mAh 6.475Wh

Limited charger voltage: 4.2V

**Input Power** 

Adapter:

Model: SKL-5WU-U050-1000 Input: 100-240V; 50/60Hz 0.15A

Output: 5.0V; 1000mA

GSM850: 31.42 dBm

Maximum

PCS1900: 28.55 dBm Conducted

AV Power to

Antenna

: UMTS-FDD Band V: 22.38 dBm UMTS-FDD Band II: 22.37 dBm

GSM850: 29.87 dBm / ERP

PCS1900:26.77 dBm / EIRP Maximum

• UMTS-FDD Band V: 19.76dBm / ERP Radiated ERP/EIRP UMTS-FDD Band II: 19.98 dBm / EIRP

Classification

Per Stipulated **Test Standard** 

: FCC Part 22(H) & FCC Part 24(E): 2013



	2. TECHNICAL DETAILS
Purpose	Compliance testing of Mobile Phone with stipulated standard
Applicant / Client	Verykool USA INC. 3636 Nobel Drive, Suite 325, San Diego, CA 92122, USA
Manufacturer	ShenZhen Konka Telecommunication Technology Co., ltd Overseas Chinese Town nanshan district, Shenzhen, China
Laboratory performing the tests	SIEMIC (Shenzhen - China) Laboratories Zone A, Floor 1, Building 2, Wan Ye Long Technology Park, South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong, China Tel: +86-0755-2601 4629 / 2601 4953 Fax: +86-0755-2601 4953-810 Email: China@siemic.com
Test report reference number	13070615-FCC-R1
Date EUT received	January 09, 2014
Standard applied	FCC Part 22(H) & FCC Part 24(E): 2013
Dates of test	January 09 to January 15, 2014
No of Units	#1
<b>Equipment Category</b>	PCE
Trade Name	Verykool
RF Operating Frequency (ies)	GSM850 TX : 824.2 ~ 848.8 MHz; RX : 869.2 ~ 893.8 MHz PCS1900 TX : 1850.2 ~ 1909.8 MHz; RX : 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX : 826.4 ~ 846.6 MHz; RX : 871.4 ~ 891.6 MHz UMTS-FDD Band II TX :1852.4 ~ 1907.6 MHz; RX : 1932.4 ~ 1987.6 MHz 802.11b/g/n: 2412-2462 MHz Bluetooth& BLE: 2402-2480 MHz
Number of Channels	299CH (PCS1900) and 124CH (GSM850) UMTS-FDD Band V : 102CH UMTS-FDD Band II : 277CH Bluetooth: 79CH 802.11b/g/n: 11CH BLE: 40CH
Modulation	GSM / GPRS: GMSK UMTS-FDD: QPSK 802.11b/g/n: DSSS/OFDM Bluetooth: GFSK& π /4DQPSK&8DPSK BLE: GFSK
GPRS Multi-slot class	8/10/12
FCC ID	WA6S450

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 6 of 61 www.siemic.com.cn



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 7 of 61 www.siemic.com.cn

#### **MODIFICATION** 3

**NONE** 

# 3. TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

#### **PCE**

**Test Results Summary** 

Test Standard	Description	Product Class	Pass / Fail
§ 1.1307, § 2.1093	RF Exposure (SAR)	See Above	Pass
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	See Above	Pass
§ 2.1047	Modulation Characteristics	See Above	N/A
§ 2.1049; § 22.905 § 22.917; § 24.238	99% & -26 dB Occupied Bandwidth	See Above	Pass
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	See Above	Pass
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	See Above	Pass
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	See Above	Pass
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	See Above	Pass

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different.

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 9 of 61 www.siemic.com.cn

# 4. <u>MEASUREMENTS, EXAMINATION AND DERIVED</u> <u>RESULTS</u>

## 5.1 §1.1307, §2.1093- RF Exposure (SAR)

**Test Result: Pass** 

The EUT is a portable device, thus requires SAR evaluation; Please refer to SIEMIC SAR Report: 13070615-FCC-H

# 5.2 §2.1046; §22.913 (a); §24.232 (c) - RF Output Power

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

3. Environmental Conditions Temperature

Relative Humidity 50% Atmospheric Pressure 1020mbar

23°C

4. Test date: January 09, 2014

Tested By: Fly Xu

#### **Procedures: (According with KDB 971168)**

#### For Conducted Power:

- 1. The transmitter output port was connected to base station.
- 2. Set EUT at maximum power through base station.
- 3. Select lowest, middle, and highest channels for each band and different test mode.
- 4. The instrument must have an available measurement/resolution bandwidth that is equal to or exceeds the OBW. If this capability is available, then the following procedure can be used to determine the total peak output power.
  - a) Set the RBW  $\geq$  OBW.
  - b) Set VBW  $\geq 3 \times RBW$ .
  - c) Set span  $\geq 2 \times RBW$
  - d) Sweep time = auto couple.
  - e) Detector = peak.
  - f) Ensure that the number of measurement points  $\geq$  span/RBW.
  - g) Trace mode = max hold.
  - h) Allow trace to fully stabilize.
  - 1) Use the peak marker function to determine the peak amplitude level.

#### For ERP/EIRP: (According with TIA 603B)

- 1. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.
- 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
- 3. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

#### Sample Calculation:

EUT Field Strength (dBm) = Reading (Signal generator) + Antenna Gain (substitution antenna) - Cable loss (From Signal Generator to substitution antenna)

#### **Test Result: Pass**

**Remark:** Conducted Burst Average power for reporting purposes only

#### **Conducted Power**

## **GSM Mode:**

Burst Average Power (dBm);								
Band		GSN	<b>1</b> 850			GSN	11900	
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	31.37	31.42	31.34	32±1	28.50	28.52	28.47	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	31.12	31.08	31.04	32±1	28.54	28.55	28.53	29±1
GPRS Multi-Slot Class 10 (2 uplink),GMSK	30.21	30.26	30.31	30±1	27.71	27.74	27.75	27±1
GPRS Multi-Slot Class 12 (4 uplink),GMSK	28.57	28.64	28.61	28±1	25.31	25.57	25.57	25±1

Remark:

GPRS, CS1 coding scheme.

 $Multi-Slot\ Class\ 8\ ,\ Support\ Max\ 4\ downlink,\ 1\ uplink\ ,\ 5\ working\ link$ 

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link

Note: Since GSM mode has higher power, so the test items below were not performed to GPRS mode.



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 12 of 61

www.siemic.com.cn

# **UMTS Mode:**

## **UMTS-FDD Band V**

Band/ Time Slot	Dand/Time Clet						
configuration	Channel	Frequency	Average power (dBm)				
DMC	4132	826.4	22.34				
RMC	4175	835	22.38				
12.2kbps	4232	846.4	21.89				
HCDDA	4133	826.4	21.84				
HSDPA Subtest1	4175	835	21.79				
Sublesti	4232	846.4	21.62				
HCDDA	4133	826.4	21.57				
HSDPA Subtest2	4175	835	21.58				
Sublest2	4232	846.4	21.43				
Habby	4133	826.4	21.38				
HSDPA Subtest3	4175	835	21.37				
Sublests	4232	846.4	21.11				
Habby	4133	826.4	21.14				
HSDPA Subtest4	4175	835	20.67				
Sublest4	4232	846.4	20.64				
HCHDA	4133	826.4	21.52				
HSUPA Subtest1	4175	835	21.51				
Sublesti	4232	846.4	21.32				
HCHDA	4133	826.4	21.34				
HSUPA Subtest2	4175	835	21.47				
Sublest2	4232	846.4	21.58				
HCHDA	4133	826.4	21.32				
HSUPA Subtest3	4175	835	21.24				
Sublests	4232	846.4	21.04				
HSUPA	4133	826.4	21.03				
Subtest4	4175	835	20.92				
Subjest4	4232	846.4	20.76				
HCHDA	4133	826.4	20.75				
HSUPA Subtest5	4175	835	20.61				
Sublests	4232	846.4	20.49				

# **UMTS-FDD Band II**

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 13 of 61

www.siemic.com.cn

Band/ Time Slot configuration         Channel         Frequency (dBm)         Average power (dBm)           RMC 12.2kbps         9262         1852.4         22.30           9400         1880.0         22.37           9538         1907.6         22.18           HSDPA Subtest1         9262         1852.4         22.16           HSDPA Subtest2         9538         1907.6         21.75           HSDPA Subtest2         9538         1907.6         21.43           HSDPA Subtest3         9962         1852.4         21.74           HSDPA Subtest3         9962         1852.4         21.34           HSDPA Subtest4         9262         1852.4         21.27           HSDPA Subtest4         9262         1852.4         21.02           HSDPA Subtest4         9262         1852.4         21.02           HSUPA Subtest4         9400         1880.0         20.84           9538         1907.6         21.74           HSUPA Subtest1         9400         1880.0         22.07           HSUPA Subtest2         9538         1907.6         21.74           HSUPA Subtest3         9538         1907.6         21.42           HSUPA Subtest3         9400 <th colspan="7">UNITS-FUD Danu II</th>	UNITS-FUD Danu II						
RMC         9400         1880.0         22.37           12.2kbps         9538         1907.6         22.18           HSDPA         9262         1852.4         22.16           Subtest1         9400         1880.0         22.08           HSDPA         9538         1907.6         21.75           HSDPA         9262         1852.4         21.74           Subtest2         9538         1907.6         21.43           HSDPA         9262         1852.4         21.34           HSDPA         9400         1880.0         21.27           9538         1907.6         21.16           HSDPA         9400         1880.0         21.27           HSDPA         9400         1880.0         20.84           9538         1907.6         21.16           HSUPA         9400         1880.0         20.84           9538         1907.6         20.73           HSUPA         9400         1880.0         22.07           HSUPA         9400         1880.0         21.64           Subtest2         9538         1907.6         21.74           HSUPA         9400         1880.0         21.64		Channel	Frequency	<u> </u>			
12.2kbps   9400   1880.0   22.37	DMG	9262	1852.4	22.30			
HSDPA Subtest1   9262   1852.4   22.16		9400	1880.0	22.37			
Subtest   9400	12.2kbps	9538	1907.6	22.18			
Subtest1         9400         1880.0         22.08           9538         1907.6         21.75           HSDPA         9262         1852.4         21.74           Subtest2         9400         1880.0         21.68           9538         1907.6         21.43           HSDPA         9400         1880.0         21.27           9538         1907.6         21.16           HSDPA         9400         1880.0         20.84           9538         1907.6         20.73           HSUPA         9400         1880.0         22.07           Subtest4         9538         1907.6         21.74           HSUPA         9400         1880.0         22.07           Subtest1         9262         1852.4         21.73           HSUPA         9400         1880.0         21.64           9538         1907.6         21.42           HSUPA         9400         1880.0         21.24           Subtest3         9538         1907.6         21.11           HSUPA         9400         1880.0         21.24           Subtest4         9538         1907.6         21.11           HSUPA	Habby	9262	1852.4	22.16			
Subtest2   9538   1907.6   21.75		9400	1880.0	22.08			
HSDPA Subtest2         9400         1880.0         21.68           9538         1907.6         21.43           HSDPA Subtest3         9262         1852.4         21.34           9400         1880.0         21.27           9538         1907.6         21.16           HSDPA Subtest4         9262         1852.4         21.02           9400         1880.0         20.84           9538         1907.6         20.73           HSUPA Subtest1         9262         1852.4         22.02           HSUPA Subtest2         9400         1880.0         22.07           HSUPA Subtest3         9400         1880.0         21.64           9538         1907.6         21.42           HSUPA Subtest3         9400         1880.0         21.24           9538         1907.6         21.11           HSUPA Subtest4         9400         1880.0         21.24           9538         1907.6         21.11           HSUPA Subtest4         9400         1880.0         20.81           9538         1907.6         20.70           HSUPA Subtest4         9400         1880.0         20.81           9538         1907.6 <td>Subtest1</td> <td>9538</td> <td>1907.6</td> <td>21.75</td>	Subtest1	9538	1907.6	21.75			
Subtest2         9400         1880.0         21.68           9538         1907.6         21.43           HSDPA         9262         1852.4         21.34           Subtest3         9400         1880.0         21.27           9538         1907.6         21.16           HSDPA         9400         1880.0         20.84           9538         1907.6         20.73           HSUPA         9262         1852.4         22.02           9400         1880.0         22.07           9538         1907.6         21.74           HSUPA         9400         1880.0         21.64           9538         1907.6         21.42           HSUPA         9400         1880.0         21.42           HSUPA         9400         1880.0         21.24           Subtest3         9538         1907.6         21.11           HSUPA         9400         1880.0         20.81           9538         1907.6         20.70           HSUPA         9400         1880.0         20.81           9538         1907.6         20.71           HSUPA         9400         1880.0         20.81	Habby	9262	1852.4	21.74			
HSDPA Subtest3	· -	9400	1880.0	21.68			
HSDPA Subtest3         9400         1880.0         21.27           9538         1907.6         21.16           HSDPA Subtest4         9262         1852.4         21.02           HSUPA Subtest4         9400         1880.0         20.84           HSUPA Subtest1         9262         1852.4         22.02           HSUPA Subtest2         9400         1880.0         22.07           HSUPA Subtest3         9400         1880.0         21.64           HSUPA Subtest3         9400         1880.0         21.42           HSUPA Subtest4         9400         1880.0         21.24           HSUPA Subtest4         9400         1880.0         21.24           HSUPA Subtest4         9400         1880.0         20.81           HSUPA Subtest5         9400         1880.0         20.81           HSUPA Subtest5         9400         1880.0         20.86           HSUPA Subtest5         9400         1880.0         20.42	Subtest2	9538	1907.6	21.43			
Subtest3         9400         1880.0         21.27           9538         1907.6         21.16           HSDPA         9262         1852.4         21.02           Subtest4         9400         1880.0         20.84           9538         1907.6         20.73           HSUPA         9262         1852.4         22.02           Subtest1         9538         1907.6         21.74           HSUPA         9400         1880.0         21.64           Subtest2         9538         1907.6         21.42           HSUPA         9262         1852.4         21.36           Subtest3         9400         1880.0         21.24           HSUPA         9400         1880.0         21.11           HSUPA         9400         1880.0         20.81           Subtest4         9538         1907.6         20.70           HSUPA         9400         1880.0         20.81           HSUPA         9400         1880.0         20.86           HSUPA         9400         1880.0         20.70           HSUPA         9400         1880.0         20.270	Habby	9262	1852.4	21.34			
HSDPA Subtest4  HSDPA Subtest4  HSUPA Subtest1  HSUPA Subtest2  HSUPA Subtest2  HSUPA Subtest3  HSUPA Subtest3  HSUPA Subtest3  HSUPA Subtest4  HSUPA Subtest5  HSUPA Subtest5  HSUPA Subtest3  HSUPA Subtest3  HSUPA Subtest4  HSUPA Subtest5  HSUPA Subtest5  HSUPA Subtest5  HSUPA Subtest4  HSUPA Subtest5  HSUPA Subtest5  HSUPA Subtest4  HSUPA Subtest5  HSUPA Subtest5  HSUPA Subtest4  HSUPA Subtest5		9400	1880.0	21.27			
HSDPA Subtest4         9400         1880.0         20.84           9538         1907.6         20.73           HSUPA Subtest1         9262         1852.4         22.02           HSUPA Subtest2         9400         1880.0         22.07           HSUPA Subtest2         9262         1852.4         21.73           HSUPA Subtest3         9400         1880.0         21.64           HSUPA Subtest3         9400         1880.0         21.24           HSUPA Subtest4         9262         1852.4         21.36           HSUPA Subtest4         9400         1880.0         21.24           HSUPA Subtest5         9400         1880.0         20.81           HSUPA Subtest5         9400         1880.0         20.86           9400         1880.0         20.42	Subtest3	9538	1907.6	21.16			
Subtest4         9400         1880.0         20.84           9538         1907.6         20.73           HSUPA         9262         1852.4         22.02           Subtest1         9400         1880.0         22.07           HSUPA         9262         1852.4         21.73           HSUPA         9400         1880.0         21.64           Subtest2         9538         1907.6         21.42           HSUPA         9400         1880.0         21.24           Subtest3         9538         1907.6         21.11           HSUPA         9262         1852.4         21.05           HSUPA         9400         1880.0         20.81           Subtest4         9538         1907.6         20.70           HSUPA         9262         1852.4         20.86           HSUPA         9262         1852.4         20.86           Subtest5         9400         1880.0         20.42	Habby	9262	1852.4	21.02			
HSUPA Subtest 9262 1852.4 22.02  HSUPA Subtest 1 9262 1852.4 22.02  HSUPA 9400 1880.0 22.07  HSUPA 9262 1852.4 21.73  HSUPA 9400 1880.0 21.64  9538 1907.6 21.42  HSUPA 9262 1852.4 21.36  HSUPA 9400 1880.0 21.24  Subtest 3 9538 1907.6 21.11  HSUPA 9400 1880.0 21.24  HSUPA 9400 1880.0 21.24  HSUPA 9400 1880.0 21.24  HSUPA 9400 1880.0 20.81  HSUPA 9400 1880.0 20.86  9538 1907.6 20.70  HSUPA 9400 1880.0 20.86		9400	1880.0	20.84			
HSUPA Subtest1         9400         1880.0         22.07           9538         1907.6         21.74           HSUPA Subtest2         9262         1852.4         21.73           HSUPA Subtest3         9400         1880.0         21.64           HSUPA Subtest3         9262         1852.4         21.36           HSUPA Subtest4         9400         1880.0         21.24           HSUPA Subtest4         9262         1852.4         21.05           HSUPA Subtest4         9400         1880.0         20.81           HSUPA Subtest5         9400         1880.0         20.70           HSUPA Subtest5         9400         1880.0         20.42	Subtest4	9538	1907.6	20.73			
Subtest1         9400         1880.0         22.07           9538         1907.6         21.74           HSUPA         9262         1852.4         21.73           Subtest2         9400         1880.0         21.64           9538         1907.6         21.42           HSUPA         9400         1880.0         21.24           Subtest3         9538         1907.6         21.11           HSUPA         9400         1880.0         20.81           Subtest4         9538         1907.6         20.70           HSUPA         9262         1852.4         20.86           HSUPA         9262         1852.4         20.86           Subtest5         9400         1880.0         20.42	Harb	9262	1852.4	22.02			
9538     1907.6     21.74       HSUPA       Subtest2     9400     1880.0     21.64       9538     1907.6     21.42       HSUPA       Subtest3     9400     1880.0     21.24       HSUPA     9262     1852.4     21.36       HSUPA     9262     1852.4     21.05       HSUPA     9400     1880.0     20.81       Subtest4     9262     1852.4     20.86       HSUPA     9262     1852.4     20.86       Subtest5     9400     1880.0     20.42		9400	1880.0	22.07			
HSUPA       Subtest2     9400     1880.0     21.64       9538     1907.6     21.42       HSUPA     9262     1852.4     21.36       Subtest3     9400     1880.0     21.24       HSUPA     9262     1852.4     21.05       HSUPA     9400     1880.0     20.81       Subtest4     9538     1907.6     20.70       HSUPA     9262     1852.4     20.86       Subtest5     9400     1880.0     20.42	Subtest1	9538	1907.6	21.74			
Subtest2     9400     1880.0     21.64       9538     1907.6     21.42       HSUPA     9262     1852.4     21.36       Subtest3     9400     1880.0     21.24       HSUPA     9262     1852.4     21.05       Subtest4     9400     1880.0     20.81       HSUPA     9538     1907.6     20.70       HSUPA     9262     1852.4     20.86       Subtest5     9400     1880.0     20.42	Harry	9262	1852.4	21.73			
HSUPA 9262 1852.4 21.36 9400 1880.0 21.24 9538 1907.6 21.11  HSUPA 9400 1880.0 21.11  HSUPA 9400 1880.0 20.11  HSUPA 9400 1880.0 20.81 9538 1907.6 20.70  HSUPA 9262 1852.4 20.86  9400 1880.0 20.42		9400	1880.0	21.64			
HSUPA Subtest3  9400  1880.0  21.24  9538  1907.6  21.11  HSUPA Subtest4  9262  1852.4  21.05  1880.0  20.81  9538  1907.6  20.70  HSUPA Subtest5  9262  1852.4  20.86  9400  1880.0  20.42	Sublest2	9538	1907.6	21.42			
Subtest3     9400     1880.0     21.24       9538     1907.6     21.11       HSUPA     9262     1852.4     21.05       Subtest4     9400     1880.0     20.81       HSUPA     9262     1852.4     20.70       HSUPA     9262     1852.4     20.86       Subtest5     9400     1880.0     20.42	HOLLDA	9262	1852.4	21.36			
HSUPA 9262 1852.4 21.05 Subtest4 9400 1880.0 20.81 HSUPA 9262 1852.4 21.05  9400 1880.0 20.81  9538 1907.6 20.70  9262 1852.4 20.86  Subtest5 9400 1880.0 20.42		9400	1880.0	21.24			
HSUPA Subtest4 9400 1880.0 20.81 9538 1907.6 20.70 HSUPA Subtest5 9400 1880.0 20.42	Sublesis	9538	1907.6	21.11			
Subtest4     9400     1880.0     20.81       9538     1907.6     20.70       HSUPA     9262     1852.4     20.86       Subtest5     9400     1880.0     20.42	HGHDA	9262	1852.4	21.05			
9538 1907.6 20.70  HSUPA 9262 1852.4 20.86  Subtest 5 9400 1880.0 20.42		9400	1880.0	20.81			
HSUPA Subtest5 9400 1880.0 20.42	Sublest4	9538	1907.6	20.70			
Subtest5 9400 1880.0 20.42	HOUDA	9262	1852.4	20.86			
9538 1907.6 20.35		9400	1880.0	20.42			
	Sublests	9538	1907.6	20.35			



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 14 of 61 www.siemic.com.cn

# ERP & EIRP (worst case) ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	12.77	V	6.80	0.44	27.53	38.45
824.2	13.49	Н	6.80	0.44	29.70	38.45
836.6	17.87	V	6.80	0.44	27.51	38.45
836.6	17.28	Н	6.80	0.44	29.86	38.45
848.8	17.79	V	6.90	0.44	27.78	38.45
848.8	16.60	Н	6.90	0.44	29.87	38.45

## **EIRP for PCS Band (Part 24E)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.20	23.38	V	7.88	0.72	24.98	33
1850.20	21.84	Н	7.88	0.72	26.41	33
1880.00	23.03	V	7.88	0.72	24.58	33
1880.00	17.21	Н	7.88	0.72	26.24	33
1909.80	21.23	V	7.86	0.72	24.67	33
1909.80	20.87	Н	7.86	0.72	26.77	33

# ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	9.98	V	6.8	0.44	18.93	33
826.4	10.39	Н	6.8	0.44	19.57	33
835	10.90	V	6.8	0.44	18.41	33
835	10.93	Н	6.8	0.44	19.63	33
846.6	11.23	V	6.9	0.44	18.58	33
846.6	11.17	Н	6.9	0.44	19.76	33

# **EIRP for UMTS-FDD Band II (Part 24E)**

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	11.16	V	7.88	0.72	18.68	33
1852.4	11.34	Н	7.88	0.72	19.98	33
1880	11.08	V	7.88	0.72	18.77	33
1880	11.18	Н	7.88	0.72	19.94	33
1907.6	10.79	V	7.86	0.72	18.73	33
1907.6	10.97	Н	7.86	0.72	19.76	33

# 5.3 §2.1047 - Modulation Characteristic

According to FCC  $\S$  2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

## 5.4 §2.1049, §22.917, §22.905 & §24.238 - Occupied Bandwidth

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyser was connected to the antenna terminal.

2. Environmental Conditions Temperature 23°C Relative Humidity 50%

Atmospheric Pressure 1020mbar

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

4. Test date: January 09, 2014

Tested By: Fly Xu

#### **Procedures:**

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.
- 3. Details according with KDB 971168 section 4.1 & 4.2.

**Test Results: Pass** 

#### Cellular Band (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	248.9122	316.214
190	836.6	246.5180	323.568
251	848.8	243.5213	319.341

#### PCS Band (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	246.8837	316.677
661	1880.0	250.2702	319.337
810	1909.8	245.0732	321.722

## UMTS-FDD Band V (Part 22H)

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 17 of 61

www.siemic.com.cn

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)								
4132	826.4	4.1612	4.704								
4175	835.0	4.1424	4.715								
4233	846.6	4.1606	4.690								

#### UMTS-FDD Band II (Part 24E)


		<u> </u>	,
Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.1498	4.679
9400	1880.0	4.1652	4.681
9538	1907.6	4.1726	4.695


Please refer to the following plots.




#### Cellular Band (Part 22H)

#### 99% Occupied Bandwidth & 26 dB Bandwidth








PCS Band (Part 24E)

99% Occupied Bandwidth & 26 dB Bandwidth
Low Channel







Issue Date: January 17, 2014 Page: 20 of 61 www.siemic.com.cn

Report No: 13070615-FCC-R1

#### Middle Channel










#### UMTS-FDD Band V (Part 22H)

#### 99% Occupied Bandwidth & 26 dB Bandwidth








#### UMTS-FDD Band II (Part 24E)


#### 99% Occupied Bandwidth & 26 dB Bandwidth






Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 23 of 61 www.siemic.com.cn

#### Middle Channel





# <u>5.5 §2.1051, §22.917(a) & §24.238(a) - Spurious Emissions at Antenna Terminals</u>

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

3. Environmental Conditions Temperature

Relative Humidity 50% Atmospheric Pressure 1020mbar

23°C

4. Test date: January 09, 2014

Tested By: Fly Xu

#### **Standard Requirement:**

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P) dB$ .

#### **Procedures:**

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
- 3. Details according with KDB 971168 section 6.0.


#### **Test Result: Pass**

Refer to the attached plots.


#### Cellular Band (Part 22H)

#### 30MHz - 10G - GSM850

#### Low Channel




#### Middle Channel




Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 26 of 61 www.siemic.com.cn





#### PCS Band (Part24E)


#### 30MHz -20G - PCS1900






Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 27 of 61 www.siemic.com.cn

#### Middle Channel







#### UMTS-FDD Band V (Part 22H)

#### 30MHz -10G - WCDMA 850

#### Low Channel




#### Middle Channel



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 29 of 61 www.siemic.com.cn


#### High Channel



#### UMTS-FDD Band II (Part24E)

#### 30MHz -25G - WCDMA1900


#### Low Channel






Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 30 of 61 www.siemic.com.cn

#### Middle Channel





## 5.6 §2.1053, §22.917 & §24.238 - Spurious Radiated Emissions

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.

2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.

3. Radiated Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 1 GHz - 40 GH is  $\pm 6.0 \text{dB}$  (for EUTs < 0.5 m X 0.5 m X 0.5 m).

4. Environmental Conditions Temperature 22°C Relative Humidity 43%

Atmospheric Pressure 1018mbar

5. Test date: January 10, 2014

Tested By: Fly Xu

#### **Standard Requirement:**

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P) dB$ . The spectrum is scanned from 30 MHz up to a frequency including its  $10^{th}$  harmonic.

#### **Procedures:** (According with TIA 603B)

- 1. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.
- 2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
- 3. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

#### Sample Calculation:

 $EUT\ Field\ Strength\ (dBm) = Reading\ (Signal\ generator) + Antenna\ Gain\ (substitution\ antenna) - Cable\ loss\ (From\ Signal\ Generator\ to\ substitution\ antenna)$ 

**Test Result: Pass** 

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 32 of 61 www.siemic.com.cn

## Cellular Band (Part 22H)

#### Low channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-33.31	230	100	V	7.95	0.78	0	-26.14	-13	-13.14
1648.4	-43.27	271	100	Н	7.95	0.78	0	-36.1	-13	-23.1
88.21	-62.44	119	180	V	1.4	0.13	0	-61.17	-13	-48.17
100.07	-62.51	320	170	Н	1.6	0.16	0	-61.07	-13	-48.07

#### Middle channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-32.91	235	100	V	7.95	0.78	0	-25.74	-13	-12.74
1673.2	-42.73	280	100	Н	7.95	0.78	0	-35.56	-13	-22.56
88.47	-61.58	120	180	V	1.4	0.13	0	-60.31	-13	-47.31
99.85	-62.01	321	170	Н	1.6	0.16	0	-60.57	-13	-47.57

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-32.72	279	110	V	7.95	0.78	0	-25.55	-13	-12.55
1697.6	-42.35	261	120	Н	7.95	0.78	0	-35.18	-13	-22.18
88.04	-63.01	120	170	V	1.4	0.13	0	-61.74	-13	-48.74
100.25	-62.58	320	190	Н	1.6	0.16	0	-61.14	-13	-48.14

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 33 of 61 www.siemic.com.cn

## PCS Band (Part 24E)

#### Low channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-52.1	261	100	V	10.25	2.73	0	-44.58	-13	-31.58
3700.4	-50.27	279	100	Н	10.25	2.73	0	-42.75	-13	-29.75
88.52	-62.31	131	180	V	1.4	0.13	0	-61.04	-13	-48.04
400.71	-63.54	275	100	Н	6.5	0.3	0	-57.34	-13	-44.34

#### Middle channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-53.01	263	100	V	10.25	2.73	0	-45.49	-13	-32.49
3760	-51.31	269	100	Н	10.25	2.73	0	-43.79	-13	-30.79
88.04	-63.01	125	170	V	1.4	0.13	0	-61.74	-13	-48.74
100.25	-62.01	323	190	Н	1.6	0.16	0	-60.57	-13	-47.57

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-52.62	208	110	V	10.36	2.73	0	-44.99	-13	-31.99
3819.6	-50.37	249	110	Н	10.36	2.73	0	-42.74	-13	-29.74
100.25	-62.78	320	190	Н	1.6	0.16	0	-61.34	-13	-48.34
400.71	-61.75	276	100	Н	6.5	0.3	0	-55.55	-13	-42.55

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 34 of 61 www.siemic.com.cn

## UMTS-FDD Band V (Part 22H)

## Low channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-53.21	230	100	V	7.95	0.78	0	-46.04	-13	-33.04
1648.4	-52.14	271	100	Н	7.95	0.78	0	-44.97	-13	-31.97
88.11	-62.44	119	180	V	1.4	0.13	0	-61.17	-13	-48.17
100.07	-62.51	320	170	Н	1.6	0.16	0	-61.07	-13	-48.07

#### Middle channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-52.82	235	100	V	7.95	0.78	0	-45.65	-13	-32.65
1673.2	-53.4	280	100	Н	7.95	0.78	0	-46.23	-13	-33.23
88.35	-61.45	120	180	V	1.4	0.13	0	-60.18	-13	-47.18
100.42	-62.67	321	170	Н	1.6	0.16	0	-61.23	-13	-48.23

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-53.81	279	110	V	7.95	0.78	0	-46.64	-13	-33.64
1697.6	-53.64	261	120	Н	7.95	0.78	0	-46.47	-13	-33.47
88.49	-63.42	120	170	V	1.4	0.13	0	-62.15	-13	-49.15
100.18	-62.69	320	190	Н	1.6	0.16	0	-61.25	-13	-48.25

# UMTS-FDD Band II (Part 24E)

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 35 of 61

www.siemic.com.cn

#### Low channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-52.89	261	100	V	10.25	2.73	0	-45.37	-13	-32.37
3700.4	-53.36	279	100	Н	10.25	2.73	0	-45.84	-13	-32.84
100.14	-63.31	131	180	V	1.6	0.16	0	-61.87	-13	-48.87
400.11	-63.22	275	100	Н	6.5	0.3	0	-57.02	-13	-44.02

## Middle channel

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-53.47	263	100	V	10.25	2.73	0	-45.95	-13	-32.95
3760	-53.69	269	100	Н	10.25	2.73	0	-46.17	-13	-33.17
88.25	-63.25	125	170	V	1.4	0.13	0	-61.98	-13	-48.98
100.78	-62.31	323	190	Н	1.6	0.16	0	-60.87	-13	-47.87

Frequency (MHz)	Substituted level (dBm)	Direction (degree)	Height (cm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Amplifier (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-52.58	208	110	V	10.36	2.73	0	-44.95	-13	-31.95
3819.6	-53.42	249	110	Н	10.36	2.73	0	-45.79	-13	-32.79
99.21	-62.41	320	190	Н	1.6	0.16	0	-60.97	-13	-47.97
400.35	-61.64	276	100	Н	6.5	0.3	0	-55.44	-13	-42.44

## 5.7 §22.917(a) & §24.238(a) - Band Edge

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 40GHz is  $\pm 1.5dB$ .

3. Environmental Conditions

Temperature 22°C
Relative Humidity 43%
Atmospheric Pressure 1018mbar

4. Test date: January 10, 2014

Tested By: Fly Xu

#### **Standard Requirement:**

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P) dB$ .

#### **Procedures:**

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
- 3. Details according with KDB 971168 section 6.0.

**Test Result: Pass** 

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 37 of 61

www.siemic.com.cn

Refer to the attached plots.

## Cellular Band (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9800	-13.62	-13
849.0150	-14.03	-13

## PCS Band (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9775	-18.87	-13
1910.0200	-18.61	-13

# UMTS-FDD Band V (Part 22H)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
824.000	-21.33	-13
849.000	-22.52	-13

## UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1850.000	-21.56	-13
1910.000	-23.34	-13

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 38 of 61 www.siemic.com.cn

#### Cellular Band, Low Channel




Note: Offset=Cable loss (4.0) + 10log (3.16/3)=4.0+0.3=4.3 dB



Note: Offset=Cable loss (4.0) + 10log (3.19/3)=4.0+0.3=4.3 dB

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 39 of 61 www.siemic.com.cn

#### **PCS Band, Low Channel**



Note: Offset=Cable loss (4.5) + 10log (3.17/3)=4.5+0.3=4.8 dB

**PCS Band, High Channel** Agilent R Peak Search Mkr1 1.9100175 GHz Ref 34.8 dBm #Atten 40 dB -18.61 dBm #Avg Meas Tools ▶ Log 10 dB/ Next Peak Offst 4.8 dΒ Next Pk Right DI -13.0 dBm Next Pk Left M1 S2 S3 FC Min Search AΑ Pk-Pk Search More Span 1 MHz Center 1.91 GHz 1 of 2 #Res BW 3 kHz #VBW 10 kHz Sweep 180.8 ms (401 pts)

Note: Offset=Cable loss (4.5) + 10log (3.22/3)=4.5+0.3=4.8dB


Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 40 of 61 www.siemic.com.cn

#### UMTS-FDD Band V, Low Channel



Note: Offset=Cable loss (4.0)

UMTS-FDD Band V, High Channel



Note: Offset=Cable loss (4.0)


Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 41 of 61 www.siemic.com.cn

#### UMTS-FDD Band II, Low Channel



Note: Offset=Cable loss (4.5)

#### UMTS-FDD Band II, High Channel



Note: Offset=Cable loss (4.5)

# 5.8 §2.1055, §22.355 & §24.235 - Frequency Stability

1. Environmental Conditions Temperature 22°C Relative Humidity 43%

Atmospheric Pressure 1018mbar

2. Test date: January 10, 2014

Tested By: Fly Xu

## **Standard Requirement:**

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.

## **Procedures:**

A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage.

Limit: The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5$ ppm) of the center frequency.

**Test Results: Pass** 

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 43 of 61 www.siemic.com.cn

**Frequency Stability versus Temperature:** The Frequency tolerance of the carrier signal shall be maintained within 2.5ppm of the operating frequency over a temperature variation of -10°C to +55°C at normal supply voltage.

Cellular Band (Part 22H)

	Middle Channel, f <sub>0</sub> = 836.6 MHz					
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)		
-10		8	0.0096	2.5		
0		15	0.0179	2.5		
10	3.7	15	0.0179	2.5		
20		-11	-0.0131	2.5		
30		4	0.0048	2.5		
40		16	0.0191	2.5		
50		12	0.0143	2.5		
55		-15	-0.0179	2.5		
25	4.2	23	0.0275	2.5		
25	3.5	3	0.0036	2.5		

## PCS Band (Part 24E)

	Middle Channel, f <sub>o</sub> = 1880 MHz					
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)		
-10		35	0.0186	2.5		
0		32	0.0170	2.5		
10	3.7	28	0.0149	2.5		
20		23	0.0122	2.5		
30		17	0.0090	2.5		
40		39	0.0207	2.5		
50		20	0.0106	2.5		
55		23	0.0122	2.5		
25	4.2	34	0.0181	2.5		
23	3.5	17	0.0090	2.5		



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 44 of 61 www.siemic.com.cn

## **UMTS-FDD Band V (Part 22H)**

	Middle Channel, $f_0 = 835 \text{ MHz}$				
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)	
-10		8	0.0096	2.5	
0		10	0.0120	2.5	
10	3.7	13	0.0156	2.5	
20		7	0.0084	2.5	
30		19	0.0228	2.5	
40		15	0.0180	2.5	
50		12	0.0144	2.5	
55		14	0.0168	2.5	
25	4.2	15	0.0180	2.5	
23	3.5	12	0.0144	2.5	

## **UMTS-FDD Band II (Part 24E)**

	UNITS-FDD Balluli (Lait 24E)					
	Middle Channel, $f_0 = 1880 \text{ MHz}$					
Temperature (°C)	Power Supplied (V <sub>DC</sub> )	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)		
-10		10	0.0053	2.5		
0		15	0.0080	2.5		
10	3.7	9	0.0048	2.5		
20		14	0.0074	2.5		
30		20	0.0106	2.5		
40		18	0.0096	2.5		
50		17	0.0090	2.5		
55		8	0.0043	2.5		
25	4.2	9	0.0048	2.5		
23	3.5	13	0.0069	2.5		

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 45 of 61 www.siemic.com.cn

# **Annex A. TEST INSTRUMENT & METHOD**

## Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Model	Serial #	Calibratio n Date	Calibration Due Date
RF conducted test				
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	CFG038	10/25/2013	10/24/2014
Power Splitter	1#	1#	02/02/2013	02/01/2014
Universal Radio Communication Tester	CMU200	121393	09/17/2013	09/16/2014
Temperature/Humidity Chamber	1007H	N/A	01/07/2014	01/06/2015
DC Power Supply	E3640A	MY40004013	03/22/2013	03/21/2014
Radiated Emissions				
EMI test receiver	ESL6	100262	11/19/2013	11/19/2014
Positioning Controller	UC3000	MF780208282	11/19/2013	11/19/2014
OPT 010 AMPLIFIER(0.1- 1300MHz)	8447E	2727A02430	11/19/2013	11/19/2014
Microwave Preamplifier( $0.5 \sim 18 \mathrm{GHz}$ )	PAM-118	443008	11/08/2013	11/07/2014
Bilog Antenna (30MHz~6GHz)	JB6	A110712	01/27/2013	01/26/2014
Bilog Antenna (30MHz~2GHz)	JB1	A112107	02/09/2013	02/09/2014
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	071259	11/20/2013	11/19/2014
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	071283	11/20/2013	11/19/2014
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	04/22/2013	04/22/2014
Tunable Notch Filter	3NF- 800/1000-S	AA4	12/14/2013	12/13/2014
Tunable Notch Filter	3NF- 1000/2000-S	AM 4	03/01/2013	02/28/2014
Universal Radio Communication Tester	CMU200	121393	09/17/2013	09/16/2014

## Annex A. ii. RADIATED EMISSIONS TEST DESCRIPTION


#### **EUT Characterisation**

EUT characterisation, over the frequency range from 30MHz to 1GHz (for FCC tests, until the  $10^{th}$  harmonic for operating frequencies  $\geq 108$ MHz),, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m or 10m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS) or EMC 3m chamber.

#### **Test Set-up**

- 1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
- 2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
- 3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



#### **Test Method**

The following procedure was performed to determine the maximum emission axis of EUT:

- 1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
- 3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

- 1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
- 2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site or EMC 10m chamber. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
- 3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
- 4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
- 5. Repeat step 4 until all frequencies need to be measured were complete.
- 6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band	Function	Resolution bandwidth	Video Bandwidth
(MHz)			
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
Above 1000	Average	1 MHz	10 Hz

## **Description of Radiated Emission Program**

This EMC Measurement software run LabView automation software and offers a common user interface for electromagnetic interference (EMI) measurements. This software is a modern and powerful tool for controlling and monitoring EMI test receivers and EMC test systems. It guarantees reliable collection, evaluation, and documentation of measurement results. Basically, this program will run a pre-scan measurement before it proceeds with the final measurement. The pre-scan routine will run the scan on four different antenna heights, 2 antenna polarity, and 360 degrees table rotation. For example, the program was set to run 30 MHz to 1 GHz scan; the program will first start from a meter antenna height and divide the 30 MHz to 1 GHz into 10 separate parts of maximum hold sweeps. Each parts of maximum hold sweep, the program will collect the data from 0 degree to 360 degrees table rotation. After the program complete the 1m scan, the antenna continues to rise to 2m and continue the scan. The step will repeated for all specified antenna height and polarity. This program will perform the Quasi Peak measurement after the signal maximization process and pre-scan routine. The final measurement will be base on the pre-scan data reduction result.

#### **Sample Calculation Example**

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

Peak = Reading + Corrected Factor

where

Corr. Factor = Antenna Factor + Cable Factor - Amplifier Gain (if any)
And the average value is

Average = Peak Value + Duty Factor or Set RBW = 1MHz, VBW = 10Hz.

Note

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 48 of 61 www.siemic.com.cn

## Annex B. EUT AND TEST SETUP PHOTOGRAPHS

# Annex B.i. Photograph 1: EUT External Photo




Whole Package - Top View



Adapter - Top View

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 49 of 61 www.siemic.com.cn



UT - Front View




EUT - Rear View

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 50 of 61 www.siemic.com.cn



EUT - Top View



EUT - Bottom View

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 51 of 61 www.siemic.com.cn



EUT - Left View



EUT - Right View

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 52 of 61 www.siemic.com.cn

# Annex B.ii. Photograph 2: EUT Internal Photo



Cover Off - Top View 1



Cover Off - Top View 2

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 53 of 61 www.siemic.com.cn




Battery - Top View




Battery - Bottom View

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 54 of 61 www.siemic.com.cn




Mainborad With Shielding - Front View



Mainborad Without Shielding - Front View



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 55 of 61 www.siemic.com.cn




Mainborad - Rear View




Antenna View

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 56 of 61 www.siemic.com.cn

# Annex B.iii. Photograph 3: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz - Front View



Radiated Spurious Emissions Test Setup Above 1GHz -Front View

Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 57 of 61

www.siemic.com.cn

# Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


# **EUT TEST CONDITIONS**

## Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description (Including Brand Name)	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

# **Block Configuration Diagram for Radiated Emissions**



#### Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 59 of 61 www.siemic.com.cn

## Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
<b>Emissions Testing</b>	The EUT was communicating with base station and set to work at maximum output power.
Others Testing	The EUT was communicating with base station and set to work at maximum output power.



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 60 of 61 www.siemic.com.cn

# Annex D.USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PART LIST

Please see attachment



Report No: 13070615-FCC-R1 Issue Date: January 17, 2014 Page: 61 of 61 www.siemic.com.cn

# **Annex E. DECLARATION OF SIMILARITY**

N/A