RF EXPOSURE REPORT



Report No.: 16070803-FCC-H2
Supersede Report No.: N/A

Applicant	Verykool U	SA Inc		
Product Name	Mobile Pho	Mobile Phone		
Model No.	s5007			
Serial No.	N/A			
Test Standard	FCC 2.109	3:2015		
Test Date	July 08 to J	luly 27, 2016		
Issue Date	July 29, 20	16		
Test Result	Pass	Fail		
Equipment compl	ied with the	specification	V	
Equipment did no	t comply with	n the specifica	tion 🗆	
Loven	Tho	David	Huang	
Loren Lu Test Engi r			Huang ked By	

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	16070803-FCC-H2
Page	2 of 9

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope	
USA	EMC, RF/Wireless, SAR, Telecom	
Canada	EMC, RF/Wireless, SAR, Telecom	
Taiwan	EMC, RF, Telecom, SAR, Safety	
Hong Kong	RF/Wireless, SAR, Telecom	
Australia	EMC, RF, Telecom, SAR, Safety	
Korea	EMI, EMS, RF, SAR, Telecom, Safety	
Japan	EMI, RF/Wireless, SAR, Telecom	
Singapore	EMC, RF, SAR, Telecom	
Europe	EMC, RF, SAR, Telecom, Safety	



Test Report	16070803-FCC-H2
Page	3 of 9

This page has been left blank intentionally.



Test Report	16070803-FCC-H2
Page	4 of 9

CONTENTS

1.	REPORT REVISION HISTORY	.5
2.	CUSTOMER INFORMATION	.5
3.	TEST SITE INFORMATION	.5
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	.6
5	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	S
Ο.	100 \$2.1000 TANDIOT REGISTROTT TANDIATION EXTENSION EVALUATION. TORTABLE DEVICES.	. •
5.1	RF EXPOSURE	.8
5.2	TEST RESULT	.9



Test Report	16070803-FCC-H2
Page	5 of 9

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16070803-FCC-H2	NONE	Original	July 29, 2016

2. Customer information

Applicant Name	Verykool USA Inc	
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, California 92122 United States	
Manufacturer	Shenzhen Fortuneship Technology Co., Ltd	
Manufacturer Add	6/F, Kanghesheng Building, No.1 Chuangsheng Road,	
	Nanshan District, Shenzhen, Guangdong, China	

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES		
Zone A, Floor 1, Building 2 Wan Ye Long Technology Park			
Lab Address	South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China		
	518108		
FCC Test Site No.	718246		
IC Test Site No.	4842E-1		
Test Software	Radiated Emission Program-To Shenzhen v2.0		



Test Report	16070803-FCC-H2
Page	6 of 9

4. Equipment under Test (EUT) Information

Description of EUT: Mobile Phone

Main Model: s5007

Serial Model: N/A

Date EUT received: July 07, 2016

Test Date(s): July 08 to July 27, 2016

GSM850: 0.68dBi

PCS1900: 0.95dBi

UMTS-FDD Band V: 0.92dBi Antenna Gain:

UMTS-FDD Band IV: 0.95dBi UMTS-FDD Band II: 0.95dBi

Bluetooth/ WIFI:1.92dBi

Antenna Type: PIFA antenna

GSM / GPRS: GMSK

EGPRS: GMSK

Type of Modulation: UMTS-FDD: QPSK

802.11b/g/n: DSSS, OFDM

Bluetooth: GFSK, π /4DQPSK, 8DPSK

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz

PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz

UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz

UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;

RF Operating Frequency (ies): RX : 2112.4 ~ 2152.6 MHz

UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;

RX: 1932.4 ~ 1987.6 MHz

WIFI: 802.11b/g/n(20M): 2412-2462 MHz

Bluetooth: 2402-2480 MHz



Test Report	16070803-FCC-H2
Page	7 of 9

GSM 850: 124CH

PCS1900: 299CH

UMTS-FDD Band V: 102CH

Number of Channels: UMTS-FDD Band IV: 202CH

UMTS-FDD Band II: 277CH

WIFI:802.11b/g/n(20M): 11CH

Bluetooth: 79CH

Port: Earphone Port, USB Port

Adapter:

Model: s5005

Input: AC 100-240V,50/60Hz;0.2A

Output: DC 5.0V,1A

Input Power:

Battery:

Model: s5005

Spec: 3.7V,2000mAh(7.4Wh) Charge limited voltage: 4.2V

Trade Name : verykool

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: WA6S5007



Test Report	16070803-FCC-H2
Page	8 of 9

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot \sqrt{f_{(GHz)}} \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 16 where

- f_(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is ≤ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result = $P\sqrt{F}/D$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	16070803-FCC-H2			
Page	9 of 9			

5.2 Test Result

Bluetooth Mode:

Modulation	СН	Freque ncy	Conducted Power	Tune Up Power	Max Tune Up Power	Max Tune Up Power	Result	Limit
		(MHz)	(dBm)	(dBm)	(dBm)	(mW)		
GFSK	Low	2402	4.874	5±1	6	3.981	1.23	3
	Mid	2441	5.644	5±1	6	3.981	1.24	3
	High	2480	5.875	5±1	6	3.981	1.25	3
π /4 DQPSK	Low	2402	6.694	7±1	8	6.310	1.96	3
	Mid	2441	7.456	7±1	8	6.310	1.97	3
	High	2480	7.384	7±1	8	6.310	1.99	3
8-DPSK	Low	2402	6.738	7±1	8	6.310	1.96	3
	Mid	2441	7.375	7±1	8	6.310	1.97	3
	High	2480	7.452	7±1	8	6.310	1.99	3

WIFI Mode:

Modulation	СН	Freque ncy	Conducted Power	Tune Up Power	Max Tune Up Power	Max Tune Up Power	Result	Limit
		(MHz)	(dBm)	(dBm)	(dBm)	(mW)		
802.11b	Low	2412	8.33	8.5±1	9.5	8.913	2.77	3
	Mid	2442	8.38	8.5±1	9.5	8.913	2.78	3
	High	2472	8.54	8.5±1	9.5	8.913	2.80	3
802.11g	Low	2412	8.28	8.5±1	9.5	8.913	2.77	3
	Mid	2442	8.24	8.5±1	9.5	8.913	2.78	3
	High	2472	8.62	8.5±1	9.5	8.913	2.80	3
802.11n (20M)	Low	2412	8.48	8.5±1	9.5	8.913	2.77	3
	Mid	2442	8.65	8.5±1	9.5	8.913	2.78	3
	High	2472	8.60	8.5±1	9.5	8.913	2.80	3

Result: Compliance

No SAR measurement is required.