



RF TEST REPORT



Report No.: 17070102-FCC-R1

Supersede Report No.: N/A

Applicant	Verykool USA Inc	
Product Name	Mobile Phone	
Model No.	SL5565	
Serial No.	N/A	
Test Standard	FCC Part 22(H):2016 ;FCC Part 24(E):2016; FCC Part 27:2016; ANSI/TIA-603-D: 2010	
Test Date	May 06 to June 15, 2017	
Issue Date	June 16, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification	☒	
Equipment did not comply with the specification	☐	
		
Vera Zhang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	10
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	11
6.1 RF EXPOSURE (SAR).....	11
6.2 RF OUTPUT POWER	12
6.3 PEAK-AVERAGE RATIO.....	25
6.4 OCCUPIED BANDWIDTH.....	30
6.5 SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	45
6.6 SPURIOUS RADIATED EMISSIONS.....	61
6.7 BAND EDGE.....	68
6.8 FREQUENCY STABILITY	82
ANNEX A. TEST INSTRUMENT.....	87
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	89
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	102
ANNEX C.II. EUT OPERATING CONKITIONS	104
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	105
ANNEX E. DECLARATION OF SIMILARITY	106

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070102-FCC-R1	NONE	Original	June 16, 2017

2. Customer information

Applicant Name	Verykool USA Inc
Applicant Add	3636 Nobel Drive, Suite 325, San Diego, California 92122 United States
Manufacturer	TEM MOBILE LIMITED
Manufacturer Add	Room 1102, 11/F, Building B, TCL Plaza, GaoXin S. Rd. 1st, Hi-Tech industrial Park, Nanshan District, Shenzhen, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT: Mobile Phone

Main Model: SL5565

Serial Model: N/A

Date EUT received: May 05, 2017

Test Date(s): May 06 to June 15, 2017

Equipment Category : PCE

Antenna Gain:

- GSM850: -2.1dBi
- PCS1900: -1.2dBi
- UMTS-FDD Band V: -2.1dBi
- UMTS-FDD Band IV: -2.2dBi
- UMTS-FDD Band II: -1.2dBi
- LTE Band II: -1.2dBi
- LTE Band IV: -2.2dBi
- LTE Band V: -2.1dBi
- LTE Band VII: 0.2dBi
- LTE Band XII: -1.7dBi
- LTE Band XVII: -1.8dBi
- Bluetooth/BLE: -0.4dBi
- WIFI: -0.4dBi
- GPS: -1.02dBi

Antenna Type: PIFA antenna

Type of Modulation:

- GSM / GPRS: GMSK
- EGPRS: GMSK, 8PSK
- UMTS-FDD: QPSK
- LTE Band: QPSK, 16QAM
- 802.11b/g/n: DSSS, OFDM
- Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
- BLE: GFSK
- GPS: BPSK

RF Operating Frequency (ies):

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
UMTS-FDD Band IV TX: 1712.4 ~ 1752.6 MHz;
RX : 2112.4 ~ 2152.6 MHz
UMTS-FDD Band II TX: 1852.4 ~ 1907.6 MHz;
RX: 1932.4 ~ 1987.6 MHz
LTE Band II TX: 1850.7 ~ 1909.3MHz; RX : 1930.7 ~ 1989.3 MHz
LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7~ 2154.3 MHz
LTE Band V TX: 824.7~ 848.3 MHz; RX : 869.7 ~ 893.3MHz
LTE Band VII TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz
LTE Band XII TX: 699.7 ~ 715.3 MHz; RX : 729.7~ 745.3MHz
LTE Band XVII TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz
WIFI: 802.11b/g/n(20M): 2412-2462 MHz
WIFI: 802.11n(40M): 2422-2452 MHz
Bluetooth& BLE: 2402-2480 MHz
GPS: 1575.42 MHz

	GSM Voice:GSM850: 31.66 dBm
	PCS1900: 29.84 dBm
	GPRS:GSM850: 31.60 dBm
	PCS1900: 29.75dBm
	EGPRS(MCS5):GSM850: 26.95dBm
	PCS1900: 25.85dBm
Maximum Conducted	RMC:UMTS-FDD Band V: 21.72 dBm
AV Power to Antenna:	UMTS-FDD Band II: 22.06 dBm
	UMTS-FDD Band IV: 21.45 dBm
	HSDPA:UMTS-FDD Band V: 20.65dBm
	UMTS-FDD Band II: 20.84 dBm
	UMTS-FDD Band IV: 20.61 dBm
	HSUPA:UMTS-FDD Band V: 20.64 dBm
	UMTS-FDD Band II: 20.87 dBm
	UMTS-FDD Band IV: 20.59 dBm
	GSM Voice:GSM850: 27.41 dBm / ERP
	PCS1900: 28.64 dBm / EIRP
	GPRS:GSM850: 27.35 dBm / ERP
	PCS1900: 28.55 dBm / EIRP
	EGPRS(MCS5):GSM850: 22.70 dBm / ERP
	PCS1900: 24.65 dBm / EIRP
	RMC:UMTS-FDD Band V: 17.47dBm / ERP
ERP/EIRP:	UMTS-FDD Band II: 20.86 dBm / EIRP
	UMTS-FDD Band IV: 19.25 dBm / EIRP
	HSDPA:UMTS-FDD Band V: 16.40dBm / ERP
	UMTS-FDD Band II: 19.64 dBm / EIRP
	UMTS-FDD Band IV: 18.41 dBm / EIRP
	HSUPA:UMTS-FDD Band V: 16.44 dBm / ERP
	UMTS-FDD Band II: 19.67 dBm / EIRP
	UMTS-FDD Band IV: 17.25dBm / EIRP

Number of Channels: GSM 850: 124CH
PCS1900: 299CH
UMTS-FDD Band V: 102CH
UMTS-FDD Band IV: 202CH
UMTS-FDD Band II: 277CH
WIFI :802.11b/g/n(20M): 11CH
WIFI :802.11n(40M): 7CH
Bluetooth: 79CH
BLE: 40CH
GPS:1CH

Port: USB Port, Earphone Port

Adapter:
Model: TPA-46B050100UU

Input Power: Input: AC100-240V~50/60Hz,0.2A
Output: DC 5.0V,1000mA
Battery:
Spec: 3.8V,2800mAh(10.64wh)

Trade Name : verykool

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: WA6SL5565

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§ 1.1307; § 2.1093	RF Exposure (SAR)	Compliance
§2.1046; § 22.913(a); § 24.232(c); § 27.50(c.10) ; § 27.50(d.4)	RF Output Power	Compliance
§ 24.232 (d) ; § 27.50(d)	Peak-Average Ratio	Compliance
§ 2.1049; § 22.905; § 22.917; § 24.238; § 27.53(a.5)	99% & -26 dB Occupied Bandwidth	Compliance
§ 2.1051; § 22.917(a); § 24.238(a); § 27.53(h)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917(a); § 24.238(a); § 27.53(h)	Field Strength of Spurious Radiation	Compliance
§ 22.917(a); § 24.238(a); § 27.53(h)	Out of band emission, Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; § 27.5(h); § 27.54	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: Testing was performed by configuring EUT to maximum output power status, the declared output power class for different

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

6.1 RF Exposure (SAR)

Test Result: Pass


The EUT is a portable device, thus requires SAR evaluation;
Please refer to RF Exposure Evaluation Report: 17070102-FCC-H.

6.2 RF Output Power

Temperature	23°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	May 20, 2017
Tested By :	Vera Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.913 (a)	a)	ERP:38.45dBm	☒
§24.232 (c)	b)	EIRP:33dBm	☒
§27.50 (c)	c)	EIRP: 30dBm	☒

Test Setup	 Base Station EUT
------------	---

Test Procedure	For Conducted Power: - The transmitter output port was connected to base station. - Set EUT at maximum power through base station. - Select lowest, middle, and highest channels for each band and different test mode. For ERP/EIRP: According with KDB 971168 v02r02 - The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - The frequency range up to tenth harmonic of the fundamental
----------------	---

	frequency was investigated. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. - Spurious emissions in dB = $10 \log (\text{TX power in Watts}/0.001)$ – the absolute level - Spurious attenuation limit in dB = $43 + 10 \text{ Log}_{10} (\text{power out in Watts})$.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Conducted Power

GSM Mode:

Burst Average Power (dBm);								
Band	GSM850				PCS1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice (1 uplink),GMSK	31.66	31.60	31.56	31±1	29.45	29.84	29.65	29±1
GPRS Multi-Slot Class 8 (1 uplink),GMSK	31.60	31.57	31.52	31±1	29.38	29.75	29.55	29±1
GPRS Multi-Slot Class 10 (2 uplink) GMSK	31.39	31.31	31.28	31±1	28.67	28.46	28.31	28±1
GPRS Multi-Slot Class 12 (4 uplink) GMSK	29.22	29.15	29.05	29±1	25.15	25.68	25.34	25±1
EGPRS Multi-Slot Class 8 (1 uplink) GMSK MCS1	31.58	31.54	31.49	31±1	29.10	29.50	29.40	29±1
EGPRS Multi-Slot Class 10 (2 uplink) GMSK MCS1	31.38	31.3	31.26	31±1	28.32	28.22	28.7	28±1
EGPRS Multi-Slot Class 12 (4 uplink) GMSK MCS1	29.18	29.08	29.01	29±1	26.48	26.39	26.72	26±1
EGPRS Multi-Slot Class 8 (1 uplink) 8PSK MCS5	26.95	26.81	26.69	26±1	25.43	25.85	25.41	25±1
EGPRS Multi-Slot Class 10 (2 uplink) 8PSK MCS5	25.76	25.69	25.51	25±1	24.63	24.35	24.43	24±1
EGPRS Multi-Slot Class 12 (4 uplink) 8PSK MCS5	22.87	22.75	22.65	22±1	21.73	21.45	21.88	21±1

Test Report	17070102-FCC-R1
Page	15 of 106

Remark :

GPRS, CS1 coding scheme.

EGPRS, MCS1 coding scheme.

EGPRS, MCS5 coding scheme.

Multi-Slot Class 8 , Support Max 4 downlink, 1 uplink , 5 working link

Multi-Slot Class 10 , Support Max 4 downlink, 2 uplink , 5 working link

Multi-Slot Class 12 , Support Max 4 downlink, 4 uplink , 5 working link

UMTS Mode:

UMTS-FDD Band V

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	4132	826.4	21.72	21.3±1
	4175	835	21.70	21.3±1
	4233	846.6	21.64	21.3±1
HSDPA Subtest1	4132	826.4	20.56	21.3±1
	4175	835	20.59	21.3±1
	4233	846.6	20.62	21.3±1
HSDPA Subtest2	4132	826.4	20.51	21.3±1
	4175	835	20.63	21.3±1
	4233	846.6	20.63	21.3±1
HSDPA Subtest3	4132	826.4	20.62	21.3±1
	4175	835	20.63	21.3±1
	4233	846.6	20.63	21.3±1
HSDPA Subtest4	4132	826.4	20.61	21.3±1
	4175	835	20.61	21.3±1
	4233	846.6	20.65	21.3±1
HSUPA Subtest1	4132	826.4	20.51	21.3±1
	4175	835	20.69	21.3±1
	4233	846.6	20.51	21.3±1
HSUPA Subtest2	4132	826.4	20.54	21.3±1
	4175	835	20.59	21.3±1
	4233	846.6	20.58	21.3±1
HSUPA Subtest3	4132	826.4	20.61	21.3±1
	4175	835	20.64	21.3±1
	4233	846.6	20.62	21.3±1
HSUPA Subtest4	4132	826.4	20.63	21.3±1
	4175	835	20.64	21.3±1
	4233	846.6	20.56	21.3±1
HSUPA Subtest5	4132	826.4	20.59	21.3±1
	4175	835	20.61	21.3±1
	4233	846.6	20.64	21.3±1

UMTS-FDD Band II

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	9262	1852.4	21.53	22±1
	9400	1880	22.06	22±1
	9538	1907.6	21.87	22±1
HSDPA Subtest1	9262	1852.4	20.60	21.3±1
	9400	1880	20.56	21.3±1
	9538	1907.6	20.53	21.3±1
HSDPA Subtest2	9262	1852.4	20.54	21.3±1
	9400	1880	20.54	21.3±1
	9538	1907.6	20.69	21.3±1
HSDPA Subtest3	9262	1852.4	20.58	21.3±1
	9400	1880	20.84	21.3±1
	9538	1907.6	20.54	21.3±1
HSDPA Subtest4	9262	1852.4	20.56	21.3±1
	9400	1880	20.53	21.3±1
	9538	1907.6	20.51	21.3±1
HSUPA Subtest1	9262	1852.4	20.56	21.3±1
	9400	1880	20.53	21.3±1
	9538	1907.6	20.56	21.3±1
HSUPA Subtest2	9262	1852.4	20.51	21.3±1
	9400	1880	20.51	21.3±1
	9538	1907.6	20.56	21.3±1
HSUPA Subtest3	9262	1852.4	20.59	21.3±1
	9400	1880	20.51	21.3±1
	9538	1907.6	20.53	21.3±1
HSUPA Subtest4	9262	1852.4	20.54	21.3±1
	9400	1880	20.84	21.3±1
	9538	1907.6	20.86	21.3±1
HSUPA Subtest5	9262	1852.4	20.87	21.3±1
	9400	1880	20.80	21.3±1
	9538	1907.6	20.59	21.3±1

UMTS-FDD Band IV

Band/ Time Slot configuration	Channel	Frequency	Average power (dBm)	Tune up Power tolerant
RMC 12.2kbps	1313	1712.6	21.45	21.3±1
	1413	1732.6	21.05	21.3±1
	1512	1752.4	20.69	21.3±1
HSDPA Subtest1	1313	1712.6	20.59	21.3±1
	1413	1732.6	20.56	21.3±1
	1512	1752.4	20.51	21.3±1
HSDPA Subtest2	1313	1712.6	20.53	21.3±1
	1413	1732.6	20.51	21.3±1
	1512	1752.4	20.61	21.3±1
HSDPA Subtest3	1313	1712.6	20.51	21.3±1
	1413	1732.6	20.31	21.3±1
	1512	1752.4	20.36	21.3±1
HSDPA Subtest4	1313	1712.6	20.42	21.3±1
	1413	1732.6	20.46	21.3±1
	1512	1752.4	20.51	21.3±1
HSUPA Subtest1	1313	1712.6	20.56	21.3±1
	1413	1732.6	20.53	21.3±1
	1512	1752.4	20.41	21.3±1
HSUPA Subtest2	1313	1712.6	20.56	21.3±1
	1413	1732.6	20.53	21.3±1
	1512	1752.4	20.53	21.3±1
HSUPA Subtest3	1313	1712.6	20.53	21.3±1
	1413	1732.6	20.50	21.3±1
	1512	1752.4	20.53	21.3±1
HSUPA Subtest4	1313	1712.6	20.56	21.3±1
	1413	1732.6	20.39	21.3±1
	1512	1752.4	20.36	21.3±1
HSUPA Subtest5	1313	1712.6	20.35	21.3±1
	1413	1732.6	20.59	21.3±1
	1512	1752.4	20.54	21.3±1

ERP & EIRP

GSM Voice

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	21.14	V	6.8	0.53	27.41	38.45
824.2	20.01	H	6.8	0.53	26.28	38.45
836.6	21.08	V	6.8	0.53	27.35	38.45
836.6	19.89	H	6.8	0.53	26.16	38.45
848.8	20.94	V	6.9	0.53	27.31	38.45
848.8	19.85	H	6.9	0.53	26.22	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	21.22	V	7.88	0.85	28.25	33
1850.2	20.1	H	7.88	0.85	27.13	33
1880	21.61	V	7.88	0.85	28.64	33
1880	20.44	H	7.88	0.85	27.47	33
1909.8	21.44	V	7.86	0.85	28.45	33
1909.8	20.35	H	7.86	0.85	27.36	33

GPRS:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	21.08	V	6.8	0.53	27.35	38.45
824.2	19.87	H	6.8	0.53	26.14	38.45
836.6	21.05	V	6.8	0.53	27.32	38.45
836.6	19.92	H	6.8	0.53	26.19	38.45
848.8	20.9	V	6.9	0.53	27.27	38.45
848.8	19.68	H	6.9	0.53	26.05	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	21.15	V	7.88	0.85	28.18	33
1850.2	20	H	7.88	0.85	27.03	33
1880	21.52	V	7.88	0.85	28.55	33
1880	20.36	H	7.88	0.85	27.39	33
1909.8	21.34	V	7.86	0.85	28.35	33
1909.8	20.26	H	7.86	0.85	27.27	33

EGPRS (MCS5):

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
824.2	16.43	V	6.8	0.53	22.70	38.45
824.2	15.25	H	6.8	0.53	21.52	38.45
836.6	16.29	V	6.8	0.53	22.56	38.45
836.6	15.11	H	6.8	0.53	21.38	38.45
848.8	16.07	V	6.9	0.53	22.44	38.45
848.8	14.84	H	6.9	0.53	21.21	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1850.2	17.62	V	7.88	0.85	24.65	33
1850.2	16.28	H	7.88	0.85	23.31	33
1880	17.2	V	7.88	0.85	24.23	33
1880	16.03	H	7.88	0.85	23.06	33
1909.8	17.2	V	7.86	0.85	24.21	33
1909.8	16.09	H	7.86	0.85	23.10	33

RMC

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	11.2	V	6.8	0.53	17.47	38.45
826.4	9.98	H	6.8	0.53	16.25	38.45
835	11.18	V	6.8	0.53	17.45	38.45
835	10.05	H	6.8	0.53	16.32	38.45
846.6	11.02	V	6.9	0.53	17.39	38.45
846.6	9.81	H	6.9	0.53	16.18	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	13.3	V	7.88	0.85	20.33	33
1852.4	12.13	H	7.88	0.85	19.16	33
1880	13.83	V	7.88	0.85	20.86	33
1880	12.71	H	7.88	0.85	19.74	33
1907.6	13.66	V	7.86	0.85	20.67	33
1907.6	12.54	H	7.86	0.85	19.55	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	12.31	V	7.76	0.82	19.25	30
1712.4	11.17	H	7.76	0.82	18.11	30
1740	11.91	V	7.76	0.82	18.85	30
1740	10.48	H	7.76	0.82	17.42	30
1752.6	11.57	V	7.74	0.82	18.49	30
1752.6	10.34	H	7.74	0.82	17.26	30

HSDPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.1	V	6.8	0.53	16.37	38.45
826.4	8.95	H	6.8	0.53	15.22	38.45
835	10.11	V	6.8	0.53	16.38	38.45
835	8.9	H	6.8	0.53	15.17	38.45
846.6	10.03	V	6.9	0.53	16.40	38.45
846.6	8.83	H	6.9	0.53	15.20	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	12.37	V	7.88	0.85	19.40	33
1852.4	10.99	H	7.88	0.85	18.02	33
1880	12.61	V	7.88	0.85	19.64	33
1880	11.42	H	7.88	0.85	18.45	33
1907.6	12.45	V	7.86	0.85	19.46	33
1907.6	11.38	H	7.86	0.85	18.39	33

EIRP for UMTS-FDD Band IV (Part 27H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	11.45	V	7.76	0.82	18.39	30
1712.4	10.28	H	7.76	0.82	17.22	30
1740	11.42	V	7.76	0.82	18.36	30
1740	10.25	H	7.76	0.82	17.19	30
1752.6	11.49	V	7.74	0.82	18.41	30
1752.6	10.43	H	7.74	0.82	17.35	30

HSUPA

ERP for UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
826.4	10.11	V	6.8	0.53	16.38	38.45
826.4	8.78	H	6.8	0.53	15.05	38.45
835	10.17	V	6.8	0.53	16.44	38.45
835	9.09	H	6.8	0.53	15.36	38.45
846.6	10.02	V	6.9	0.53	16.39	38.45
846.6	8.87	H	6.9	0.53	15.24	38.45

EIRP for UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1852.4	12.64	V	7.88	0.85	19.67	33
1852.4	11.41	H	7.88	0.85	18.44	33
1880	12.61	V	7.88	0.85	19.64	33
1880	11.48	H	7.88	0.85	18.51	33
1907.6	12.65	V	7.86	0.85	19.66	33
1907.6	11.51	H	7.86	0.85	18.52	33

EIRP for UMTS-FDD Band IV (Part 27H)


Frequency (MHz)	Substituted level (dBm)	Antenna Polarization	Antenna Gain correction (dBi)	Cable Loss (dB)	Absolute Level (dBm)	Limit (dBm)
1712.4	11.42	V	7.76	0.82	18.36	30
1712.4	10.3	H	7.76	0.82	17.24	30
1740	11.45	V	7.76	0.82	18.39	30
1740	10.31	H	7.76	0.82	17.25	30
1752.6	11.42	V	7.74	0.82	18.34	30
1752.6	10.26	H	7.74	0.82	17.18	30

6.3 Peak-Average Ratio

Temperature	23°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	May 20, 2017
Tested By :	Vera Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§24.232(d) § 27.50(d)	a)	The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.	☒

Test Setup	 Base Station Spectrum Analyzer EUT
------------	---

Test Procedure	According with KDB 971168 v02r02 5.7.2 Alternate procedure for PAPR 5.1.2 Peak power measurements with a peak power meter The total peak output power may be measured using a broadband peak RF power meter. The power meter must have a video bandwidth that is greater than or equal to the emission bandwidth and utilize a fast-responding diode detector. 5.2.3 Average power measurement with average power meter As an alternative to the use of a spectrum/signal analyzer or EMI receiver to perform a measurement of the total in-band average output power, a wideband RF average power meter with a thermocouple detector or equivalent can be used under certain conditions If the EUT can be configured to transmit continuously (i.e., the burst duty cycle $\geq 98\%$) and at all times the EUT is transmitting at its maximum output
----------------	--

	power level, then a conventional wide-band RF power meter can be used. If the EUT cannot be configured to transmit continuously (i.e., the burst duty cycle < 98%), then there are two options for the use of an average power meter. First, a gated average power meter can be used to perform the measurement if the gating parameters can be adjusted such that the power is measured only over active transmission bursts at maximum output power levels. A conventional average power meter can also be used if the measured burst duty cycle is constant (i.e., duty cycle variations are less than ± 2 percent) by performing the measurement over the on/off burst cycles and then correcting (increasing) the measured level by a factor equal to $10\log(1/\text{duty cycle})$
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

GSM : GSM 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.33	29.45	0.88
1880	30.66	29.84	0.82
1909.8	30.75	29.65	1.10

GPRS 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	30.31	29.38	0.93
1880	30.56	29.75	0.81
1909.8	30.71	29.55	1.16

EGPRS (MSC5) 1900 PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1850.2	28.43	25.85	2.58
1880	28.51	25.92	2.59
1909.8	28.62	25.41	3.21

RMC : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.42	21.53	1.89
1880	23.51	22.06	1.45
1907.6	23.43	21.87	1.56

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1713	24.81	21.45	3.36
1733	24.83	21.05	3.78
1752	24.79	20.69	4.10

HSUPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.33	20.56	2.77
1880	23.36	20.53	2.83
1907.6	23.41	20.56	2.85

UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1713	22.61	20.56	2.05
1733	22.63	20.53	2.10
1752	22.31	20.41	1.90

HSDPA : UMTS-FDD Band II PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1852.4	23.33	20.6	2.73
1880	23.29	20.56	2.73
1907.6	23.43	20.53	2.90


UMTS-FDD Band IV PK-AV POWER (PART 24E)

Frequency (MHz)	Conducted power(dBm)		Peak-Average Ratio(PAR)
	Peak	Average	
1713	22.69	20.59	2.10
1733	22.63	20.56	2.07
1752	22.62	20.51	2.11

6.4 Occupied Bandwidth

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	May 22, 2017
Tested By :	Vera Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1049, §22.917, §22.905 §24.238 §27.53(a)	a)	99% Occupied Bandwidth(kHz)	☒
	b)	26 dB Bandwidth(kHz)	☒
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.8905	319.356
190	836.6	244.4634	319.040
251	848.8	246.9602	320.623

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.3510	321.559
661	1880.0	245.3007	318.814
810	1909.8	244.8767	318.370

GPRS:

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	245.4948	321.311
190	836.6	248.8023	319.041
251	848.8	247.2361	318.664

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	245.8212	323.060
661	1880.0	248.3357	320.613
810	1909.8	249.0726	319.471

EGPRS (MCS 5):

Cellular Band (Part 22H) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
128	824.2	246.3220	320.017
190	836.6	248.7614	318.254
251	848.8	245.6840	324.408

PCS Band (Part 24E) result

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
512	1850.2	248.1164	320.483
661	1880.0	243.6284	319.390
810	1909.8	253.7157	320.553

RMC:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.2255	4.892
4175	835.0	4.2217	4.898
4233	846.4	4.2153	4.912

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2134	4.892
9400	1880.0	4.2010	4.904
9538	1907.6	4.2176	4.906

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.2175	4.873
1413	1733	4.2049	4.896
1512	1752	4.2089	4.906

HSDPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.6	4.2082	4.903
4175	835.0	4.2190	4.902
4233	846.6	4.2240	4.911

UMTS-FDD Band II (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2161	4.906
9400	1880.0	4.2240	4.875
9538	1907.6	4.2129	4.900

UMTS-FDD Band IV (Part 27)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.2147	4.881
1413	1733	4.2067	4.909
1512	1752	4.2190	4.910

HSUPA:

UMTS-FDD Band V (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
4132	826.4	4.2311	4.905
4175	835.0	4.2301	4.907
4233	846.6	4.2178	4.885

UMTS-FDD Band II (Part 24E)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
9262	1852.4	4.2096	4.910
9400	1880.0	4.2088	4.901
9538	1907.6	4.2181	4.901

UMTS-FDD Band IV (Part 27)


Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
1313	1713	4.2224	4.912
1413	1733	4.2131	4.896
1512	1752	4.2108	4.902

Test Plots


GMS Voice:




GPRS:




GSM 850 BW - Low CH 824.2MHz




GSM 850 BW - Mid CH 836.6MHz




GSM 850 BW - High CH 848.8MHz



PCS 1900 BW - Low CH 1850.2MHz




PCS 1900 BW - Mid CH 1880MHz





PCS 1900 BW - High CH 1910MHz

EGPRS:




RMC:






Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz

HSDPA:






Band IV BW - Low CH 1713MHz





Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz


HSUPA:




Band V BW - Low CH 826.6 MHz




Band V BW - Mid CH 835.0 MHz



Band V BW - High CH 846.4 MHz




Band II BW - Low CH 1853MHz




Band II BW - Mid CH 1880MHz


Band II BW - High CH 1907MHz



Band IV BW - Low CH 1713MHz



Band IVBW - Mid CH 1733MHz




Band IV BW - High CH 1752MHz

6.5 Spurious Emissions at Antenna Terminals

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	May 22, 2017
Tested By :	Vera Zhang

Requirement(s):


Spec	Item	Requirement	Applicable
§2.1051, §22.917(a)& §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB	☒
Test Setup			
Test Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. - Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A


Test Plots

GSM Voice:

Cellular Band (Part 22H) result




PCS Band (Part24E) result




GPRS:

Cellular Band (Part 22H) result




PCS Band (Part24E) result




EGPRS (MCS 5):

Cellular Band (Part 22H) result




PCS Band (Part24E) result




RMC


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)




HSUPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)




UMTS-FDD Band IV (Part 27)




HSDPA:


UMTS-FDD Band V (Part 22H)



UMTS-FDD Band II (Part 24E)



UMTS-FDD Band IV (Part 27)




6.6 Spurious Radiated Emissions

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	May 22, 2017
Tested By :	Vera Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§2.1053, §22.917 & §24.238 § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.	☒

Test setup	
------------	--

Test Procedure	- The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable. - The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis. - Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution. Sample Calculation: EUT Field Strength = Raw Amplitude (dBμV/m) – Amplifier Gain (dB) + Antenna Factor (dB) + Cable Loss (dB) + Filter Attenuation (dB, if used)
----------------	---

Test Report	17070102-FCC-R1
Page	62 of 106

Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A
 Test Plot ☐ Yes (See below) ☒ N/A

Cellular Band (Part 22H) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1648.4	-43.12	V	7.95	0.78	-35.95	-13	-22.95
1648.4	-43.69	H	7.95	0.78	-36.52	-13	-23.52
327.5	-52.27	V	6.4	0.26	-46.13	-13	-33.13
606.1	-52.55	H	6.8	0.37	-46.12	-13	-33.12

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1673.2	-43.05	V	7.95	0.78	-35.88	-13	-22.88
1673.2	-43.61	H	7.95	0.78	-36.44	-13	-23.44
327.2	-52.18	V	6.4	0.26	-46.04	-13	-33.04
606.4	-52.22	H	6.8	0.37	-45.79	-13	-32.79

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1697.6	-42.98	V	7.95	0.78	-35.81	-13	-22.81
1697.6	-43.32	H	7.95	0.78	-36.15	-13	-23.15
327.8	-52.16	V	6.4	0.26	-46.02	-13	-33.02
606.3	-52.07	H	6.8	0.37	-45.64	-13	-32.64

Note:

1, The testing has been conformed to $10 \times 848.8 \text{ MHz} = 8,488 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

PCS Band (Part24E) result

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3700.4	-48.21	V	10.25	2.73	-40.69	-13	-27.69
3700.4	-48.78	H	10.25	2.73	-41.26	-13	-28.26
325.5	-52.86	V	6.4	0.26	-46.72	-13	-33.72
604.7	-53.34	H	6.8	0.37	-46.91	-13	-33.91

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.11	V	10.25	2.73	-40.59	-13	-27.59
3760	-48.85	H	10.25	2.73	-41.33	-13	-28.33
325.3	-53.77	V	6.4	0.26	-47.63	-13	-34.63
607.2	-53.23	H	6.8	0.37	-46.8	-13	-33.8

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3819.6	-48.06	V	10.36	2.73	-40.43	-13	-27.43
3819.6	-48.94	H	10.36	2.73	-41.31	-13	-28.31
325.4	-52.93	V	6.4	0.26	-46.79	-13	-33.79
607.8	-52.32	H	6.8	0.37	-45.89	-13	-32.89

Note:

1, The testing has been conformed to $10 \times 1909.8 \text{ MHz} = 19,098 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, GSM voice, GPRS and EGPRS mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band V (Part 22H)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1652.8	-45.93	V	7.95	0.78	-38.76	-13	-25.76
1652.8	-45.36	H	7.95	0.78	-38.19	-13	-25.19
323.3	-52.28	V	6.4	0.26	-46.14	-13	-33.14
601.2	-52.71	H	6.8	0.37	-46.28	-13	-33.28

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1670	-46.01	V	7.95	0.78	-38.84	-13	-25.84
1670	-45.18	H	7.95	0.78	-38.01	-13	-25.01
323.5	-52.1	V	6.4	0.26	-45.96	-13	-32.96
601.6	-52.45	H	6.8	0.37	-46.02	-13	-33.02

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
1693.2	-46.13	V	7.95	0.78	-38.96	-13	-25.96
1693.2	-45.15	H	7.95	0.78	-37.98	-13	-24.98
323.7	-52.21	V	6.4	0.26	-46.07	-13	-33.07
601.5	-52.58	H	6.8	0.37	-46.15	-13	-33.15

Note:

1, The testing has been conformed to $10 \times 846.6 \text{ MHz} = 8,466 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

UMTS-FDD Band II (Part 24E)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3704.8	-48.96	V	10.25	2.73	-41.44	-13	-28.44
3704.8	-49.37	H	10.25	2.73	-41.85	-13	-28.85
326.2	-53.04	V	6.4	0.26	-46.9	-13	-33.9
609.1	-52.89	H	6.8	0.37	-46.46	-13	-33.46

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3760	-48.81	V	10.25	2.73	-41.29	-13	-28.29
3760	-49.16	H	10.25	2.73	-41.64	-13	-28.64
326.5	-53.12	V	6.4	0.26	-46.98	-13	-33.98
609.8	-52.97	H	6.8	0.37	-46.54	-13	-33.54

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3815.2	-48.75	V	10.36	2.73	-41.12	-13	-28.12
3815.2	-49.04	H	10.36	2.73	-41.41	-13	-28.41
326.7	-53.01	V	6.4	0.26	-46.87	-13	-33.87
609.4	-53.37	H	6.8	0.37	-46.94	-13	-33.94

Note:

1, The testing has been conformed to $10 \times 1907.6 \text{ MHz} = 19,076 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case

UMTS-FDD Band IV (Part 27)

Low channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3424.8	-45.48	V	10.07	2.52	-37.93	-13	-24.93
3424.8	-47.96	H	10.07	2.52	-40.41	-13	-27.41
320.5	-56.73	V	6.4	0.26	-50.59	-13	-37.59
735.1	-52.04	H	7.1	0.42	-45.36	-13	-32.36

Middle channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3480	-45.71	V	10.09	2.52	-38.14	-13	-25.14
3480	-46.86	H	10.09	2.52	-39.29	-13	-26.29
320.6	-56.35	V	6.4	0.26	-50.21	-13	-37.21
735.4	-52.63	H	7.1	0.42	-45.95	-13	-32.95

High channel

Frequency (MHz)	Substituted level (dBm)	Polarity (H/V)	Antenna Gain Correction (dB)	Cable Loss (dB)	Corrected Reading (dBm)	Limit (dBm)	Margin (dB)
3505.2	-45.67	V	10.09	2.52	-38.1	-13	-25.1
3505.2	-46.59	H	10.09	2.52	-39.02	-13	-26.02
321.2	-56.82	V	6.4	0.26	-50.68	-13	-37.68
735.8	-52.25	H	7.1	0.42	-45.57	-13	-32.57

Note:

1, The testing has been conformed to $10 \times 1752.6 \text{ MHz} = 17,526 \text{ MHz}$

2, All other emissions more than 30 dB below the limit


3, RMC, HSUPA and HSDPA mode were investigated. The results above show only the worse cases.

4, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

6.7 Band Edge

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	May 22, 2017
Tested By :	Vera Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§22.917(a) §24.238(a) § 27.53(h)	a)	The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.	☒
Test setup	 Base Station Spectrum Analyzer EUT		
Procedure	- The EUT was connected to Spectrum Analyzer and Base Station via power divider. - The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

GSM Voice:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-16.24	-13
849.0175	-14.87	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9700	-15.69	-13
1910.0200	-16.89	-13

GPRS:

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-15.39	-13
849.0175	-15.78	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9950	-16.84	-13
1910.0200	-16.12	-13

EGPRS (MCS5):

Cellular Band (Part 22H) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.9975	-14.89	-13
849.0200	-15.25	-13

PCS Band (Part24E) result

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.9875	-16.91	-13
1910.0200	-16.32	-13

RCM:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-24.36	-13
849.975	-22.15	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-26.88	-13
1910.750	-26.49	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-27.46	-13
1755.025	-28.30	-13

HSUPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-18.54	-13
848.975	-21.14	-13

UMTS-FDD Band II (Part 24E)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1849.975	-25.62	-13
1910.875	-27.24	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-27.38	-13
1755.025	-28.10	-13

HSDPA:

UMTS-FDD Band V (Part 22H)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
823.975	-24.72	-13
848.975	-21.54	-13

UMTS-FDD Band II (Part 24E)


Frequency (MHz)	Emission (dBm)	Limit (dBm)
1848.975	-27.17	-13
1910.025	-27.12	-13

UMTS-FDD Band IV (Part 27)

Frequency (MHz)	Emission (dBm)	Limit (dBm)
1709.975	-27.60	-13
1755.025	-28.40	-13


GSM Voice:

Test Plots




GPRS:

Test Plots




EGPRS (MCS5):

Test Plots




RMC:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(48.92/30)=4.0+2.1=6.1 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(49.12/30)=4.0+2.1=6.1 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(48.92/30)=4.5+2.1=6.6 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(49.06/30)=4.5+2.1=6.6 dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(48.73/30)=4.5+2.1=6.6 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.0) + 10log
(49.06/30)=4.5+2.1=6.6 dB

HSUPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(49.05/30)=4.0+2.1=6.1 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(48.85/30)=4.0+2.1=6.1 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(49.10/30)=4.5+2.1=6.6 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(49.01/30)=4.5+2.1=6.6 dB



UMTS-FDD Band IV - Low Channel


Note: Offset=Cable loss (4.5) + 10log
(49.12/30)=4.5+2.1=6.6 dB



UMTS-FDD Band IV - High Channel


Note: Offset=Cable loss (4.5) + 10log
(49.02/30)=4.5+2.1=6.6 dB

HSDPA:




UMTS-FDD Band V - Low Channel

Note: Offset=Cable loss (4.0) + 10log
(49.03/30)=4.0+2.1=6.1 dB




UMTS-FDD Band V - High Channel

Note: Offset=Cable loss (4.0) + 10log
(49.11/30)=4.0+2.1=6.1 dB




UMTS-FDD Band II - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(49.06/30)=4.5+2.1=6.6 dB




UMTS-FDD Band II - High Channel

Note: Offset=Cable loss (4.5) + 10log
(49/30)=4.5+2.1=6.6 dB



UMTS-FDD Band IV - Low Channel

Note: Offset=Cable loss (4.5) + 10log
(48.81/30)=4.5+2.1=6.6 dB




UMTS-FDD Band IV - High Channel

Note: Offset=Cable loss (4.5) + 10log
(49.10/30)=4.5+2.1=6.6 dB

6.8 Frequency Stability

Temperature	25°C
Relative Humidity	53%
Atmospheric Pressure	1020mbar
Test date :	May 22, 2017
Tested By :	Vera Zhang

Requirement(s):

Spec	Item	Requirement	Applicable																																
§2.1055, §22.355 & §24.235 § 27.5(h); § 27.54	a)	According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below: Frequency Tolerance for Transmitters in the Public Mobile Services <table border="1"> <thead> <tr> <th>Frequency Range (MHz)</th><th>Base, fixed (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th><th>Mobile ≤ 3 watts (ppm)</th></tr> </thead> <tbody> <tr> <td>25 to 50</td><td>20.0</td><td>20.0</td><td>50.0</td></tr> <tr> <td>50 to 450</td><td>5.0</td><td>5.0</td><td>50.0</td></tr> <tr> <td>450 to 512</td><td>2.5</td><td>5.0</td><td>50.0</td></tr> <tr> <td>821 to 896</td><td>1.5</td><td>2.5</td><td>2.5</td></tr> <tr> <td>928 to 960</td><td>5.0</td><td>N/A</td><td>N/A</td></tr> <tr> <td>929 to 960</td><td>1.5</td><td>N/A</td><td>N/A</td></tr> <tr> <td>2110 to 2220</td><td>10.0</td><td>N/A</td><td>N/A</td></tr> </tbody> </table> According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized frequency block.	Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)	25 to 50	20.0	20.0	50.0	50 to 450	5.0	5.0	50.0	450 to 512	2.5	5.0	50.0	821 to 896	1.5	2.5	2.5	928 to 960	5.0	N/A	N/A	929 to 960	1.5	N/A	N/A	2110 to 2220	10.0	N/A	N/A	
Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)																																
25 to 50	20.0	20.0	50.0																																
50 to 450	5.0	5.0	50.0																																
450 to 512	2.5	5.0	50.0																																
821 to 896	1.5	2.5	2.5																																
928 to 960	5.0	N/A	N/A																																
929 to 960	1.5	N/A	N/A																																
2110 to 2220	10.0	N/A	N/A																																
Test setup	 The diagram shows a Base Station (represented by a green rectangle with a smaller green rectangle inside) connected by a line to a Thermal Chamber (represented by a blue rectangle inside a dashed-line box). Both components have a small circle representing an antenna or connector.																																		

Procedure	A communication link was established between EUT and base station. The frequency error was monitored and measured by base station under variation of ambient temperature and variation of primary supply voltage. Limit: The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

GSM Voice:

Cellular Band (Part 22H) result

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	17	0.0203	2.5
0		15	0.0179	2.5
10		14	0.0167	2.5
20		16	0.0191	2.5
30		20	0.0239	2.5
40		18	0.0215	2.5
50		20	0.0239	2.5
55		13	0.0155	2.5
25	4.2	19	0.0227	2.5
	3.6	17	0.0203	2.5

PCS Band (Part 24E) result

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	14	0.0074	2.5
0		19	0.0101	2.5
10		16	0.0085	2.5
20		18	0.0096	2.5
30		17	0.0090	2.5
40		13	0.0069	2.5
50		15	0.0080	2.5
55		17	0.0090	2.5
25	4.2	15	0.0080	2.5
	3.6	17	0.0090	2.5

RMC:

UMTS-FDD Band V (Part 22H)

Middle Channel, $f_0 = 835$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	14	0.0168	2.5
0		19	0.0228	2.5
10		18	0.0216	2.5
20		15	0.0180	2.5
30		17	0.0204	2.5
40		20	0.0240	2.5
50		16	0.0192	2.5
55		20	0.0240	2.5
25	4.2	19	0.0228	2.5
	3.6	14	0.0168	2.5

UMTS-FDD Band II (Part 24E)

Middle Channel, $f_0 = 1880$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	14	0.0074	2.5
0		19	0.0101	2.5
10		17	0.0090	2.5
20		18	0.0096	2.5
30		16	0.0085	2.5
40		15	0.0080	2.5
50		13	0.0069	2.5
55		14	0.0074	2.5
25	4.2	20	0.0106	2.5
	3.6	17	0.0090	2.5

UMTS-FDD Band IV (Part 27)

Middle Channel, $f_0 = 1733$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-10	3.8	14	0.0168	2.5
0		16	0.0192	2.5
10		18	0.0216	2.5
20		17	0.0204	2.5
30		13	0.0156	2.5
40		20	0.0240	2.5
50		19	0.0228	2.5
55		15	0.0180	2.5
25	4.2	17	0.0204	2.5
	3.6	13	0.0156	2.5

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
RF Conducted Test					
Agilent ESA-E SERIES SPECTRUM ANALYZER	E4407B	MY45108319	09/15/2016	09/14/2017	☒
Power Splitter	1#	1#	08/31/2016	08/30/2017	☒
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	☒
Temperature/Humidity Chamber	UHL-270	001	10/08/2016	10/07/2017	☒
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	☒
RF Power Sensor	Dare RPR3006C/P/W	AY554013	09/16/2016	09/15/2017	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☒
Bilog Antenna (30MHz~2GHz)	JB1	A112017	09/20/2016	09/19/2017	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71259	09/23/2016	09/22/2017	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☒
SYNTHESIZED SIGNAL GENERATOR	8665B	3744A01293	09/16/2016	09/15/2017	☒
Power Amplifier	SMC150D	R1553-0313	03/08/2017	03/07/2018	☒
Power Amplifier	S41-25D	R1553-0314	05/27/2016	05/26/2017	☒
Tunable Notch Filter	3NF-800/1000-S	AA4	08/31/2016	08/30/2017	☒


Test Report	17070102-FCC-R1
Page	88 of 106

Tunable Notch Filter	3NF- 1000/2000-S	AM 4	08/31/2016	08/30/2017	☒
----------------------	---------------------	------	------------	------------	-------------------------------------

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View



Adapter - Label View



EUT - Front View



EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View



EUT - Right View



Annex B.ii. Photograph: EUT Internal Photo


Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Mainboard with Shielding – Rear View




Mainboard without Shielding – Rear View



Smallboard – Front View



Smallboard – Rear View



LCD – Front View



LCD – Rear View



GSM/PCS/UMTS-FDD Antenna View




WIFI/BT/BLE - Antenna View




LTE - Antenna View



Annex B.iii. Photograph: Test Setup Photo



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK

Block Configuration Diagram for Radiated Emissions



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Verykool USA Inc	Adapter	TPA-46B050100UU	S20170127

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	S20170127

Annex C.ii. EUT OPERATING CONKITIONS

N/A

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Annex E. DECLARATION OF SIMILARITY

N/A