FCC ID: WAJ-9602MWD Sheet 1 of 89 Sheets ETC Report No.: 08-04-MAS-052-01



CONFORMANCE TEST REPORT FOR

FCC Part 15, subpart D

Report No.: 08-04-MAS-052-01

Client: Telematrix, Inc.

Product: US DECT PHONE - Handset (PP)

Model: 9602MWD (Multiple Model List please see page 5.)

FCC ID: WAJ-9602MWD

Manufacturer/supplier: JiangSu ZhongXun Digital Electronic CO., LTD.

Date test item received: 2008/04/08

Date test campaign completed: 2008/05/26

Date of issue: 2008/05/27

The test result only corresponds to the tested sample. It is not permitted to copy this report, in part or in full, without the permission of the test laboratory.

Total number of pages of this test report: 89 pages

Total number of pages of photos: External photos 1 pages

Internal photos 3 pages Setup photos 2 pages

Test Engineer	Checked By	Approved By	
Erie Lin	David You	Joe Hieh	
Eric Lin	David You	Joe Hsieh	

Table of Contents Page

1 GENARAL INFORMATION	4
1.1 Testing Laboratory	4
2 TEST INFORMATION	
2.1 Description of Tested Device(s)	5
3 TEST REPORT SUMMARY	
3.1 Test Summary	
4 TEST SETUP	8
4.1 Frequency and Timing Measurements 4.2 Conducted Emission Tests 4.3 Radiated Emission Tests 4.4 Power line Conducted Tests 4.5 Monitoring Tests	8 9 9
5 TEST EQUIPMENT LIST	11
6 TEST RESULT	12
6.1 Coordination with fixed microwave	13
6.4 Power line Conducted Emissions	17
6.6 Digital Modulation Techniques	18
6.8 Power Spectral Density	
6.10 Automatic discontinuation of transmission	
6.12 Emission Bandwidth B	28
6.13 Monitoring time	33
6.15 Maximum transmit period	34

 6.16 System Acknowledgement
 36

 6.17 Least Interfered Channel, LIC
 41

 6.18 Random waiting
 51

 6.19 Monitoring bandwidth and reaction time
 52

 6.20 Monitoring antenna
 59

 6.21 Monitoring threshold relaxation
 60

 6.22 Duplex system LBT
 61

 6.23 Co-located device LBT
 62

 6.24 Fair Access
 63

 6.25 Emissions inside and outside the subband
 64

 6.26 Frame period and jitter
 86

 6.27 Carrier frequency stability
 88

FCC ID: WAJ-9602MWD Sheet 4 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

1 GENARAL INFORMATION

1.1 Testing Laboratory

Name: Electronic Testing Center, Taiwan

Address: No. 8, Lane 29, Wenming Rd., Leshan Tsuen, Guishan Shiang,

Taoyuan Country, 33383, Taiwan, R.O.C.

Telephone: 886-3-3280026 Fax: 886-3-3276188

NVLAP lab registration #: 200133-0 IC OATS registration #: IC 2949-1

E-Mail: hsieh@etc.org.tw

1.2 Client Information

Name: Telematrix, Inc.
Address: Telematrix, Inc.
Telephone: +1.719.638.8821
Contact person: Sun Bingnan

1.3 Manufacturer

Name: JiangSu ZhongXun Digital Electronic CO., LTD.

Address: Dingshu YiXing Jiangsu

FCC ID: WAJ-9602MWD Sheet 5 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

2 TEST INFORMATION

2.1 Description of Tested Device(s)

The tested equipment is a DECT base station that complies with ETSI EN 300175. The frequencies have been reprogrammed to comply with the FCC and IC requirements to an Isochronous UPCS device after FCC Part 15D and Industry Canada RSS-213 Issue 2.

The EUT is a responding device as described in ANSI C63.17 and is designed to operate together with a DECT handset, which is then the initiating device.

Frequency Channel	Frequency	Test Frequency
CH4	1921.536 MHz	FL
СНЗ	1923.264 MHz	-
CH2	1924.992 MHz	Fм
CH1	1926.720 MHz	-
CH0	1928.448 MHz	Fн

Model Different Description:

Multiple Model List:

9602MWD5, 9600MWD, 9600MWD5

There is no different for the series except for the model name change.

2.2 Test Environment

Normal test condition

Temperature:	20 - 25 °C
Relative humidty:	55 - 75%

Extreme test condition (declared by manufacturer)

Please see the manufacturer declaration form.

3 TEST REPORT SUMMARY

3.1 Test Summary

Requirement	FCC Paragraph #	Required	Customer Declaration	Test Pass
Coordination with fixed microwave	15.307(b)	\boxtimes	\boxtimes	
Cross Reference	15.309(b)			
Labeling requirements	15.311,15.19(a)(3)	\boxtimes	\boxtimes	
Power line Conducted Emission	15.315,15.207			
Antenna Requirement	15.317, 15.203	\boxtimes	\boxtimes	
Digital Modulation Techniques	15.319(b)	\boxtimes	\boxtimes	
Peak transmit Power	15.319(c)	\boxtimes		
Power Spectral Density	15.319(d)	\boxtimes		
Antenna gain	15.319(e)		\boxtimes	
Automatic discontinuation of transmission	15.319(f)	\boxtimes	\boxtimes	
Safety exposure levels	15.319(i)	\boxtimes		
Emission Bandwidth	15.323(a)	\boxtimes		
Monitoring time	15.323(c)(1)	\boxtimes		
Monitoring threshold	15.323(c)(2)		\boxtimes	
Maximum transmit period	15.323(c)(3)	\boxtimes		
System acknowledgement	15.323(c)(4)			
Least Interfered Channel, LIC	15.323(c)(5)			
Random waiting	15.323(c)(6)		\boxtimes	
Monitoring bandwidth and reaction time	15.323(c)(7)	\boxtimes		\boxtimes
Monitoring antenna	15.323(c)(8)	\boxtimes	\boxtimes	
Monitoring threshold relaxation	15.323(c)(9)	\boxtimes		
Duplex system LBT	15.323(c)(10)	\boxtimes	\boxtimes	
Co-located device LBT	15.323(c)(11)	\boxtimes		
Fair access	15.323(c)(12)	\boxtimes		
Emissions inside and outside the subband	15.323(d)	\boxtimes		\boxtimes
Frame period and jitter	15.323(e)	\boxtimes		\boxtimes
Carrier frequency stability	15.323(f)			

FCC ID: WAJ-9602MWD Sheet 7 of 89 Sheets
ETC Report No.: 08-04-MAS-052-01

3.2 Other Comments

All measurements are traceable to national standards.

The tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC CFR47 Part 15, Paragraph 15.323 for Isochronous UPCS Devices and Industry Canada RSS-213 Issue 2.

The conducted test methods have been in accordance with ANSI C63.17-1998 and ANSI C63.17-2006 Draft where applicable. Radiated tests were conducted is accordance with ANSI C63.4-2003.

Where a test method specified in this Standard cannot be followed, a test method given in ANSI C63.17 may be used by quoting the test section number. An equivalent alternative method may also be used provided that it is fully described in the test report.

Where a test is not practicable (e.g. the test for an access protocol of Section 4.3.4), the certification applicant may submit to Industry Canada the manufacturer's declaration that the access protocol has nevertheless been met in the design and prototype tests. Full justification as to why testing is not practicable should be given for Industry Canada's consideration.

A mid-band carrier frequency should normally be used for tests.

When an antenna conducted measurement is used to determine the RF output power of the device, the effective gain of the antenna intended for the device must be stated, based on measurement or on data from the antenna manufacturer. Any antenna gain in excess of 3 dBi (3 dB above isotropic gain) shall be added to the measured RF output power before using the power limits specified in this standard.

Accessories and peripheral equipment that are normally required to be connected to the device in actual use, shall be so connected with representative cable lengths for the tests. Only one test using representative peripherals and accessories is required. The emission tests shall be performed with the device and accessories configured in a manner which tends to produce the maximum level of emissions within the range of variations that can be expected under normal operating conditions.

4 TEST SETUP


4.1 Frequency and Timing Measurements



Test Set-up 1

This setup is used for measuring Frame repetition stability, Jitter, Carrier frequency stability at normal and extreme temperatures.

4.2 Conducted Emission Tests




Test Set-up 2

This setup is used for all conducted emission tests.

FCC ID: WAJ-9602MWD Sheet 9 of 89 Sheets ETC Report No.: 08-04-MAS-052-01


4.3 Radiated Emission Tests



Test Set-Up 3


This test setup is used for all radiated emissions tests. For frequencies below 30 MHz the measuring distance is 10 m, for all other frequencies it is 3 m. Emissions above 1 GHz were measured with the Spectrum Analyzer, Horn Antenna and the preamplifier after the antenna.

4.4 Power line Conducted Tests



Test Set-Up 4

4.5 Monitoring Tests



Test Set-Up 5

This test setup is used for all Monitoring and Time and Spectrum Access Procedure tests.

Companion Device	А _{СD} (dВ)	EUT	А еит (dB)
Base	50	Handset	0
Handset	30	Base	0

FCC ID: WAJ-9602MWD Sheet 11 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

5 TEST EQUIPMENT LIST

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment and ancillaries are identified (numbered) by the Test Laboratory.

Equipment	Manufacturer	Model No.	Next Calibration
			Date
			(MM/DD/YY)
EMI Test Receiver	Rohde & Schwarz	ESU	07/23/2008
BiLog Antenna	Schaffner	CBL 6112B	06/19/2008
Horn Antenna	EMCO	3115	07/22/2008
Horn Antenna	EMCO	3116	07/22/2008
Preamplifier	Hewlett-Packard	8449B	09/18/2008
Spectrum Analyzer	Hewlett-Packard	8564EC	09/22/2008
Spectrum Analyzer	Rohde & Schwarz	Rohde & Schwarz FSU46	
LISN	EMCO	3825	03/30/2009
Test Receiver	Rohde & Schwarz	ESCS30	05/18/2008
Radio Communication Tester	Rohde & Schwarz	CTS60	03/04/2009
Vector Signal Generator	National Instruments	PXI-5670	03/07/2009
Spectrum Analyzer	National Instruments	PXI-5660	03/06/2009
Scope 1	National Instruments	PXI-5114	03/05/2009
Scope 2	National Instruments	PXI-5114	03/05/2009

FCC ID: WAJ-9602MWD Sheet 12 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6 TEST RESULT

6.1 Coordination with fixed microwave

6.1.1 Standard Applicable: FCC 15.307(b)

Each application for certification of equipment operating under the provisions of this Subpart must be accompanied by an affidavit from UTAM, Inc. certifying that the applicant is a participating member of UTAM, Inc. In the event a grantee fails to fulfill the obligations attendant to participation in UTAM, Inc., the Commission may invoke administrative sanctions as necessary to preclude continued marketing and installation of devices covered by the grant of certification, including but not limited to revoking certification.

Result

The affidavit from UTAM, Inc. is in	ncluded in the documentation	supplied by the applicant:
⊠Yes		
□No		

FCC ID: WAJ-9602MWD Sheet 13 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.2 Cross Reference

6.2.1 Standard Applicable:

15.309(b)

The requirements of Subpart D apply only to the radio transmitter contained in the PCS device. Other aspects of the operation of a PCS device may be subject to requirements contained else where in this Chapter. In particular, a PCS device that includes digital circuitry not direct associated with the radio transmitter also is subject to the requirements for unintentional radiators in Subpart B.

15.109(a)

For unintentional device, according to **FCC §15.109(a)**, the field strength of radiated emissions from unintentional except for class A digital device radiators at a distance of 3 meters shall not exceed the following values:

Frequency Distance MHz Meters		Radiated μV/m	Radiated dB μV/m	
30 - 88	3	100	40.0	
88 - 216	3	150	43.5	
216 - 960	3	200	46.0	
above 960	3	500	54.0	

6.2.2 Test Results:

This requirement is not applicable because test sample do not include digital circuitry which is not direct associated with the radio transmitter	
For test results according to FCC part 15 subpart B, see the EMC report as attached	
For test results according to FCC part 15 subpart B, see the measurement data as follow	
This requirement is covered by results of power line conducted emission test according to FCC 15.315	\boxtimes

Note: For radiated test, if EUT is a handset, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission as a worse case.

Sheet 14 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Radiated Emission Test

EUT: 1.9GHz DECT Phone	Model: 9602MWD	Status : Worse case of all operation modes	
Condition : Horizontal	Date : 2008/5/12	Temp. : 22°ℂ	Humi. : 60%

	Freq (MHz)	QP Level (dBuV)	Factor (dB/m)	QP Result (dBuV/m)	QP Limit (dBuV/m)	QP Margin (dB)
1	35.832	9.4	17.0	26.4	40.0	-13.6
2	113.587	5.5	14.2	19.7	43.5	-23.8
3	154.409	9.6	12.6	22.2	43.5	-21.3
4	331.303	5.3	18.0	23.3	46.0	-22.7
5	436.273	5.9	20.8	26.7	46.0	-19.3
6	965.010	11.6	28.2	39.8	54.0	-14.2

EUT: 1.9GHz DECT Phone	Model: 9602MWD	Status : Worse case of all of	operation modes
Condition : Vertical	Date : 2008/5/12	Temp. : 22℃	Humi. : 60%

	Freq (MHz)	QP Level (dBuV)	Factor (dB/m)	QP Result (dBuV/m)	QP Limit (dBuV/m)	QP Margin (dB)
1	35.832	12.5	17.0	29.5	40.0	-10.5
2	162.184	16.3	12.0	28.3	43.5	-15.2
3	331.303	9.2	18.0	27.2	46.0	-18.8
4	492.645	13.2	21.8	35.0	46.0	-11.0
5	591.784	11.0	23.4	34.4	46.0	-11.6
6	963.066	11.5	28.2	39.7	54.0	-14.3

Note:

- 1. Place of Measurement: Measuring site of the ETC.
- 2. If the data table appeared symbol of "***" means the value was too low to be measured.
- 3. The symbol of "#" means the noise was too low, so record the peak value.
- 4. The estimated measurement uncertainty of the result measurement is
 - ±4.6dB (30MHz≤f<300MHz).
 - ±4.4dB (300MHz≤f<1000MHz).
 - ±4.1dB (1GHz≦f<18GHz).
 - ± 4.4 dB (18GHz \leq f \leq 40GHz).

FCC ID: WAJ-9602MWD Sheet 15 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.3 Labeling Requirements

6.3.1 Standard Applicable: FCC 15.19, RSS-213 3

The FCC Identifier shall be displayed on the label, and the device(s) shall bear the following statement in a conspicuous location on the device or in the user manual if the device is too small:

Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label itself shall be of a permanent type, not a paper label, and shall last the lifetime of the equipment.

6.3.2 Result

See separate documents showing the label design and the placement of the label on the EUT.

Sheet 16 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.4 Power line Conducted Emissions

6.4.1 Standard Applicable:

FCC 15.315

An unlicensed PCS device that is designed to be connected to the public utility (AC) power line must meet the limits specified in Section 15.207.

FCC 15.207(a)

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency MHz	Quasi Peak dB μ V	Average dB μ V
0.15 - 0.5	66-56*	56-46*
0.5 - 5.0	56	46
5.0 - 30.0	60	50

^{*}Decreases with the logarithm of the frequency.

RSS-213 6.3

The limits of AC power line conducted emissions are given is RSS-Gen, Section 7.

6.4.2 Measurement Procedure

ANSI C63.4-2003 using 50 μ H/50 ohms LISN.

6.4.3 Test Results: Not applied

FCC ID: WAJ-9602MWD Sheet 17 of 89 Sheets
ETC Report No.: 08-04-MAS-052-01

6.5 Antenna Requirement

6.5.1 Standard Applicable: FCC 15.317, 15.203. RSS-213 4.1(e)
Does the EUT have detachable antenna? ☐Yes
⊠No
If detachable, is the antenna connector non-standard? ☐Yes ☐No
The tested equipment has only integral antennas. The conducted tests were performed on a sample with a temporary antenna connector.

6.6 Digital Modulation Techniques

6.6.1 Standard Applicable: FCC 15.319(b), RSS-213 6.1

All transmissions must use only digital modulation techniques.

6.6.2 Result: Meets the requirement

Please see the declaration provided by applicant.

FCC ID: WAJ-9602MWD Sheet 18 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

LTO Report No.: 00-04-MAG-032-0

6.7 Peak Transmit Power

6.7.1 Standard Applicable: FCC 15.319(c) & (e) same as RSS-213 6.5

- (c) Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in hertz. Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.
- (e) The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

RSS-213 4.3.1 Peak Transmit Power

The transmitter shall be modulated with digital sequence(s) representative of those encountered in a real system operation. The peak transmit power shall be measured and recorded.

6.7.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 6.1.2

6.7.3 Test Results: Complies

Measurement Data:

Channel	Frequency (MHz)	Maximum Peak Output Power (dBm)	Limit (dBm)
FL	1921.536	19.59	21.02
Fм	1924.992	19.57	21.02
Fн	1928.448	19.56	21.02


Limit:

Conducted: 5 Log (B) - 10 = 21.02 dBm


Where B is the emission bandwidth in Hz measured at 26 dBm.

FCC ID: WAJ-9602MWD Sheet 19 of 89 Sheets ETC Report No.: 08-04-MAS-052-01


Maximum Peak Output Power: CH FL



Maximum Peak Output Power: CH FM



Maximum Peak Output Power: CH Fн



Sheet 22 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.8 Power Spectral Density

6.8.1 Standard Applicable: FCC 15.319(d)

Power spectral density shall not exceed 3 milliwatts in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

RSS-213 4.3.2.1 Peak Power Spectral Density Test

This test is to measure the occupied bandwidth and the maximum power spectral density. With the transmitter modulated as in Section 4.3.1, obtain spectrum plots. Record the maximum spectral level of the modulated signal as the reference spectral level (dBs). Measure and record the 99% bandwidth. Measure and record the power spectral density per 3 kHz.

RSS-213 6.6 Power Spectral Density

The peak-hold power spectral density shall not exceed 12 milliwatts per any 3 kHz bandwidth. As an alternative to the peak-hold power spectral density, the time-averaged power spectral density may be measured and it shall not exceed 3 milliwatts per any 3 kHz bandwidth.

6.8.2 Measurement procedure


Measurement method according to ANSI C63.17 2006 paragraph 6.1.5

6.8.3 Test Results: Complies


Measurement Data:

Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limit (dBm)
FL	1921.536	-0.89	4.77
FM	1924.992	-1.00	4.77
FH	1928.448	-0.68	4.77


Power Spectral Density: CH FL



Power Spectral Density: CH FM



Power Spectral Density: CH FH



FCC ID: WAJ-9602MWD Sheet 26 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.9 Antenna Gain

6.9.1 Standard Applicable: FCC 15.323(e)

The peak transmit power shall be reduced by the amount in decibels that the maximum directional gain of the antenna exceeds 3 dBi.

6.9.2 Results: Meets the requirement

The antenna gain value provided by manufacturer is 2 dBi.

6.10 Automatic discontinuation of transmission

6.10.1 Standard Applicable: FCC 15.319(f) same as 4.3.4 (a)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

6.10.2 Procedure

Please see the declaration provided by applicant.

6.10.3 Results: Meets the requirement

FCC ID: WAJ-9602MWD Sheet 27 of 89 Sheets

ETC Report No.: 08-04-MAS-052-01

6.11 Safety exposure levels

6.11.1 Standard Applicable: FCC 15.319(i)

UPCS devices are subject to the radio frequency radiation exposure requirements specified in FCC parts 1.1307 (b), 2.1091 and 2.1093, as appropriate. All equipment shall be considered to operate in a "general population / uncontrolled environment. For portable devices tests according to IEEE 1528 are requested, if applicable.

6.11.2 Measurement procedure

Consideration of radio frequency radiation exposure for EUT is done as

SAR test according IEEE1528 (for PP)	\square
MPE calculation as below (for FP, Repeater)	

SAR test results: See SAR test report.

MPE calculation: not applicable

The EUT is considered as a mobile device according to OET Bulletin 65, Edition -97-01. Therefore distance to human body of min. 20 cm is determined.

The limit of Power density for General Population / Umcontrolled Exposure is 1.0 mW/cm². Formula:

 $S = EIRP / 4\pi R^2$

Calculation:

EIRP	Radiated Power (dBm)	n.a.
EIRP	Radiated Power (mW)	n.a.
R	Distance (cm)	n.a.
S	Power Density (mW/cm²)	n.a.

6.11.3 Results: Complies

FCC ID: WAJ-9602MWD Sheet 28 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.12 Emission Bandwidth B

6.12.1 Standard Applicable: FCC 15.323(a)

The 26 dB Bandwidth B shall be larger than 50 kHz and less than 2.5 MHz.

6.12.2 Measurement procedure


Measurement method according to ANSI C63.17 2006 paragraph 6.1.3

6.12.2 Results: Complies


Measurement Data:

Channel	Frequency (MHz)	26 dB Bandwidth (MHz)
FL	1921.536	1.60
FM	1924.992	1.63
FH	1928.448	1.62


26 dB Bandwidth B: CH FL



26 dB Bandwidth B: CH FM



26 dB Bandwidth B: CH FH



Sheet 32 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.13 Monitoring time

6.13.1 Standard Applicable: FCC 15.323(c)(1) same as RSS-213 4.3.4 (b)(1)

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 millisecond or shorter frame period or at least 20 milliseconds for systems designed to use a 20 millisecond frame period.

6.13.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 7.3.4

6.13.2 Results: Complies

EUT monitors the combined time and spectrum window prior to initiation of transmission.

Measurement Data:

This requirement is covered by results of Least Interfered Channel (LIC) test according to FCC 15.323(c) (5)	This requirement is covered by results of Least Interfered Channel (LIC) test according to FCC 15.323(c) (5)	
--	--	--

FCC ID: WAJ-9602MWD Sheet 33 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.14 Monitoring threshold

6.14.1 Standard Applicable: FCC 15.323(c)(2) same as RSS-213 4.3.4 (b)(2)

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth of the device.

6.14.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 7.3.1

6.14.3 Result: Not apply

Note: For EUT which support LIC there is no need to measure lower threshold because it is automatically met by LIC Procedure.

FCC ID: WAJ-9602MWD Sheet 34 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.15 Maximum transmit period

6.15.1 Standard Applicable: FCC 15.323(C) (3) same as RSS-213 4.3.4 (b)(3)

Occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

6.15.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 8.2.2

6.15.3 Test Results: Complies

Measurement Data:

	Observation	Limit
Maximum transmission time	7 hours 44 minutes	8 hours

FCC ID: WAJ-9602MWD Sheet 35 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Start to transmission time and Cease of transmission time:



FCC ID: WAJ-9602MWD Sheet 36 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.16 System Acknowledgement

6.16.1 Standard Applicable: FCC 15.323 (c)(4) same as RSS-213 4.3.4 (b)(4)

Once access to specific combined time and spectrum windows is obtained an acknowledgement from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgements must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgement, at which time the access criteria must be repeated.

6.16.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 8

6.16.3 Results: Complies

Measurement Data

Unacknowledged transmission:

Limit:

Requirement	Value
Change of access criteria for control information	30 s
Pause length	> 10 ms
Change of access channel	mandatory

Result:

Requirement	Time	Verdict
Change of access criteria for control information		n.a.
Pause length		n.a.
Change of access channel		n.a.

FCC ID: WAJ-9602MWD Sheet 37 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Connection acknowledgement:

Limit:


Requirement	Value
Connection acknowledgement	1 s
Termination of transmission	30 s

Result:

Requirement	Time observed	Verdict
Connection acknowledgement	5 ms	Pass
Termination of transmission	5.08 s	Pass


FCC ID: WAJ-9602MWD Sheet 38 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: Connection acknowledgement




FCC ID: WAJ-9602MWD Sheet 39 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: Connection acknowledgement



FCC ID: WAJ-9602MWD Sheet 40 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: Termination of transmission



Sheet 41 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.17 Least Interfered Channel, LIC

6.17.1 Standard Applicable: FCC 15.323(c) (5) same as RSS-213 4.3.4 (b)(5)

If access to spectrum is not available as determined by the above, and a minimum of 40 duplex system access channels are defined for the system, the time and spectrum windows with a power level below a monitoring threshold of 50 dB above the thermal noise power determined for the occupied bandwidth may be accessed.

A device utilizing the provisions of this paragraph (5) must have monitored all access channels defined for its system within the last 10 seconds and must verify, within the 20 milliseconds (40 milliseconds for devices designed to use a 20 millisecond frame period) immediately preceding actual channel access, that the detected power of the selected time and spectrum windows is no higher than the previously detected value.

The power measurement resolution bandwidth for this comparison must be accurate to within 6 dB. No device or group of cooperating devices located within 1 metre of each other shall during any frame period occupy more than 6 MHz of aggregate bandwidth, or alternatively, more than one third of the time and spectrum windows defined by the system.

6.17.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 7.3.2, 7.3.3, 7.3.4

6.17.3 Results: Complies

Measurement Data

Calculation of monitoring threshold limits:

Lower threshold: $T_L = 15 \log_{10}B - 184 + 30 - P (dBm)$ Upper threshold: $T_U = 15 \log_{10}B - 184 + 50 - P (dBm)$

B = emission bandwidth (Hz)
P = peak transmit power (dBm)

Calculated thresholds:

T _L : Lower threshold (dBm)	-80.5
Tu: Upper threshold (dBm)	-60.5

Limit:

Used	Emission bandwidth (MHz)	1.60
results Peak transmit power (dBm)		19.59
Limits	$T_{LR} < T_{L} + U_{M} = -80.5 + 6 = -74.5 \text{ (dBm)}$	
	Tur < Tu+Um = -60.5 + 6 = -54.5 (dBm)	

FCC ID: WAJ-9602MWD Sheet 42 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Result:


Least interfered channel	Pass
TLR: Lower threshold (dBm)	n.a.
Tur: Upper threshold (dBm)	-64.5

Note 1: The upper threshold is applicable for systems which have defined a minimum of 40 duplex system access channels.

Note 2: f1=1921.536 MHz, f2=1928.448MHz

FCC ID: WAJ-9602MWD Sheet 43 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.2, initial setup




Comment1: Trace1 (green) is the interference on all 5 carriers. The level is Tu+UM+10dB.

Comment2: Trace2 (blue) is interference on all 5 carriers. The level is Tur.

Comment3: Trace3 (Red) is the EUT begins to transmit the beacon when interference is Tur.

FCC ID: WAJ-9602MWD Sheet 44 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.2 (zoom in)




Comment1: Trace1 (green) is the interference on all 5 carriers. The level is Tu+UM+10dB.

Comment2: Trace2 (blue) is interference on all 5 carriers. The level is Tur.

Comment3: Trace3 (Red) is the EUT begins to transmit the beacon when interference level is Tur.

FCC ID: WAJ-9602MWD Sheet 45 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.3b




Comment1: Trace1 (green) shows the EUT transmissions are occurring.

Comment2: Trace2 (blue) shows the interference profile.

Comment3: The EUT always transmits on f2 (the carrier with the lower interference level) and so

FCC ID: WAJ-9602MWD Sheet 46 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.3c




Comment1: Trace1 (green) shows the EUT transmissions are occurring.

Comment2: Trace2 (blue) shows the interference profile.

Comment3: The EUT always transmits on f1 (the carrier with the lower interference level) and so

FCC ID: WAJ-9602MWD Sheet 47 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.3d




Comment1: Trace1 (green) shows the EUT transmissions are occurring.

Comment2: Trace2 (blue) shows the interference profile.

Comment3: The EUT always transmits on f2 (the carrier with the lower interference level) and so

FCC ID: WAJ-9602MWD Sheet 48 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.3e




Comment1: Trace1 (green) shows the EUT transmissions are occurring.

Comment2: Trace2 (blue) shows the interference profile.

Comment3: The EUT always transmits on f1 (the carrier with the lower interference level) and so

FCC ID: WAJ-9602MWD ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.4



Comment1: Trace1 (deep blue, top) shows interference on f1.

Comment2: Trace2 (red, 2nd from top) shows the interference on f2.

Comment3: Trace3 (green, 3rd from top) shows EUT transmissions on f1.

Comment4: Trace4 (light blue, 4th from top) shows the signal to the handset to trigger the

transmissions.


Comment5: Set interference on all system carriers except f2, at a level of Tu+UM, in-band per carrier.

Comment6: Apply interference on f2 at a level of Tu+Um, in-band, and immediately remove all interference from f1 and immediately (but not sooner than 20 ms after the interference on f2 is applied) cause the EUT to attempt transmission.

Comment7: The EUT transmits on f1 and so meets the requirement.

FCC ID: WAJ-9602MWD Sheet 50 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

Comment: 7.3.4 (Zoom in)



Comment1: Trace1 (deep blue, top) shows interference on f1.

Comment2: Trace2 (red, 2nd from top) shows the interference on f2.

Comment3: Trace3 (green, 3rd from top) shows EUT transmissions on f1.

Comment4: Trace4 (light blue, 4th from top) shows the signal to the handset to trigger the

transmissions.

The signal is not sooner than 20 ms after the interference on f2 is applied.

FCC ID: WAJ-9602MWD Sheet 51 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.18 Random waiting

6.18.1 Standard Applicable: FCC 15.323 (c)(6) same as RSS-213 4.3.4 (b)(6)

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

6.18.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 8.1.3

6.18.3 Results:

The manufacturer declares that this provision is not utilized by the EUT.

FCC ID: WAJ-9602MWD

Sheet 52 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.19 Monitoring bandwidth and reaction time

6.19.1 Standard Applicable: FCC 15.323(c)(7)

The monitoring system band width must be equal to or greater than the emission band width of the intended transmission and have a maximum reaction time less than 50 x SQRT (1.25/emission band width in MHz) microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microsecond. If a signal is detected that is 6 dB or more above the applicable threshold level, the maximum reaction time shall be 35 x SQRT (1.25/emission band width in MHz) microseconds but shall not be required to be less than 35 microseconds.

RSS-213 4.3.4 (b)(7)

The monitoring system bandwidth must be equal to or greater than the occupied bandwidth of the intended transmission. **Note:** Testing of the monitoring system bandwidth is not required if the designed bandwidth from the manufacturer is available and given in the test report.

The monitor shall have a maximum reaction time less than $50\sqrt{(1.25/\text{occupied bandwidth in MHz)}}$ microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds.

If a signal is detected that is 6 dB or more above the threshold level, the maximum reaction time shall be $35\sqrt{(1.25/\text{occupied bandwidth in MHz})}$ microseconds but shall not be required to be less than 35 microseconds.

6.19.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 7.5

6.19.3 Results: Meets the requirement

Measurement Data

Calculation of applied pulse eidth and maximum reaction time:

For emission bandwidth > 1.25MHz, the pulse width is always 35us and 50us.

Used results	Emission bandwidth B (MHz)	1.60MHz
Maximum reaction time	50√1.25/B (μs)	44.2 µs
and pulse width	35√1.25/B (μs)	30.9 µs

Result:

Pulse width (μs)	Connection
50 μs or 50√ (1.25/B)	no
35 μs or 35√(1.25/B)	no

ETC Report No.: 08-04-MAS-052-01 Comment: 50us

Sheet 53 of 89 Sheets

Sheet 54 of 89 Sheets

Sheet 55 of 89 Sheets

ETC Report No.: 08-04-MAS-052-01

Comment: 35us

Sheet 56 of 89 Sheets

ETC Report No.: 08-04-MAS-052-01

Sheet 57 of 89 Sheets

ETC Report No.: 08-04-MAS-052-01

Sheet 58 of 89 Sheets

ETC Report No.: 08-04-MAS-052-01

6.20 Monitoring antenna

6.20.1 Standard Applicable: FCC 15.323(c) (8)

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

RSS-213 4.3.4 (b)(8)

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location. Note: A monitoring antenna of the same model (and manufacturer) as the transmitting antenna is considered equivalent. An antenna not of the same model but of the same type (e.g. both are horn antennas of different manufacturers) is considered equivalent if the main beam antenna gains are within 3 dB of each other. Both antennas are to be installed to point at the same general coverage area.

6.20.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 4

6.20.3 Results: Complies

The EUT uses the same antennas for transmission and reception as for monitoring.

Sheet 60 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.21 Monitoring threshold relaxation

6.21.1 Standard Applicable: FCC 15.323(c)(9)

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

RSS-213 4.3.4 (b)(9)

Devices that have a power output lower than the maximum permitted under this standard may increase their detection threshold by 1 dB for each 1 dB that the transmitter power is below the maximum permitted.

6.21.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 4

6.21.3 Results: Complies

Measurement Data:

FCC ID: WAJ-9602MWD Sheet 61 of 89 Sheets
ETC Report No.: 08-04-MAS-052-01

6.22 Duplex system LBT

6.22.1 Standard Applicable: FCC 15.323(c) (10)

An initiating device may attempt to establish a duplex connection by monitoring both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

RSS-213 4.3.4 (b)(10)

A device initiating a communication (hereafter called an initiating device) may attempt to establish a duplex connection by monitoring both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.s

6.22.2 Measurement procedure

Measurement method according to ANSI C63.17, clause 8.3 This test is required for equipment that uses the access criteria in FCC 15.323(c)(10).

6.22.3 Test Results:

The manufacturer declares that this provision is not utilized by the EUT.

FCC ID: WAJ-9602MWD Sheet 62 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.23 Co-located device LBT

6.23.1 Standard Applicable: FCC 15.323 (c)(11) same as RSS-213 4.3.4 (b)(11)

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating device. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

6.23.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 8.4

6.23.3 Results:

The manufacturer declares that this provision is not utilized by the EUT.

FCC ID: WAJ-9602MWD Sheet 63 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.24 Fair Access

6.24.1 Standard Applicable: FCC 15.323 (c)(12) same as RSS-213 (b)(12)

The provisions of (c) (10) or (c) (11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum for other devices.

6.24.2 Results:

The manufacturer declares that EUT does not work in a mode which denies fair access to spectrum for other devices.

FCC ID: WAJ-9602MWD Sheet 64 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.25 Emissions inside and outside the subband

6.25.1 Standard Applicable: FCC 15.323(d)

Emissions inside the subband same as RSS-213 6.7.2

 $B < f \le 2B$: less than or equal to 30 dB below the maximum permitted peak power level $2B < f \le 3B$: less than or equal to 50 dB below the maximum permitted peak power level $3B < f \le UPCS$ Band Edge: less than or equal to 60 dB below the maximum permitted peak power level

Where B is the occupied bandwidth in hertz.

Emissions outside the subband same as RSS-213 6.7.1

 $f \le$ 1.25MHz outside UPCS band : \le -9.5dBm 1.25MHz $\le f \le$ 2.5MHz outside UPCS band : \le -29.5 dBm $f \ge$ 2.5MHz outside UPCS band: \le -39.5 dBm

6.25.2 Measurement procedure

Measurement method according to ANSI C63.17 2006 paragraph 6.1.6

6.25.3 Results: Complies


Measurement Data:

See plots.

Note: Photos of worst-case display follow:


FCC ID: WAJ-9602MWD

In-band Unwanted Emissions: CH FL




FCC ID: WAJ-9602MWD

In-band Unwanted Emissions: CH FM



FCC ID: WAJ-9602MWD Sheet 67 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

In-band Unwanted Emissions: CH FH




FCC ID: WAJ-9602MWD Sheet 68 of 89 Sheets ETC Report No.: 08-04-MAS-052-01


Out-of-band Unwanted Emission:

a) CH FL

Out-of-band Unwanted Emissions (below 1GHz): CH FL



FCC ID: WAJ-9602MWD Sheet 69 of 89 Sheets ETC Report No.: 08-04-MAS-052-01




Note:

- 1. Place of Measurement: Measuring site of the ETC.
- 2. If the data table appeared symbol of "***" means the value was too low to be measured.
- 3. The estimated measurement uncertainty of the result measurement is
- ±4.6dB (30MHz≤f<300MHz).
- ±4.4dB (300MHz≤f<1000MHz).


FCC ID: WAJ-9602MWD ETC Report No.: 08-04-MAS-052-01

Out-of-band Unwanted Emissions: CH FL




FCC ID: WAJ-9602MWD

Out-of-band Unwanted Emissions: CH FL.




FCC ID: WAJ-9602MWD ETC Report No.: 08-04-MAS-052-01

Out-of-band Unwanted Emissions: CH FL.




FCC ID: WAJ-9602MWD Sheet 73 of 89 Sheets ETC Report No.: 08-04-MAS-052-01




FCC ID: WAJ-9602MWD Sheet 74 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

b) CH FM

Out-of-band Unwanted Emissions (below 1GHz): CH FM




FCC ID: WAJ-9602MWD ETC Report No.: 08-04-MAS-052-01




Note:

- 1. Place of Measurement: Measuring site of the ETC.
- 2. If the data table appeared symbol of "***" means the value was too low to be measured.
- 3. The estimated measurement uncertainty of the result measurement is
- ± 4.6 dB (30MHz $\le f$ <300MHz).
- $\pm 4.4 dB (300 MHz \le f < 1000 MHz).$


FCC ID: WAJ-9602MWD Sheet 76 of 89 Sheets ETC Report No.: 08-04-MAS-052-01




FCC ID: WAJ-9602MWD Sheet 77 of 89 Sheets ETC Report No.: 08-04-MAS-052-01



FCC ID: WAJ-9602MWD Sheet 78 of 89 Sheets ETC Report No.: 08-04-MAS-052-01





FCC ID: WAJ-9602MWD Sheet 79 of 89 Sheets ETC Report No.: 08-04-MAS-052-01



c) CH F_H

Out-of-band Unwanted Emissions (below 1GHz): CH FH







Note:

- 1. Place of Measurement: Measuring site of the ETC.
- 2. If the data table appeared symbol of "***" means the value was too low to be measured.
- 3. The estimated measurement uncertainty of the result measurement is
- ±4.6dB (30MHz≤f<300MHz).
- ±4.4dB (300MHz≤f<1000MHz).


FCC ID: WAJ-9602MWD ETC Report No.: 08-04-MAS-052-01




FCC ID: WAJ-9602MWD Sheet 83 of 89 Sheets ETC Report No.: 08-04-MAS-052-01



FCC ID: WAJ-9602MWD Sheet 84 of 89 Sheets ETC Report No.: 08-04-MAS-052-01



FCC ID: WAJ-9602MWD Sheet 85 of 89 Sheets ETC Report No.: 08-04-MAS-052-01



FCC ID: WAJ-9602MWD Sheet 86 of 89 Sheets
ETC Report No.: 08-04-MAS-052-01

6.26 Frame period and jitter

6.26.1 Standard Applicable: FCC 15.323(e) same as RSS-213 4.3.4 (C)

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these subbands shall be 20 milliseconds/X where X is a positive whole number. Each device that implements time division for the purposes of maintaining a duplex connection on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 50 parts per millions (ppm). Each device which further divides access in time in order to support multiple communication links on a given frequency carrier shall maintain a frame repetition rate with a frequency stability of at least 10 ppm. The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 microseconds for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for the device.

6.26.2 Measurement Requirement:

- Frame frequency stability ≤ 50 ppm
- TDMA frame frequency stability ≤ 10 ppm (That translates to frequency drift of19.2 kHz/slot for 1920 MHz carrier)
- Frame jitter ≤ 25 μs


6.26.3 Test Results: Complies

Measurement Data:


Channel No.	Frequency (KHz/slot)		Jitter (us)	
	Drift	Limit	Result	Limit
FL	-6	<u>+</u> 19.2	0.00	<u>+</u> 25
Fм	-6	<u>+</u> 19.2	0.00	<u>+</u> 25
FH	-6	<u>+</u> 19.2	0.00	<u>+</u> 25

Photos of worst-case display follow:

Frequency Drift



TDMA Frame Jitter



Sheet 88 of 89 Sheets ETC Report No.: 08-04-MAS-052-01

6.27 Carrier frequency stability

6.27.1 Standard Applicable: FCC 15.323(f)

The frequency stability of the carrier frequency of the intentional radiator shall be maintained within \pm 10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20°C to +50°C at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20°C. For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage.

RSS-213 6.2 Frequency Stability

The carrier frequency stability shall be maintained within ±10 ppm (±0.001%).

6.27.2 Measurement Requirement:

- Carrier frequency stability ≤ 10 ppm over 1 hour or interval between channel access monitoring, whichever is shorter (That translates to frequency drift of19.2 kHz for 1920 MHz carrier)
- Carrier frequency stability over -20°C to +50°C at normal supply voltage, and over 85% to 115% of rated supply voltage (voltage variation not required for battery operated device)

6.27.3 Test Results: Complies

Measurement Data:

a) Carrier Frequency Stability with Supply voltage

Channel No.	Frequency Offset (kHz)			Limit
	2.04V (85%)	2.4V (Normal)	2.76V (115%)	(kHz)
FL	n/a	n/a	n/a	<u>+</u> 19.2
FM	n/a	n/a	n/a	<u>+</u> 19.2
FH	n/a	n/a	n/a	<u>+</u> 19.2

b) Carrier Frequency Stability with Temperature and Time

Channel No.	Frequency Offset (kHz)			Limit
	0 ℃	20 ℃	45 ℃	(kHz)
F∟	0	0	0	<u>+</u> 19.2
FM	0	0	0	<u>+</u> 19.2
FH	0	0	0	<u>+</u> 19.2

Test was conducted for duration longer than 1 hour. Photo of worst-case display follows:

