





ISO/IEC17025 Accredited Lab.

Report No: FCC0805096-02
File reference No: 2008-05-28

Applicant: Shenzhen Chuyar Electronics Co,.Ltd.

Product: 2.4G Wireless Nunchuk

Model No: CY-637

Brand Name: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: May 28, 2008

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 0805089-02 Page 2 of 42

Date: 2008-05-28



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Date: 2008-05-28



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	4
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	5
3.0	Technical Details	7
3.1	Summary of Test Results.	7
3.2	Test Standards.	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	10
5.1	Test Method and Test Procedure.	10
6.2	Configuration of the EUT.	10
6.3	EUT Operation Condition.	10
5.4	Radiated Emission Limit.	11
6.5	Test Result.	12
7.0	Band Edge	25
7.1	Test Method and Test Procedure.	25
7.2	Radiated Test Setup.	25
7.3	Configuration of the EUT	25
7.4	EUT Operating Condition.	25
7.5	Band Edge Limit.	26
7.6	Band Edge Test Result.	27
8.0	Antenna Requirement.	28
9.0	20dB Bandwidth measurement.	29
10.0	FCC ID Label	32
11.0	Photo of Test Setup and EUT View.	33

Date: 2008-05-28



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Page 4 of 42

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Shenzhen Chuyar Electronics Co,.Ltd.

Address: Bldg3,Baozhou Ind ,Estate 117 Jiuwei Road ,Xixiang Bao'an Shenzhen 518126PRC China

Telephone: 86-755-27478575 Fax: 86-755-27478596

1.3 Description of EUT

Product: Shenzhen Chuyar Electronics Co,.Ltd.

Manufacturer: 2.4G Wireless Nunchuk

Brand Name: N/A Model Number: CY-637

Additional Model Name CY-638, CY-639

Additional Trade Name N/A

Rating: DC5.0V, 50mA

Modulation Type: GFSK

Operation Frequency 2402-2481MHz

Number of Channel 80

Antenna Designation Printed antenna, which is built-in, designed as an indispensable part of the EUT.

1.4 Submitted Sample

1 Sample

1.5 Test Duration


2008-05-04 to 2008-05-23

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 5 of 42



Conducted Emissions Uncertainty =3.6dB Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

2.0		Test Equi	ipments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2007-12-05	2008-12-04
Absorbing Clamp	ROHDE&SCHWARZ	MDS-21	100126	2007-12-05	2008-12-04
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2007-12-05	2008-12-04
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2007-12-05	2008-12-04
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2007-12-05	2008-12-04
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2007-03-30	2008-03-29
4-WIRE ISN	ROHDE&SCHWARZ	ENY 41	830663/044	2008-02-18	2009-02-17
GG ENY22 Double 2-Wire ISN	ROHDE&SCHWARZ	ENY22	83066/016	2008-02-18	2009-02-17
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2008-02-18	2009-02-17
System Controller	CT	SC100	-	2008-02-18	2009-02-17
Printer	EPSON	РНОТО ЕХЗ	CFNH234850	2008-02-18	2009-02-17
FM-AM Signal Generator	JUNG.JIN	SG-150M	389911177	2008-02-18	2009-02-17
Color TV Pattern Generator	PHILIPS	PM5418	LO621747	2008-02-18	2009-02-17
Computer	IBM	8434	1S8434KCE99BLX LO*	-	-
Oscillator	KENWOOD	AG-203D	3070002	2008-02-18	2009-02-17

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 6 of 42

Report No: 0805089-02

		12/	<i>₹</i>		
Spectrum Analyzer	HAMEG	HM 5012	- -	-	-
Power Supply	LW	APS1502	-	-	-
5K VA AC Power Source	California Instruments	5001iX	56060	2008-02-18	2009-02-17
CDN	EM TEST	CDN M2/M3	-	2008-02-18	2009-02-17
Attenuation	EM TEST	ATT6/75	-	2008-02-18	2009-02-17
Resistance	EM TEST	R100	-	2008-02-18	2009-02-17
Electromagnetic Injection Clamp	LITTHI	EM101	35708	2008-02-18	2009-02-17
Signal Generator	ROHDE&SCHWARZ	SMT03	100029	2008-02-18	2009-02-17
Power Amplifier	AR	150W1000	300999	2008-02-18	2009-02-17
Field probe	Holaday	HI-6005	105152	2008-02-18	2009-02-17
Bilog Antenna	Chase	CBL6111C	2576	2008-02-18	2009-02-17
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2008-02-18	2009-02-17
3m OATS			N/A	2008-02-18	2009-02-17
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2007-08-16	2008-08-15
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2007-07-03	2008-07-02

Page 7 of 42

Report No: 0805089-02

Date: 2008-05-28



3.0 **Technical Details**

3.1 **Summary of test results**

The EUT has been tested according to the following specifications:					
Standard	Test Type	Result	Notes		
FCC Part 15, Paragraph 15.207	Conducted Emission Test	N/A	Complies		
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	PASS	Complies		
FCC Part 15, Paragraph 15.209	Radiated Emission Test	PASS	Complies		
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	PASS	Complies		

3.2 **Test Standards**


FCC Part 15 Subpart C, Paragraph 15.249

4.0 **EUT Modification**

No modification by Shenzhen Timeway Technology Consulting Co.,Ltd

Report No: 0805089-02 Date: 2008-05-28 TESTREP 5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

One channels are provided to the EUT

A. EUT

Device	Manufacturer	Model	FCC ID
2.4G Wireless	Shenzhen Chuyar Electronics Co., Ltd.	CY-637	WAMCY-637R
Nunchuk			

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 9 of 42

Report No: 0805089-02

Date: 2008-05-28

Device	Manufacturer	Model FCC ID/DOC	Cable			
N/A						

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

<u> </u>						
Eraguanay(MHz)	Class A Lir	nits (dB µ V)	Class B Limits (dB µ V)			
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level		
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*		
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0		
5.00 ~ 30.00	73.0	60.0	60.0	50.0		

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: Due to DC operation, this test item not applicable

Page 10 of 42

Report No: 0805089-02


Date: 2008-05-28



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Page 11 of 42

Report No: 0805089-02

Date: 2008-05-28



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Ī	Fundamental Frequency	Field Stre	Field Strength of Fundamental (3m)			trength of Harmo	onics (3m)
	(MHz)	mV/m	dBuV/m		uV/m	dBu	V/m
Ī	2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note:

- 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.
- 5. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK and AV detector.

Report No: 0805089-02 Page 12 of 42

Date: 2008-05-28



6.5 Test result

\mathbf{A} **Fundamental & Harmonics Radiated Emission Data**

Product:	2.4G Wireless Nunchuk	Test Mode:	Low Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	5VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2402.035	78.9/66.4	Н	114/94	-35.1/-27.6
2402.035	81.8/67.2	V	114/94	-32.2/-26.8
4804		H/V	74/54	
7206		H/V	74/54	
9608		H/V	74/54	
12010		H/V	74/54	
14412		H/V	74/54	
16814		H/V	74/54	
19216		H/V	74/54	
21618		H/V	74/54	
24020		H/V	74/54	

Page 13 of 42

Report No: 0805089-02

Product:	2.4G Wireless Nunchuk	Test Mode:	Middle Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	5VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2441.102	81.7//69.1	Н	114/94	-32.3/-24.9
2441.102	85.2/70.2	V	114/94	-28.8/-23.8
4880		H/V	74/54	
7320		H/V	74/54	
9760		H/V	74/54	
12200		H/V	74/54	
14640		H/V	74/54	
17080		H/V	74/54	
19520		H/V	74/54	
21960		H/V	74/54	
24400		H/V	74/54	

Page 14 of 42

Report No: 0805089-02

Date: 2008-05-28

Product:	2.4G Wireless Nunchuk	Test Mode:	High Channel
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	5VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2481.046	84.6/73.5	Н	114/94	-29.4/-20.5
2481.046	89.0/74.9	V	114/94	-25.0/-19.1
4940		H/V	74/54	
7410		H/V	74/54	
9880		H/V	74/54	
12350		H/V	74/54	
14820		H/V	74/54	
17290		H/V	74/54	
19760		H/V	74/54	
22230		H/V	74/54	
24700		H/V	74/54	

Note:

- (1) PK= Peak, AV= Average
- (2) Emission Level = Reading Level + Probe Factor + Cable Loss.
- (3)Margin=Emission-Limits
- (4)According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) Due to measured PK value less than the AV limit, the measured AV value must be less than AV limit


Date: 2008-05-28



Test Figure above 1G

Low Channel

Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2008-05-28



Low Channel

Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 0805089-02 Date: 2008-05-28



Middle Channel

Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2008-05-28



Middle Channel

Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2008-05-28



High Channel

Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2008-05-28



High Channel

Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 0805089-02 Date: 2008-05-28

18-25G **High Channel**




The report refers only to the sample tested and does not apply to the bulk.

Report No: 0805089-02 Date: 2008-05-28



18-25G High Channel



The report refers only to the sample tested and does not apply to the bulk.

Date: 2008-05-28




EUT set Condition: Keep Tx transmitting

Mode: Low Channel

Results: Pass


Please refer to following diagram for individual

Radiated Emission Measurement



Report No: 0805089-02 Page 24 of 42

Date: 2008-05-28




EUT set Condition: Keep Tx transmitting

Mode: Low Channel

Results: Pass

Please refer to following diagram for individual

Radiated Emission Measurement



Date: 2008-05-28




7. Band Edge

7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) Set Spectrum as RBW=VBW=100kHz and Peak detector used
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

7.3 Configuration of The EUT

Same as section 5.3 of this report

7.4 EUT Operating Condition

Same as section 5.4 of this report.

7.5 Band Edge Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 50dB below that in the 100kHz, bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

The report refers only to the sample tested and does not apply to the bulk.

Page 26 of 42

Report No: 0805089-02 Date: 2008-05-28



7.6 Test Result

	roduct:			2 4G	Wire	eless Nu	nchuk	Te	st Mode:		Low C	hannel	
	Mode		Keeping Transmitting					Test Voltage		DC5.0V			
Temperature			24 deg. C,					Humidity		56% RH			
Test Result:		Pass				-	Detector		PK				
2400MHz			PK (dBμV/m) 38.0						74(dBμV/m)				
		-	AV(dBμV/m)			26.3		Limit		54(dBμV/m)			
_	^					1 [T1]	[T1]		RBW 100 kHz				
(^{\$} / _{\$})	Ref Lvl		Marker 1			84.66 dBμV		VBW	100 F		л ни	10 00	
$107 \text{ dB}\mu\text{V}$		u٧	2.			40236473 GHz		SWT	28 n				,
107									▼ 1	F T 4 3	0.4	CC 1D V	1
100									*1	[T1]	84.	66 dBμV 473 cuz	Α
100									∇2	[T1]	33.	28 dBμV	
90												, 1000 GHz	
00											1		
0.0													
80													1
	1MAX												1MA
70													1
	—D1 64.	66	$dB\mu V$										
60													l
50											 		ł
]		
40										1	<u> </u>		
										.	″ ነ ዛ		
30	//_///	W	halana	N	Ww.			Marine Commence	J. Mar. March	M/m/N/		MILLON	
20													
10													
7			1 ()				1	MLI				10.511	J
	Start 2						11	MHz/			Stop 2	2.42 GHz	
Date	: 2	21.	MAY 2	008	14:	:59:50							

Note: Field Strength in restrict band measured in conventional manner

Page 27 of 42

Report No: 0805089-02 Date: 2008-05-28

Product:	2.4G Wireless Nunchuk				Test Mode:		High Channel		
Mode	Keeping Transmitting			Test V	oltage o	DC5.0V			
Temperature	deg. C,	deg. C,		Humidity		56% RH			
Test Result:	Pass				Detector		PK		
2483.5MHz	$PK \left(dB\mu V/m \right)$		40.6		- Limit		$74(dB\mu V/m)$		
2403.3WIIIZ	$AV(dB\mu V/m)$		28.0		Diffit		54(dBµV/m)		
Ŕ	Marker	1 [T1]		RBW	100 kl	Hz RF	Hz RF Att 10 dB		
Ref Lvl			$2 \text{ dB}\mu\text{V}$	VBW	100 kl				
$107 \; \mathrm{dB}\mu\mathrm{V}$	2	2.481362	73 GHz	SWT	12.5 m	s Ur	nit	dB μ V	/
107					v ₁	[T1]	83.	82 dB <i>μ</i> V	A
100							2.48138	273 GHz	•
					∇2	[T1]		08 dB μ V	
90							2.48350	000 GHz	l
					1 Y				
80									l
1MAX									1٢
-D1 63.82	dB μ V								
60	·				91				ł
50									
30	ave alla			4	/ 2 V				
40	- Miles Leavil	hh.		-11	- \	N			ł
us Allena	₁ M" V	\	ı la	M			الله الما		
30		A. Marie		/- - 		- - - - - - - - - -	I_////////////////////////////////////	Myler while	\
20									1
10									1
Start 2.45	5 GHz		5 M	Hz/			Stop	2.5 GHz	-

Note: Field Strength in restrict band measured in conventional manner

Report No: 0805089-02 Page 28 of 42

Date: 2008-05-28




8.0 Antenna Requirement

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.


This product has a PCB permanent antenna, fulfill the requirement of this section.


Test Result: Pass



Page 30 of 42

Report No: 0805089-02





Page 32 of 42

Report No: 0805089-02

Date: 2008-05-28




10.0 FCC ID Label

FCC ID: WAMCY-637R

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Date: 2008-05-28



11.0 **Photo of testing**

11.1 Conducted test View--

11.2 Radiated emission test view



Page 34 of 42

Report No: 0805089-02

Date: 2008-05-28



11.3 Photo for the EUT

Outside View



Page 35 of 42

Report No: 0805089-02





Page 36 of 42

Report No: 0805089-02





Page 37 of 42

Report No: 0805089-02





Page 38 of 42

Report No: 0805089-02





Canon DIGITAL IXUS 60 F5.6 1/60s

Page 39 of 42

Report No: 0805089-02





Canon DIGITAL IXUS 60 F5.6 1/60s

Page 40 of 42

Report No: 0805089-02





Canon DIGITAL IXUS 60 F5.6 1/60s

Page 41 of 42

Report No: 0805089-02





Canon DIGITAL IXUS 60 F5.6 1/60s

Page 42 of 42

Report No: 0805089-02

Date: 2008-05-28





Canon DIGITAL IXUS 60 F5.6 1/60s

-- End of the report--