



## EMI TEST REPORT

### Test Report No. : 28IE0193-HO-03-A

**Applicant** : Mitsubishi Electric Corporation Himeji Works  
**Type of Equipment** : SMART KEYLESS SYSTEM (Receiver)  
**Model No.** : SKE11A-03  
**FCC ID** : WAZX1T530SKE11A03  
**Test regulation** : FCC Part 15 Subpart B 2008  
**Test Result** : Complied

1. This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
2. The results in this report apply only to the sample tested.
3. This sample tested is in compliance with the above regulation.
4. The test results in this report are traceable to the national or international standards.

**Date of test:**

June 3, 2008

**Tested by:**

*A. Hayashi*

Akio Hayashi  
EMC Services

**Approved by:**

*M. Kosaka*

Makoto Kosaka  
EMC Services



NVLAP LAB CODE: 200572-0

This laboratory is accredited by the NVLAP LAB CODE 200572-0, U.S.A. The tests reported herein have been performed in accordance with its terms of accreditation.

\*As for the range of Accreditation in NVLAP, you may refer to the WEB address,  
<http://uljapan.co.jp/emc/nvlap.htm>

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

MF060b (09.01.08)

<u>CONTENTS</u>	<u>PAGE</u>
SECTION 1: Customer information .....	3
SECTION 2: Equipment under test (E.U.T.) .....	3
SECTION 3: Test specification, procedures & results .....	4
SECTION 4: Operation of E.U.T. during testing .....	7
SECTION 5: Radiated Emission .....	9
APPENDIX 1: Photographs of test setup.....	10
Radiated Emission .....	10
Worst Case Position.....	11
(Horizontal: Z-axis/ Vertical:Z-axis) .....	11
APPENDIX 2: Data of EMI test .....	12
Radiated Emission .....	12
APPENDIX 3: Test instruments .....	14

## **SECTION 1: Customer information**

Company Name : Mitsubishi Electric Corporation Himeji Works  
Address : 840 Chiyoda-machi Himeji Hyogo 670-8677 Japan  
Telephone Number : +81-792-98-8896  
Facsimile Number : +81-792-98-9262  
Contact Person : Yoshiharu Goto

## **SECTION 2: Equipment under test (E.U.T.)**

### **2.1 Identification of E.U.T.**

Type of Equipment : SMART KEYLESS SYSTEM (Receiver)  
Model No. : SKE11A-03  
Serial No. : 20080512-R1  
Receipt Date of Sample : May 15, 2008  
Country of Mass-production : Japan  
Condition of EUT : Production prototype  
(Not for Sale: This sample is equivalent to mass-produced items.)  
Modification of EUT : No Modification by the test lab

### **2.2 Product Description**

Model No: SKE11A-03 (referred to as the EUT in this report) is the SMART KEYLESS SYSTEM (Receiver).  
Clock frequency(ies) : 5MHz (CPU), 10MHz, 9.850625MHz (VCO)

Type of Receiver : SuperHeterodyne  
Frequency of Operation : 315MHz  
Intermediate Frequency : 220kHz  
Antenna Type : Bar antenna  
Local Oscillator : 9.850625MHz x 32 = 315.22MHz  
Method of Frequency Generation : Crystal  
Operating voltage (Inner) : DC 5.0V

### **FCC15.111(b)**

The receiving antennas (of this EUT) are installed in the place where the end users cannot remove them.  
Therefore, this EUT complies with the requirement in section 15.111(b).

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

## **SECTION 3: Test specification, procedures & results**

### **3.1 Test specification**

Test Specification : FCC Part 15 Subpart B 2008, final revised on May 19, 2008  
 Title : FCC 47CFR Part15 Radio Frequency Device  
           Subpart B Unintentional Radiators

### **3.2 Procedures and results**

Item	Test Procedure	Limits	Deviation	Worst margin	Result
Conducted emission	<b>FCC: ANSI C63.4: 2003</b> 7. AC powerline conducted emission measurements <b>IC: RSS-Gen 7.2.2</b>	Receiver	N/A	N/A *1)	N/A
Radiated emission	<b>FCC: ANSI C63.4: 2003</b> 8. Radiated emission measurements <b>IC: RSS-Gen 4.10</b>	Receiver	N/A	19.6dB 945.660MHz Horizontal,Vertical, QP	Complied

\*Note: UL Japan, Inc's EMI Work Procedure QPM05.

\*1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line.

\*These tests were performed without any deviations from test procedure except for additions or exclusions.

### **3.3 Additions or deviations to standards**

No addition, deviation, nor exclusion has been made from standards.

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

### 3.4 Uncertainty

#### EMI

The following uncertainties have been calculated to provide a confidence level of 95% using a coverage factor k=2.

Test room	Conducted emission	Radiated emission (10m*)			Radiated emission (3m*)			Radiated emission (3m*)	
		150kHz-30MHz	9kHz-30MHz	30MHz-300MHz	300MHz-1GHz	9kHz-30MHz	30MHz-300MHz	300MHz-1GHz	1GHz-18GHz
No.1 semi-anechoic Chamber ( $\pm$ )	3.7dB	3.1dB	4.4dB	4.2dB	3.2dB	3.8dB	3.9dB	5.9dB	6.1dB
No.2 semi-anechoic chamber ( $\pm$ )	3.7dB	-	-	-	3.2dB	4.4dB	4.0dB	5.9dB	6.1dB
No.3 semi-anechoic chamber ( $\pm$ )	3.7dB	-	-	-	3.2dB	4.6dB	4.0dB	5.9dB	6.1dB
No.4 semi-anechoic chamber ( $\pm$ )	3.7dB	-	-	-	3.2dB	3.9dB	3.9dB	5.9dB	6.1dB

\*10m/3m = Measurement distance

#### Radiated emission test (3m)

The data listed in this test report has enough margin, more than the site margin.

### 3.5 Test Location

UL Japan, Inc. Head Office EMC Lab. \*NVLAP Lab. code: 200572-0

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116 Facsimile : +81 596 24 8124

	FCC Registration Number	IC Registration Number	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms
No.1 semi-anechoic chamber	313583	2973C-1	19.2 x 11.2 x 7.7m	7.0 x 6.0m	No.1 Power source room
No.2 semi-anechoic chamber	655103	2973C-2	7.5 x 5.8 x 5.2m	4.0 x 4.0m	-
No.3 semi-anechoic chamber	148738	2973C-3	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.3 Preparation room
No.3 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.4 semi-anechoic chamber	134570	2973C-4	12.0 x 8.5 x 5.9m	6.8 x 5.75m	No.4 Preparation room
No.4 shielded room	-	-	4.0 x 6.0 x 2.7m	N/A	-
No.5 semi-anechoic chamber	-	-	6.0 x 6.0 x 3.9m	6.0 x 6.0m	-
No.6 shielded room	-	-	4.0 x 4.5 x 2.7m	4.75 x 5.4 m	-
No.6 measurement room	-	-	4.75 x 5.4 x 3.0m	4.75 x 4.15 m	-
No.7 shielded room	-	-	4.7 x 7.5 x 2.7m	4.7 x 7.5m	-
No.8 measurement room	-	-	3.1 x 5.0 x 2.7m	N/A	-
No.9 measurement room	-	-	8.0 x 4.5 x 2.8m	2.0 x 2.0m	-
No.10 measurement room	-	-	2.6 x 2.8 x 2.5m	2.4 x 2.4m	-
No.11 measurement room	-	-	3.1 x 3.4 x 3.0m	2.4 x 3.4m	-

\* Size of vertical conducting plane (for Conducted Emission test) : 2.0 x 2.0m for No.1, No.2, No.3, and No.4 semi-anechoic chambers and No.3 and No.4 shielded rooms.

### 3.6 Test set up, Data of EMI, and Test instruments

Refer to APPENDIX 1 to 3.

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116


Facsimile : +81 596 24 8124

## **SECTION 4: Operation of E.U.T. during testing**

### **4.1 Operating modes**

The mode is used : Continuous Receiving 315MHz mode  
 This EUT receives 315MHz signal (FSK modulated) from hand unit.

### **4.2 Configuration and peripherals**



#### **Description of EUT and Support equipment**

No.	Item	Model number	Serial number	Manufacturer	Remark
A	Antenna A	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
B	Antenna B	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
C	Antenna C	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
D	Antenna D	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
E	Antenna E	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
F	Antenna F	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
G	Antenna G	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
H	Smart ECU	SKE11A-03	20080523-01	Mitsubishi Electric Corporation Himeji Works	-
I	SMART KEYLESS SYSTEM (Receiver)	SKE11A-03	20080512-R1	Mitsubishi Electric Corporation Himeji Works	EUT
J	Jig	-	-	Mitsubishi Electric Corporation Himeji Works	-
K	Hand Unit	SKE11A-03	20080424-02	Mitsubishi Electric Corporation Himeji Works	-

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124

**List of cables used**

No.	Name	Length (m)	Shield	
			Cable	Connector
1	Antenna Cable	1.5	Unshielded	Unshielded
2	Antenna Cable	1.5	Unshielded	Unshielded
3	Antenna Cable	1.4	Unshielded	Unshielded
4	Antenna Cable	1.4	Unshielded	Unshielded
5	Antenna Cable	1.4	Unshielded	Unshielded
6	Antenna Cable	1.4	Unshielded	Unshielded
7	Antenna Cable	1.4	Unshielded	Unshielded
8	Signal & DC cable	1.3	Unshielded	Unshielded
9	Signal & DC cable	1.4	Unshielded	Unshielded
10	DC Cable	1.3	Unshielded	Unshielded

## **SECTION 5: Radiated Emission**

### **5.1 Operating environment**

Test place : No.2 semi anechoic chamber  
Temperature : See data  
Humidity : See data

### **5.2 Test configuration**

EUT was placed on a urethane platform of nominal size, 1.0m by 1.5m, raised 80cm above the conducting ground plane. The EUT was set on the edge of the tabletop. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength. Photographs of the set up are shown in Appendix 1.

### **5.3 Test conditions**

Frequency range : 30MHz-300MHz (Biconical antenna) / 300MHz-1000MHz (Logperiodic antenna)  
1GHz-2GHz (Horn antenna)  
Test distance : 3m  
EUT position : Table top  
EUT operation mode : See Clause 4.1

### **5.4 Test procedure**

The height of the measuring varied between 1 and 4m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field intensity.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

Frequency	Below 1GHz	Above 1GHz
Instrument used	Test Receiver	Spectrum Analyzer
IF Bandwidth	QP: BW 120kHz	PK: RBW:1MHz/VBW: 1MHz AV: RBW:1MHz/VBW:10Hz

- The noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

### **5.5 Test result**

Summary of the test results: Pass

Date: June 3, 2008

Test engineer: Akio Hayashi

---

**UL Japan, Inc.**

**Head Office EMC Lab.**

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 JAPAN

Telephone : +81 596 24 8116

Facsimile : +81 596 24 8124