

## **RF Exposure Evaluation**

## 1 Applicable Standard

According to RSS-102 RF exposure is calculated.

Environment)					
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Dentisty (W/m <sup>2</sup> )	Reference Period (minutes)	
0.003-10 <u>21</u>	83	90	-	Instantaneous*	
0.1-10	-	0.73/ <i>f</i>	-	6**	
1.1-10	87/ f 0.5	-	-	6**	
10-20	27.46	0.0728	-2	6	
20-48	58.07/ f0.25	0.1540/ f0.25	8.944/ f0.5	6	
48-300	22.06	0.05852	1.291	6	
300-6000	3.142 f 0.3417	0.008335 f 0.3417	0.02619 f 0.6834	6	

0.163

0.163

4.21 x 10-4 f 0.5

10

6.67 x 10-5 f

616000/ f 1.2

616000/f1.2

**Note:** f is frequency in MHz.

6000-15000

15000-150000

150000-300000

61.4

61.4

0.158 f 0.5

## 2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum peak output power at antenna input terminal (dBm):	37.38
Maximum peak output power at antenna input terminal (mW):	5470
Maximum antenna gain: (dBi):	17.00
Maximum Antenna Gain (numeric):	50.12
Prediction distance (cm):	600
Prediction frequency (MHz):	737.00
Power density at predication frequency and distance (W/m2):	0.61
MPE limit for uncontrolled exposure at predication frequency (W/m2):	2.39

**Conclusion: compliant** 

<sup>\*</sup> Based on nerve stimulation (NS).

<sup>\*\*</sup> Based on specific absorption rate (SAR).