

## RF Exposure Evaluation

### 1 Applicable Standard

According to RSS-102 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Averaging Time (minutes)
0.003-1	280	2.19	-	6
1-10	280/ <i>f</i>	2.19/ <i>f</i>	-	6
10-30	28	2.19/ <i>f</i>	-	6
30-300	28	0.073	2 <sup>*</sup>	6
300-1500	1.585 <i>f</i> <sup>0.5</sup>	0.0042 <i>f</i> <sup>0.5</sup>	<i>f</i> /150	6
1500-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> <sup>1.2</sup>
150000-300000	0.158 <i>f</i> <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> <i>f</i> <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> <i>f</i>	616000/ <i>f</i> <sup>1.2</sup>

**Note:** *f* is frequency in MHz.

\* Power density limit is applicable at frequencies greater than 100 MHz.

### 2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

Where:

S = power density

P = power input to the antenna

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

Maximum peak output power at antenna input terminal (dBm):	37.75
Maximum peak output power at antenna input terminal (mW):	5957
Maximum antenna gain: (dBi):	16.00
Maximum Antenna Gain (numeric):	39.80
Prediction distance (cm):	550
Prediction frequency (MHz):	2145.00
Power density at predication frequency and distance (mW/cm <sup>2</sup> ):	0.062
MPE limit for uncontrolled exposure at predication frequency (mW/cm <sup>2</sup> ):	1.0

**Conclusion: compliant**