



APPENDIX 1

RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT Specification

EUT	802.11a/b/g/n access point
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input checked="" type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	IEEE 802.11b mode: 15. 74dBm(37.2mW) IEEE 802.11g mode: 16. 12dBm(40.9mW) draft 802.11gn Standard-20 MHz Channel mode: 22.50 dBm(177.8mW) draft 802.11gn Wide-40 MHz Channel mode: 21.88 dBm(154.2mw) IEEE 802.11a mode: 18. 11dBm(64.7mW) draft 802.11an Standard-20 MHz Channel mode: 22.94 dBm(196.8mw) draft 802.11an Wide-40 MHz Channel mode: 22.85 dBm(192.8mw)
Antenna gain (Max)	Gain 3. 2dBi(2.09)(2.4GHz) /Total gain 7.97(6.27) and Gain 2dBi(2.09)(5GHz) /Total gain 6.77(4.75)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation <input type="checkbox"/> N/A
Remark:	
1. The maximum output power is <u>22.50dBm (177.8mW)</u> at <u>2462MHz</u> (with <u>6.27 numeric antenna gain.</u>); <u>22.94dBm (196.8mw)</u> at <u>5805MHz</u> (with <u>4.75 numeric antenna gain.</u>)	
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.	
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm ² even if the calculation indicates that the power density would be larger.	



TEST RESULTS

No non-compliance noted.

**Calculation**

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(\text{mW}) = P(\text{W}) / 1000 \text{ and}$$

$$d(\text{cm}) = d(\text{m}) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²



IEEE 802.11b:

EUT output power = 37. 2mW

Numeric Antenna gain = 6.27

\Rightarrow Power density = 0.0464 mW/cm²

IEEE 802.11g:

EUT output power = 40. 9mW

Numeric Antenna gain = 6.27

\Rightarrow Power density = 0.0510 mW/cm²

draft 802.11gn Standard-20 MHz Channel mode

EUT output power = 177. 8mW

Numeric Antenna gain = 6.27

\Rightarrow Power density = 0.222 mW/cm²

draft 802.11gn Wide-40 MHz Channel mode

EUT output power = 154. 2mW

Numeric Antenna gain = 6.27

\Rightarrow Power density = 0.192 mW/cm²

IEEE 802.11a:

EUT output power = 64. 7mW

Numeric Antenna gain = 4.75

\Rightarrow Power density = 0.0612 mW/cm²

draft 802.11an Standard-20 MHz Channel mode

EUT output power = 196. 8mW

Numeric Antenna gain = 4.75

\Rightarrow Power density = 0.186 mW/cm²

draft 802.11an Wide-40 MHz Channel mode

EUT output power = 192. 8mW

Numeric Antenna gain = 4.75

\Rightarrow Power density = 0.182 mW/cm²

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.)