

FCC 47 CFR PART 15 SUBPART C TEST REPORT

For

Applicant: Wonders Technology Co., Ltd.

DOSS Industrial Zone, Qiping Kengdu Industrial Area Guihua

Address: Village, Guanlan Town Baoan District, Shenzhen, China

Product Name: Bluetooth Speaker

Model Name: SP58114, DS-1553

Brand Name: N/A

FCC ID: WC2-SP58114

Report No.: MTE/SAL/F14101362

Date of Issue: Oct. 20, 2014

Issued by: Most Technology Service Co., Ltd.

No.5, Langshan 2nd Road, North District, Hi-tech Industrial Park, Address:

Nanshan, Shenzhen, Guangdong, China

Tel: 86-755-8617 0306

Fax: 86-755-8617 0310

The report consists 53 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by MOST. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver.

TABLE OF CONTENTS	

Report No.: MTE/SAL/F14101362

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1 Product Information	5
2.2 Objective	6
2.3 Test Standards and Results	6
2.4 Environmental Conditions	6
2.5 MEASUREMENT UNCERTAINTY	6
3. TEST FACILITY	7
3.1TEST FACILITY	7
3.2 Test Conditions	7
3.3 Channel List	8
3.4 Description of Test Modes	8
3.5 Table of Parameters of Text Software Setting	9
3.6 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	10
4. SETUP OF EQUIPMENT UNDER TEST	11
4.1 SUPPORT EQUIPMENT	11
4.2 TEST EQUIPMENT LIST	12
5. 47 CFR Part 15C 15.249 Requirements	13
5.1 Spurious Emission Test	13
5.1.1 Requirement	13
5.1.2 Test Description	14
5.1.3 Test Description	15
5.1.5 Test Result	16
5.2 Band Edge	28
5.2.1 Requirement	28
5.2.2 Test Description	28
5.2.3Test Result	
5.3 LINE CONDUCTED EMISSION TEST	41
5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST	
5.3.2. BLOCK DIAGRAM OF TEST SETUP	41
5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	42
5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	42
5.3.5. Test result	42
5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	42
5.4 20 dB Bandwidth	
5.4.1 Definition	45

FCC ID: WC2-SP58114

5.4.2 Block Diagram Of Test Setup	45
5.4.3 Test Result	45
5.5 Antenna Requirement	50
5.5.1 Definition	50
5.5.2 Evaluation Criteria	50
5.5.3 Evaluation Results	50
APPENDIX 1	51
PHOTOGRAPHS OF TEST SETUP	51

Report No.: MTE/SAL/F14101362

1. VERIFICATION OF CONFORMITY

Equipment Under Test: Bluetooth Speaker

Brand Name: N/A

Model Number: SP58114
Series Number: DS-1553

Description of Differences: Only different in model name.

FCC ID: WC2-SP58114

Applicant: Wonders Technology Co., Ltd.

DOSS Industrial Zone, Qiping Kengdu Industrial Area Guihua Village,

Guanlan Town Baoan District, Shenzhen, China

Manufacturer: Wonders Technology Co., Ltd.

DOSS Industrial Zone, Qiping Kengdu Industrial Area Guihua Village,

Guanlan Town Baoan District, Shenzhen, China

Technical Standards: 47 CFR Part 15 Subpart C
File Number: MTE/SAL/F14101362

Date of test: Oct. 09-13, 2014

Deviation:

Condition of Test Sample:

Normal

Normal

PASS

The above equipment was tested by MOST for compliance with the requirements set forth in FCC rules and the Technical Standards mentioned above. This said equipment in the configuration described in this report shows the maximum emission levels emanating from equipment and the level of the immunity endurance of the equipment are within the compliance requirements.

The test results of this report relate only to the tested sample identified in this report.

Tested by (+ signature):

Sophia Liu

Oct. 09, 2014

Review by (+ signature):

Henry Chen

Oct. 20, 2014

Yvette Zhou(Manager)

Oct. 20, 2014

2. GENERAL INFORMATION

2.1 Product Information

Z.I I IOuuct IIIIOIIIIatic	···
Product:	Bluetooth Speaker
Trade Name:	N/A
Model Number:	SP58114
Series Number:	DS-1553
Description of Differences:	Only different in model name.
Power Supply:	DC 5V by PC Input AC 120V/60Hz DC 3.7V by Battery
Frequency Range:	2402MHz -2480MHz
Modulation Type:	GFSK, π /4-DQPSK, 8-DPSK
Modulation Technique:	FHSS
Antenna Type:	PCB
Antenna Gain:	0dBi
Channel Spacing:	1MHz
Channel Number:	79
Temperature Range:	-40°C ~ +80°C

NOTE:

1. For a more detailed features description about the EUT, please refer to User's Manual.

2.2 Objective

Perform FCC Part 15 Subpart C tests for FCC Marking.

2.3 Test Standards and Results

Test items and the results are as bellow:

No.	Section	Description	Result	Date of Test
1	15.249(a)	Spurious Emission	PASS	2014-10-11
2	15.249(a)	Band Edge	PASS	2014-10-13
3	15.207	Power Line Conducted Emission Test	PASS	2014-10-09
4	15.249	20dB Bandwidth	PASS	2014-10-13
5	15.203	Antenna Requirement	PASS	2014-10-13

Note:

- 1. The test result judgment is decided by the limit of measurement standard
- 2. The information of measurement uncertainty is available upon the customer's request.

2.4 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35°CHumidity: 30-60 %

- Atmospheric pressure: 86-106 kPa

2.5 MEASUREMENT UNCERTAINTY

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

The report uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2,Providing a level of confidence of approximately 95%

- Uncertainty of Conducted Emission, Uc = ±1.8dB
- Uncertainty of Radiated Emission, Uc = ±3.2dB

3. TEST FACILITY 3.1TEST FACILITY

Test Site: Most Technology Service Co., Ltd.

Location: No.5, Langshan 2nd Rd., North Hi-Tech Industrial park, Nanshan, Shenzhen,

Guangdong, China

Description: There is one 3m semi-anechoic an area test sites and two line conducted labs for final

test. The Open Area Test Sites and the Line Conducted labs are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009 and CISPR

16 requirements.

The FCC Registration Number is **490827**. The **IC** Registration Number is **7103A-1**.

The CNAS Registration Number is CNAS L3573.

Site Filing: The site description is on file with the Federal Communications

Commission, 7435 Oakland Mills Road, Columbia, MD 21046.

Instrument Tolerance: All measuring equipment is in accord with ANSI C63.4:2009 and CISPR 16

requirements that meet industry regulatory agency and accreditation agency

requirement.

Ground Plane: Two conductive reference ground planes were used during the Line Conducted

Emission, one in vertical and the other in horizontal. The dimensions of these ground planes are as below. The vertical ground plane was placed distancing 40 cm to the rear of the wooden test table on where the EUT and the support equipment were placed during test. The horizontal ground plane projected 50 cm beyond the footprint of the EUT system and distanced 80 cm to the wooden test table. For Radiated Emission Test, one horizontal conductive ground plane extended at least 1m beyond the periphery of the EUT and the largest measuring antenna, and covered the entire

area between the EUT and the antenna.

3.2 Test Conditions

The EUT has been tested under normal operating (TX).

The field strength of radiation emission was measured in the following position: EUT stand-up position (Y axis).

The following data show Y axis setup.

Based on client request, all normal using modes of the normal function were tested but only the worst test data of the worst mode is reported by this report.

3.3 Channel List

	Channel List for GFSK, π /4-DQPSK, 8-DPSK Mode				
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402MHz	27	2429MHz	54	2456MHz
01	2403MHz	28	2430MHz	55	2457MHz
02	2404MHz	29	2431MHz	56	2458MHz
03	2405MHz	30	2432MHz	57	2459MHz
04	2406MHz	31	2433MHz	58	2460MHz
05	2407MHz	32	2434MHz	59	2461MHz
06	2408MHz	33	2435MHz	60	2462MHz
07	2409MHz	34	2436MHz	61	2463MHz
08	2410MHz	35	2437MHz	62	2464MHz
09	2411MHz	36	2438MHz	63	2465MHz
10	2412MHz	37	2439MHz	64	2466MHz
11	2413MHz	38	2440MHz	65	2467MHz
12	2414MHz	39	2441MHz	66	2468MHz
13	2415MHz	40	2442MHz	67	2469MHz
14	2416MHz	41	2443MHz	68	2470MHz
15	2417MHz	42	2444MHz	69	2471MHz
16	2418MHz	43	2445MHz	70	2472MHz
17	2419MHz	44	2446MHz	71	2473MHz
18	2420MHz	45	2447MHz	72	2474MHz
19	2421MHz	46	2448MHz	73	2475MHz
20	2422MHz	47	2449MHz	74	2476MHz
21	2423MHz	48	2450MHz	75	2477MHz
22	2424MHz	49	2451MHz	76	2478MHz
23	2425MHz	50	2452MHz	77	2479MHz
24	2426MHz	51	2453MHz	78	2480MHz
25	2427MHz	52	2454MHz		
26	2428MHz	53	2455MHz		

3.4 Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level, Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively

Pre-test Mode	Description
	·
Mode 1	GFSK CH00/CH39/CH78
Mode 2	Pi/4-DQPSK CH00/CH39/CH78
Mode 3	8-DPSK CH00/CH39/CH78

Note:

The measurements are performed at the highest, middle, lowest available channels.

3.5 Table of Parameters of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level, the RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth.

Test software Version	Test channels		
GFSK Mode	2402MHz	2441MHz	2480MHz
π/4-DQPSK	2402MHz	2441MHz	2480MHz
8-DPSK	2402MHz	2441MHz	2480MHz

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4:2009, Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4:2009.

3.6 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110 10.495 - 0.505 2.1735 - 2.1905 4.125 - 4.128 4.17725 - 4.17775 4.20725 - 4.20775 6.215 - 6.218 6.26775 - 6.26825 6.31175 - 6.31225 8.291 - 8.294 8.362 - 8.366 8.37625 - 8.38675 8.41425 - 8.41475 12.29 - 12.293 12.51975 - 12.52025	16.42 - 16.423 16.69475 - 16.69525 16.80425 - 16.80475 25.5 - 25.67 37.5 - 38.25 73 - 74.6 74.8 - 75.2 108 - 121.94 123 - 138 149.9 - 150.05 156.52475 - 156.52525 156.7 - 156.9 162.0125 - 167.17 167.72 - 173.2 240 - 285	399.9 - 410 608 - 614 960 - 1240 1300 - 1427 1435 - 1626.5 1645.5 - 1646.5 1660 - 1710 1718.8 - 1722.2 2200 - 2300 2310 - 2390 2483.5 - 2500 2655 - 2900 3260 - 3267 3332 - 3339 3345.8 - 3358	4.5 - 5.15 5.35 - 5.46 7.25 - 7.75 8.025 - 8.5 9.0 - 9.2 9.3 - 9.5 10.6 - 12.7 13.25 - 13.4 14.47 - 14.5 15.35 - 16.2 17.7 - 21.4 22.01 - 23.12 23.6 - 24.0 31.2 - 31.8 36.43 - 36.5
12.57675 - 12.57725 13.36 - 13.41	322 - 335.4	3600 - 4400	(-)

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

² Above 38.6

4. SETUP OF EQUIPMENT UNDER TEST

4.1 SUPPORT EQUIPMENT

Device Type	Manufacturer	Model Name	Serial No.	Data Cable	Power Cable
Notebook	Lenovo	E425	R9-KZL4B	1.6m Un-shielded	1.8m Un-shielded

Remark:

All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.2 TEST EQUIPMENT LIST

Instrumentation: The following list contains equipment used at Most for testing. The equipment conforms to the CISPR 16-1 / ANSI C63.2 Specifications for Electromagnetic Interference and Field Strength Instrumentation from 10 kHz to 1.0 GHz or above.

No.	Equipment	z to 1.0 GHz or above Manufacturer	Model No.	S/N	Calculator	Calculator
1	Test Receiver	Rohde & Schwarz	ESCI	100492	date 2014/03/10	Interval 1 Year
2	L.I.S.N.	Rohde & Schwarz	ENV216	100093	2014/03/10	1 Year
3	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2014/03/10	1 Year
4	Terminator	Hubersuhner	50Ω	No.1	2014/03/07	1 Year
5	RF Cable	SchwarzBeck	N/A	No.1	2014/03/07	1 Year
6	Test Receiver	Rohde & Schwarz	ESPI	101202	2014/03/07	1 Year
7		Sunol	JB3	A121206	2014/03/10	1 Year
8	Bilog Antenna Horn Antenna	SCHWARZBECK	BBHA9120D	756	2014/03/14	1 Year
9	Horn Antenna		9034	8376	2014/03/14	1 Year
10	Cable	Penn Engineering	9034 N/A	NO.1		1 Year
11	Cable	Resenberger SchwarzBeck	N/A N/A	NO.1	2014/03/07	1 Year
		SchwarzBeck				
12	Cable		N/A	NO.3	2014/03/07	1 Year
13	DC Power Filter	DuoJi	DL2×30B	N/A	2014/03/07	1 Year
14	Single Phase Power Line Filter	DuoJi	FNF 202B30	N/A	2014/03/07	1 Year
15	3 Phase Power Line Filter	DuoJi	FNF 402B30	N/A	2014/03/07	1 Year
16	Test Receiver	Rohde & Schwarz	ESCI	100492	2014/03/10	1 Year
17	Absorbing Clamp	Luthi	MDS21	3635	2014/03/12	1 Year
18	Coaxial Switch	Anritsu Corp	MP59B	6200283933	2014/03/07	1 Year
19	AC Power Source	Kikusui	AC40MA	LM003232	2014/03/10	1 Year
20	Test Analyzer	Kikusui	KHA1000	LM003720	2014/03/10	1 Year
21	Line Impendence Network	Kikusui	LIN40MA- PCR-L	LM002352	2014/03/10	1 Year
22	ESD Tester	Kikusui	KES4021	LM003537	2014/03/07	1 Year
23	EMCPRO System	EM Test	UCS-500-M4	V0648102026	2014/03/10	1 Year
24	Signal Generator	IFR	2032	203002/100	2014/03/10	1 Year
25	Amplifier	A&R	150W1000	301584	2014/03/14	1 Year
26	CDN	FCC	FCC-801-M2-25	47	2014/03/10	1 Year
27	CDN	FCC	FCC-801-M3-25	107	2014/03/10	1 Year
28	EM Injection Clamp	FCC	F-203I-23mm	403	2014/03/10	1 Year
29	RF Cable	MIYAZAKI	N/A	No.1/No.2	2014/03/10	1 Year
30	Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	0304789	2014/03/10	1 Year
31	Telecommunication Antenna	European Antennas	PSA 75301R/170	0304213	2014/03/10	1 Year
32	Telecommunication Test Equipment	R&S	CMU200	N/A	2014/03/07	1 Year
33	8 Loop Antenna	ARA	PLA-1030/B	1029	2014/02/19	1 Year
34	Power Meter	R&S	NRVS	100696	2014/07/06	1 Year
35	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014/07/06	1 Year

NOTE: Equipments listed above have been calibrated and are in the period of validation.

5. 47 CFR Part 15C 15.249 Requirements

5.1 Spurious Emission Test

5.1.1 Requirement

According to FCC section 15.249(a):

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

According to FCC section 15.109 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


In the above emission table, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3


5.1.2 Test Description

Test Setup:


From 9KHz to 30MHz:



From 30MHz to 1GHz:



Above 1GHz:



5.1.3 Test Description

- 1. The EUT is placed on a turntable, which is 0.8m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Set the spectrum analyzer in the following setting as:

Below 1GHz: RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz PEAK: RBW=VBW=1MHz / Sweep=AUTO

AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.

5.1.4 Test Result

From 9 KHz to 30MHz:

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	al Fs	Peak Limit	AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
N/A	Н								>20
N/A	V								>20

-Note: No test data was detected in below 30MHz.

From 30MHz to 1GHz:

The following test mode(s) were scanned during the preliminary test:

Preliminary Radiated Emission Test										
Frequency Range Investigated 9KHz TO 26 GHz										
Mode of operation	Date	Report No.	Data#	Worst Mode						
Charging+ BT Mode	2014-10-11	MTE/SAL/F14101362	SP58114_1_(V, H)	\boxtimes						

Note:

The GFSK Low channel modulation type was the worst case condition, The worse test data was shown on the summary data page.



 $\label{eq:Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong , China$

Tel: 0755-86026850 Fax: 0755-26013350

Radiated Emission Measurement File:SP58114 Data :#5 Date: 2014-10-11 Time: 16:23:11 70.0 dBuV/m Margin: 60 50 40 30 20 10 0 -10.0 30.000 1000.000 60 70 80 300 500 600 700 40 (MHz) 400

Site Chamber #1

Limit: FCC Part15 B 3M Radiation

EUT: Bluetooth Speaker

M/N: SP58114 Mode: Charging+BT

Note:

Polarization: *Horizontal* Temperature: 26
Power: DC 5.0V by USB Port Humidity: 50 %

Distance: 3m

No.	MI	k. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBu∨	dB	dBu∨/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	80.3619	24.64	11.40	36.04	40.00	-3.96	QР			
2		160.9089	17.70	17.29	34.99	43.50	-8.51	QР			
3	ļ	216.0240	25.56	16.14	41.70	46.00	-4.30	QP			
4		240.8303	22.71	17.22	39.93	46.00	-6.07	QP			
5	ļ	416.1791	21.05	19.65	40.70	46.00	-5.30	QP			
6	ļ	444.8810	20.50	20.20	40.70	46.00	-5.30	QP			

Cesc

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China

Tel: 0755-86026850 Fax: 0755-26013350

Radiated Emission Measurement File:SP58114 Data :#6 Date: 2014-10-11 Time: 16:38:55 70.0 dBuV/m Margin: 60 50 40 30 20 10 0 -10.0 30.000 500 1000.000 60 70 80 (MHz) 300 600 700 40 400

Polarization: Vertical

Power: DC 5.0V by USB Port

Site Chamber #1

Limit: FCC Part15 B 3M Radiation

EUT: Bluetooth Speaker

614.2142

M/N: |SP58114 Mode: Charging+BT

Note:

6

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		81.7833	17.38	11.40	28.78	40.00	-11.22	QP			
2	2	216.0240	19.35	16.14	35.49	46.00	-10.51	QΡ			
3	4	26.5210	14.74	20.20	34.94	46.00	-11.06	QP			
4	4	147.9822	19.11	20.14	39.25	46.00	-6.75	QΡ			
5	* 5	31.9635	17.31	22.12	39.43	46.00	-6.57	QP			

46.00

-8.38

QΡ

14.30

23.32

37.62

Temperature: 26

50 %

Humidity:

Distance: 3m

^{*:}Maximum data x:Over limit !:over margin

Above 1 GHz

Operation Mode: GFSK Mode/CH Low Test Date: Oct. 11, 2014

Temperature: 20°C Tested by: Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actual Fs		Peak Limit	AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2402.00	Н	80.99	68.58	16.25	97.24	84.83	114.00	94.00	-9.17
4804.00	Н	29.23	19.17	20.18	49.41	39.35	74.00	54.00	-14.65
N/A									>20
2402.00	V	80.30	71.18	16.25	96.55	87.43	114.00	94.00	-6.57
4804.00	V	29.44	23.81	20.18	49.62	43.99	74.00	54.00	-10.01
N/A									>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: GFSK Mode/CH Mid Test Date: Oct. 11, 2014

Temperature: 20°C Tested by: Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2441.00	Н	80.45	69.88	17.01	97.46	86.89	114.00	94.00	-7.11
4882.00	Н	28.62	22.32	21.57	50.19	43.89	74.00	54.00	-10.11
N/A									>20
2441.00	V	81.14	70.32	17.01	98.15	87.33	114.00	94.00	-6.67
4882.00	V	32.51	20.79	21.57	54.08	42.36	74.00	54.00	-11.64
N/A									>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: GFSK Mode/CH High Test Date: Oct. 11, 2014

Temperature: 20°C Tested by: Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2480.00	Н	80.57	69.82	17.24	97.81	87.06	114.00	94.00	-6.94
4960.00	Н	29.96	21.26	21.57	51.53	42.83	74.00	54.00	-11.17
N/A									>20
2480.00	٧	79.77	71.32	17.24	97.01	88.56	114.00	94.00	-5.44
4960.00	V	29.51	19.56	21.57	51.08	41.13	74.00	54.00	-12.87
N/A		·							>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: π / 4-DQPSK/CH Low **Test Date:** Oct. 11, 2014

Temperature: 20°C Tested by: Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2402.00	Н	80.78	70.53	16.25	97.03	86.78	114.00	94.00	-7.22
4804.00	Н	30.58	19.55	20.18	50.76	39.73	74.00	54.00	-14.27
N/A									>20
2402.00	V	78.81	68.59	16.25	95.06	84.84	114.00	94.00	-9.16
	·								
4804.00	V	26.21	21.92	20.18	46.39	42.10	74.00	54.00	-11.90
N/A									>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: π / 4-DQPSK/CH Mid **Test Date:** Oct. 11, 2014

Temperature: 20°C Tested by: Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Ant. / CL Reading CF		Actual Fs		Peak Limit	AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2441.00	Н	79.82	70.58	17.01	96.83	87.59	114.00	94.00	-6.41
4882.00	Н	29.73	20.78	21.57	51.30	42.35	74.00	54.00	-11.65
N/A									>20
2441.00	V	78.62	69.28	17.01	95.63	86.29	114.00	94.00	-7.71
4882.00	V	28.49	21.29	21.57	50.06	42.86	74.00	54.00	-11.14
N/A									>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: π / 4-DQPSK Mode /CH High **Test Date:** Oct. 11, 2014

Temperature: 20°C Tested by: Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2480.00	Η	80.34	70.62	17.24	97.58	87.86	114.00	94.00	-6.14
	-				-	-			
4960.00	Η	28.96	23.65	21.57	50.53	45.22	74.00	54.00	-8.78
N/A									>20
2480.00	V	79.69	69.39	17.24	96.93	86.63	114.00	94.00	-7.37
4960.00	V	30.66	19.70	21.57	52.23	41.27	74.00	54.00	-12.73
N/A									>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: 8-DPSK Mode /CH Low Test Date: Oct. 11, 2014

Temperature: 20°C **Tested by:** Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2402.00	Н	78.50	69.52	16.25	94.75	85.77	114.00	94.00	-8.23
	-					-			
4804.00	Н	26.76	20.38	20.18	46.94	40.56	74.00	54.00	-13.44
N/A									>20
2402.00	V	79.56	70.08	16.25	95.81	86.33	114.00	94.00	-7.67
						· · · · · · · · · · · · · · · · · · ·		•	
4804.00	V	27.57	21.44	20.18	47.75	41.62	74.00	54.00	-12.38
N/A									>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: 8-DPSK Mode /CH Mid Test Date: Oct. 11, 2014

Temperature: 20°C Tested by: Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2441.00	Н	79.74	70.49	17.01	96.75	87.5	114.00	94.00	-6.50
4882.00	Η	28.87	20.86	21.57	50.44	42.43	74.00	54.00	-11.57
N/A									>20
2441.00	V	78.81	69.69	17.01	95.82	86.70	114.00	94.00	-7.30
	•								•
4882.00	V	28.03	20.48	21.57	49.60	42.05	74.00	54.00	-11.95
N/A		·							>20

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode: 8-DPSK Mode /CH High Test Date: Oct. 11, 2014

Temperature: 20°C **Tested by:** Allen

Humidity: 70 % RH **Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading	AV Reading	Ant. / CL CF	Actu	Actual Fs		AV Limit	AV Margin
		(dBuV)	(dBuV)	(dB)	Peak	AV	(dBuV/m)	(dBuV/m)	(dB)
					(dBuV/m)	(dBuV/m)			
2480.00	Н	79.77	69.67	17.24	97.01	86.91	114.00	94.00	-7.09
	-				-	-		-	
4960.00	Н	27.65	20.91	21.57	49.22	42.48	74.00	54.00	-11.52
N/A									>20
2480.00	V	80.39	69.87	17.24	97.63	87.11	114.00	94.00	-6.89
4960.00	V	30.16	21.25	21.57	51.73	42.82	74.00	54.00	-11.18
N/A			·						>20


- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
- 4. Spectrum setting:
 - a. Peak Setting 1GHz 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.
 - b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

5.2 Band Edge

5.2.1 Requirement

According to FCC section 15.249(a), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.2.2 Test Description




5.2.3Test Result

The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China Tel: 0755-86170306 Fax: 0755-86170310



Site site #1

Limit: FCC 1000M-18000M PEAK

EUT: Bluetooth Speaker

M/N: SP58114 Mode: Low CH Note: GFSK

Power: DC 5V by USB port

Polarization: Vertical

Temperature: 26 Humidity: 61 %


Distance:

No. Mk	. Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
	MHz	dBu√	dB	dBuV/m	dBu√/m	dB	Detector	cm	degree	Comment
1	2390.000	36.02	10.36	46.38	74.00	-27.62	peak			
2 *	2390.000	29.84	10.36	40.20	54.00	-13.80	AVG			

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China Tel: 0755-86170306 Fax: 0755-86170310



Site site #1

Limit: FCC 1000M-18000M PEAK

EUT: Bluetooth Speaker

M/N: SP58114 Mode: Low CH Note: GFSK

Temperature: 26 Polarization: Horizontal Power: DC 5V by USB port Humidity:

Distance:

61 %

N	o. N	1k.	Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
			MHz	dBu√	dB	dBuV/m	dBu√/m	dB	Detector	cm	degree	Comment
	1	2	390.000	36.10	10.36	46.46	74.00	-27.54	peak			
	2 *	2	390.000	29.87	10.36	40.23	54.00	-13.77	AVG			

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement Time: 09:20:52 File:SP58114 Data:#15 Date: 2014-10-13 102.0 dBuV/m AVG: 92 82 72 62 52 42 32 22.0 2478.000 2480.20 2482.40 2484.60 2486.80 2489.00 2491.20 2493.40 2495.60 2500.00 MHz

Site site #1 Polarization: Vertical
Limit: FCC 1000M-18000M PEAK Power: DC 5V by USB port

EUT: Bluetooth Speaker Distance:

M/N: SP58114 Mode: High CH Note: GFSK

No	. Mk	k. Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
		MHz	dBu√	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
		2483.500	38.65	10.73	49.38	74.00	-24.62	peak			
- 2	*	2483.500	32.36	10.73	43.09	54.00	-10.91	AVG			

Temperature: 26

61 %

Humidity:

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement Time: 09:21:09 File:SP58114 Data:#16 Date: 2014-10-13 102.0 dBuV/m AVG: 92 82 72 62 52 42 32 22.0 2478.000 2480.20 2482.40 2484.60 2486.80 2489.00 2491.20 2493.40 2495.60 2500.00 MHz

Temperature: 26 Site site #1 Polarization: Horizontal Limit: FCC 1000M-18000M PEAK

EUT: Bluetooth Speaker

M/N: SP58114 Mode: High CH Note: GFSK

Power: DC 5V by USB port

Humidity: 61 %


Distance:

No.	Mk	. Freq.		Correct Factor	Measure- ment	Limit	Over		Antenna Height		
		MHz	dBuV	dB	dBu∨/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2483.500	35.97	10.73	46.70	74.00	-27.30	peak			
2	*	2483.500	29.73	10.73	40.46	54.00	-13.54	AVG			

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310



Site site #1 Polarization: Horizontal
Limit: FCC 1000M-18000M PEAK Power: DC 5V by USB port

EUT: Bluetooth Speaker Distance:

M/N: SP58114 Mode: Low CH Note: Pi/4-DQPSK

No.	Mk	. Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
		MHz	dBuV	dB	dBuV/m	dBu√/m	dB	Detector	cm	degree	Comment
1		2390.000	35.61	10.36	45.97	74.00	-28.03	peak			
2	*	2390.000	29.17	10.36	39.53	54.00	-14.47	AVG			

Roy

Temperature: 26


61 %

Humidity:

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310



Site site #1

Limit: FCC 1000M-18000M PEAK

EUT: Bluetooth Speaker

M/N: SP58114 Mode: Low CH Note: Pi/4-DQPSK Polarization: Vertical

Power: DC 5V by USB port

Temperature: 26

Humidity: 61 %

Distans

Distance:

No.	MI	k. Fr				Measure- ment	Limit	Over		Antenna Height		
		MH	łz	dBu√	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2390.0	00	37.37	10.36	47.73	74.00	-26.27	peak			
2	*	2390.0	00	31.06	10.36	41.42	54.00	-12.58	AVG			

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement Time: 09:58:51 File:SP58114 Data:#23 Date: 2014-10-13 102.0 dBuV/m AVG: 92 82 72 62 52 42 32 22.0 2478.000 2480.20 2482.40 2484.60 2486.80 2489.00 2491.20 2493.40 2495.60 2500.00 MHz

Site site #1

Limit: FCC 1000M-18000M PEAK

EUT: Bluetooth Speaker

M/N: SP58114 Mode: High CH Note: Pi/4-DQPSK Polarization: Horizontal

Power: DC 5V by USB port

ort

Temperature: 26 Humidity: 61 %


Distance:

No. MI	k. Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
	MHz	dBu√	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	2483.500	39.51	10.73	50.24	74.00	-23.76	peak			
2 *	2483.500	33.18	10.73	43.91	54.00	-10.09	AVG			

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China Tel: 0755-86170306 Fax: 0755-86170310



Site site #1

Limit: FCC 1000M-18000M PEAK

EUT: Bluetooth Speaker

M/N: SP58114 Mode: High CH Note: Pi/4-DQPSK Polarization: Vertical

Power: DC 5V by USB port

Temperature: 26 Humidity: 61 %

Distance:

N	Ο.	Mk	. Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
			MHz	dBu√	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
	1		2483.500	39.77	10.73	50.50	74.00	-23.50	peak			
	2	*	2483.500	33.26	10.73	43.99	54.00	-10.01	AVG			

Roy

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement Time: 09:36:42 File:SP58114 Data:#19 Date: 2014-10-13 102.0 dBuV/m AVG: 92 82 72 62 52 42 32 22.0 2310.000 2319.50 2329.00 2338.50 2348.00 2357.50 2367.00 2376.50 2386.00 2405.00 MHz

Site site #1

Limit: FCC 1000M-18000M PEAK EUT: Bluetooth Speaker

M/N: SP58114 Mode: Low CH Note: 8-DPSK Polarization: Horizontal

Power: DC 5V by USB port

Humidity.

Distance:

Temperature: 26

61 %


No. M	<. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height		
	MHz	dBu√	dB	dBu∨/m	dBuV/m	dB	Detector	cm	degree	Comment
1	2390.000	36.32	10.36	46.68	74.00	-27.32	peak			
2 *	2390.000	30.04	10.36	40.40	54.00	-13.60	AVG			

Roy

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310



Site site #1 Polarization: Vertical
Limit: FCC 1000M-18000M PEAK Power: DC 5V by USB port

EUT: Bluetooth Speaker Distance:

M/N: SP58114 Mode: Low CH Note: 8-DPSK

No.	Mk	. Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
		MHz	dBu√	dB	dBuV/m	dBu√/m	dB	Detector	cm	degree	Comment
1		2390.000	35.96	10.36	46.32	74.00	-27.68	peak			
2	*	2390.000	29.65	10.36	40.01	54.00	-13.99	AVG			

Roy

Humidity:

61 %

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310

Radiated Emission Measurement Time: 09:26:48 File:SP58114 Data:#17 Date: 2014-10-13 102.0 dBuV/m AVG: 92 82 72 62 52 42 32 22.0 2478.000 2480.20 2482.40 2484.60 2486.80 2489.00 2491.20 2493.40 2495.60 2500.00 MHz

Site site #1

Limit: FCC 1000M-18000M PEAK

EUT: Bluetooth Speaker

M/N: SP58114 Mode: High CH Note: 8-DPSK Polarization: Horizontal

Power: DC 5V by USB port

Temperature: 26 Humidity: 61 %

Distance:


No. M	lk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height		
		MHz	dBu√	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	248:	3.500	40.34	10.73	51.07	74.00	-22.93	peak			
2 *	248:	3.500	33.86	10.73	44.59	54.00	-9.41	AVG			

Roy

^{*:}Maximum data x:Over limit !:over margin



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China
Tel: 0755-86170306 Fax: 0755-86170310



Site site #1 Polarization: Vertical Temperature: 26
Limit: FCC 1000M-18000M PEAK Power: DC 5V by USB port Humidity. 61 %

EUT: Bluetooth Speaker Distance:

M/N: SP58114 Mode: High CH Note: 8-DPSK

No. Mk	Freq.	Reading Level		Measure- ment	Limit	Over		Antenna Height		
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	2483.500	38.72	10.73	49.45	74.00	-24.55	peak			
2 *	2483.500	32.43	10.73	43.16	54.00	-10.84	AVG			

^{*:}Maximum data x:Over limit !:over margin


5.3 LINE CONDUCTED EMISSION TEST

5.3.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Eroguanov	Maximum RF Line Voltage						
Frequency	Q.P.(dBuV)	Average(dBuV)					
150kHz-500kHz	66-56	56-46					
500kHz-5MHz	56	46					
5MHz-30MHz	60	50					

^{**}Note: 1. the lower limit shall apply at the transition frequency.

5.3.2. BLOCK DIAGRAM OF TEST SETUP



^{2.} The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

5.3.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1) The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per FCC Part 15 (see Test Facility for the dimensions of the ground plane used). When the EUT is floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2) Support equipment, if needed, was placed as per FCC Part 15.
- 3) All I/O cables were positioned to simulate typical actual usage as per FCC Part 15.
- 4) The EUT received DC 5V by Adapter which received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5) All support equipments received power from a second LISN supplying power of AC 120V/60Hz, if any.
- 6) The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7) Analyzer / Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.
- 8) During the above scans, the emissions were maximized by cable manipulation.

5.3.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

EUT and support equipment was set up on the test bench as per step 9 of the preliminary test. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.

5.3.5. Test result

The following test mode(s) were scanned during the preliminary test:

Preliminary Conducted Emission Test									
Frequency Range In	vestigated	150KHz TO 30 MHz							
Mode of operation	Date	Report No.	Data#	Worst Mode					
Charging+ BT Mode	2014-10-09	MTE/SAL/F14101362	SP58114_1_(L, N)	\boxtimes					

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

Note:


The GFSK Low channel modulation type was the worst case condition, The worse test data was shown on the summary data page.

5.3.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China

Tel: 0755-86026850 Fax: 0755-26013350



Power: DC 5V by USB Port

Site MOST #1

Limit: FCC Part15 B Class B QP

EUT: Bluetooth Speaker

M/N: SP58114 Mode: BT+Charging

Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBu∨	dB	dBu∀	dBu∀	dB	Detector	Comment
1	0.2431	37.74	11.71	49.45	61.99	-12.54	QP	
2	0.2431	29.51	11.71	41.22	51.99	-10.77	AVG	
3	0.5175	33.70	10.00	43.70	56.00	-12.30	QP	
4	0.5175	25.19	10.00	35.19	46.00	-10.81	AVG	
5 *	0.5556	37.67	10.00	47.67	56.00	-8.33	QP	
6	0.5556	25.36	10.00	35.36	46.00	-10.64	AVG	
7	0.6164	37.09	10.00	47.09	56.00	-8.91	QР	
8	0.6164	27.62	10.00	37.62	46.00	-8.38	AVG	
9	1.3367	30.67	9.66	40.33	56.00	-15.67	QP	
10	1.3367	23.27	9.66	32.93	46.00	-13.07	AVG	
11	2.7845	20.34	9.78	30.12	56.00	-25.88	QP	
12	2.7845	11.28	9.78	21.06	46.00	-24.94	AVG	

^{*:}Maximum data x:Over limit !:over margin


Engineer Signature: Kang

Humidity: 45 %



Address:No.5,Langshan 2nd Rd., North Hi-Tech Industrial park Guangdong ,China

Tel: 0755-86026850 Fax: 0755-26013350



Power: DC 5V by USB Port

Site MOST #1

Limit: FCC Part15 B Class B QP

EUT: Bluetooth Speaker

M/N: SP58114 Mode: BT+Charging

Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
	MHz	dBu∨	dB	dBu∀	dBu∀	dB	Detector	Comment
1	0.2040	37.74	11.97	49.71	63.45	-13.74	QР	
2 *	0.2040	33.40	11.97	45.37	53.45	-8.08	AVG	
3	0.2472	35.35	11.69	47.04	61.85	-14.81	QP	
4	0.2472	28.17	11.69	39.86	51.85	-11.99	AVG	
5	0.5113	34.08	10.00	44.08	56.00	-11.92	QР	
6	0.5113	27.75	10.00	37.75	46.00	-8.25	AVG	
7	0.6097	35.02	10.00	45.02	56.00	-10.98	QР	
8	0.6097	26.16	10.00	36.16	46.00	-9.84	AVG	
9	1.1086	27.61	9.89	37.50	56.00	-18.50	QP	
10	1.1086	19.72	9.89	29.61	46.00	-16.39	AVG	
11	3.6770	25.04	10.68	35.72	56.00	-20.28	QP	
12	3.6770	18.10	10.68	28.78	46.00	-17.22	AVG	

^{*:}Maximum data x:Over limit !:over margin

Engineer Signature: Kang

Humidity: 45 %


5.4 20 dB Bandwidth

5.4.1 Definition

Intentional radiators operating under the alternative provisions to the general emission limits, as Contained in §§15.217 through 15.257 and in sub-part E of this part, must be designed to ensure that the 20 dB Bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific Rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

5.4.2 Block Diagram Of Test Setup


The EUT is powered by the Battery, is coupled to the Spectrum Analyzer (SA) through the Attenuator/DC Block. The path loss as the factor is calibrated to correct the reading. During the measurement, the EUT is activated and is set to operate at maximum power. The RF load attached to the EUT antenna terminal is 500hm.




5.4.3 Test Result


GFSK Modulation test result:

Channel	Frequency (MHz)	Test Result(kHz)
0	2402	851.062
39	2441	858.333
78	2480	861.067






CH MID




CH High

π / 4-DOPSK Modulation test result:


Channel	Frequency (MHz)	Test Result(MHz)
0	2402	1.326
39	2441	1.303
78	2480	1.296



CH Low




CH MID




CH High

8DPSK Modulation test result:


Channel	Frequency (MHz)	Test Result(MHz)
0	2402	1.257
39	2441	1.258
78	2480	1.242



CH Low



CH MID



CH High

5.4 Antenna Requirement

5.4.1 Definition

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device, An analysis of the EUT was performed to determine compliance with FCC Section 15.203. This section requires specific handling and control of antennas used for devices subject to regulations.

5.4.2 Evaluation Criteria

Section 15.203 of the rules states that the subject device must meet at least one of the following criteria:

- (a) Antenna must be permanently attached to the unit.
- (b) Antenna must use a unique type of connector to attach to the EUT.
- (c) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

5.4.3 Evaluation Results

The antenna used in this product is PCB antenna. The antenna is permanently attached. It is inaccessible to the user.

The EUT is therefore compliant with the regulation.

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP


CONDUCTED TEST SETUP



CE TEST SETUP



RE TEST SETUP





-----END OF REPORT-----