



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Navigation Device

Model: X4545 M20; X4545 M40

Trade Name: MEDION

Issued to

**Medion AG
Am Zehnthof 7745307, Essen, Germany**

Issued by

**Compliance Certification Services Inc.
No. 81-1, Lane 210, Pa-De 2nd Rd., Luchu Hsiang,
Taoyuan Shien, (338) Taiwan, R.O.C.
TEL: 886-3-324-0332
FAX: 886-3-324-5235
<http://www.ccsrf.com>
service@ccsrf.com**



Testing Laboratory
0363

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.



Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545 Date of Issue: February 1, 2010

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	February 1, 2010	Initial Issue	ALL	Celine Chou



TABLE OF CONTENTS

1 TEST RESULT CERTIFICATION	4
2 EUT DESCRIPTION	5
3 TEST METHODOLOGY	6
3.1. EUT CONFIGURATION	6
3.2. EUT EXERCISE	6
3.3. GENERAL TEST PROCEDURES	6
3.4. FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
3.5. DESCRIPTION OF TEST MODES	8
4 INSTRUMENT CALIBRATION	9
4.1. MEASUREMENT EQUIPMENT USED	9
4.2. MEASUREMENT UNCERTAINTY	10
5 FACILITIES AND ACCREDITATIONS	11
5.1. FACILITIES	11
5.2. EQUIPMENT	11
5.3. TABLE OF ACCREDITATIONS AND LISTINGS	12
6 SETUP OF EQUIPMENT UNDER TEST	13
6.1. SETUP CONFIGURATION OF EUT	13
6.2. SUPPORT EQUIPMENT	13
7 FCC PART 15.247 REQUIREMENTS	14
7.1. 20DB BANDWIDTH	14
7.2. PEAK POWER	18
7.3. AVERAGE POWER	20
7.4. BAND EDGES MEASUREMENT	21
7.5. FREQUENCY SEPARATION	30
7.6. NUMBER OF HOPPING FREQUENCY	32
7.7. TIME OF OCCUPANCY (DWELL TIME)	35
7.8. SPURIOUS EMISSIONS	47
7.9. POWERLINE CONDUCTED EMISSIONS	61
APPENDIX I RADIO FREQUENCY EXPOSURE	64
APPENDIX II PHOTOGRAPHS OF TEST SETUP	65



1 TEST RESULT CERTIFICATION

Applicant: Medion AG
Am Zehnthal 7745307, Essen, Germany

Equipment Under Test: Navigation Device

Trade Name: MEDION

Model: X4545 M20; X4545 M40

Date of Test: January 16 ~ 29, 2010

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2003 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Ethan Huang
Section Manager

Reviewed by:

Stan Lin
Supervisor



2 EUT DESCRIPTION

Product	Navigation Device		
Trade Name	MEDION		
Model Number	X4545 M20; X4545 M40		
Model Name Discrepancy	Client consigns only one sample to test (model number: X4545 M20). Therefore, the testing Lab. just guarantees the unit, which has been tested.		
EUT Power Rating	5VDC, 1A		
Power Adapter	PHIHONG	Model	PSAA05R-050
Power Adapter Power Rating	I/P: 100-240VAC, 50-60Hz, 0.3A O/P: 5VDC, 1A		
Car Charger	MiTAC	Model	CA-051-00U-00
Car Charger Power Rating	I/P: 12/24VDC, 800mA(Max) O/P: 5V, 1A (Max)		
Cradle	MEDION	Model	X4X4X ActiveCradle
Operating Frequency Range	2402 ~ 2480 MHz		
Transmit Power	0.42 dBm (1.10mW)		
Modulation Technique	GFSK; $\pi/4$ -DQPSK; 8DPSK		
Transmit Data Rate	GFSK for 1Mbps; $\pi/4$ -DQPSK for 2Mbps; 8DPSK for 3Mbps		
Number of Channels	79 Channels		
Antenna Specification	-0.24 dBi		
Antenna Designation	PIFA Antenna		

Remark:

1. The sample selected for test was production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **WCE-X4545** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3 TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 (2003) and FCC CFR 47 15.207, 15.209 and 15.247.

3.1. EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2. EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3. GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 (2003) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4 (2003).



3.4. FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5. DESCRIPTION OF TEST MODES

The EUT (model: X4545 M20) had been tested under operating condition and had been reported as worst case on this test report.

Test program used to control the EUT for staying in continuous transmitting mode was programmed.

Following channels were selected for the for radiated emission testing only as listed below:

Tested Channel	Modulation Type	Packet Type	Date Rate
Low, Mid, High	GFSK	DH 5	1
Low, Mid, High	8DPSK	DH 5	3

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz, which worst case was in normal link mode only.

For the power line conducted emissions test, the EUT has three charge modes, (USB charge mode, power adapter mode and car charger mode), after the preliminary test, the power adapter mode was found to the worst case and chosen for testing.

Channel Low (2402MHz), Mid (2441MHz) and High (2480MHz) with 1Mbps data rate was chosen for full testing.

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.



4 INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.1. MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY48250064	11/05/2010
Spectrum Analyzer	R&S	FSEB	825829/011	11/02/2010
Pre-Amplifier	HP	8447D	2944A06530	01/02/2011
Pre-Amplifier	HP	8449B	3008A01738	04/17/2010
EMI Test Receiver	SCHAFFNER	SCR 3501	436	01/26/2011
Loop Antenna	EMCO	6502	2356	05/28/2010
Bilog Antenna	SCHWAZBECK	VULB9160	3084	09/11/2010
Horn Antenna	EMCO	3115	00022250	05/08/2010
Turn Table	CCS	CC-T-1F	N/A	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R
Test S/W	LabVIEW 6.1 (Wugu Chamber EMI Test V1_4.5.3)			

Conducted Emission Test site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY48250064	11/05/2010
Spectrum Analyzer	R&S	FSEB	825829/011	11/02/2010
USB Power Sensor	BOONTON	52012	2061194	06/08/2010



Powerline Conduction Emission Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	845552/030	04/08/2010
LISN	R&S	ENV216	100074	12/09/2010
LISN	FCC	FCC-LISN-50/250-16-2-07	06013	10/12/2010
Test S/W		CCS-3A1-CE		

4.2. MEASUREMENT UNCERTAINTY

Parameter	Uncertainty
Powerline Conducted Emission	±1.7806
3M Semi Anechoic Chamber / 30MHz ~ 1GHz	±4.0235
3M Semi Anechoic Chamber / Above 1GHz	±3.8718

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.3. MEASUREMENT UNCERTAINTY

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [2] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 6 is based on such expansion factors.

Table 6: Maximum measurement uncertainty

Parameter	Uncertainty
RF frequency	$+/- 1 * 10^{-5}$
Total RF power conducted	$+/- 1,5$ dB
RF power density, conducted	$+/- 3$ dB
Spurious emissions, conducted	$+/- 3$ dB
All emissions, radiated	$+/- 6$ dB
Humidity	$+/- 5$ %
Temperature	$+/- 1$ °C
DC and low frequency voltages	$+/- 3$ %



5 FACILITIES AND ACCREDITATIONS

5.1. FACILITIES

All measurement facilities used to collect the measurement data are located at

- No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.
Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029
- No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan
Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045
- No. 81-1, Lane 210, Pa-De 2nd Rd., Luchu Hsiang, Taoyuan Shien, (338) Taiwan, R.O.C.
Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

5.2. EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



5.3. TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	CFR 47, FCC Part15/18, CISPR 22, EN 55022, ICES-003, AS/NZS CISPR 22, VCCI V-3, EN 55011, CISPR 11, IEC/EN 61000-4-2/3/4/5/6/8/11, EN 61000-6-1/2/3/4, EN 55024, CISPR 24, AS/NZS CISPR 24, AS/NZS 61000.6.2, EN 55014-1/-2, ETSI EN 300 386 v1.3.2/v1.3.3, IEC/EN 61000-3-2, AS/NZS 61000.3.2, IEC/EN 61000-3-3, AS/NZS 61000.3.3	 ACCREDITED No. 0824-01
USA	FCC MRA	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	 TW1026
Japan	VCCI	3/10 meter Open Area Test Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-2882/2541/2798/725/1868 C-402/747/912 T-321/325
Taiwan	TAF	EN 55014-1, CISPR 14, CNS 13781-1, EN 55013, CISPR 13, CNS 13439, EN 55011, CISPR 11, CNS 13803, PLMN09, IS2045-0, LP0002 FCC Part 27/90, Part 15B/C/D/E, RSS-192/193/210/310 ETSI EN 300 328/ 300 220-1/ 300 220-2/ 301 893/ 301 489-01/ 301 489-03/ 301 489-07 / 301 489-17/ 300 440-1/ 300 440-2 AS/NZS 4268, AS/NZS 4771 CISPR 22, EN 55022, CNS 13438, AS/NZS CISPR 22, VCCI, IEC/EN 61000-4-2/3/4/5/6/8/11, CNS 14676-2/3/4/5/6/8, CNS 14934-2/3, CNS 13783-1, CNS 13439, CNS 13803	 ilac-MRA Testing Laboratory 0363 TAF
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	SL2-IS-E-0014 / IN-E-0014 /A1-E-0014 /R1-E-0014 /R2-E-0014 /L1-E-0014
Canada	Industry Canada	RSS212, Issue 1	 IC 2324C-3 IC 2324C-5

Note: No part of this report may be used to claim or imply product endorsement by A2LA, TAF or other government agency.



6 SETUP OF EQUIPMENT UNDER TEST

6.1. SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2. SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	N/A						

****No any support equipment during the test.**

Remark: Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.




7 FCC PART 15.247 REQUIREMENTS

7.1. 20DB BANDWIDTH

LIMIT

None; for reporting purposes only.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=30kHz, VBW = 100kHz, Span = 3MHz, Sweep = auto.
4. Mark the peak frequency and 20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

TEST RESULTS


No non-compliance noted




Test Plot

GFSK Mode

20dB Bandwidth (CH Low)




20dB Bandwidth (CH Mid)






20dB Bandwidth (CH High)



Date: 28.JAN.2010 23:53:51

8DPSK Mode


20dB Bandwidth (CH Low)



Date: 28.JAN.2010 23:57:15




20dB Bandwidth (CH Mid)



Date: 28.JAN.2010 23:59:06

20dB Bandwidth (CH High)



Date: 29.JAN.2010 00:00:42




7.2. PEAK POWER

LIMIT

According to §15.247, the maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
2. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
3. According to §15.247(b) (4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted



TEST DATA

GFSK

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Test Result
Low	2402	0.21	0.00105	0.125	PASS
Mid	2441	-0.18	0.00096		PASS
High	2480	-1.87	0.00065		PASS

8DPSK

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Test Result
Low	2402	0.42	0.00110	0.125	PASS
Mid	2441	-0.34	0.00092		PASS
High	2480	-2.30	0.00059		PASS




7.3. AVERAGE POWER

LIMIT

None; for reporting purposes only.

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer. The Spectrum Analyzer is set to the average power detection.

TEST RESULTS

No non-compliance noted

TEST DATA

GFSK

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2402	-1.36	0.00073
Mid	2441	-1.59	0.00069
High	2480	-3.28	0.00047

8DPSK


Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2402	-2.76	0.00053
Mid	2441	-3.60	0.00044
High	2480	-5.52	0.00028

7.4. BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of thsnder this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=100ms
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

No non-compliance noted

TEST DATA


Refer to attach spectrum analyzer data chart.



Band Edges (Bluetooth GFSK / CH Low)


Detector mode: Peak

Polarity: Vertical



Detector mode: Average


Polarity: Vertical






Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal






Band Edges (Bluetooth GFSK / CH High)


Detector mode: Peak

Polarity: Vertical



Detector mode: Average


Polarity: Vertical






Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal






Band Edges (Bluetooth 8DPSK / CH Low)


Detector mode: Peak

Polarity: Vertical



Detector mode: Average


Polarity: Vertical






Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal






Band Edges (Bluetooth 8DPSK / CH High)


Detector mode: Peak

Polarity: Vertical



Detector mode: Average


Polarity: Vertical






Detector mode: Peak

Polarity: Horizontal



Detector mode: Average

Polarity: Horizontal






7.5. FREQUENCY SEPARATION

LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW = 30kHz, VBW = 100kHz, Span = 3MHz, Sweep = auto.
5. Max hold, mark 3 peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

TEST DATA

GFSK

Channel Separation (MHz)	two-thirds of the 20 dB bandwidth	Channel Separation Limit	Result
1.00	642	> 20dB Bandwidth or two-thirds of the 20 dB bandwidth	Pass

8DPSK


Channel Separation (MHz)	two-thirds of the 20 dB bandwidth	Channel Separation Limit	Result
1.00	866	> 20dB Bandwidth or two-thirds of the 20 dB bandwidth	Pass



Test Plot


Measurement of Channel Separation

GFSK



Date: 29.JAN.2010 09:15:27

8DPSK



Date: 29.JAN.2010 09:21:45




7.6. NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 15 hopping frequencies.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = auto and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = auto.
4. Set the spectrum analyzer as RBW, VBW=500kHz.
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

TEST DATA

Result (No. of CH)	Limit (No. of CH)	Result
79	>15	PASS




Test Plot


GFSK

Channel Number

2.4 GHz – 2.4415 GHz



2.4415 GHz – 2.4835 GHz







8DPSK

Channel Number

2.4 GHz – 2.4415 GHz



2.4415 GHz – 2.4835 GHz






7.7. TIME OF OCCUPANCY (DWELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=1MHz, Span = 0Hz, Sweep = 10ms.
5. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

No non-compliance noted



TEST DATA

GFSK

DH 1

CH Low: $0.381 * (1600/2)/79 * 31.60 = 121.92$ (ms)

CH Mid: $0.381 * (1600/2)/79 * 31.60 = 121.92$ (ms)

CH High: $0.385 * (1600/2)/79 * 31.60 = 123.20$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.381	121.92	31.60	400.00	PASS
Mid	0.381	121.92	31.60		PASS
High	0.385	123.20	31.60		PASS

DH 3

CH Low: $1.643 * (1600/4)/79 * 31.60 = 262.88$ (ms)

CH Mid: $1.643 * (1600/4)/79 * 31.60 = 262.88$ (ms)

CH High: $1.647 * (1600/4)/79 * 31.60 = 263.52$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.643	262.88	31.60	400.00	PASS
Mid	1.643	262.88	31.60		PASS
High	1.647	263.52	31.60		PASS

DH 5

CH Low: $2.906 * (1600/6)/79 * 31.60 = 309.97$ (ms)

CH Mid: $2.906 * (1600/6)/79 * 31.60 = 309.97$ (ms)

CH High: $2.908 * (1600/6)/79 * 31.60 = 310.19$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.906	309.97	31.60	400.00	PASS
Mid	2.906	309.97	31.60		PASS
High	2.908	310.19	31.60		PASS



8DPSK

DH 1

CH Low: $0.407 * (1600/2)/79 * 31.60 = 130.24$ (ms)

CH Mid: $0.407 * (1600/2)/79 * 31.60 = 130.24$ (ms)

CH High: $0.403 * (1600/2)/79 * 31.60 = 128.96$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.407	130.24	31.60	400.00	PASS
Mid	0.407	130.24	31.60		PASS
High	0.403	128.96	31.60		PASS

DH 3

CH Low: $1.645 * (1600/4)/79 * 31.60 = 263.20$ (ms)

CH Mid: $1.665 * (1600/4)/79 * 31.60 = 266.40$ (ms)

CH High: $1.665 * (1600/4)/79 * 31.60 = 266.40$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.645	263.20	31.60	400.00	PASS
Mid	1.665	266.40	31.60		PASS
High	1.665	266.40	31.60		PASS

DH 5

CH Low: $2.908 * (1600/6)/79 * 31.60 = 310.19$ (ms)

CH Mid: $2.908 * (1600/6)/79 * 31.60 = 310.19$ (ms)

CH High: $2.906 * (1600/6)/79 * 31.60 = 309.97$ (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.908	310.19	31.60	400.00	PASS
Mid	2.908	310.19	31.60		PASS
High	2.906	309.97	31.60		PASS




Test Plot

GFSK


DH 1

(CH Low)



Date: 29.JAN.2010 00:15:54


(CH Mid)



Date: 29.JAN.2010 00:19:33




(CH High)



Date: 29.JAN.2010 00:23:02

DH 3

(CH Low)



Date: 29.JAN.2010 00:17:04




Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545


Date of Issue: February 1, 2010

(CH Mid)



Date: 29.JAN.2010 00:20:29

(CH High)




Date: 29.JAN.2010 00:23:58




DH 5

(CH Low)



Date: 29.JAN.2010 00:18:22


(CH Mid)



Date: 29.JAN.2010 00:21:39



(CH High)




Date: 29.JAN.2010 00:24:56

8DPSK

DH 1

(CH Low)



Date: 29.JAN.2010 00:29:13




Compliance Certification Services Inc.


Report No: T100108104-RP1 FCC ID: WCE-X4545

Date of Issue: February 1, 2010

(CH Mid)




(CH High)






DH 3

(CH Low)



Date: 29.JAN.2010 00:30:15


(CH Mid)



Date: 29.JAN.2010 00:33:25




(CH High)



Date: 29.JAN.2010 00:36:31

DH 5

(CH Low)



Date: 29.JAN.2010 00:31:11




Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545


Date of Issue: February 1, 2010

(CH Mid)



Date: 29.JAN.2010 00:34:21

(CH High)



Date: 29.JAN.2010 00:37:40




7.8. SPURIOUS EMISSIONS

7.8.1 Conducted Measurement

LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted


TEST DATA

Refer to attach spectrum analyzer data chart.




Test Plot

GFSK / CH Low




GFSK / CH Mid






GFSK / CH High




8DPSK / CH Low






8DPSK / CH Mid



8DPSK / CH High





7.8.2 RADIATED EMISSIONS

LIMIT



- According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μ V/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

- In the emission table above, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

TEST CONFIGURATION**Below 1 GHz****Above 1 GHz**



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=100kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS

No non-compliance noted



TEST DATA

Below 1 GHz

Operation Mode: Normal Link

Test Date: January 29, 2010

Temperature: 18°C

Tested by: Alonso Lu

Humidity: 60 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
42.1250	V	QP	41.45	-13.55	27.90	40.00	-12.10
49.4000	V	QP	41.90	-13.77	28.13	40.00	-11.87
63.9500	V	QP	44.46	-16.66	27.80	40.00	-12.20
163.3750	V	QP	46.20	-13.21	32.99	43.50	-10.51
173.0750	V	QP	45.35	-13.99	31.36	43.50	-12.14
182.7750	V	QP	47.13	-14.66	32.47	43.50	-11.03
386.4750	V	QP	36.24	-9.52	26.72	46.00	-19.28
786.6000	V	QP	33.48	-2.16	31.32	46.00	-14.68
903.0000	V	QP	36.96	0.36	37.32	46.00	-8.68
136.7000	H	QP	44.32	-12.95	31.37	43.50	-12.13
163.3750	H	QP	45.34	-13.21	32.13	43.50	-11.37
182.7750	H	QP	50.43	-14.66	35.77	43.50	-7.73
187.6250	H	QP	49.77	-14.88	34.89	43.50	-8.61
231.3120	H	QP	44.32	-14.21	30.11	46.00	-15.89
257.9500	H	QP	40.49	-12.32	28.17	46.00	-17.83
321.0000	H	QP	39.72	-10.52	29.20	46.00	-16.80
386.4750	H	QP	40.67	-9.52	31.15	46.00	-14.85
434.9750	H	QP	37.57	-8.65	28.92	46.00	-17.08
939.3750	H	QP	33.01	1.23	34.24	46.00	-11.76

Remark:

1. No emission found between lowest internal used / generated frequency to 30 MHz. (9kHz ~ 30MHz)
2. Measuring frequencies from 30 MHz to the 1GHz.
3. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.



Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545 Date of Issue: February 1, 2010

Above 1 GHz

GFSK

Operation Mode: TX / CH Low

Test Date: January 28, 2010

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 53 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1676.67	V	51.18	---	-2.79	48.39	---	74.00	54.00	-5.61	Peak
1863.33	V	50.47	---	-0.94	49.53	---	74.00	54.00	-4.47	Peak
2220.00	V	49.75	---	0.73	50.48	---	74.00	54.00	-3.52	Peak
2543.33	V	49.18	---	1.88	51.06	---	74.00	54.00	-2.94	Peak
3925.00	V	39.48	---	7.24	46.71	---	74.00	54.00	-7.29	Peak
4908.33	V	40.23	---	7.59	47.82	---	74.00	54.00	-6.18	Peak
6283.33	V	38.67	---	10.54	49.21	---	74.00	54.00	-4.79	Peak
2093.33	H	49.33	---	-1.71	47.62	---	74.00	54.00	-6.38	Peak
2316.67	H	50.03	---	-1.36	48.68	---	74.00	54.00	-5.32	Peak
2586.67	H	49.05	---	-0.00	49.05	---	74.00	54.00	-4.95	Peak
3675.00	H	41.49	---	6.04	47.53	---	74.00	54.00	-6.47	Peak
4808.33	H	41.09	---	7.73	48.82	---	74.00	54.00	-5.18	Peak
6108.33	H	39.59	---	9.87	49.46	---	74.00	54.00	-4.54	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545 Date of Issue: February 1, 2010

Operation Mode: TX / CH Mid

Test Date: January 28, 2010

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 53 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1760.00	V	50.21	---	-1.64	48.57	---	74.00	54.00	-5.43	Peak
1850.00	V	49.34	---	-0.95	48.39	---	74.00	54.00	-5.61	Peak
2203.33	V	49.39	---	0.79	50.18	---	74.00	54.00	-3.82	Peak
2486.67	V	49.30	---	2.28	51.58	---	74.00	54.00	-2.42	Peak
3891.67	V	39.76	---	7.15	46.92	---	74.00	54.00	-7.08	Peak
5300.00	V	38.73	---	9.50	48.23	---	74.00	54.00	-5.77	Peak
1723.33	H	49.80	---	-3.85	45.95	---	74.00	54.00	-8.05	Peak
2166.67	H	49.62	---	-1.98	47.63	---	74.00	54.00	-6.37	Peak
2300.00	H	49.26	---	-1.32	47.94	---	74.00	54.00	-6.06	Peak
2613.33	H	48.72	---	0.13	48.85	---	74.00	54.00	-5.15	Peak
3908.33	H	40.06	---	7.75	47.81	---	74.00	54.00	-6.19	Peak
4650.00	H	38.63	---	9.44	48.07	---	74.00	54.00	-5.93	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545 Date of Issue: February 1, 2010

Operation Mode: TX / CH High

Test Date: January 28, 2010

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 53 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1816.67	V	49.71	---	-0.97	48.74	---	74.00	54.00	-5.26	Peak
2130.00	V	49.72	---	-1.32	48.40	---	74.00	54.00	-5.60	Peak
2266.67	V	50.04	---	0.55	50.60	---	74.00	54.00	-3.40	Peak
2646.67	V	49.35	---	1.33	50.68	---	74.00	54.00	-3.32	Peak
7258.33	V	38.55	---	13.44	51.99	---	74.00	54.00	-2.01	Peak
N/A										
1430.00	H	50.62	---	-6.28	44.34	---	74.00	54.00	-9.66	Peak
2156.67	H	48.94	---	-1.92	47.03	---	74.00	54.00	-6.97	Peak
2613.33	H	47.95	---	0.13	48.08	---	74.00	54.00	-5.92	Peak
4958.33	H	40.63	---	8.75	49.39	---	74.00	54.00	-4.61	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



8DPSK

Operation Mode: TX / CH Low

Test Date: January 28, 2010

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 53 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1810.00	V	49.96	---	-0.97	48.99	---	74.00	54.00	-5.01	Peak
2240.00	V	49.94	---	0.65	50.59	---	74.00	54.00	-3.41	Peak
2476.67	V	49.75	---	2.16	51.92	---	74.00	54.00	-2.08	Peak
2753.33	V	49.03	---	1.31	50.35	---	74.00	54.00	-3.65	Peak
3925.00	V	39.06	---	7.24	46.30	---	74.00	54.00	-7.70	Peak
5075.00	V	39.90	---	6.19	46.09	---	74.00	54.00	-7.91	Peak
7183.33	V	38.08	---	13.81	51.89	---	74.00	54.00	-2.11	Peak
1720.00	H	50.00	---	-3.82	46.17	---	74.00	54.00	-7.83	Peak
2103.33	H	49.72	---	-1.57	48.15	---	74.00	54.00	-5.85	Peak
2310.00	H	49.39	---	-1.34	48.05	---	74.00	54.00	-5.95	Peak
2600.00	H	49.12	---	0.23	49.35	---	74.00	54.00	-4.65	Peak
4808.33	H	42.65	---	7.73	50.38	---	74.00	54.00	-3.62	Peak
5425.00	H	39.77	---	10.72	50.49	---	74.00	54.00	-3.51	Peak
6158.33	H	39.08	---	9.93	49.01	---	74.00	54.00	-4.99	Peak

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545 Date of Issue: February 1, 2010

Operation Mode: TX / CH Mid

Test Date: January 28, 2010

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 53 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1796.67	V	50.11	---	-1.03	49.08	---	74.00	54.00	-4.92	Peak
2216.67	V	48.13	---	0.74	48.87	---	74.00	54.00	-5.13	Peak
2570.00	V	48.83	---	1.55	50.37	---	74.00	54.00	-3.63	Peak
5425.00	V	39.86	---	9.05	48.90	---	74.00	54.00	-5.10	Peak
N/A										
1750.00	H	50.49	---	-4.03	46.47	---	74.00	54.00	-7.53	Peak
2126.67	H	49.23	---	-1.72	47.51	---	74.00	54.00	-6.49	Peak
2600.00	H	48.40	---	0.23	48.63	---	74.00	54.00	-5.37	Peak
4883.33	H	41.99	---	7.75	49.73	---	74.00	54.00	-4.27	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Compliance Certification Services Inc.

Report No: T100108104-RP1 FCC ID: WCE-X4545 Date of Issue: February 1, 2010

Operation Mode: TX / CH High

Test Date: January 28, 2010

Temperature: 16°C

Tested by: Alonso Lu

Humidity: 53 % RH

Polarity: Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1816.67	V	49.06	---	-0.97	48.09	---	74.00	54.00	-5.91	Peak
2200.00	V	49.19	---	0.80	49.99	---	74.00	54.00	-4.01	Peak
2440.00	V	49.66	---	1.74	51.40	---	74.00	54.00	-2.60	Peak
2550.00	V	49.64	---	1.80	51.44	---	74.00	54.00	-2.56	Peak
N/A										
2096.67	H	49.00	---	-1.63	47.37	---	74.00	54.00	-6.63	Peak
2253.33	H	50.29	---	-1.73	48.56	---	74.00	54.00	-5.44	Peak
2620.00	H	48.56	---	0.08	48.65	---	74.00	54.00	-5.35	Peak
4958.33	H	41.22	---	8.75	49.97	---	74.00	54.00	-4.03	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with “ N/A ” remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



7.9. POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

TEST CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.



TEST DATA

Operation Mode: Power Adapter Charging **Test Date:** January 16, 2010

Temperature: 25°C **Tested by:** Louis Shen

Humidity: 57% RH **Test**

Freq. (MHz)	QP Reading	AV Reading	Corr. factor	QP Result	AV Result	QP Limit	AV Limit	QP Margin	AV Margin	Note
0.3766	43.50	30.20	0.10	43.60	30.30	58.35	48.35	-14.75	-18.05	L1
0.4977	41.90	30.40	0.00	41.90	30.40	56.04	46.04	-14.14	-15.64	L1
0.5367	43.90	31.70	0.00	43.90	31.70	56.00	46.00	-12.10	-14.30	L1
0.6813	41.10	26.60	0.00	41.10	26.60	56.00	46.00	-14.90	-19.40	L1
0.8180	41.70	27.50	0.00	41.70	27.50	56.00	46.00	-14.30	-18.50	L1
0.8961	40.50	28.70	0.00	40.50	28.70	56.00	46.00	-15.50	-17.30	L1
0.4083	43.91	32.11	0.09	44.00	32.20	57.68	47.68	-13.68	-15.48	L2
0.5250	43.30	31.20	0.00	43.30	31.20	56.00	46.00	-12.70	-14.80	L2
0.8023	42.80	31.20	0.00	42.80	31.20	56.00	46.00	-13.20	-14.80	L2
0.9586	39.80	28.20	0.00	39.80	28.20	56.00	46.00	-16.20	-17.80	L2
1.2164	40.88	29.18	0.02	40.90	29.20	56.00	46.00	-15.10	-16.80	L2
2.9977	37.70	28.50	0.10	37.80	28.60	56.00	46.00	-18.20	-17.40	L2


Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. “--” denotes the emission level was or more than 2dB below the Average limit
4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
5. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)





APPENDIX I

RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

EUT SPECIFICATION

EUT	Navigation Device
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others <u>Bluetooth: 2.402GHz ~ 2.480GHz</u>
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	0.42 dBm (1.10mW)
Antenna gain (Max)	-0.24 dBi (Numeric gain: 0.95)
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation <input checked="" type="checkbox"/> N/A
Remark:	1. The maximum output power is <u>0.42dBm (1.10mW)</u> at <u>2402MHz</u> (with <u>1.26 numeric antenna gain</u> .)

TEST RESULTS

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(\text{GHz})} = 60/2.441 = 24.58\text{mW}$)
even if the calculation indicates that the power density would be larger.)