



# **Compliance Testing, LLC**

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

[info@ComplianceTesting.com](mailto:info@ComplianceTesting.com)

## **Test Report**

**Prepared for: Packet Power, LLC**

**Model: P5J6**

**Description: Smart Current Monitor**

**FCC ID: WCGP5J6**

**To**

**FCC Part 1.1310**

**Date of Issue: February 5, 2015**

**On the behalf of the applicant:**

**Packet Power, LLC  
2716 Summer St NE  
Minneapolis, MN 55413**

**Attention of:**

**Paul Bieganski, CTO  
Ph: (877)560-8770  
E-Mail: [paul@packetpower.com](mailto:paul@packetpower.com)**

**Prepared By  
Compliance Testing, LLC  
1724 S. Nevada Way  
Mesa, AZ 85204  
(480) 926-3100 phone / (480) 926-3598 fax  
[www.compliancetesting.com](http://www.compliancetesting.com)  
Project No: p14b0020**

**Alex Macon  
Project Test Engineer**

This report may not be reproduced, except in full, without written permission from Compliance Testing  
All results contained herein relate only to the sample tested



### Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	January 30, 2015	Alex Macon	Original Document



## ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

**Non-accredited tests contained in this report:**

N/A

### EUT Description

**Model:** EMB1

**Description:** Battery Powered Environmental Monitor

**Software:** NMX Packet Power URL

**Serial Number:** N/A

**Additional Information:**

The EUT is an inline voltage and current meter which incorporates a 2.4 GHz radio and a 900 MHz radio with an integral antenna.



### Average Power calculations

Average Power = Peak Power \* duty-cycle%

Tuned Frequency (MHz)	Radiated Peak Output Power (mW)	Duty Cycle	Average Power (mW)
902.4	0.163 mW	100%	mW
2464	0.277 mW	100%	mW

**Limits Uncontrolled Exposure**  
**47 CFR 1.1310**  
**Table 1, (B)**

0.3-1.234 MHz:	Limit [mW/cm <sup>2</sup> ] = 100
1.34-30 MHz:	Limit [mW/cm <sup>2</sup> ] = (180/f <sup>2</sup> )
30-300 MHz:	Limit [mW/cm <sup>2</sup> ] = 0.2
300-1500 MHz:	Limit [mW/cm <sup>2</sup> ] = f/1500
1500-100,000 MHz	Limit [mW/cm <sup>2</sup> ] = 1.0

927.6 MHz Limit is 0.6016 mW/cm<sup>2</sup>

2401 MHz limit is 1.0 mW/cm<sup>2</sup>

END OF TEST REPORT