

## MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended to comply with Section Part 22, subpart H and Part 24, subpart E and Part 27 subpart C & subpart L of the FCC CFR 47 Rules. And RSS-102 issue 4 For 47 CFR 1.1310 Radio frequency Radiation Exposure requirement.

### SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

### EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

### LIMITATION

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

\* = Plane-wave equipment power density

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m <sup>2</sup> )	Averaging Time (minutes)
0.003-1	280	2.19	-	6
1-10	280/f	2.19/f	-	6
10-30	28	2.19/f	-	6
30-300	28	0.073	2*	6
300-1500	1.585 f <sup>0.5</sup>	0.0042 f <sup>0.5</sup>	f/150	6
1500-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/f <sup>1.2</sup>
150000-300000	0.158 f <sup>0.5</sup>	4.21 x 10 <sup>-4</sup> f <sup>0.5</sup>	6.67 x 10 <sup>-5</sup> f	616000/f <sup>1.2</sup>

Note: f is frequency in MHz.

\* Power density limit is applicable at frequencies greater than 100 MHz.

In this application we seek approval to the 16/32 Ports VoIP GSM Gateway. Based on the FCC OET Bulletin 65 Supplement C and 47 CFR §2.1091, we have concluded MV-3716 , MV-3732 will comply with the FCC rules on RF exposure for mobile devices in cellular band and PCS band. The following analysis will demonstrate such compliance. The analysis will be done in two US bands.

Operation in cellular band (824.2 – 848.8 MHz)

The ERP of MV-3716 , MV-3732 in cellular band is 27.15dBm max at GSM 850 mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	ERP	Limit
		MHz		V/H	dBm	dBd	dB	dBm	dBm
GSM850	E2	824.2	128	V	21.00	3.96	-3.03	21.94	38.45
				H	25.08	3.96	-3.03	26.02	38.45
		836.6	190	V	23.01	4.00	-3.07	23.94	38.45
				H	26.22	4.00	-3.07	<b>27.15</b>	38.45
		848.8	251	V	22.13	4.03	-3.11	23.05	38.45
				H	24.64	4.03	-3.11	25.56	38.45

$$\text{ERP} = 27.15 \text{ dBm} = 518.80 \text{ mW}$$

$$\begin{aligned} \text{Power Density} &= \text{ERP} * \text{Duty Cycle} / (4 \pi R^2) \\ &= 518.80 * 0.125 / (4 * \pi * 20^2) = 0.012902 \text{ mW/cm}^2 \end{aligned}$$

where Duty Cycle is 0.125 for GSM operation and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 836.6 / 1500 = 0.56 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore MV-3716 , MV-3732 in cellular band is compliant with the FCC rules on RF exposure

### Operation in PCS band (1850.2 – 1909.8 MHz)

The EIRP of MV-3716 , MV-3732 in PCS band is 11.11dBm max at GSM 1900 mode. The resulted power density at a distance of 20 cm can be deducted as follows:

EUT				Measurement					
Operation Band	Pol.	Fundamental Frequency	CH	Antenna Pol.	S.G. Output	Antenna Gain	Cable Loss	EIRP	Limit
		MHz		V/H	dBm	dBi	dB	dBm	dBm
GSM 1900	E2	1850.2	512	V	8.56	4.17	-4.67	8.07	33.00
				H	0.82	4.51	-4.67	0.66	33.00
		1880.0	661	V	11.68	4.13	-4.70	<b>11.11</b>	33.00
				H	3.45	4.44	-4.70	3.19	33.00
		1909.8	810	V	11.22	4.10	-4.74	10.57	33.00
				H	3.92	4.36	-4.74	3.55	33.00

$$\text{EIRP} = 11.11 \text{ dBm} = 129.12 \text{ mW}$$

$$\text{Power Density} = \text{EIRP} * \text{Duty Cycle} / (4 \pi R^2)$$

$$= 129.12 * 0.25 / (4 * \pi * 20^2) = 0.003211 \text{ mW/cm}^2$$

where Duty Cycle is 0. 25 for GPRS operation (class 10) and R is 20 cm.

The MPE limit for General Population/Uncontrolled Exposure is shown in the FCC OET Bulletin 65 Supplement C and can be calculated as follows:

$$\text{MPE limit} = 1.0 \text{ mW/cm}^2$$

As we can see the resulted power density is below the MPE limit, therefore MV-3716 , MV-3732 in PCS band is compliant with the FCC rules on RF exposure.