

MRT Technology (Suzhou) Co., Ltd Phone: +86-512-66308358

e: +86-512-66308358 Report Version: www.mrt-cert.com Issue Date:

Report No.: 1909WSU012-U2 Report Version: V01 Issue Date: 11-18-2019

RF Exposure Evaluation Declaration

FCC ID: WDU-BPHP

APPLICANT: Nanjing Chervon Industry Co., Ltd

Application Type: Certification

Product: Batterypack

Model No.: 8709, BP 18 Li 4,0 HPC-ASI

FCC Classification: Digital Transmission System (DTS)

Test Procedure(s): KDB 447498 D01v06

Test Date: November 05, 2019

Reviewed By

(Kevin Guo

Approved By

Kevin Guo)

Robin Wu)





The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

FCC ID: WDU-BPHP Page Number: 1 of 8



Revision History

Report No.	Version	Description	Issue Date	Note
1909WSU012-U2	Rev. 01	Initial report	11-18-2019	Valid

FCC ID: WDU-BPHP Page Number: 2 of 8



§2.1033 General Information

Applicant:	Nanjing Chervon Industry Co., Ltd		
Applicant Address	529 Jiang-jun Rd., Jiangning Economic & Technical Development		
Applicant Address:	Zone, Nanjing, Jiangsu 211106 P.R. China		
Manufacturer: Nanjing Chervon Industry Co., Ltd			
Manufacturer Address:	529 Jiang-jun Rd., Jiangning Economic & Technical Development		
Manufacturer Address.	Zone, Nanjing, Jiangsu 211106 P.R. China		
Test Site:	MRT Technology (Suzhou) Co., Ltd		
Test Site Address:	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development		
	Zone, Suzhou, China		
Test Device Serial No.:	N/A Production Pre-Production Engineering		

Test Facility / Accreditations

Measurements were performed at MRT Laboratory located in Tian'edang Rd., Suzhou, China.

- MRT facility is a FCC registered (MRT Reg. No. 893164) test facility with the site description report on file and has met all the requirements specified in ANSI C63.4-2014.
- MRT facility is an IC registered (MRT Reg. No. 11384A-1) test laboratory with the site description on file at Industry Canada.
- MRT facility is a VCCI registered (R-20025, G-20034, C-20020, T-20020) test laboratory with the site description on file at VCCI Council.
- MRT Lab is accredited to ISO 17025 by the American Association for Laboratory Accreditation (A2LA) under the American Association for Laboratory Accreditation Program (A2LA Cert. No. 3628.01) in EMC, Telecommunications, Radio and SAR testing.



FCC ID: WDU-BPHP Page Number: 3 of 8



1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	Batterypack
Model No.:	8709, BP 18 Li 4,0 HPC-ASI
Bluetooth Version:	V4.0single mode

Note 1: Different models are for different customers, and there is the same design between these models

Note 2: Adapter (Model: ADS-12B-06 05010E) used for test is provided by manufacturer.

1.2. Product Specification

Bluetooth Frequency:	2402~2480MHz
Channel Number:	40
Type of modulation:	GFSK
Data Rate:	1Mbps
Antenna Type:	PCB Antenna
Antenna Gain:	0dBi

FCC ID: WDU-BPHP Page Number: 4 of 8



2. RF Exposure Evaluation

2.1. Limits

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in Note 1 must be applied to determine SAR test exclusion.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test
300	27	55	82	110	137	Exclusion
450	22	45	67	89	112	Threshold
835	16	33	49	66	82	(mW)
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	
MHz	30	35	40	45	50	mm
150	232	271	310	349	387	SAR Test
300	164	192	219	246	274	Exclusion
450	134	157	179	201	224	Threshold
835	98	115	131	148	164	(mW)
900	95	111	126	142	158	
1500	73	86	98	110	122	
1900	65	76	87	98	109	
2450	57	67	77	86	96	
3600	47	55	63	71	79	
5200	39	46	53	59	66	
5400	39	45	52	58	65	

Note: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

FCC ID: WDU-BPHP Page Number: 5 of 8



[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * $[\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 20°C and 75% RH.

FCC ID: WDU-BPHP Page Number: 6 of 8



2.3. Test Result of RF Exposure Evaluation

Product	Batterypack
Test Item	RF Exposure Evaluation

Output Power into Antenna:

Test Mode	Frequency Band	Maximum EIRP	Maximum EIRP	SAR Test Exclusion
	(MHz)	(dBm)	(mW)	Threshold (mW)
Bluetooth-LE	2402 ~ 2480	-1.46	0.7145	10

Per FCC KDB 447498 D01v06, the SAR exclusion threshold for distances<50mm is defined by the following equation:

$$\frac{Max\ Power\ of\ Channel\ (mW)}{Test\ Separation\ Dist\ (mm)}*\sqrt{Frequency(GHz)} \leq 3.0$$

Based on the maximum conducted power of Bluetooth and the antenna to use separation distance, Bluetooth SAR was not required;

$$[(0.7145 \text{mW/5})^* \sqrt{2.402}] = 0.2215 < 3.0$$

The Max
$$P_d = 0.2215 < 3.0$$

Note: When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

The End

FCC ID: WDU-BPHP Page Number: 7 of 8



Appendix A – EUT Photograph

Refer to "1909WSU012-UE" file.

FCC ID: WDU-BPHP Page Number: 8 of 8