



47 CFR PART 15 SUBPART B

TEST REPORT

of


Watch Phone

Model Name: M820, M810, M830
Brand Name: Rider
Report No.: SZ08050137E01
FCC ID: WELRIDERM820

prepared for

Rider Technology Industrial limited

Suite 1213, 12/F., Ocean Centre Harboor Ciry, 5canton Road, TST Kowloon, Hong kong



NOTE: This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

TABLE OF CONTENTS

1. TEST CERTIFICATION	3
2. GENERAL INFORMATION	4
2.1 EUT Description	4
2.2 Test Standards and Results	5
2.3 Facilities and Accreditations	6
2.3.1 Facilities	6
2.3.2 Test Environment Conditions.....	6
3. TEST CONDITIONS SETTING	7
3.1 Test Mode	7
3.2 Test Setup and Equipments List	8
3.2.1 Conducted Emission.....	8
3.2.2 Radiated Emission.....	9
4. 47 CFR PART 15B REQUIREMENTS	10
4.1 Conducted Emission	10
4.1.1 Requirement	10
4.1.2 Test Description	10
4.1.3 Test Result.....	10
4.2 Radiated Emission	13
4.2.1 Requirement	13
4.2.2 Test Description	13
4.2.3 Test Result.....	13

1. TEST CERTIFICATION

Equipment under Test: Watch Phone

Brand Name: Rider

Model Name: M820, M810, M830

FCC ID: WELRIDERM820

Applicant: Rider Technology Industrial limited

Suite 1213, 12/F., Ocean Centre Harboor Ciry, 5canton Road, TST
Kowloon, Hong kong

Manufacturer: Rider Technology Industrial limited

Suite 1213, 12/F., Ocean Centre Harboor Ciry, 5canton Road, TST
Kowloon, Hong kong

Emission Designator 300KGXW

Test Standards: 47 CFR Part 15 Subpart B

Test Date(s): June 4, 2008 –June 17, 2008

Test Result: PASS

* We Hereby Certify That:


The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by: Ni Yong Dated: 2008.06.20
Ni Yong

Reviewed by: Wei Yanquan Dated: 2008.06.20
Wei Yanquan

Approved by: Zeng Dexin Dated: 2008.06.20
Zeng Dexin



2. GENERAL INFORMATION

2.1 EUT Description

EUT Type Watch Phone
Model Name..... M820, M810, M830
Serial No. (n.a, marked #1 by test site)
IMEI IMEI:135790246811220 IMEISV:78
Hardware Version..... M1000_HW_V1.0
Software Version M1000_U2_TH9_V3.0
Modulation Type GMSK
Power Supply Battery
Brand name: (n.a)
Mode no.: M800
Capacitance: 400mAh
Rated voltage: 3.7V
Manufacturer: ZHONG GUANG INTERNATIONAL CO., LTD KENENG
COMMUNICATION ELECTRONICS CO., LTD
Manufacturer Address: 88XingwangRoad, Silian, HenggangStreet, Longgang,
Shen, P.R.China
Ancillary Equipment 1 ... AC Adapter (Charger for Battery)
Model Name: NBT-005A-B04
Brand Name: (n.a)
Serial No.: (n.a. marked #1 by test site)
Rated Input: ~ 100-240V, 0.15A,50/60Hz
Rated Output: == 5V, 500mA
Manufacturer: Shenzhen Nanbang Electronic Co., Ltd
Manufacturer Address: A1/f, Nan An Ke Ji Gong Ye Yuan, Haosi Nan Bu
Road, Shajing Town, Baoan, Shenzhen City. Guangdong, P.R.China.
Wire Length: 87cm
Declaration
The applicant declares that the model M820, M810 and M830 are accordant
in both hardware and software. Only shell change.

Note 1: The EUT is a Watch Phone; it supports GSM 850MHz, 1900MHz, GSM 850MHz and 1900MHz bands are tested in this report.

Note 2: A connecting between EUT and a System Simulator (SS) was established at the start of the test, and maintained during the all test in this report

Note 3: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-05 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE:

The tests were performed according to the method of measurements prescribed in ANSI C63.4 2003.

2.3 Facilities and Accreditations

2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	96-106

3. TEST CONDITIONS SETTING

3.1 Test Mode

During the measurement, there are four Test Modes that will be tested in Conducted Emission and Radiated Emission. These test modes are showed as below:

(1) The first test mode: traffic operating mode

The EUT configuration of the emission tests is EUT + Battery + Charger.

Before the measurement, the lithium battery was completely discharged.

During the measurement, the lithium battery was installed into the EUT, and the charger was connected to the EUT. A communication link was established between the EUT and a System Simulator (SS). The EUT operated at GSM 900MHz mid ARFCN (65) and maximum output power (level 5).

(2) The first test mode: idle mode

The EUT configuration of the emission tests is EUT + Battery + Charger.

Before the measurement, the lithium battery was completely discharged.

During the measurement, the lithium battery was installed into the EUT, and the charger was connected to the EUT. No communication link was established between the EUT and a System Simulator (SS).

(3) The second test mode

The EUT configuration of the emission tests is EUT + Battery + PC.

The EUT is connected with a PC via a special USB cable supplied by applicant. During the measurement, a communication link was established between the EUT and a System Simulator (SS), simultaneity, the date is transmitting between the PC and the EUT.


NOTE: The first test mode and the second test mode were both tested, and only the worst cases are recorded in this report..

The third test mode was only tested in Radiated Disturbance.

3.2 Test Setup and Equipments List

3.2.1 Conducted Emission

A. Test Setup:




The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2007.07	1year
LISN	Schwarzbeck	NSLK 8127	812744	2006.08	1year
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)
System Simulator	Agilent	E5515C	GB43130131	2007.06	1year
Personal Computer	HP	Pavilion ze2202	CNF5460DNL	(n.a.)	(n.a.)
Bluetooth-Headset	Nokia	HS-36W	(n.a.)	(n.a.)	(n.a.)
Wireless Router	(n.a.)	D-Link	BN64448000052	(n.a.)	(n.a.)
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)	(n.a.)

3.2.2 Radiated Emission

C. Test Setup:



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower. The Common Antenna is used for the call between the EUT and the System Simulator (SS).

D. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2007.07	1year
Full-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2006.08	2year
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2007.07	1year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2007.07	1year
System Simulator	Agilent	E5515C	GB43130131	2007.06	1year
Personal Computer	HP	Pavilion ze2202	CNF5460DNL	(n.a.)	(n.a.)
Wireless Router	(n.a.)	D-Link	BN64448000052	(n.a.)	(n.a.)
Bluetooth-Headset	Nokia	HS-36W	(n.a.)	(n.a.)	(n.a.)
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)	(n.a.)

4. 47 CFR PART 15B REQUIREMENTS

4.1 Conducted Emission

4.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

4.1.2 Test Description

See section 3.2.1 of this report.

4.1.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

4.1.3.1 The first test mode


The EUT configuration of the emission tests is EUT + Battery + Charger.

A. Test Verdict Recorded for Suspicious Points:

No.	@Frequency (MHz)	Measured Emission Level (dB μ V)				Limit (dB μ V)		Verdict
		PK	QP	AV	Phase	QP	AV	
1	0.611	49.1	44.9	34.1	L	56.0	46.0	PASS

No.	@Frequency (MHz)	Measured Emission Level (dB μ V)				Limit (dB μ V)		Verdict
		PK	QP	AV	Phase	QP	AV	
2	1.034	47.2	45.1	32.6	L	56.0	46.0	PASS
3	1.547	46.9	43.6	29.7	L	56.0	46.0	PASS
4	2.067	53.7	51.3	36.6	L	56.0	46.0	PASS
5	2.738	55.9	52.9	38.0	L	56.0	46.0	PASS
6	0.590	47.4	43.7	34.7	N	56.0	46.0	PASS
7	1.117	47.4	44.3	28.7	N	56.0	46.0	PASS
8	2.451	46.9	43.7	31.8	N	56.0	46.0	PASS
9	2.817	48.8	44.8	31.2	N	56.0	46.0	PASS

B. Test Plot:


 dB μ V


03/06/2008 08:56:26

(Start = 0.15, Stop = 30.00) MHz

(Plot A: L Phase)

dBuV



03/06/2008 08:51:21

(Start = 0.15, Stop = 30.00) MHz

(Plot B: N Phase)

4.2 Radiated Emission

4.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength	
	µV/m	dBµV/m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

NOTE:

- a) Field Strength (dBµV/m) = $20 \log_{10} [\text{Field Strength} (\mu\text{V/m})]$.
- b) In the emission tables above, the tighter limit applies at the band edges.

4.2.2 Test Description

See section 3.2.2 of this report.

4.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

4.2.3.1 The first test mode

The EUT configuration of the emission tests is EUT + Battery + Charger.


A. Test Verdict Recorded for Suspicious Points:

No.	@Frequency (MHz)	Emission Level (dBµV/m)			Quasi-Peak Limit (dBµV/m)	Result
		PK	QP	Antenna Polarization		
1	28.92	28.1	22.8	Vertical	40	PASS
2	31.53	32.8	33.8	Vertical	40	PASS
3	55.72	22.9	17.2	Vertical	40	PASS
4	67.96	23.9	18.4	Vertical	40	PASS
6	68.94	16.9	10.6	Horizontal	40	PASS
7	110.38	23.7	--	Horizontal	43.5	PASS

B. Test Plot:


Note: Following is the plots for emission measurement; please note that marked spikes with circle should be ignored because they are MS and SS carrier frequency.

dBuV/m



(Plot A: Test Antenna Vertical)

dBuV/m



(Plot B: Test Antenna Horizontal)

4.2.3.2 The second test mode

The EUT configuration of the emission tests is EUT + Battery + PC.


A. Test Verdict Recorded for Suspicious Points:

No.	@Frequency (MHz)	Emission Level (dB μ V/m)			Quasi-Peak Limit (dB μ V/m)	Result
		PK	QP	Antenna Polarization		
1	132.100	32.5	-----	Horizontal	40.0	PASS
2	143.930	32.2	-----	Horizontal	40.0	PASS
3	305.041	33.8	-----	Horizontal	47.0	PASS
4	334.013	33.2	-----	Horizontal	47.0	PASS
5	445.134	32.5	-----	Horizontal	47.0	PASS
6	730.100	34.3	-----	Horizontal	47.0	PASS
7	54.054	29.6	-----	Vertical	40.0	PASS
8	143.930	32.5	-----	Vertical	40.0	PASS
9	232.403	25.8	-----	Vertical	47.0	PASS
10	300.012	32.3	-----	Vertical	47.0	PASS
11	392.391	33.4	-----	Vertical	47.0	PASS
12	497.698	33.2	-----	Vertical	47.0	PASS
13	566.331	32.1	-----	Vertical	47.0	PASS

B. Test Plot:

Note: Following is the plots for emission measurement; please note that marked spikes with circle should be ignored because they are MS and SS carrier frequency.

dB μ V/m




06/06/2008 12:30:05

(Start = 30.00, Stop = 1000.00) MHz

(Plot A: Test Antenna Vertical)

dBuV/m



06/06/2008 13:06:15

(Start = 30.00, Stop = 1000.00) MHz

(Plot B: Test Antenna Horizontal)

** END OF REPORT **