

TEST REPORT



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (1) / (64) Pages

1. Client

- Name : J. STEPHEN CO., LTD.
- Address : 28-6, Gajangsaneopdong-ro, Osan-si, gyeonggi-do, 18103, Korea
- Date of Receipt : 2019-01-16

2. Manufacturer

- Name : J. STEPHEN CO., LTD.
- Address : 28-6, Gajangsaneopdong-ro, Osan-si, gyeonggi-do, 18103, Korea

3. Use of Report : For FCC & ISED Certification

4. Test Sample / Model: Bluetooth Module / SBT-M2

5. Date of Test : 2019-01-16 to 2019-01-29

6. Test Standard(method) used : FCC 47 CFR part 15 subpart C 15.247

ANSI C63.10-2013, RSS-247 Issue 2

7. Testing Environment: Temp.: (23 ± 1) °C, Humidity: (48 ± 5) % R.H.

8. Test Results : Compliance

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full.

Affirmation	Gwanyong Kim: (Signature)	Technical Manager Young-taek Lee: (Signature)
-------------	---------------------------	--

2019-01-29

Republic of KOREA **CTK Co., Ltd.**



CTK Co., Ltd.
The Prime Leader of Global Regulatory Certification

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (2) / (64) Pages

REPORT REVISION HISTORY

Date	Revision	Page No
2019-01-29	Issued (CTK-2019-00375)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (3) / (64) Pages

CONTENTS

1. General Product Description	4
1.1 Client Information	4
1.2 Product Information.....	4
1.3 Peripheral Devices	4
2. Facility and Accreditations.....	5
2.1 Test Facility	5
2.2 Laboratory Accreditations and Listings.....	5
2.3 Calibration Details of Equipment Used for Measurement.....	5
3. Test Specifications	6
3.1 Standards	6
3.2 Mode of operation during the test	6
3.3 Maximum Measurement Uncertainty	7
4. Technical Characteristic Test.....	8
4.1 Carrier Frequency Separation.....	8
4.2 Number of Hopping Frequencies	10
4.3 20 dB bandwidth & 99% Bandwidth	13
4.4 Time of Occupancy (Dwell Time)	19
4.5 Maximum peak Conducted Output Power	27
4.6 Unwanted Emissions (Conducted)	35
4.7 Radiated Emission	46
4.8 Frequency Hopping System Requirements.....	61
APPENDIX A – Test Equipment Used For Tests	63
APPENDIX B – EUT Photographs	64



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (4) / (64) Pages

1. General Product Description

1.1 Client Information

Company	J. STEPHEN CO., LTD.
Contact Point	28-6, Gajangsaneopdong-ro, Osan-si, gyeonggi-do, 18103, Korea
Contact Person	Name : Min Seok Song E-mail : sms@miniprinter.com Tel : +82-70-4035-3372 Fax : +82-31-459-7780

1.2 Product Information

FCC ID	WF5SBTM2
Product Description	Bluetooth Module
Model name	SBT-M2
Operating Frequency	2 402 MHz – 2 480 MHz
RF Output Power	GFSK : -0.72 dBm (0.85 mW) 8-DPSK : -0.29 dBm (0.94 mW)
Antenna type	Chip Antenna
Antenna gain	2.5 dBi
Number of channels	79
Channel Spacing	1 MHz
Type of Modulation	GFSK(1Mbps), $\pi/4$ DQPSK(2Mbps), 8-DPSK(3Mbps)
Power Source	DC 3.3 V
Test Software(Version)	Broadcom BlueTool (1.8.0.8)
RF Power setting in Test SW	Specify Power Table index "0"

1.3 Peripheral Devices

Device	Manufacturer	Model No.	Serial No.
Notebook Computer	TOSHIBA	PSAA8K-IGF03	X6207068Q
AC/DC Adapter	TOSHIBA	SADP-75PB B	PA3469E-1AC3



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (5) / (64) Pages

2. Facility and Accreditations

2.1 Test Facility

The measurement facility is located at (Ho-dong), 113, Yejik-ro, Cheoin-gu, Yong-in-si, Gyeonggi-do, Korea.

2.2 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Registration Number	Logo
USA	FCC	FCC Part 15 & 18 EMI (Electromagnetic Interference / Emission)	805871	
CANADA	ISED	ISED EMI (3/10m test site)	8737A-2	
JAPAN	VCCI	VCCI V-3 EMI (Electromagnetic Interference / Emission)	C-986 T-1843 R-3627 G-387	
KOREA	MSIP	EMI (Electromagnetic Interference / Emission) EMS (Electromagnetic Susceptibility / Immunity)	KR0025	

2.3 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (6) / (64) Pages

3. Test Specifications

3.1 Standards

Section in FCC	Section in RSS	Requirement(s)	Status (Note 1)	Test Condition
15.247(a)	RSS-247 5.1(b)	Carrier Frequency Separation	C	Conducted
15.247(a)	RSS-247 5.1(d)	Number of Hopping Frequencies	C	
15.247(a)	RSS-247 5.1(a)	20 dB Bandwidth	C	
15.247(a)	RSS-247 5.1(d)	Time of occupancy (Dwell Time)	C	
15.247(b)	RSS-247 5.1(b)	Maximum peak conducted output power	C	
15.247(d)	RSS-247 5.5	Unwanted emission	C	
15.209	RSS-Gen 6.13	Transmitter emission	C	Radiated
15.207(a)	RSS-Gen 8.8	AC Conducted Emission	C	Line Conducted

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

Note 3: The equipment is operated on battery power only.

Note 4: The sample was tested according to the following specification: FCC Part 15.247, ANSI C63.10-2013, RSS-247 Issue 2, RSS-Gen Issue 5

Note 5: The tests were performed according to the method of measurements prescribed in KDB No.558074.

3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments. During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests. The results are only attached worst cases.

Test Frequency

Lowest channel	Middle channel	Highest channel
2 402 MHz	2 441 MHz	2 480 MHz

Test mode

Modulation	Packet type	Data rate	Duty Cycle
GFSK	DH5	1 Mbps	43.42%
8-DPSK	3-DH5	3 Mbps	43.60%



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (7) / (64) Pages

3.3 Maximum Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
Coverage factor $k = 2$, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	± 1.5 dB
Occupied Bandwidth	± 0.1 MHz
Unwanted Emission(conducted)	± 3.0 dB
Radiated Emissions ($f \leq 1$ GHz)	± 4.0 dB
Radiated Emissions ($f > 1$ GHz)	± 5.0 dB

4. Technical Characteristic Test

4.1 Carrier Frequency Separation

Test Procedures

ANSI C63.10-2013 7.8.2

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to:

- a) Span = 5 MHz (wide enough to capture the peaks of two adjacent channels)
- b) RBW = 30 kHz (Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel)
- c) VBW = 30 kHz (\geq RBW)
- d) Sweep = auto
- e) Detector function = peak
- f) Trace = max hold




Figure 1 : Measurement setup for the carrier frequency separation

Limit

FHSS operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater.

Test Results

Test mode : GFSK

Channel	Adjacent Hopping Channel Separation [kHz]	Two-third of 20dB bandwidth [kHz]	Minimum Bandwidth [kHz]	Result
Middle	1005	631.3	25	Complies

Test mode : 8-DPSK

Channel	Adjacent Hopping Channel Separation [kHz]	Two-third of 20dB bandwidth [kHz]	Minimum Bandwidth [kHz]	Result
Middle	0.990	872.0	25	Complies

See next pages for actual measured spectrum plots.



CTK Co., Ltd.


(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (9) / (64) Pages

Test mode : GFSK



Test mode : 8-DPSK



4.2 Number of Hopping Frequencies


Test Procedures

ANSI C63.10-2013 7.8.3

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to:

a) Frequency range	1: Start = 2 389.5 MHz, 2: Start = 2 439.5 MHz,	Stop = 2 439.5 MHz Stop = 2 489.5 MHz
b) RBW = 300 kHz (To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller)		
c) VBW = 300 kHz (\geq RBW)	d) Sweep = auto	
e) Detector function = peak	f) Trace = max hold	



Limit

FHSs operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels.

Test Results

Test mode : GFSK


Total number of Hopping Channels	Result
79	Complies

Test mode : 8-DPSK

Total number of Hopping Channels	Result
79	Complies

See next pages for actual measured spectrum plots.

Test Mode : GFSK







CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (12) / (64) Pages

Test Mode : 8-DPSK





CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (13) / (64) Pages

4.3 20 dB bandwidth & 99% Bandwidth

Test Procedures

ANSI C63.10-2013 6.9.2

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Test Procedures

ANSI C63.10-2013 6.9.3


The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

- a) Span = 3 MHz (between 2 times and 5 times the OBW)
- b) RBW = 30 kHz (1% to 5% of the OBW)
- c) VBW = 100 kHz (approximately 3 times RBW)
- d) Sweep = auto
- e) Detector function = peak
- f) Trace = max hold



Limit

Limit : N/A



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (14) / (64) Pages

Test Results

Test mode : GFSK


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]	Result
Low	2 402	0.937	0.890	Complies
Middle	2 441	0.947	0.889	Complies
High	2 480	0.932	0.890	Complies

Test mode : 8-DPSK


Channel	Frequency [MHz]	20 dB Bandwidth [MHz]	99% Bandwidth [MHz]	Result
Low	2 402	1.326	1.224	Complies
Middle	2 441	1.308	1.223	Complies
High	2 480	1.310	1.233	Complies

See next pages for actual measured spectrum plots.

20 dB bandwidth & 99% Bandwidth - GFSK
[Low channel]



[Middle channel]






CTK Co., Ltd.


(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (16) / (64) Pages


[High channel]



20 dB bandwidth & 99% Bandwidth - 8-DPSK
[Low channel]



[Middle channel]






CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (18) / (64) Pages

[High channel]



4.4 Time of Occupancy (Dwell Time)

Test Procedures

ANSI C63.10-2013 7.8.4


The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function enabled.

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set $>> 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

Number of hops in the period specified in the requirements =
 (number of hops on spectrum analyzer) \times (period specified in the requirements / analyzer sweep time)



Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (20) / (64) Pages

Test Results

Test mode : GFSK

Mode	Number of hops Channels	Transmit time per hop(msec)	Result (msec)	Limit (msec)
DH1	79	0.380	121.6	400
DH3	79	1.645	263.2	400
DH5	79	2.865	306.5	400

Test mode : $\pi/4$ DQPSK

Mode	Number of hops Channels	Transmit time per hop(msec)	Result (msec)	Limit (msec)
2-DH1	79	0.389	124.5	400
2-DH3	79	1.640	262.4	400
2-DH5	79	2.875	307.6	400

Test mode : 8-DPSK

Mode	Number of hops Channels	Transmit time per hop(msec)	Result (msec)	Limit (msec)
3-DH1	79	0.390	124.8	400
3-DH3	79	1.644	263.0	400
3-DH5	79	2.904	310.7	400

* Remark:


Average time of occupancy = Transmit time per hop * Number of hopping channels in 31.6s

According the BLUETOOTH STANDARD SPECIFICATION, the nominal hop rate is 1600 hop/s. All bluetooth units participating in the piconet are time and hop synchronized to the channel.


- The maximum number of hopping channels in 31.6s for DH1 = $1600 / 2 / 79 * 31.6 = 320$
- The maximum number of hopping channels in 31.6s for DH3 = $1600 / 4 / 79 * 31.6 = 160$
- The maximum number of hopping channels in 31.6s for DH5 = $1600 / 6 / 79 * 31.6 = 107$

See next pages for actual measured spectrum plots.


Time of Occupancy for PACKET Type DH1(GFSK)




Time of Occupancy for PACKET Type DH3(GFSK)




Time of Occupancy for PACKET Type DH5(GFSK)




Time of Occupancy for PACKET Type 2-DH1($\pi/4$ DQPSK)




Time of Occupancy for PACKET Type 2-DH3($\pi/4$ DQPSK)




Time of Occupancy for PACKET Type 2-DH5($\pi/4$ DQPSK)




Time of Occupancy for PACKET Type 3-DH1(8-DPSK)



Time of Occupancy for PACKET Type 3-DH3(8-DPSK)



Time of Occupancy for PACKET Type 3-DH5(8-DPSK)





CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (27) / (64) Pages

4.5 Maximum peak Conducted Output Power

Test Procedures


ANSI C63.10-2013 7.8.5

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

- a) Span = 5 MHz (approximately 5 times of the 20 dB bandwidth)
- b) RBW = 3 MHz (greater than the 20 dB bandwidth of the emission being measured)
- c) VBW = 3 MHz (\geq RBW)
- d) Detector = peak
- e) Trace = max hold
- f) Sweep = auto



Limit

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (28) / (64) Pages

Test Results

Test mode : GFSK

Frequency [MHz]	Channel No.	Output Power [dBm]	Output power [mW]	Result
Low	0	-0.72	0.85	Complies
Middle	39	-1.52	0.70	Complies
High	78	-2.14	0.61	Complies

Test mode : $\pi/4$ DQPSK

Frequency [MHz]	Channel No.	Output Power [dBm]	Output power [mW]	Result
Low	0	-1.44	0.72	Complies
Middle	39	0.34	1.08	Complies
High	78	-0.73	0.85	Complies

Test mode : 8-DPSK

Frequency [MHz]	Channel No.	Output Power [dBm]	Output power [mW]	Result
Low	0	-0.29	0.94	Complies
Middle	39	-0.96	0.80	Complies
High	78	-1.53	0.70	Complies


See next pages for actual measured spectrum plots.

Test Mode : GFSK

[Low channel]



[Middle channel]






CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (30) / (64) Pages

[High channel]






CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501


Report No.:
CTK-2019-00375
Page (31) / (64) Pages

Test Mode : $\pi/4$ DQPSK

[Low channel]



[Middle channel]






CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (32) / (64) Pages

[High channel]






CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501


Report No.:
CTK-2019-00375
Page (33) / (64) Pages

Test Mode : 8-DPSK

[Low channel]



[Middle channel]






CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (34) / (64) Pages

[High channel]





4.6 Unwanted Emissions (Conducted)

Test Procedures

ANSI C63.10-2013 7.8.6 / ANSI C63.10-2013 7.8.8


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB.

The bandwidth at 20 dB down from the highest inband spectral density was measured with a spectrum analyzer connected to the antenna terminal, while EUT has its hopping function disabled at the highest, middle and the lowest available channels.

The spectrum analyzer is set to:

Center frequency = the highest, middle and the lowest channels

a) RBW = 100 kHz	b) VBW = 300 kHz (\geq RBW)
c) Span = 10 MHz	d) Detector = peak
e) Trace = max hold	f) Sweep = auto



Limit

> 20 dBc



Test Results

All conducted emission in any 100 kHz bandwidth outside of the spectrum band was at least 20 dB lower than the highest level of the in-band spectral density.
Therefore the applying equipment meets the requirement.



See next pages for actual measured spectrum plots.

Band Edge



Test Mode : Hopping mode, GFSK





Test Mode : Hopping mode, 8-DPSK



Test Mode : Non-Hopping mode, GFSK




Test Mode : Non-Hopping mode, 8-DPSK



Spurious Emission

Test Mode : GFSK

[Low Channel]






CTK Co., Ltd.



(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (41) / (64) Pages

[Middle Channel]





[High Channel]




Test Mode : 8-DPSK


[Low Channel]



[Middle Channel]



[High Channel]





CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (46) / (64) Pages

4.7 Radiated Emission

Test Location

- 10 m SAC (test distance : 10 m, 3 m)
- 3 m SAC (test distance : 3 m)

Test Procedures

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is carried from 1m to 4m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Test Settings:

Frequency Range = 9 kHz ~ 25 GHz (2.4 GHz 10th harmonic)

- a) RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz, 9 kHz for $f < 30$ MHz
- b) VBW \geq RBW
- c) Sweep time = auto couple



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (47) / (64) Pages

Limit :

Unwanted emissions that do not fall within the restricted frequency bands of Table 1 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

FCC Part 15 § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
¹ 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475-156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	² Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (48) / (64) Pages

FCC Part 15 § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Except when the requirements applicable to a given device state otherwise, emissions from licence-exempt transmitters shall comply with the field strength limits shown in Table 2. Additionally, the level of any transmitter emission shall not exceed the level of the transmitter's fundamental emission.

Table 2. General Field Strength Limits for Licence-Exempt Transmitters

Frequency(MHz)	Field Strength uV/m@3m	Field Strength dBuV/m@3m	Deasurement Distance (meters)
0.009-0.490	2400/F(kHz)	-	300
0.490-1.705	24000/F(kHz)	-	30
1.705-30	30	-	30
30-88	100**	40	3
88-216	150**	43.5	3
216-960	200**	46	3
Above 960	500	54	3


** Except as provided in 15.209(g).fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72MHz, 76-88MHz, 174-216MHz, 470-806MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g.15.231 and 15.241.

Note :


- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3m (AV) and 74 dBuV/m@3m (PK)
- 3) For measurement above 1GHz, the resolution bandwidth is set to 1 MHz and video bandwidth is set to 3 MHz for peak measurement.

Test Setup:


1) For field strength of emissions from 9 kHz to 30 MHz



2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz



Test results

1) 9 kHz to 30 MHz

The requirements are:
 Complies

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
-	-	-	See note

Note :

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB)

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (51) / (64) Pages


2) 30 MHz to 1 GHz

Test mode : Transmitter, GFSK, Hopping mode

The requirements are:

Complies

Test Data



Spectrum Selection

No.	Frequency (P)	Reading	c.f	Result	Limit	Margin	Height	Angle
	[MHz]	[dB(uV)]	[dB(1/m)]	[dB(uV/m)]	[dB(uV/m)]	[dB]	[cm]	[deg]
1	50.128	V	46.3	-15.8	30.5	40.0	9.5	101.0
2	63.223	V	50.6	-18.3	32.3	40.0	7.7	101.0
3	78.379	V	47.2	-16.6	30.6	40.0	9.4	101.0
4	86.866	V	45.5	-15.5	30.0	40.0	10.0	101.0
5	122.029	V	36.2	-11.8	24.4	43.5	19.1	101.0
6	555.498	V	26.4	-0.5	25.9	46.0	20.1	300.0

Remark :


1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain

Test mode : Transmitter, 8-DPSK, Hopping mode

The requirements are:

Complies

Test Data



Spectrum Selection

No.	Frequency (P) [MHz]	Reading [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]
1	38.488	V 32.8	-10.9	21.9	40.0	18.1	101.0	2.0
2	63.101	V 51.4	-18.3	33.1	40.0	6.9	101.0	2.0
3	87.230	V 46.0	-15.5	30.5	40.0	9.5	101.0	216.0
4	95.596	V 44.5	-14.3	30.2	43.5	13.3	101.0	163.0
5	121.665	V 36.6	-11.8	24.8	43.5	18.7	101.0	137.0
6	847.104	V 29.3	4.0	33.3	46.0	12.7	200.0	249.0

Remark :

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(Correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (53) / (64) Pages

3) above 1 GHz

Test mode : Transmitter, GFSK

The requirements are:

Complies

Test Data

Test mode : Lowest frequency

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1 919.17	H	33.00	-4.00	29.00	54	25.00	Average
1 920.49	H	44.60	-4.00	40.60	74	33.40	Peak

Test mode : Middle frequency

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1 919.17	H	33.30	-4.00	29.30	54	24.70	Average
1 919.17	H	43.70	-4.00	39.70	74	34.30	Peak

Test mode : Highest frequency

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1 919.17	H	33.10	-4.00	29.10	54	24.90	Average
1 920.35	H	43.70	-4.00	39.70	74	34.30	Peak

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (54) / (64) Pages

Test mode : Transmitter, 8-DPSK

The requirements are:

Complies

Test Data

Test mode : Lowest frequency

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1 919.17	H	33.20	-4.00	29.20	54	24.80	Average
1 920.49	H	44.90	-4.00	40.90	74	33.10	Peak

Test mode : Middle frequency

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1 919.17	H	33.00	-4.00	29.00	54	25.00	Average
1 919.17	H	44.40	-4.00	40.40	74	33.60	Peak

Test mode : Highest frequency

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
1 919.17	H	33.10	-4.00	29.10	54	24.90	Average
1 919.17	H	45.00	-4.00	41.00	74	33.00	Peak

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (55) / (64) Pages

4) Restricted Frequency Bands

Test mode : Transmitter, GFSK

Test frequency range : 2 310 MHz – 2 390 MHz

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
2 385.30	V	30.80	-3.80	27.00	54	27.00	Average
2 353.90	H	45.90	-3.80	42.10	74	31.90	Peak

Test frequency range : 2 483.5 MHz – 2 500 MHz

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
2 487.75	H	29.80	-3.70	26.10	54	27.90	Average
2 487.50	H	44.30	-3.70	40.60	74	33.40	Peak

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain

Test mode : Transmitter, 8-DPSK

Test frequency range : 2 310 MHz – 2 390 MHz

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
2 378.83	V	30.00	-3.80	26.20	54	27.80	Average
2 354.26	H	44.00	-3.80	40.20	74	33.80	Peak

Test frequency range : 2 483.5 MHz – 2 500 MHz

Frequency [MHz]	Ant. Pol. (V/H)	Reading [dBuV/m]	c.f [dB/m]	Result [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Remark
2 484.51	H	30.10	-3.70	26.40	54	27.60	Average
2 484.13	H	47.40	-3.70	43.70	74	30.30	Peak

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (56) / (64) Pages

4.8 AC Power Line Conducted Emissions

A radio apparatus that is designed to be connected to the public utility (AC) power line shall ensure that the radio frequency voltage, which is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz-30 MHz, shall not exceed the limits.

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average**
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* The level decreases linearly with the logarithm of the frequency.

** A linear average detector is required.

Test Results

The requirements are:

Complies



CTK Co., Ltd.


(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (57) / (64) Pages

Test Data

Test mode : GFSK

[LINE]




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.159000	43.1	1000.0	9.000	On	L1	10.2	22.4	65.5
0.186000	40.0	1000.0	9.000	On	L1	10.2	24.2	64.2
0.235500	33.8	1000.0	9.000	On	L1	10.0	28.5	62.3
0.316500	27.1	1000.0	9.000	On	L1	10.1	32.7	59.8
21.669000	48.1	1000.0	9.000	On	L1	10.2	11.9	60.0
26.641500	36.2	1000.0	9.000	On	L1	10.2	23.8	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.415500	20.6	1000.0	9.000	On	L1	10.1	27.0	47.5
8.245500	24.8	1000.0	9.000	On	L1	10.1	25.2	50.0
8.749500	26.4	1000.0	9.000	On	L1	10.1	23.6	50.0
19.437000	30.0	1000.0	9.000	On	L1	10.1	20.0	50.0
22.272000	43.9	1000.0	9.000	On	L1	10.2	6.1	50.0
25.624500	33.6	1000.0	9.000	On	L1	10.2	16.4	50.0

[NEUTRAL]



Final Result 1


Frequency (MHz)	QuasiPeak (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	45.1	1000.0	9.000	On	N	10.3	20.9	66.0
0.154500	43.6	1000.0	9.000	On	N	10.4	22.1	65.8
0.199500	37.9	1000.0	9.000	On	N	10.4	25.8	63.6
19.594500	34.5	1000.0	9.000	On	N	10.5	25.5	60.0
21.669000	47.6	1000.0	9.000	On	N	10.6	12.4	60.0
25.741500	36.5	1000.0	9.000	On	N	10.6	23.5	60.0

Final Result 2

Frequency (MHz)	CAverage (dBμV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
8.245500	25.4	1000.0	9.000	On	N	10.4	24.6	50.0
8.754000	27.7	1000.0	9.000	On	N	10.4	22.3	50.0
13.726500	24.9	1000.0	9.000	On	N	10.5	25.1	50.0
19.432500	30.1	1000.0	9.000	On	N	10.5	19.9	50.0
22.272000	44.2	1000.0	9.000	On	N	10.6	5.8	50.0
25.728000	33.5	1000.0	9.000	On	N	10.6	16.5	50.0

Test mode : 8-DPSK

[LINE]




Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
0.154500	43.7	1000.0	9.000	On	L1	10.1	22.1	65.8
0.199500	38.2	1000.0	9.000	On	L1	10.1	25.4	63.6
0.231000	34.1	1000.0	9.000	On	L1	10.0	28.3	62.4
19.437000	36.2	1000.0	9.000	On	L1	10.1	23.8	60.0
21.565500	46.8	1000.0	9.000	On	L1	10.2	13.2	60.0
27.352500	36.8	1000.0	9.000	On	L1	10.2	23.2	60.0

Final Result 2

Frequency (MHz)	CAverage (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)
8.245500	25.1	1000.0	9.000	On	L1	10.1	24.9	50.0
8.754000	27.4	1000.0	9.000	On	L1	10.1	22.6	50.0
14.334000	22.6	1000.0	9.000	On	L1	10.1	27.4	50.0
19.437000	29.6	1000.0	9.000	On	L1	10.1	20.4	50.0
22.272000	43.8	1000.0	9.000	On	L1	10.2	6.2	50.0
25.624500	33.8	1000.0	9.000	On	L1	10.2	16.2	50.0

[NEUTRAL]



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	45.3	1000.0	9.000	On	N	10.3	20.7	66.0
0.186000	40.3	1000.0	9.000	On	N	10.5	23.9	64.2
0.231000	36.1	1000.0	9.000	On	N	10.3	26.3	62.4
0.294000	30.2	1000.0	9.000	On	N	10.3	30.2	60.4
22.272000	45.2	1000.0	9.000	On	N	10.6	14.8	60.0
25.845000	40.1	1000.0	9.000	On	N	10.6	19.9	60.0

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
8.344500	24.4	1000.0	9.000	On	N	10.4	25.6	50.0
8.754000	29.9	1000.0	9.000	On	N	10.4	20.1	50.0
15.450000	24.2	1000.0	9.000	On	N	10.5	25.8	50.0
19.428000	28.4	1000.0	9.000	On	N	10.5	21.6	50.0
22.272000	39.3	1000.0	9.000	On	N	10.6	10.7	50.0
25.624500	39.1	1000.0	9.000	On	N	10.6	10.9	50.0

4.9 Frequency Hopping System Requirements

Standard Applicable


According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.


(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

EUT Pseudorandom Frequency Hopping Sequence

The pseudo random sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9 Length of pseudo-random sequence: $2^9 - 1 = 511$ bits Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter. The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



CTK Co., Ltd.
The Prime Leader of Global Regulatory Certification

CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (62) / (64) Pages

Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule. This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

*Example for a Bluetooth device using channel numbers would be :

Ch 44, 35, 78, 03, 15, 21, 76, 40, 56, 13, 02, 19, 67, 39, 78, 20, 21, 64, 75 etc.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (63) / (64) Pages

APPENDIX A – Test Equipment Used For Tests

	Name of Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Signal Analyzer	Agilent	N9020A	MY50510324	2019-01-26	2020-01-28
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2018-10-24	2019-10-24
3	EMI Test Receiver	Rohde & Schwarz	ESCI7	100814	2018-10-25	2019-10-25
4	Bilog Antenna	SCHAFFNER	CBL6111C	2551	2017-04-19	2019-04-19
5	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-125	2018-05-02	2020-05-02
6	6dB Attenuator	Rohde & Schwarz	DNF	272.4110.50-2	2018-10-25	2019-10-25
7	AMPLIFIER	SONOMA	310	291721	2019-01-28	2020-01-28
8	EMI Test Receiver	Rohde & Schwarz	ESU40	100336	2019-01-29	2020-01-29
9	Preamplifier	Agilent	8449B	3008A02011	2018-11-30	2019-12-03
10	Horn Antenna	ETS-Lindgren	3116	00062504	2017-12-04	2019-12-04
11	Horn Antenna	ETS-Lindgren	3117	00154525	2017-09-14	2019-09-14
12	Band Reject Filter	Micro Tronics	BRM50702	G233	2019-01-28	2020-01-28
13	Signal Analyzer	Rohde & Schwarz	FSV40	101574	2019-01-28	2020-01-28

	Cable	Manufacturer	Model No.	Serial No.	Check Date
1	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27558/4	2018-12-19
2	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	N/A (below 1GHz)	2018-12-19
3	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27573/4	2018-12-19
4	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 106	N/A (above 1GHz)	2018-12-19
5	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY2374/2	2018-12-19
6	RF Cable (Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY4728/2	2018-12-19



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu,
Yongin-si, Gyeonggi-do, Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2019-00375
Page (64) / (64) Pages

APPENDIX B – EUT Photographs

