

FCC Part 1 Subpart I FCC Part 2 Subpart J INDUSTRY CANADA RSS 102 ISSUE 5

RF EXPOSURE REPORT

FOR

RF ID Reader

MODEL NUMBER: CS-445B

FCC ID: WFQCS-445B IC: 10717A-CS445B

REPORT NUMBER: 12540676B

ISSUE DATE: 2019-04-12

Prepared for RF CONTROLS LLC Suite 200 1400 S 3rd St SAINT LOUIS, MO, 63104 US

Prepared by
UL LLC
333 Pfingsten Road
Northbrook, IL 60062 U.S.A.
TEL: (847) 272-8800



REPORT NO:12540676B FCC ID: WFQCS-445B

Revision History

DATE: 2019-04-12

IC: 10717A-CS445B

Rev.	Issue Date	Revisions	Revised By
V1	x/x/2018	Initial Issue	

TABLE OF CONTENTS

DATE: 2019-04-12

IC: 10717A-CS445B

1.	AT.	TESTATION OF TEST RESULTS	4		
2.	TE	TEST METHODOLOGY			
3.	REFERENCES				
		CILITIES AND ACCREDITATION			
5.	MA	XIMUM PERMISSIBLE RF EXPOSURE	6		
	5.1.	FCC RULES	<i>6</i>		
	5.2.	IC RULES	7		
	5.3.	EQUATIONS	8		
	5.4.	LIMITS AND IC EXEMPTION	S		
6.	RF	EXPOSURE RESULTS	10		

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: RF CONTROLS LLC

Suite 200 1400 S 3rd St SAINT LOUIS, MO, 63104

US

EUT DESCRIPTION: RF ID Reader

MODEL: CS-445B

SERIAL NUMBER: non-serialized

DATE TESTED: 2018-10-17 to 2019-03-06

APPLICABLE STANDARDS

STANDARD TEST RESULTS

FCC PART 1 SUBPART I & PART 2 SUBPART J Complies
INDUSTRY CANADA RSS 102 ISSUE 5 Complies

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of the U.S. government.

Approved & Released For UL LLC By: Jeff Moser

Prepared By: Bart Mucha

Project Engineer/Operations Leader Consumer Technology Division

Test Engineer
Consumer Technology Division

Page 4 of 10

Morey

2. TEST METHODOLOGY

All calculations were made in accordance with FCC KDB 447498 D01 and KDB447498 D03 and IC Safety Code 6.

DATE: 2019-04-12

IC: 10717A-CS445B

3. REFERENCES

All measurements were made as documented in test report UL Verification Services Inc. Document 12540676A for operation in the 902MHz-928MHz

EiRP levels were measured and are extracted from the above referenced report.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 333 Pfingsten Road, Northbrook, IL 60062 USA. IC OATS number 2180A-1.

UL NBK is accredited by NVLAP, Laboratory Code 100414-0. The full scope of accreditation can be viewed at http://ts.nist.gov

5. MAXIMUM PERMISSIBLE RF EXPOSURE

5.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

DATE: 2019-04-12

IC: 10717A-CS445B

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)		
(A) Limits for Occupational/Controlled Exposure						
0.3-3.0	614	1.63	*100	6		
3.0-30	1842/f	4.89/f	*900/f²	6		
30-300	61.4	0.163	1.0	6		
300-1,500			f/300	6		
1,500-100,000			5	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3-1.34	614	1.63	*100	30		
1.34-30	824/f	2.19/f	*180/f ²	30		
30-300	27.5	0.073	0.2	30		
300-1,500			f/1500	30		
1,500-100,000			1.0	30		

f = frequency in MHz

Notes:

- (1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
- (2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure

^{* =} Plane-wave equivalent power density

5.2. IC RULES

For the purpose of this standard, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)

DATE: 2019-04-12

IC: 10717A-CS445B

Frequency RangeElectric	: Field Magnetic Field	Power DentistyReference Period
-------------------------	------------------------	--------------------------------

(MHz)	(V/m rms)	(A/m rms)	(W/m²)	(minutes)
0.003-1021	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f 0.3417	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f 0.5	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}

Note: *f* is frequency in MHz.

^{*} Based on nerve stimulation (NS).

^{**} Based on specific absorption rate (SAR).

5.3. EQUATIONS

POWER DENSITY

Power density is given by:

 $S = EIRP / (4 * Pi * D^2)$

Where

S = Power density in mW/cm^2 EIRP = Equivalent Isotropic Radiated Power in mW D = Separation distance in cm

Power density in units of mW/cm² is converted to units of W/m² by multiplying by 10.

DATE: 2019-04-12

IC: 10717A-CS445B

DISTANCE

Distance is given by:

D = SQRT (EIRP / (4 * Pi * S))

Where

D = Separation distance in cm EIRP = Equivalent Isotropic Radiated Power in mW S = Power density in mW/cm²

5.4. LIMITS AND IC EXEMPTION

FIXED LIMITS

900MHz band

From FCC §1.1310 Table 1 (B), the maximum value of S = 0.61 mW/cm² From IC Safety Code 6, Section 2.2 Table 4 Column 4, S = 2.77 W/m²

INDUSTRY CANADA EXEMPTION

RSS-102 Clause 2.5.2 RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

DATE: 2019-04-12

IC: 10717A-CS445B

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 4.49/f0.5 W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1.31 x 10-2 f0.6834 W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

6. RF EXPOSURE RESULTS

For FCC the minimum separation distance between bystanders and the antenna is: 20cm Maximum measured EiRP = 34.17dBm = 2612.16mW

DATE: 2019-04-12

IC: 10717A-CS445B

 $D = SQRT(2612.16 / (4 \times Pi \times 0.61)) = 18.46 \text{ cm}$

For IC the minimum separation distance between the bystanders and the antenna is: 30cm

 $D = SQRT(2.61216 / (4 \times Pi \times 2.77)) = 0.27 \text{ meters}$

END OF TEST REPORT